

Features and Components

High Load Plates are heavy duty Galvalume®-coated steel seam plates with eye hooks.

High Load Plus Plates (not pictured) are heavy duty Galvalume-coated steel seam plates with barbs.

JM 90 Seam Plate are heavy duty Galvalume-coated steel seam plates with eye hooks. Utilize with 8' - 12" O.C. TPO Installations if applicable.

Use: Membranes

Material: Galvalume-Coated Steel

Gauge: 20-Gauge Steel

Size: High Load Plate - 2 $\frac{3}{8}$ " (6.03 cm) round
High Load Plus Plate - 2 $\frac{3}{4}$ " (6.99 cm) round
JM 90 Seam Plate - 3" (7.62 cm)

Color: Grey (Galvalume-coated steel)

* Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.



Component

F
Fastening

Type

M
Membrane

Multi-Ply
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	CA	MF
Compatible with the selected Multi-Ply system above									

Single Ply	TPO		PVC		EPDM			
	MF	FA	MF	FA	MF	FA	BA	
Compatible with the selected Single Ply systems above								

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and the Environment

Recycled Content	This steel based product contains a minimum of 25% post consumer recycled materials by weight
------------------	---

Peak Advantage® Guarantee Information

Systems
Approved to use with any Peak Advantage Guarantee

Codes and Approvals*



*Fastener approvals are based on system approvals

Installation/Application

Refer to the application instructions guidelines for proper utilization of this product.

Packaging and Dimensions

Plate Size	Size	Packaging
High Load Plate	2 $\frac{3}{8}$ " (6.03 cm) round	1,000/pail
High Load Plus Plate	2 $\frac{3}{4}$ " (7 cm) round	500/pail
JM 90 Seam Plate	3" (7.62 cm)	500/pail
Producing Location	Itasca, IL	

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.