


Features and Components

- Use:** To seal seam laps where perimeter and/or header sheets intersect (T-Joints) in EPDM systems.
- Materials:** 45 mil (1.14 mm), uncured EPDM (ethylene propylene diene monomer) with a factory laminated, self-adhering seam tape.
- Color:** Black



Component

A
Accessory

Single Ply

Type

MS
Membrane
Seaming

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS					Single Ply	TPO				PVC			EPDM			
	HA	CA	CA	HW	HA	CA	HW	SA	MF		MF	AD	SA	IW	MF	AD	IW	MF	AD	BA	SA
Do not use with Multi-Ply systems										Compatible with the selected Single Ply systems above											

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer Plus or JM Tape Primer Plus (Low VOC) before applying to JM EPDM Peel & Stick T-Joint Patches.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Size	5.75" (14.61 cm) diameter
Thickness	
Membrane	0.045" (1.14 mm)
Tape	0.030" (0.76 mm)
Total	0.075" (1.91 mm)
Patches per Box	100
Weight per Box	2 lb (0.9 kg)

Storage

Shelf Life	9 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.