

Features and Components

- Use:** For field seaming JM EPDM membranes. Utilizes a clear polyethylene release liner for ease of installation.
- Materials:** 3" or 6" (7.62 cm or 15.24 cm) wide, self-adhering, extruded EPDM (ethylene propylene diene monomer) with a clear polyethylene release liner.
- Color:** Black



Component

A
Accessory

Single Ply

Type

MS
Membrane Seaming

System Compatibility

This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP			SBS				Single Ply	TPO				PVC			EPDM			
	HA	CA	CA	HW	HA	CA	HW	SA	MF		MF	AD	SA	IW	MF	AD	IW	MF	AD	BA	SA
Do not use with Multi-Ply systems										Compatible with the selected Single Ply systems above											

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer Plus or JM Tape Primer Plus (Low VOC) before applying to JM EPDM Seam Tape Plus.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Sizes	3" x 100' (7.62 cm x 30.48 m)	6" x 100' (15.24 cm x 30.48 m)
Thickness	0.030" (0.76 mm)	
Roll Coverage	25 ft² (2.33 m²)	50 ft² (4.65 m²)
Rolls per Box*	4	2
Linear Units per Box	400 lin ft (121.92 lin m)	200 lin ft (60.96 lin m)
Weight per Box	24 lb (10.89 kg)	25 lb (11.34 kg)

*Each box of JM EPDM Seam Tape Plus includes scrubber pads and handle for seam priming.

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
Temperature Range	60°F – 80°F (16°C – 27°C)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.