

Features and Components

Use: JM PVC Polyester Slipsheet is intended for use as a separation layer between extruded polystyrene insulation and roofing membrane in protected membrane (inverted) roof assemblies, as well as a separating sheet in some recover systems. It is also used as a protective layer between pavers and JM single ply membrane.

Material: 4.2 oz/yd² (142 g/m²) needle-punched, UV-resistant polyester fabric.

Color: White



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
									Not compatible with Multi-ply systems

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
										Compatible with the selected Single Ply systems above

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Loose Laid



Mechanically Fastened

- JM PVC Polyester Slipsheet is typically installed between the overlying extruded polystyrene insulation and JM PVC roofing membrane.
- Refer to JM PVC applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Size	130' wide x 100' long (3.3 m x 30.48 m)
Coverage per Roll	1,083.33 ft ² (100.64 m ²) (gross)
Weight per Roll	31 lb (14.06 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location prior to application.
--------------------	--

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.