


Features and Components

- Use:** To seal edges of JM PVC membrane seams after the membrane has been welded to itself or to JM PVC-Coated Metal.
- Type:** One-part, membrane edge sealing agent.
- Color:** Clear



System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
Compatible with the selected multi-ply systems above									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Do not use in single ply systems										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Maximum VOC	757.3 g/l
-------------	-----------

Physical Properties

Property	JM PVC Edge Sealant
Weight per Unit (approx.)	7.8 lb/gal (0.935 kg/l)
Vapor Pressure	143 mm Hg
Specific Gravity	0.94

Precautions

Johns Manville PVC Edge Sealant is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all bottles tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.

Installation/Application



Bead

Refer to the application instructions guidelines for proper utilization of this sealant.

Packaging and Coverage

Container Size	Box of twelve 16 oz (473 ml) bottles
Shipping Weight (approx.)	14 lb (6.4 kg)/box
Boxes per Pallet	60
Pallet Weight	900 lb (kg)
Pallets per Truck	22
Coverage Rate* (approx.)	100 lin ft/16 fl oz (30.48 m/473 ml) with 1/8" (3.18 mm) bead

* Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only. If FM Global® or UL® approval is required, consult specific RoofNavSM or the UL Certifications Directory for specific application rates.

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment, unopened container
Temperature Range	60°F – 80°F (16°C – 27°C) - Protect from freezing