

Features and Components

ENRGY® MEP Anchor is a lightweight, roof-top integrated equipment mounting solution consisting of a Galvalume®*-coated steel plate welded to stainless steel studs, with a JM membrane. Each assembly includes a leveling washer and membrane separator.

High Wind Rating: Unlike a ballasted system, ENRGY MEP Anchor can be installed on most buildings in high wind zones without adding substantially more weight. The systems can be installed flat and nearly flush to further reduce wind load.

Design Flexibility: The ENRGY MEP Anchor is compatible with most roof-top mounted solutions. Whether the roof-top mounted solution calls for a ballasted or penetrating attachment, using the ENRGY MEP Anchor proves a guaranteeable solution that save labor dollars.

* Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.



Color

Dependent on membrane

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP			SBS				
	HA	CA	HW	HA	CA	HW	SA	MF		

Compatible with all multi-ply systems

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA

Compatible with the selected single ply systems above

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Pre-Consumer Recycled Content	0%
Post-Consumer Recycled Content	0%

Physical Properties

Property	ENRGY MEP Anchor TPO/PVC	ENRGY MEP Anchor EPDM	ENRGY MEP Anchor SBS/APP
Weight	1.4 lb (0.64 kg)	1.5 lb (0.68 kg)	2.5 lb (1.13 kg)
Membrane Dimensions	17.5" x 11.75" (45 cm x 30 cm)	17.5" x 11.75" (45 cm x 30 cm)	17.5" x 11.75" (45 cm x 30 cm)
Membrane Thickness*	60 mil (1.5 mm)	60 mil (1.5 mm)	130 mil (3.3 mm)
Plate Dimensions	11" x 5.5" (28 cm x 14 cm)	11" x 5.5" (28 cm x 14 cm)	11" x 5.5" (28 cm x 14 cm)

Testing Results are based on plate performance only. Applicable to all membranes.

Ultimate Load- Shear	3,140 lbs
Ultimate Load- Tension	2,700 lbs

* Tested in accordance with ICC AC467

Peak Advantage® Guarantee Information

Systems
Can be included in any Peak Advantage Guarantee*

* Contact JM Technical Services for specific system requirements or guarantee terms.

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

Installation/Application



- Refer to the ENRGY MEP Anchor Application Guide and/or detail drawings for instructions.
- Use of ENRGY MEP Anchor on ballasted EPDM systems requires prior approval by JM Technical.
- All roof-top mounted equipment applications must be in accordance with building codes.
- BUR should use the SBS ENRGY MEP Anchor.

Packaging and Dimensions

Property	ENRGY MEP Anchor TPO/PVC	ENRGY MEP Anchor EPDM	ENRGY MEP Anchor SBS/APP
Box Dimensions	19" x 14" x 14" (48 cm x 36 cm x 36 cm)	19" x 13" x 9" (48 cm x 33 cm x 23 cm)	19" x 13" x 9" (48 cm x 33 cm x 23 cm)
Box Weight	17 lb (7.7 kg)	18 lb (8.2 kg)	31 lb (14.1 kg)
Units per Box	10	10	10
Pallet Dimensions	40 x 48" x 61" (102 cm x 122 cm x 155 cm)	40 x 48" x 50" (102 cm x 122 cm x 127 cm)	40 x 48" x 50" (102 cm x 122 cm x 127 cm)
Boxes per Pallet	24	30	30

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.