

Features and Components

Use: Used to seal uneven penetrations through the membrane that are difficult to flash. The penetration pan is comprised of two pieces that allow for positioning around objects to be flashed. A welding tab is included to seal the penetration pan once positioned.

Material: Two-piece molded TPO (thermoplastic polyolefin) pocket with a rigid vertical wall and preformed flange.

Color: White



Component

A
Accessory

Single Ply

Type

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use with Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Size	7.5" x 6" (19 cm x 15 cm) Oval
Nominal Thickness	0.156" (3.97 mm)
Pockets per Box	5

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---