

Features and Components

Use: A prefabricated, reinforced 60 mil JM TPO, round-shaped 1" to 6" (2.54 cm to 15.24 cm) split-pipe boot for flashing application. Pipe boots minimize the need for field fabrication. Custom sizes and colors are available upon request. Contact your JM representative for minimum order quantity and lead time.

Material: JM TPO 60 mil reinforced membrane, with one of the widest weld windows, is factory fabricated into a one-piece round split-pipe boot.

Color: White



Component

A
Accessory

Single Ply

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
	Do not use in Multi-Ply systems							

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
	Compatible with the selected Single Ply systems above						

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and the Environment

Standard		Reflectivity	Emissivity
CRRCC®	Initial	0.77	0.87
	3 Yr. Aged	0.70	0.86
CA Title 24	Pass	0.77	0.87
ENERGY STAR®	Initial	0.78	0.87
	3 Yr. Aged	0.68	
LEED® (SRI)	Initial	101	
	3 Yr. Aged	85	
Recycled Content	Post-consumer	0%	
	Post-industrial	5%	

The LEED® Solar Reflectance Index (SRI) is calculated per ASTM E1980.

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Do not install JM TPO Round Split Pipe Boots in direct contact with asphalt or coal tar pitch.
- Standard-sized clamps are included for each split pipe boot.
- Refer to JM TPO application guides or detail drawings for instructions.

Packaging and Dimensions

	Nominal Diameter	O.D. of Pipe Range	Base Size
Size/Round Base	1"	0.25" - 1.25"	12.5"
	2"	1" - 2"	12.5"
	3"	2" - 3"	14"
	4"	3" - 4"	14"
	5"	4" - 5"	16"
	6"	5" - 6"	16"
Height	8" (20.32 cm)		
Boots per Box	8		
Weight per Box	1" – 6.3 lb (2.86 kg)		
	2" – 6.8 lb (3.08 kg)		
	3" – 7.8 lb (3.54 kg)		
	4" – 8.3 lb (3.76 kg)		
	5" – 9.6 lb (4.36 kg)		
	6" – 10 lb (4.54 kg)		