

Features and Components

The High Load AccuSeam System is a premier automated system for mechanically attached seams. The System positions the 2 3/8" (6.03 cm), round, High Load Plate with eye hooks, and installs the High Load Fastener, up to 6" (15.24 cm) in length in a one-step, continuous process. Standard High Load Plates are not compatible with the AccuSeam Fastener and Plate System.

- Use:** Membranes
- Material:** High Load Fastener - Case-hardened steel
High Load AccuSeam Plate - Galvalume®*-Coated Steel
- Gauge:** #15
- Head:** #3 Phillips head
- Plate:** 2 3/8" (6.03 cm) round
- Color:** Blue (fasteners), Grey (plates)
- Deck Type:** Wood or 18 - 24 gauge (1.25 mm - 0.56 mm) Metal.

* Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.



Component

F
Fastening

Type

M
Membrane
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR	APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF
Compatible with the selected multi-ply systems above								

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Do not use in single ply systems										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Recycled Content	This steel based product contains a minimum of 25% post consumer recycled materials by weight
------------------	---

Peak Advantage® Guarantee Information

Systems
Approved to use with any Peak Advantage Guarantee

Codes and Approvals*



*Fastener approvals are based on system approvals

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.

Installation/Application

Refer to the application instructions guidelines for proper utilization of this product.

Packaging and Dimensions*

Fastener Sizes	Quantity/Container
1 1/4", 2" to 5" (3.2 cm, 5.1 to 12.7 cm)	1,000/pail
6" to 8" (15.2 cm to 20.3 cm)	500/pail
9" to 14" (22.7 cm to 35.6 cm)	500/box
16" to 24" (40.6 cm to 61 cm)	250/box
2 3/8" Plates	Quantity/Container
18 sleeves of stacked plates	1,000 plates/pail
Producing Locations**	Agawam, MA and Itasca, IL

* The High Load AccuSeam Plate is packaged specifically for use with the AccuSeam automated system. Note: To be ordered with the blue High Load Fastener.

**The point of manufacture for fasteners and plates varies depending on the specific part. Call your local JM sales professional for assistance.