

1. Write a class for a **Vector** with the instance variables and methods listed below.

A vector in the xy -plane is a quantity that has both direction and magnitude.

It can be written in the form $v = ax + by$, where a and b are real numbers.

Some examples of vectors include:

- $v_1 = 3x + 2y$
- $v_2 = -2x + 6y$
- $v_3 = 2x$ (which is the same as $2x + 0y$)

Vector
a (x-component)
b (y-component)
<code>__init__</code>
<code>__add__</code>
<code>__str__</code>

Your class should support:

- Creating a vector with x and y components
- Adding two vectors using the `__add__` method
- Printing a readable version of the vector

Hint: Vectors are added component-wise.

For example, $(2x + 3y) + (4x + 5y) = 6x + 8y$.

After writing the class, initialize three vectors and write code to add them together.

2. Write a class for a **Point** with the instance variables and methods listed below.

A point in the coordinate plane has an x and y coordinate. Points can be added together, and the distance between two points can be calculated using the distance formula.

For example:

- $p_1 = (3, 4)$
- $p_2 = (0, 0)$
- Distance between p_1 and p_2 is $\sqrt{(3-0)^2 + (4-0)^2} = 5$
- $p_1 + p_2 = (3 + 0, 4 + 0) = (3, 4)$

Point
x (x-coordinate)
y (y-coordinate)
<code>__init__</code>
<code>__add__</code>
<code>distance(other)</code>
<code>__str__</code>

Your class should support:

- Creating a point with x and y coordinates
- Adding two points using the `__add__` method
- Calculating the distance to another point using `distance(other)`
- Printing a readable version of the point

Once you have created the class, add code that:

- Instantiate two Points
- Adds them together
- Print a readable version of one of the Points you created.

3. Write a class for a **LinearEquation** with the instance variables and methods listed below.

A linear equation is of the form $y = mx + b$, where m is the slope and b is the y -intercept.

For example:

- $y_1 = 2x + 3$
- $y_2 = -x + 5$

You should be able to add two equations together:

- $y_1 + y_2 = (2 - 1)x + (3 + 5) = x + 8$

Your class should support:

- Creating a linear equation with slope and y-intercept
- Adding two equations using the `__add__` method
- Printing a readable version of the equation

Once you have created the class, add code that:

- Instantiate two linear equations
- Add them together
- print a readable version of one of the `LinearEquations` you created.

4. Write a class for a **Time** object with the instance variables and methods listed below.

Time can be represented in hours and minutes (e.g., 2 hours and 45 minutes).

When adding times, make sure minutes are correctly carried into hours.

For example:

- $t_1 = 1$ hour 30 minutes
- $t_2 = 2$ hours 45 minutes
- $t_1 + t_2 = 4$ hours 15 minutes (because $30 + 45 = 75$ minutes, which becomes 1 hour 15 minutes)

Your class should support:

- Creating a time object with hours and minutes
- Adding two times using the `__add__` method
- Printing time in a readable format (e.g., "2h 45m")
Hint: you don't need to consider days. You can have 30 hours.

Once you have created the class, add code that:

- Creates two time objects
- Adds them together
- Prints the result

5. Write a class for an **RGBColor** with the instance variables and methods listed below. Colors on a screen are often represented using Red, Green, and Blue components (values from 0 to 255). Colors can be added together by taking the average of adding each component.

LinearEquation
m (slope)
b (y-intercept)
<code>__init__</code>
<code>__add__</code>
<code>__str__</code>

Time
hours
minutes
<code>__init__</code>
<code>__add__</code>
<code>__str__</code>

Some examples of RGB colors:

- $c_1 = (170, 150, 200)$
- $c_2 = (30, 100, 60)$
- $c_3 = c_1 + c_2 = (\frac{170+30}{2}, \frac{150+100}{2}, \frac{200+60}{2})$ becomes $(100, 125, 130)$

Your class should support:

- Creating a color with red, green, and blue values (each from 0 to 255)
- Adding two colors using the `__add__` method (cap each result at 255)
- Printing the color in a readable format (e.g., "RGB(150, 200, 255)")

After writing the class, create three colors and write code to add them together. Print the result.

6. Write a class for a **RationalNumber** with the instance variables and methods listed below.
A RationalNumber is a number that can be expressed as the ratio of two integers: $\frac{a}{b}$, where $b \neq 0$.

Some examples of RationalNumber addition include:

- $\frac{1}{3} + \frac{1}{2} = \frac{5}{6}$ (not $0.8333\dots$)
- $\frac{2}{5} + \frac{1}{5} = \frac{3}{5}$

Your class should support:

- Creating a rational number with a numerator and denominator
- Adding two rational numbers using the `__add__` method
- Printing a readable version (e.g., as a fraction)

Hint: To add fractions, find a common denominator.

For example, $\frac{1}{3} + \frac{1}{2} = \frac{2}{6} + \frac{3}{6} = \frac{5}{6}$.

After writing the class, create two rational numbers and demonstrate adding and printing.

7. Write a class for a **ComplexNumber** with the instance variables and methods listed below.
A ComplexNumber is a number of the form $a + bi$, where a is the real part and b is the imaginary part.

Some examples of a ComplexNumber include:

- $z_1 = 3 + 2i$
- $z_2 = -1 + 4i$
- $z_3 = 2$ (which is the same as $2 + 0i$)

Once you have created the class, add code that:

- Instantiates two ComplexNumbers with a real and imaginary parts
- Adds two ComplexNumbers using the `__add__` method
- Printing a readable version (e.g., "3 + 2i" or "5 - 1i")

RGBColor
r (red)
g (green)
b (blue)
__init__
__add__
__str__

RationalNumber
numerator
denominator
__init__
__add__
__str__

ComplexNumber
a (real part)
b (imaginary part)
__init__
__add__
__str__

Hint: ComplexNumbers are added component-wise.
 For example, $(2 + 3i) + (4 + 5i) = 6 + 8i$.

After writing the class, initialize three ComplexNumbers and write code to add them together.

8. Write a class for a **Playlist** with the instance variables and methods listed below.

A Playlist should have a default name of "New Playlist".

It can be instantiated with initial songs, but it is not required to.

Create a method called *add_song* which adds a song title (a string) to the Playlist.

You should be able to combine two Playlists, and print them in a readable way.

For example:

- $p_1 = [\text{"Song A"}, \text{"Song B"}]$
- $p_2 = [\text{"Song C"}]$
- $p_1 + p_2 = [\text{"Song A"}, \text{"Song B"}, \text{"Song C"}]$

Your class should support:

- Creating a playlist with a name and list of songs
- Adding two playlists (combines song lists)
- Printing the playlist in a readable way (e.g., list songs)

Once you have created the class, add code that:

- Creates two playlists and at least one song to each.
- Combines the playlists
- Prints the result

Playlist
name
songs (list of strings)
__init__
add_song
__add__
__str__

9. Write a class for a **ShoppingCart** with the instance variables and methods listed below.

It can be instantiated with initial items in the cart, but it is not required to.

Create a method called *add_items* which adds an item (a string) to the ShoppingCart. The same item can be added more than once. If the item is already in the ShoppingCart, increase its quantity by one. If its not in the ShoppingCart, set the quantity to 1.

Hint: think about what type of data structure you should use.

When two ShoppingCarts are added together, the result should be a ShoppingCart containing the items in both. Overlapping items should have a sum of their quantities.

For example:

- $p_1 = \{\text{"tea"} : 1, \text{"energy drink"} : 2\}$
- $p_2 = \{\text{"energy drink"} : 3, \text{"hat"} : 1, \}$
- $p_1 + p_2 = \{\text{"tea"} : 1, \text{"energy drink"} : 5, \text{"hat"} : 1, \}$

Your class should support:

- Creating a ShoppingCart
- Adding two ShoppingCarts (combines items)
- Printing the ShoppingCart in a readable way (e.g., lists all items with quantities)

Once you have created the class, add code that:

ShoppingCart
items (dict→str:int)
__init__
add_item
__add__
__str__

- Creates two ShoppingCarts and at least one item to each.
- Combines the ShoppingCarts
- Prints the result


10. Write a class for a **Rectangle** with the instance variables and methods listed below.

A Rectangle has a width and a height. You should be able to calculate its area and multiply a Rectangle by an integer. The result of multiplying by an integer should be that the height and width of the current Rectangle are multiplied (modified) by the integer value.

Some examples:

- $r_1 = \text{width: 4, height: 5}$
- $r_2 = \text{width: 3, height: 2}$
- $r_1 * 3 = \text{width: 12, height: 15}$

Rectangle
width
height
<code>__init__</code>
<code>area()</code>
<code>__mul__</code>
<code>__str__</code>



Your class should support:

- Creating a rectangle with width and height.
- Calculating the area using `area()`.
- Multiplying a rectangle by an integer using the `__mul__` method.
- Printing the rectangle in a readable format (e.g., "Rectangle(4 x 5)")

Once you have created the class, add code that:

- Creates a rectangle
- Multiplies it by an integer.
- Prints the result