



Ovo je prikaz, mog projekta, kako da ga pokrenem, da vidim sta se desi

Tvoj projekt je standardna ASP.NET Core MVC aplikacija. Evo kako je pokrenuti:

Način 1 — Visual Studio (najlakše)

Budući da vidiš `.slnx` file u korijenu, otvori ga dvoklikom:^[1]

1. Otvori `PostMatchSummary.slnx` u Visual Studiju
2. Pritisni `F5` (s debuggerom) ili `Ctrl+F5` (bez debuggera)
3. Automatski se otvara browser na `https://localhost:PORT`

Način 2 — Terminal (dotnet CLI)

Otvori terminal i navigiraj do foldera gdje se nalazi `.csproj` file:^[2]

```
cd putanja\do\ASP.NET\PostMatchSummary
dotnet run
```

Nakon toga terminal ispiše nešto poput:

```
Now listening on: https://localhost:5001
```

Onda otvori taj URL u browseru.

Što očekivati

Iz strukture projekta vidiš `PostMatchController.cs` i `RiotServices.cs` (zadnji edit 14:52), što znači aplikacija vjerojatno poziva **Riot API** za dohvaćanje podataka o matchevima. Kad pokreneš, prikazat će se MVC stranice — `Home` i `PostMatch` view.^[3] ^[4]

Napomena: Ako `RiotServices.cs` zahtijeva `API key`, provjeri je li postavljen u `appsettings.json` ili kao `environment` varijabla — inače ćeš dobiti grešku pri dohvaćanju podataka.

Imaš li već `API key` od Riota postavljen u projektu, ili trebaš pomoć s tim?

Microsoft Windows [Version 10.0.19044.6809]

(c) Microsoft Corporation. All rights reserved.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>dotnet run
```

```
Using launch settings from C:\Users\Matej\Desktop\ASP.NET
```

```
\PostMatchSummary\Properties\launchSettings.json...
```

```
Building...
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Program.cs(1,1): error CS8802:
```

```
Only one compilation unit can have top-level statements.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Program.cs(1,1): error CS8802: Only one  
compilation unit can have top-level statements.
```

The build failed. Fix the build errors and run again.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>
```

ovo kad odem dotnet run u postmatchsummary folderu u asp.net projektu

Greška je jasna — imaš dva filea s top-level statements, a C# dozvoljava samo jedan u cijelom projektu:^[26]

- `PostMatchSummary/Program.cs` ← pravi entry point aplikacije ✓
- `PostMatchSummary/Models/Program.cs` ← ovo uzrokuje konflikt ✗

Kako popraviti

`Models/Program.cs` vjerojatno treba biti klasa, ne standalone top-level kod. Otvori taj file i umotaj sadržaj u namespace i class:

Prije (što vjerojatno piše):

```
// neki kod direktno ovdje
```

Nakon (ispravno):

```
namespace PostMatchSummary.Models  
{  
    public class Program  
    {  
        // sadržaj filea ovdje  
    }  
}
```

Brzi koraci

1. Otvori `Models/Program.cs` u editoru
2. Provjeri što piše unutra — ako je to model (npr. League champion "Program" skin line), samo ga umotaj u klasu kao gore
3. Spremi i opet pokreni `dotnet run`

Savjet: Ime `Program.cs` u `Models` folderu je zbunjujuće — razmisli o preimenovanju u npr. `ProgramChampion.cs` ili sl. da izbjegneš ovakve konflikte u budućnosti.

Možeš paste-ati sadržaj tog `Models/Program.cs` filea da ti kažem točno što treba promijeniti?

✱✱

```
var matches = new List<Match>();
```

```
var match1 = new Match
{
    MatchId = "1",
    GameCreation = DateTime.Now,
    Duration = 1800,
    Players = new List<Player>()
};
```

```
var match2 = new Match
{
    MatchId = "2",
    GameCreation = DateTime.Now,
    Duration = 2000,
    Players = new List<Player>()
};
```

```
matches.Add(match1);
matches.Add(match2);
```

```
// svi match-evi duži od 1900 sekundi
var longMatches = matches
    .Where(m => m.Duration > 1900)
    .ToList();
```

```
// prvi match
var firstMatch = matches.FirstOrDefault();
```

```
// broj match-eva
var count = matches.Count();
```

ovo je u `models`

```

a ovo ispod u foleru postmatchsummary
var builder = WebApplication.CreateBuilder(args);

// Add services to the container.
builder.Services.AddControllersWithViews();

var app = builder.Build();

// Configure the HTTP request pipeline.
if (!app.Environment.IsDevelopment())
{
    app.UseExceptionHandler("/Home/Error");
    // The default HSTS value is 30 days. You may want to change this for production scenarios, see
    https://aka.ms/aspnetcore-hsts.
    app.UseHsts();
}

app.UseHttpsRedirection();
app.UseRouting();

app.UseAuthorization();

app.MapStaticAssets();

app.MapControllerRoute(
    name: "default",
    pattern: "{controller=Home}/{action=Index}/{id?}")
    .WithStaticAssets();

app.Run();

```

Problem je što `Models/Program.cs` sadrži **test/scratch kod** koji nisi trebao commitati tamo — to su samo privremeni testovi LINQ querija, nije pravi model.

Rješenje — izbriši taj file

`Models/Program.cs` nema nikakve vrijednosti u projektu, to je bio samo test kod. Jednostavno ga **obriši**:

```
del "C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Program.cs"
```

Ili ga ručno obriši u File Exploreru / Visual Studiju.

Zašto ne treba wrap u klasu?

Taj kod nije model — nema smisla stavljati ga u klasu jer samo kreira `Match` objekte i radi LINQ filter. To je bio scratch/debug kod koji je slučajno završio u pogrešnom folderu.

Nakon brisanja

```
dotnet run
```

Trebalo bi raditi bez grešaka. Prava `Program.cs` u korijenu projekta (ona s `WebApplication.CreateBuilder`) ostaje i služi kao entry point aplikacije. ^[27]

✱✱

Microsoft Windows [Version 10.0.19044.6809]

(c) Microsoft Corporation. All rights reserved.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>dotnet run
```

```
Using launch settings from C:\Users\Matej\Desktop\ASP.NET\
\PostMatchSummary\Properties\launchSettings.json...
```

```
Building...
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Program.cs(1,1): error CS8802: Only one
compilation unit can have top-level statements.
```

The build failed. Fix the build errors and run again.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>
```

nakon brisanja `program.cs` iz `models`a

Još uvijek postoji drugi file s top-level statementima. Primjeti da si imao `Main.cs` u `Models` folderu — to je vjerojatno novi krivac!

Provjeri Models/Main.cs

Otvori `Models/Main.cs` i paste-aj sadržaj ovdje. Gotovo sigurno ima sličan scratch kod kao i stari `Program.cs`.

Ako da, obriši i njega:

```
del "C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Main.cs"
```

Kako pronaći sve problematične fileove odjednom

Pokreni ovo u terminalu da vidiš sve `.cs` fileove koji imaju top-level statements (kod izvan klase/namespaca):

```
findstr /r /l /s "^var \|^using \|^new " "*.cs"
```

Generalno, svaki `.cs` file u `Models` folderu treba imati strukturu ovog oblika — ako file počinje direktno s `var`, `new`, `LINQ` itd. bez namespace/class — to je problem.

```
namespace PostMatchSummary.Models
{
    public class NeštoModel
    {
        // properties ovdje
    }
}
```

Što piše u `Main.cs`?

`static void Main(string[] args)`

```
{
    var service = new RiotService();

    var task = service.GetMatchAsync("EUW1_7796385639");

    task.Wait();

    var json = task.Result;

    Console.WriteLine(json);
}
```

To je bio **test file** za ručno testiranje `RiotService` — više ti ne treba u ASP.NET projektu jer se servis poziva kroz controller, ne kroz `Main`.

Rješenje — obriši `Models/Main.cs`

```
del "C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models>Main.cs"
```

Zašto je to bio problem?

`static void Main(string[] args)` je entry point konzolne aplikacije. C# kompajler ne zna koji entry point koristiti kada vidi i taj `Main` i top-level statements u `Program.cs` — pa baca CS8802 grešku.

ASP.NET Core projekt već ima svoj entry point u `Program.cs` (onaj s `WebApplication.CreateBuilder`), pa `Main.cs` nije potreban.

Nakon brisanja

```
dotnet run
```

Sada bi trebalo buildati i pokrenuti bez grešaka. ☑

Microsoft Windows [Version 10.0.19044.6809]

(c) Microsoft Corporation. All rights reserved.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>dotnet run
```

```
Using launch settings from C:\Users\Matej\Desktop\ASP.NET
```

```
\PostMatchSummary\Properties\launchSettings.json...
```

```
Building...
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\MatchSummary.cs(3,19):
```

```
warning CS8618: Non-nullable property 'MatchId' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Player.cs(3,19): warning CS8618:
```

```
Non-nullable property 'SummonerName' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Team.cs(6,25): warning CS8618:
```

```
Non-nullable property 'Players' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Player.cs(4,19): warning CS8618:
```

```
Non-nullable property 'Champion' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\MatchSummary.cs(4,19):
```

```
warning CS8618: Non-nullable property 'WinnerTeam' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Player.cs(9,17): warning CS8618:
```

```
Non-nullable property 'Team' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Champion.cs(3,19): warning
```

```
CS8618: Non-nullable property 'Name' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\RiotResponse.cs(3,18): warning
```

```
CS8618: Non-nullable property 'Info' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Match.cs(3,19): warning CS8618:
```

```
Non-nullable property 'MatchId' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Match.cs(7,25): warning CS8618:
```

```
Non-nullable property 'Players' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Models\Match.cs(8,23): warning CS8618:
```

```
Non-nullable property 'Teams' must contain a non-null value when exiting constructor. Consider adding the 'required' modifier or declaring the property as nullable.
```

```
info: Microsoft.Hosting.Lifetime[14]
```

```
Now listening on: http://localhost:5044
```

```
info: Microsoft.Hosting.Lifetime[0]
```

```
Application started. Press Ctrl+C to shut down.
```

info: Microsoft.Hosting.Lifetime[0]
Hosting environment: Development
info: Microsoft.Hosting.Lifetime[0]
Content root path: C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary
warn: Microsoft.AspNetCore.HttpsPolicy.HttpsRedirectionMiddleware[3]
Failed to determine the https port for redirect.

Projekt radi! 🎉 Vidiš default ASP.NET stranicu na `http://localhost:5044` — to je uspjeh. ^[28]

Što su te poruke?

Warnings (upozorenja) — nisu greške, build je prošao i aplikacija se pokrenula. Možeš ih ignorirati za sada. Znače da tvoji modeli imaju `string` i `List` propertyje koji nisu inicijalizirani na null-safe način, npr:

```
// Trenutno (warning)
public string MatchId { get; set; }

// Opcija 1 - nullable (dodaj ?)
public string? MatchId { get; set; }

// Opcija 2 - required modifier
public required string MatchId { get; set; }
```

Failed to determine the https port — samo znači da HTTPS redirect ne radi jer nemaš SSL cert konfiguriran, ali HTTP na portu 5044 radi normalno.

Sljedeći korak

Tvoj projekt ima `PostMatchController` — idi na:

```
http://localhost:5044/PostMatch
```

To bi trebao biti tvoj glavni view s match summary podacima. Ako baca grešku, paste-aj je ovdje pa gledamo zajedno.

✖

An unhandled exception occurred while processing the request.

`InvalidOperationException: Unable to resolve service for type 'RiotService' while attempting to activate 'PostMatchController'.`

`Microsoft.Extensions.DependencyInjection.ActivatorUtilities.ThrowHelper.UnableToResolveService(Type type, Type requiredBy)`

Stack

Query

Cookies

Headers

Routing

InvalidOperationException: Unable to resolve service for type 'RiotService' while attempting to activate 'PostMatchController'.

Microsoft.Extensions.DependencyInjection.ActivatorUtilities.ThrowHelper.UnableToResolveService(Type type, Type requiredBy)

lambda_method31(Closure, IServiceProvider, object[])

Microsoft.AspNetCore.Mvc.Controllers.ControllerFactoryProvider+<>c__DisplayClass6_0.

<CreateControllerFactory>g__CreateController|0(ControllerContext controllerContext)

Microsoft.AspNetCore.Mvc.Infrastructure.ControllerActionInvoker.Next(ref State next, ref Scope scope, ref object state, ref bool isCompleted)

Microsoft.AspNetCore.Mvc.Infrastructure.ControllerActionInvoker.InvokeInnerFilterAsync()

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.

<InvokeNextResourceFilter>g__Awaited|25_0(ResourceInvoker invoker, Task lastTask, State next, Scope scope, object state, bool isCompleted)

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.Rethrow(ResourceExecutedContextSealed context)

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.Next(ref State next, ref Scope scope, ref object state, ref bool isCompleted)

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.InvokeFilterPipelineAsync()

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.

<InvokeAsync>g__Awaited|17_0(ResourceInvoker invoker, Task task, IDisposable scope)

Microsoft.AspNetCore.Mvc.Infrastructure.ResourceInvoker.

<InvokeAsync>g__Awaited|17_0(ResourceInvoker invoker, Task task, IDisposable scope)

Microsoft.AspNetCore.Authorization.AuthorizationMiddleware.Invoke(HttpContext context)

Microsoft.AspNetCore.Authentication.AuthenticationMiddleware.Invoke(HttpContext context)

Microsoft.AspNetCore.Diagnostics.DeveloperExceptionPageMiddlewareImpl.Invoke(HttpContext context)

Show raw exception details

Greška je jasna — `RiotService` nije registriran u `Dependency Injection containeru`. ASP.NET Core ne zna kako ga kreirati kada ga `PostMatchController` traži.

Rješenje — dodaj u `Program.cs`

Otvori `Program.cs` (u korijenu projekta) i dodaj jednu liniju prije `builder.Build()`:

```
var builder = WebApplication.CreateBuilder(args);

// Add services to the container.
builder.Services.AddControllersWithViews();
builder.Services.AddHttpClient<RiotService>(); // ← DODAJ OVO

var app = builder.Build();
```

Koristi `AddHttpClient<RiotService>()` jer tvoj `RiotService` vjerojatno koristi `HttpClient` za pozivanje Riot API-ja.

Ako `RiotService` ne koristi `HttpClient`

Koristi jednostavniji oblik:

```
builder.Services.AddScoped<RiotService>();
```

Nakon izmjene

Spremi, zaustavi server (Ctrl+C), pa opet:

```
dotnet run
```

Iodina `http://localhost:5044/PostMatch` — sada bi trebao raditi bez greške. Paste-aj sadržaj `RiotServices.cs` ako nisi siguran koja varijanta ti treba.

using LeagueOfLegendsApp.Services;

```
var builder = WebApplication.CreateBuilder(args);
```

```
// Add services to the container.
```

```
builder.Services.AddControllersWithViews();
```

```
builder.Services.AddHttpClient<RiotService>(); // ← DODAJ OVO
```

```
var app = builder.Build();
```

```
// Configure the HTTP request pipeline.
```

```
if (!app.Environment.IsDevelopment())
```

```
{
```

```
    app.UseExceptionHandler("/Home/Error");
```

```
    // The default HSTS value is 30 days. You may want to change this for production scenarios, see
```

```
https://aka.ms/aspnetcore-hsts.
```

```
    app.UseHsts();
```

```
}
```

```
app.UseHttpsRedirection();
```

```
app.UseRouting();
```

```
app.UseAuthorization();
```

```
app.MapStaticAssets();
```

```
app.MapControllerRoute(
```

```
    name: "default",
```

```
    pattern: "{controller=Home}/{action=Index}/{id?}")
```

```
    .WithStaticAssets();
```

```
app.Run();
```

Problem je **pogrešan namespace** u `using` liniji! Projekt se zove `PostMatchSummary`, ali pišeš `LeagueOfLegendsApp.Services` — taj namespace ne postoji.

Ispravi using liniju

```
// Pogrešno:  
using LeagueOfLegendsApp.Services;  
  
// Ispravno:  
using PostMatchSummary.Services;
```

Dakle cijeli `Program.cs` treba izgledati ovako:

```
using PostMatchSummary.Services;  
  
var builder = WebApplication.CreateBuilder(args);  
  
builder.Services.AddControllersWithViews();  
builder.Services.AddHttpClient<RiotService>();  
  
var app = builder.Build();  
  
if (!app.Environment.IsDevelopment())  
{  
    app.UseExceptionHandler("/Home/Error");  
    app.UseHsts();  
}  
  
app.UseHttpsRedirection();  
app.UseRouting();  
app.UseAuthorization();  
app.MapStaticAssets();  
  
app.MapControllerRoute(  
    name: "default",  
    pattern: "{controller=Home}/{action=Index}/{id?}"  
    .WithStaticAssets());  
  
app.Run();
```

Spremi, `Ctrl+C`, `dotnet run` i probaj opet `/PostMatch`. ☒

(c) Microsoft Corporation. All rights reserved.

```
C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>dotnet run  
Using launch settings from C:\Users\Matej\Desktop\ASP.NET  
\PostMatchSummary\Properties\launchSettings.json...  
Building...
```

C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary\Program.cs(1,24): error CS0234: The type or namespace name 'Services' does not exist in the namespace 'PostMatchSummary' (are you missing an assembly reference?)

The build failed. Fix the build errors and run again.

C:\Users\Matej\Desktop\ASP.NET\PostMatchSummary>

Greška znači da `RiotServices.cs` nema dobar namespace deklariran unutar filea. Paste-aj sadržaj `Services/RiotServices.cs` da vidim što piše, ali najvjerojatnije nedostaje ili je pogrešan namespace.

Brzi fix — provjeri `RiotServices.cs`

Otvori `Services/RiotServices.cs` i provjeri je li na vrhu filea:

```
namespace PostMatchSummary.Services // ← mora točno ovako pisati
{
    public class RiotService
    {
        // ...
    }
}
```

Ako piše nešto drugo (npr. `LeagueOfLegendsApp.Services`, ili uopće nema namespace), ispravi na `PostMatchSummary.Services`.

Alternativno rješenje — bez using

Ako ne želiš dirati `RiotServices.cs`, možeš ukloniti `using` liniju iz `Program.cs` i koristiti puni naziv:

```
// Makni: using PostMatchSummary.Services;

builder.Services.AddHttpClient<PostMatchSummary.Services.RiotService>();
```

Paste-aj sadržaj `RiotServices.cs` pa ćemo točno vidjeti što treba promijeniti.

evo ti sve pa mi reci

Vidim problem! `RiotServices.cs` nema **nikakav namespace** — klasa je u globalnom namespace-u, a ti pokušavaš koristiti `PostMatchSummary.Services` koji ne postoji.^[29]

Imaš dvije opcije:

Opcija 1 — Dodaj namespace u RiotServices.cs (preporučeno)

Otvori `Services/RiotServices.cs` i dodaj namespace na vrh:

```
using System.Net.Http;
using System.Threading.Tasks;

namespace PostMatchSummary.Services // ← DODAJ OVO
{
    public class RiotService
    {
        private string apiKey = "RGAPI-...";

        public async Task<string> GetMatchAsync(string matchId)
        {
            using var client = new HttpClient();
            client.DefaultRequestHeaders.Add("X-Riot-Token", apiKey);
            string url = $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}";
            var response = await client.GetAsync(url);
            return await response.Content.ReadAsStringAsync();
        }
    }
}
```

Opcija 2 — Makni using iz Program.cs

Ako ne želiš dirati `RiotServices.cs`, u `Program.cs` makni `using` i koristi `AddScoped`:

```
// Makni: using PostMatchSummary.Services;

builder.Services.AddScoped<RiotService>(); // radi jer je u global namespace-u
```

⚠ **Važno:** Tvoj API key je vidljiv u kodu (RGAPI-603eb17f-...) — taj key je vjerojatno već expiran jer Riot Development keyevi traju 24h, ali svakako ga makni iz koda i stavi u `appsettings.json`.^[29]

Preporučam Opciju 1 — dodaj namespace, to je čistije. Nakon toga `dotnet run` bi trebao proći. ☑

✱

ajde mi samo daj full klase napisane

Evo svih fileova ispravljenih s pravilnim namespaceima:

Program.cs

```
using PostMatchSummary.Services;

var builder = WebApplication.CreateBuilder(args);
```

```

builder.Services.AddControllersWithViews();
builder.Services.AddHttpClient<RiotService>();

var app = builder.Build();

if (!app.Environment.IsDevelopment())
{
    app.UseExceptionHandler("/Home/Error");
    app.UseHsts();
}

app.UseHttpsRedirection();
app.UseRouting();
app.UseAuthorization();
app.MapStaticAssets();

app.MapControllerRoute(
    name: "default",
    pattern: "{controller=Home}/{action=Index}/{id?}")
    .WithStaticAssets();

app.Run();

```

Services/RiotServices.cs

```

using System.Net.Http;
using System.Threading.Tasks;

namespace PostMatchSummary.Services
{
    public class RiotService
    {
        private readonly HttpClient _httpClient;
        private string apiKey = "TV0J-API-KEY-OVDJE";

        public RiotService(HttpClient httpClient)
        {
            _httpClient = httpClient;
        }

        public async Task<string> GetMatchAsync(string matchId)
        {
            _httpClient.DefaultRequestHeaders.Remove("X-Riot-Token");
            _httpClient.DefaultRequestHeaders.Add("X-Riot-Token", apiKey);
            string url = $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}";
            var response = await _httpClient.GetAsync(url);
            return await response.Content.ReadAsStringAsync();
        }
    }
}

```

Controllers/PostMatchController.cs

```
using Microsoft.AspNetCore.Mvc;
using PostMatchSummary.Services;
using System.Threading.Tasks;

namespace PostMatchSummary.Controllers
{
    public class PostMatchController : Controller
    {
        private readonly RiotService _riotService;

        public PostMatchController(RiotService riotService)
        {
            _riotService = riotService;
        }

        public async Task<IActionResult> Index(string matchId)
        {
            var data = await _riotService.GetMatchAsync(matchId);
            return View("Index", data);
        }
    }
}
```

Models/Match.cs

```
namespace PostMatchSummary.Models
{
    public class Match
    {
        public string MatchId { get; set; } = string.Empty;
        public DateTime GameCreation { get; set; }
        public int Duration { get; set; }
        public List<Player> Players { get; set; } = new();
        public List<Team> Teams { get; set; } = new();
    }
}
```

Models/Player.cs

```
namespace PostMatchSummary.Models
{
    public class Player
    {
        public string SummonerName { get; set; } = string.Empty;
        public string Champion { get; set; } = string.Empty;
        public int Kills { get; set; }
        public int Deaths { get; set; }
        public int Assists { get; set; }
    }
}
```

```

        public Team Team { get; set; } = new();
    }
}

```

Models/Team.cs

```

namespace PostMatchSummary.Models
{
    public class Team
    {
        public int TeamId { get; set; }
        public bool Win { get; set; }
        public List<Player> Players { get; set; } = new();
    }
}

```

Models/MatchSummary.cs

```

namespace PostMatchSummary.Models
{
    public class MatchSummary
    {
        public string MatchId { get; set; } = string.Empty;
        public string WinnerTeam { get; set; } = string.Empty;
        public int TotalKills { get; set; }
    }
}

```

Models/RiotResponse.cs

```

namespace PostMatchSummary.Models
{
    public class RiotResponse
    {
        public object? Info { get; set; }
    }
}

```

Zamijeni sve fileove ovim sadržajem, pa dotnet run. Ključne promjene su: svi modeli dobili namespace PostMatchSummary.Models, RiotService dobio namespace PostMatchSummary.Services i prima HttpClient kroz DI umjesto da ga kreira sam.^[47]

I dobro i gdje dobijem ispis traženih podataka

Moraš otići na URL s `matchId` parametrom u query stringu:^[56]

```
http://localhost:5044/PostMatch?matchId=EUW1_7796385639
```

`PostMatchController.Index` prima `matchId` kao parametar iz URL-a, šalje request na Riot API i vraća raw JSON koji se prikazuje u `<pre>` tagu na stranici.^[57]

Kako dobiti validan `matchId`?

Riot API match ID-evi izgledaju ovako: `EUW1_` + broj. Možeš ih dobiti:

1. Riot Developer Portal — <https://developer.riotgames.com> → API Explorer
2. Direktno API pozivom za nekog igrača:

```
https://europe.api.riotgames.com/lol/match/v5/matches/by-puuid/{PUUID}/ids
```

3. OP.GG ili League of Graphs — otvori neki match i iz URL-a izvuci ID

Što ćeš vidjeti

Na stranici će se ispisati sirovi JSON od Riot API-ja — sve informacije o matchu (igrači, championsi, KDA, trajanje...). Ako dobiješ 403 Forbidden, znači da ti je API key **expirao** — Riot development keyevi traju samo 24h pa trebaš generirati novi na developer.riotgames.com.



Match Data

```
{"status":{"message":"Forbidden","status_code":401}}
```

Očekivano — API key je **expirao**. Riot Development keyevi traju samo 24 sata.

Koraci za novi key

1. Idi na developer.riotgames.com
2. Prijavi se s League of Legends računom
3. Na dashboardu klikni "Regenerate" pored Development API Key
4. Kopiraj novi key (izgleda kao `RGAPI-xxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx`)

Gdje ga upisat u projektu

Otvori `Services/RiotServices.cs` i zamijeni stari key:

```
private string apiKey = "RGAPI-NOVI-KEY-OVDJE";
```

Spremi, `Ctrl+C`, `dotnet run`, pa opet probaj:

```
http://localhost:5044/PostMatch?matchId=EUW1_7796385639
```

⚠ Svaki put kad pokrećeš projekt za razvoj, provjeri je li key još validan — expira točno 24h nakon generiranja.

Imam dobar key, generiran prije 1h

Onda je problem što key nije ispravno proslijeđen u headeru. Provjeri `RiotServices.cs` — ako si koristio moju verziju s `AddHttpClient<RiotService>()`, problem može biti što se header dodaje više puta.

Ispravi `GetMatchAsync` ovako:

```
public async Task<string> GetMatchAsync(string matchId)
{
    using var request = new HttpRequestMessage(HttpMethod.Get,
        $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}");

    request.Headers.Add("X-Riot-Token", apiKey);

    var response = await _httpClient.SendAsync(request);
    return await response.Content.ReadAsStringAsync();
}
```

Alternativno — testiraj key direktno u browseru

Otvori ovaj URL direktno (zamijeni key):

```
https://europe.api.riotgames.com/lol/match/v5/matches/EUW1_7796385639?api_key=RGAPI-TV0J
```

Riot API podržava i `api_key` kao query parametar — ako ovo radi u browseru a projekt ne, znači da je problem u headeru unutar koda. Ako ni ovo ne radi, key nije valjan.

Što dobiveš kad testiraš direktno u browseru?

a gdje je taj async

U `Services/RiotServices.cs` — zamijeni cijelu `GetMatchAsync` metodu:

```
namespace PostMatchSummary.Services
{
    public class RiotService
    {
        private readonly HttpClient _httpClient;
        private string apiKey = "RGAPI-TV0J-KEY-OVDJE";

        public RiotService(HttpClient httpClient)
        {
            _httpClient = httpClient;
        }

        public async Task<string> GetMatchAsync(string matchId)
        {
            using var request = new HttpRequestMessage(HttpMethod.Get,
                $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}");

            request.Headers.Add("X-Riot-Token", apiKey);

            var response = await _httpClient.SendAsync(request);
            return await response.Content.ReadAsStringAsync();
        }
    }
}
```

Spremi → `Ctrl+C` → `dotnet run` → probaj opet URL. Što piše u browseru kad testiraš key direktno?

Match Data

```
{"metadata":{"dataVersion":"2","matchId":"EUW1_7796385639","participants":
["E5HqRAUQiffhAL52ujlD9TAo_rwM8a_JT65osce_c61-
ou68OWNv5RdkmUvd6Bg2AvTMwgb3Wmxvw","oM0e5ckTrND5
```

dobio sam nesto ovako dugacko jako

Radi! ☑ To je raw JSON od Riot API-ja s kompletnim podacima o matchu.

Što sad možeš napraviti

Trenutno view samo ispisuje sirovi JSON kao tekst. Sljedeći logičan korak je **parsati taj JSON u C# modele** i prikazati ga lijepo u HTML tablici.

Trebat ćeš:

1. **Deserijalizirati JSON** u `RiotResponse` model koristeći `System.Text.Json`
2. **Prikazati podatke** u Razor viewu — igrači, championsi, KDA...

Želiš da ti napišem kako parsati taj JSON i prikazati ga kao normalnu stranicu s tablicom igrača, ili je za sada dovoljno da radi ovako s raw JSONom?

Hocu ga parsati

Trebamo napraviti 4 stvari: novi modeli za JSON strukturu, update controllera, i novi view.

1. Models/RiotResponse.cs

```
using System.Text.Json.Serialization;

namespace PostMatchSummary.Models
{
    public class RiotResponse
    {
        [JsonPropertyName("metadata")]
        public Metadata Metadata { get; set; } = new();

        [JsonPropertyName("info")]
        public MatchInfo Info { get; set; } = new();
    }

    public class Metadata
    {
        [JsonPropertyName("matchId")]
        public string MatchId { get; set; } = string.Empty;
    }

    public class MatchInfo
    {
        [JsonPropertyName("gameDuration")]
        public int GameDuration { get; set; }

        [JsonPropertyName("gameMode")]
        public string GameMode { get; set; } = string.Empty;

        [JsonPropertyName("participants")]
        public List<Participant> Participants { get; set; } = new();
    }

    public class Participant
    {
        [JsonPropertyName("summonerName")]
        public string SummonerName { get; set; } = string.Empty;

        [JsonPropertyName("riotIdGameName")]
        public string RiotIdGameName { get; set; } = string.Empty;

        [JsonPropertyName("championName")]
        public string ChampionName { get; set; } = string.Empty;

        [JsonPropertyName("kills")]
        public int Kills { get; set; }
    }
}
```

```

        [JsonPropertyName("deaths")]
        public int Deaths { get; set; }

        [JsonPropertyName("assists")]
        public int Assists { get; set; }

        [JsonPropertyName("totalMinionsKilled")]
        public int CS { get; set; }

        [JsonPropertyName("goldEarned")]
        public int GoldEarned { get; set; }

        [JsonPropertyName("win")]
        public bool Win { get; set; }

        [JsonPropertyName("teamId")]
        public int TeamId { get; set; }
    }
}

```

2. Services/RiotServices.cs

```

using System.Text.Json;
using PostMatchSummary.Models;

namespace PostMatchSummary.Services
{
    public class RiotService
    {
        private readonly HttpClient _httpClient;
        private string apiKey = "RGAPI-TV0J-KEY-OVDJE";

        public RiotService(HttpClient httpClient)
        {
            _httpClient = httpClient;
        }

        public async Task<RiotResponse?> GetMatchAsync(string matchId)
        {
            using var request = new HttpRequestMessage(HttpMethod.Get,
                $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}");

            request.Headers.Add("X-Riot-Token", apiKey);

            var response = await _httpClient.SendAsync(request);
            var json = await response.Content.ReadAsStringAsync();

            return JsonSerializer.Deserialize<RiotResponse>(json);
        }
    }
}

```

3. Controllers/PostMatchController.cs

```
using Microsoft.AspNetCore.Mvc;
using PostMatchSummary.Services;

namespace PostMatchSummary.Controllers
{
    public class PostMatchController : Controller
    {
        private readonly RiotService _riotService;

        public PostMatchController(RiotService riotService)
        {
            _riotService = riotService;
        }

        public async Task<IActionResult> Index(string matchId)
        {
            var data = await _riotService.GetMatchAsync(matchId);
            return View(data);
        }
    }
}
```

4. Views/PostMatch/Index.cshtml

```
@model PostMatchSummary.Models.RiotResponse

<h2>Match: @Model.Metadata.MatchId</h2>
<p>Trajanje: @(Model.Info.GameDuration / 60) min | Mode: @Model.Info.GameMode</p>

@foreach (var team in Model.Info.Participants.GroupBy(p => p.TeamId))
{
    var won = team.First().Win;
    <h3>Tim @team.Key – @(won ? "✓ Pobjeda" : "✗ Poraz")</h3>
    <table border="1" cellpadding="6">
        <thead>
            <tr>
                <th>Igrač</th>
                <th>Champion</th>
                <th>K/D/A</th>
                <th>CS</th>
                <th>Gold</th>
            </tr>
        </thead>
        <tbody>
            @foreach (var p in team)
            {
                <tr>
                    <td>@(string.IsNullOrEmpty(p.RiotIdGameName) ? p.SummonerName : p.F
                    <td>@p.ChampionName</td>
                    <td>@p.Kills/@p.Deaths/@p.Assists</td>
                    <td>@p.CS</td>
```

```

        <td>@p.GoldEarned</td>
    </tr>
}
</tbody>
</table>
}

```

dotnet run pa idina:

```
http://localhost:5044/PostMatch?matchId=EUW1_7796385639
```

Treba o bi vidjeti lijepu tablicu s dva tima, igračima i njihovim KDA statistikama.☒

An unhandled exception occurred while processing the request.

InvalidOperationException: The view '{'metadata':

{"dataVersion":2,"matchId":"EUW1_7796385639","participants":

["E5HqRAUQiffhAL52ujylD9TAo_rwM8a_JT65osce_c61-

ou68OWNv5RdkmUvd6Bg2AvTMwgb3Wmxvw","oM0e5ckTrND5LcFMnKDDvdyQAeVYEP6o3Iwy1FaA-

dko3Am4KBsq8G7t4kqROXyvOp28lwgXyOv5w","9tAtIHnOkHNUU0q7jXLKvpoad2n2eTf2hJNJqCLEWhrdn1bUdwc9Mb0xuZuPsL_RCEM7aoqaNNArw","2nQO588pbuuLS8XYJfFmk1MX-ZMhSu_isCyP90IHgPdNufRlZTfTXOKVaw2QsCnTir2J6rj874xZbA","p4MSfH5rXQQ57fnLLN2h3i2jOS5R9IV99rrkfSBKR-ozq0uvjjGIqY_uYCt-

ZmtdHegdbihhsmhrtQ","aRZHKlm8mt1ht6LnjZSRfl3lUgG9FuC9Qs18ge6w9K2UJA71KSR0o4PFCcMg8yAdvW868VlMm5AZg","R3EYf6JwIZYpCClWNNdQf_uIUbVhGuqXuY1jyJxAg2afB_I5ZQDXKfLpO4LhVdPFG4SKELIye4EDZA","LxlNIWkIAojxKEDSseE5Lw8Jp1H2EoOSfQ5mJEtdvdRhsf5829IHVJUUhLbNh1vwX1xp6IpRuofcMlg","OMB92kJbLV7sFuKpYLwSot5h6Zf67YyYL_DN6JO09behrmdaBEK_y2Q763lQyiuB6sJrLZWxwrE73g","9B2bf4Alq1sVV5sh73MUea4IPBHnYXTnI50cY5M9ea7Yxy81sS5rRonvWMvMjuYnYaf5cM8DOZRdXA"]},"info":

{"endOfGameResult":"GameComplete","gameCreation":1774350929484,"gameDuration":2352,"gameEndTimestamp":1774353298562,"gameId":7796385639,"gameMode":"CLASSIC","gameName":"team builder-match-

7796385639","gameStartTimestamp":1774350946674,"gameType":"MATCHED_GAME","gameVersion":"16.6756931","mapId":11,"participants":{"PlayerBehavior":

{"PlayerBehavior_IsHeroInCombat":0,"PlayerScore0":0,"PlayerScore1":0,"PlayerScore10":0,"PlayerScore11":0,"PlayerScore2":0,"PlayerScore3":0,"PlayerScore4":0,"PlayerScore5":0,"PlayerScore6":0,"PlayerScore7":0,"PlayerScore8":0,"PlayerScore9":0,"allInPings":0,"assistMePings":0,"assists":8,"baronKills":0,"basicPings":0,"challenges":

{"12AssistStreakCount":0,"HealFromMapSources":1176.4481048583984,"InfernalScalePickup":0,"SWARM_DefeatAatrox":0,"SWARM_DefeatBriar":0,"SWARM_DefeatMiniBosses":0,"SWARM_EvolveWeapon":0,"SWARM_Have3Passives":0,"SWARM_KillEnemy":0,"SWARM_PickupGold":0,"SWARM_ReachLevel50":0,"SWARM_Survive15Min":0,"SWARM_WinWith5EvolvedWeapons":0,"abilityUses":464,"acesBefore15Minutes":0,"alliedJungleMonsterKills":0,"baronBuffGoldAdvantageOverThreshold":1,"baronTakedowns":1,"blastConeOppositeOpponentCount":0,"bountyGold":0,"buffsStol

en":0,"completeSupportQuestInTime":0,"controlWardsPlaced":0,"damagePerMinute":709.234088081006,"damageTakenOnTeamPercentage":0.24536141431676436,"dancedWithRiftHerald":0,"deathsByEnemyChamps":3,"dodgeSkillShotsSmallWindow":0,"doubleAces":0,"dragonTakedowns":1,"earliestBaron":1726406115538,"earliestDragonTakedown":1134.5085056100002,"earlyLaningPhaseGoldExpAdvantage":0,"effectiveHealAndShielding":3520.75732421875,"elderDragonKillsWithOpposingSoul":0,"elderDragonMultikills":0,"enemyChampionImmobilizations":83,"enemyJungleMonsterKills":3,"epicMonsterKillsNearEnemyJungler":0,"epicMonsterKillsWithin30SecondsOfSpawn":0,"epicMonsterSteals":0,"epicMonsterStolenWithoutSmite":0,"firstTurretKilled":1,"firstTurretKilledTime":880.8083404140001,"fistBumpParticipation":0,"flawlessAces":0,"fullTeamTakedown":0,"gameLength":2352.226227523,"getTakedownsInAllLanesEarlyJungleAsLaner":0,"goldPerMinute":408.21361078432284,"hadOpenNexus":0,"immobilizeAndKillWithAlly":7,"initialBuffCount":0,"initialCrabCount":0,"jungleCsBefore10Minutes":0,"junglerTakedownsNearDamagedEpicMonster":0,"kTurretsDestroyedBeforePlatesFall":0,"kda":5,"killAfterHiddenWithAlly":1,"killParticipation":0.40540540540540543,"killedChampTookFullTeamDamageSurvived":0,"killingSprees":1,"killsNearEnemyTurret":3,"killsOnOtherLanesEarlyJungleAsLaner":0,"killsOnRecentlyHealedByAramPack":0,"killsUnderOwnTurret":0,"killsWithHelpFromEpicMonster":0,"knockEnemyIntoTeamAndKill":8,"landSkillShotsEarlyGame":0,"laneMinionsFirst10Minutes":81,"laningPhaseGoldExpAdvantage":0,"legendaryCount":0,"legendaryItemUsed":[6662,6665,2504,6664,3075],"lostAnInhibitor":0,"maxCsAdvantageOnLaneOpponent":25.75,"maxKillDeficit":0,"maxLevelLeadLaneOpponent":3,"mejaisFullStackInTime":0,"moreEnemyJungleThanOpponent":0,"multiKillOneSpell":0,"multiTurretRiftHeraldCount":0,"multikills":0,"multikillsAfterAggressiveFlash":0,"outerTurretExecutesBefore10Minutes":0,"outnumberedKills":1,"outnumberedNexusKill":0,"perfectDragonSoulsTaken":0,"perfectGame":0,"pickKillWithAlly":10,"playedChampSelectPosition":1,"poroExplosions":0,"quickCleanse":0,"quickFirstTurret":0,"quickSoloKills":0,"riftHeraldTakedowns":0,"saveAllyFromDeath":0,"scuttleCrabKills":0,"skillshotsDodged":77,"skillshotsHit":0,"snowballsHit":0,"soloBaronKills":0,"soloKills":2,"stealthWardsPlaced":13,"survivedSingleDigitHpCount":0,"survivedThreeImmobilizesInFight":17,"takedownOnFirstTurret":0,"takedowns":15,"takedownsAfterGainingLevelAdvantage":0,"takedownsBeforeJungleMinionSpawn":0,"takedownsFirstXMinutes":4,"takedownsInAlcove":0,"takedownsInEnemyFountain":0,"teamBaronKills":1,"teamDamagePercentage":0.17475951767462683,"teamElderDragonKills":0,"teamRiftHeraldKills":1,"tookLargeDamageSurvived":1,"turretPlatesTaken":10,"turretTakedowns":2,"turretsTakenWithRiftHerald":5,"twentyMinionsIn3SecondsCount":0,"twoWardsOneSweeperCount":0,"unseenRecalls":0,"visionScoreAdvantageLaneOpponent":0.025036334991455078,"visionScorePerMinute":1.227348569444985,"voidMonsterKill":1,"wardTakedowns":4,"wardTakedownsBefore20M":0,"wardsGuarded":2,"champExperience":25570,"champLevel":20,"championId":897,"championName":"K'Sante","championTransform":0,"commandPings":7,"consumablesPurchased":1,"damageDealtToBuildings":8119,"damageDealtToEpicMonsters":2723,"damageDealtToObjectives":10843,"damageDealtToTurrets":8119,"damageSelfMitigated":117176,"dangerPings":0,"deaths":3,"detectorWardsPlaced":0,"doubleKills":0,"dragonKills":0,"eligibleForProgression":true,"enemyMissingPings":2,"enemyVisionPings":0,"firstBloodAssist":false,"firstBloodKill":false,"firstTowerAssist":false,"firstTowerKill":false,"gameEndedInEarlySurrender":false,"gameEndedInSurrender":false,"getBackPings":0,"goldEarned":16003,"goldSpent":16100,"holdPings":0,"individualPosition":"TOP","inhibitorKills":0,"inhibitorTakedowns":0,"inhibitorsLost":3,"item0":6665,"item1":2504,"item2":3047,"item3":6662,"item4":3075,"item5":6664,"item6":3340,"itemsPurchased":21,"killingSprees":1,"kills":7,"lane":"JUNGLE","largestCriticalStrike":6,"largestKillingSpree":7,"largestMultiKill":1,"longestTimeSpentLiving":1997,"magicDamageDealt":16353,"magicDamageDealtToChampions":2554,"magicDamageTaken":15228,"missions":


```
{"playerScore0":0,"playerScore1":0,"playerScore2":0,"playerScore3":0,"playerScore4":0,"playerScore5":0,"playerScore6":0,"playerScore7":0,"playerScore8":0}
```

nesto dugo

Greška je jasna — `RiotServices.cs` još uvijek vraća string umjesto `RiotResponse`, pa controller šalje JSON string kao naziv viewa!

Provjeri je li `RiotServices.cs` ažuriran s mojom verzijom. Metoda mora vraćati `Task<RiotResponse?>`, ne `Task<string>`:

Services/RiotServices.cs — mora biti OVAKO:

```
using System.Text.Json;
using PostMatchSummary.Models;

namespace PostMatchSummary.Services
{
    public class RiotService
    {
        private readonly HttpClient _httpClient;
        private string apiKey = "RGAPI-TV0J-KEY-OVDJE";

        public RiotService(HttpClient httpClient)
        {
            _httpClient = httpClient;
        }

        public async Task<RiotResponse?> GetMatchAsync(string matchId) // ← RiotResponse
        {
            using var request = new HttpRequestMessage(HttpMethod.Get,
                $"https://europe.api.riotgames.com/lol/match/v5/matches/{matchId}");

            request.Headers.Add("X-Riot-Token", apiKey);

            var response = await _httpClient.SendAsync(request);
            var json = await response.Content.ReadAsStringAsync();

            return JsonSerializer.Deserialize<RiotResponse>(json); // ← parsamo JSON!
        }
    }
}
```

Controllers/PostMatchController.cs — mora biti OVAKO:

```
using Microsoft.AspNetCore.Mvc;
using PostMatchSummary.Services;

namespace PostMatchSummary.Controllers
{
    public class PostMatchController : Controller
    {
        private readonly RiotService _riotService;
```

```

        public PostMatchController(RiotService riotService)
        {
            _riotService = riotService;
        }

        public async Task<IActionResult> Index(string matchId)
        {
            var data = await _riotService.GetMatchAsync(matchId);
            return View(data); // ← bez "Index" kao prvi parametar!
        }
    }
}

```

Ctrl+C → dotnet run → probaj ponovo. ☒

PostMatchSummary

Home

Privacy

Match: EUW1_7796385639

Trajanje: 39 min | Mode: CLASSIC

Tim 100 — ✖ Poraz

Igrač Champion K/D/ACSGold

Liuval

KSante

7/3/8

324

16003

bamses ven

Kayn

8/3/12

42

17772

Seijun

Mel

16/9/6

292

20306

FsG kasterZ

Velkoz

5/13/7

230

13745

do not disturb

Amumu

1/12/14

31
10193
Tim 200 — ✓ Pobjeda
IgračChampionK/D/ACSGold
MZIP Westman
Gnar
3/7/6
327
16931
provinko
LeeSin
11/7/14
39
16785
PatatoMajor
Ahri
5/9/14
291
17381
asol 아우렐리온 솔
AurelionSol
19/5/13
279
21125
Tisaur
Leona
1/9/26
33
11493

dobijem ovakav prikaz

Savršeno radi! ☑ Imaš kompletan post-match summary s oba tima, igračima, championima i KDA statistikama.

Sad možeš uljepšati prikaz ako želiš — evo nekoliko ideja što možeš dodati:

Moguća poboljšanja

- CSS stilizacija — bojanje redova po timu (plavo/crveno), highlight pobjedničkog tima
- KDA ratio — izračunati (Kills + Assists) / Deaths i prikazati
- Forma za unos — input polje na stranici umjesto da ručno pišeš matchId u URL
- Lista više matcheva — dohvatiti zadnjih N matcheva nekog igrača po PUUID-u
- Champion ikone — dohvatiti slike iz Riot Data Dragon CDN-a

Što te najviše zanima kao sljedeći korak?

1. <https://learn.microsoft.com/en-us/visualstudio/get-started/csharp/tutorial-aspnet-core?view=visualstudio>
2. <https://learn.microsoft.com/ka-ga/dotnet/core/tools/dotnet-run>
3. image-7.jpg
4. image-9.jpg
5. image-6.jpg
6. image-8.jpg
7. image-10.jpg
8. <https://learn.microsoft.com/en-us/dotnet/core/tools/dotnet-run>
9. https://secretgeek.net/dotnet_run
10. <https://github.com/dotnet/docs/blob/main/docs/core/tools/dotnet-run.md>
11. <https://phaisarn.com/2019/dotnet-core-command/>
12. <https://learn.microsoft.com/en-us/answers/questions/2074809/tutorial-create-an-asp-net-core-app-with-angular-i>
13. <https://support.microsoft.com/hr-hr/office/omogućite-gostima-da-vidite-vaš-projekt-u-project-za-web-81e1c210-74b2-4711-98ab-dea58f1b566b>
14. <https://www.youtube.com/watch?v=7b9l2J6U5lY>
15. <https://support.microsoft.com/hr-hr/office/pokretanje-prezentacije-i-pregledavanje-bilješki-u-prikazu-izlagača-4de90e28-487e-435c-9401-eb49a3801257>
16. <https://softchris.github.io/pages/dotnet-10-commands.html>
17. <https://georgestocker.com/2017/01/30/how-do-i-debug-asp-net-core-1-1-applications-in-visual-studio-2015/>
18. https://web-arhiva.skole.hr/os-dpejacevic-na/upload/os-dpejacevic-na/images/static3/1218/attachment/KAKO_PRIKAZATI_PROJEKT.pdf
19. <https://stackoverflow.com/questions/58978232/can-we-use-dotnet-run-for-running-aspnet-core-application-without-project-file>
20. <https://learn.microsoft.com/en-us/visualstudio/debugger/how-to-enable-debugging-for-aspnet-applications?view=visualstudio>
21. image.jpg
22. image-2.jpg
23. image-3.jpg
24. image-4.jpg
25. image-4.jpg
26. <https://learn.microsoft.com/ka-ga/dotnet/core/tools/dotnet-run>
27. <https://learn.microsoft.com/ka-ga/dotnet/core/tools/dotnet-run>
28. image.jpg
29. RiotServices-11.cs
30. RiotResponse-9.cs
31. Team-10.cs
32. ViewImports-12.cshtml

33. ViewStart-13.cshtml
34. Privacy-15.cshtml
35. Index-15.cshtml
36. Layout.cshtml-17.css
37. Error-19.cshtml
38. Layout-16.cshtml
39. PostMatchController-2.cs
40. HomeController.cs
41. Champion-3.cs
42. ChampionRole-4.cs
43. Match-6.cs
44. ErrorViewModel-5.cs
45. MatchSummary-7.cs
46. Player-8.cs
47. RiotServices-11.cs
48. RiotResponse-9.cs
49. ErrorViewModel-5.cs
50. ChampionRole-4.cs
51. Match-6.cs
52. MatchSummary-7.cs
53. Team-10.cs
54. Player-8.cs
55. Champion-3.cs
56. Index-15.cshtml
57. PostMatchController-2.cs
58. Layout-16.cshtml