

# ScriptingLanguageSpecification

Design Patterns Team

November 29, 2015

## Contents

<b>1</b>	<b>Overview of Scripting Language</b>	<b>1</b>
1.1	Built in functions . . . . .	2
1.1.1	define . . . . .	2
1.1.2	concat-string . . . . .	2
1.1.3	cons . . . . .	2
1.1.4	card . . . . .	2
1.1.5	render . . . . .	3
1.1.6	list . . . . .	3
1.1.7	position-scaled . . . . .	3
1.1.8	leaf-layout . . . . .	3
1.1.9	layout . . . . .	4
1.1.10	family . . . . .	4
1.1.11	eval-file . . . . .	5
1.1.12	Decals . . . . .	5
1.1.13	Position-Scaleds . . . . .	6
1.1.14	Size . . . . .	6
<b>2</b>	<b>Config file</b>	<b>6</b>

## 1 Overview of Scripting Language

For the scripting language, we have choosen a lisp style language. While far from a complete lisp, it has a syntax similar to scheme, and could easily be extended, without breaking existing scripts.

## 1.1 Built in functions

### 1.1.1 define

```
(define name value)
(define fooConstant 3)
```

Assigns to the name the given value. This version does support defining functions atm. (See <http://www.scheme.com/tspl2d/binding.html>)

- Right now, defines may not be nested, and must be done at top level.
- A variable name can't start with a number, to make it determinable from an int atom.
  - It must start with an alpha character.

### 1.1.2 concat-string

Takes in n string, or numbers, returns one string of all those concatenated

```
(concat-string "foo" 3 "bar")
(concat-string "Foo" "bar")
```

### 1.1.3 cons

Takes two arguments, returns a pair holding the two arguments as one object

```
(cons a b)
(cons 1 2)
```

(See [http://download.plt-scheme.org/doc/4.2.4/html/guide/Pairs\\_\\_Lists\\_\\_and\\_\\_Scheme\\_Syntax.html](http://download.plt-scheme.org/doc/4.2.4/html/guide/Pairs__Lists__and__Scheme_Syntax.html))

### 1.1.4 card

Takes a card-size, name, and two layouts, one for the front, one for the back.

```
(card card-size "name" frontLayout backLayout)
```

When a card is rendered, it will pair the layout with the wholeCard position-scaled (0 0 100 100)

### 1.1.5 render

Takes in a single card, a list of cards, or a pair of cards, and 0-n families. Renders them.

```
(render card family)
(render cards family)
(render (cons carda cardb) family)
(render some-cards family0 ... familyn-1)
```

Note: The family is an optional argument, leaving it empty is the same as calling

```
(render cards (family))
```

Which runs render with an empty family.

### 1.1.6 list

Takes in a n arguments, and returns a list of them.

```
(list N0 ... Nn-1)
(list 1 2 3 4 5 6 7)
```

### 1.1.7 position-scaled

Takes in a x-offset%, y-offset%, and a scale-width% and scale-height%, and returns a position-scaled object.

- The two scale arguments are optional, default to 100.

```
(position-scaled x-offset% y-offset% scale-width% scale-height%)
(position-scaled 0 0 50 50)
(define wholeCard (position-scaled 0 0 100 100))
```

### 1.1.8 leaf-layout

Returns a layout. Takes in a decal, or a string. In the event a string is given, the decal will be looked up in the family. This layout can then be used with the above layout function.

```
(layout image)
(layout foobarImage)
(layout "foo")
```

1. Leaf-Layout options A Leaf-Layout can be given a third argument, to determine some extra behavior. Takes an extra parameter, either a W, or an H, A, or O.
  - If W, width will be at most maximum width of an image.
  - If H, height will be at most, maximum height of given image
  - If A, the original aspect ratio will be maintained.
  - If O, original size will be mantained.
  - IF S, stretch to fit.
  - All the options aside S, which does need to, will add transparent padding to return a size render desires.
  - The default is "S", so calling with the "S" argument is the same as not having a third argument

#### 1.1.9 layout

Creates a Layout object. A layout contains 0-n pairs of layouts and position-scaleds. Takes 0-n pairs of layouts and position-scaleds as arguments.

```
(Layout
  (cons layout0 position-scaled0)
  (cons layout1 position-scaled1)
  ...
  (cons layoutn-1 position-scaledn-1))

(Layout
  (cons layoutFoo position-scaledFoo)
  (cons (layout foobarImage) wholeCard)
  (cons (layout "foo") wholeCard)
)
```

#### 1.1.10 family

Creates a map of strings to decals, a family. Takes in a name, and N pairs.

- Requires a family name.
  - The family name is added to the card name when a card is rendered, to avoid name collisions when rendering the same card with multiple families.

- If a multiple families given, append the names of all the families.

```
(family name pair0 ... pairn-1)
(family "fooFamily" (cons "foo" fooImage) (cons "bar" barImage))
```

#### 1.1.11 eval-file

Takes in n filepaths, evals each file in given order

```
(eval-file "filename.filename")
(eval-file "foo.script")
(eval-file "foo.script" "bar.script")
```

Evals foo.script. Returns null.

#### 1.1.12 Decals

- Image Decal

```
(image "filepath.[jpg|png|etc]")
(image "foo.jpg")
```

- Rectangle Decal

```
(rectangle "color" width height)
(rectangle "white" 100 200)
```

- Triangle Decal

```
(triangle "color" lengthA lengthB lengthC)
(triangle "white" 100 200 300)
```

- AnyShape Decal

- Connect point0 -> point1, and then pointn-1 -> point0 to make a shape

```
(any-shape "color" point0x point0y point1x point1y ... pointn-1x pointn-1y)
(any-shape "white" 100 100 200 200 300 300)
```

- Circle Decal

```
(circle "color" radius)
(Circle "white" 100)
```

- String decal

A string from a given font.

```
(string "StringText" "Font" "Color" Size)
(string "Hello World!" "Arial.font" "Red" 12)
(string "1" "Arial.font" "Red" 12)
```

### 1.1.13 Position-Scaleds

A position-scaled that can be used in the script

```
(position-scaled x-offset% y-offset% scale-width% scale-height%)
(position-scaled 0 0 100 100)
```

### 1.1.14 Size

A size is used by a card to determine how many pixels it will be.

```
(size width height)
```

## 2 Config file

- Allows one to set various options
- Current options are
  - script-file
    - \* Specify the script to run
    - \* No default, can be overridden by terminal args
  - output-format
    - \* Specify what format to output in
    - \* Defaults to png
  - output-file
    - \* Specify where to output the result to
    - \* Defaults to ./
  - logfile
    - \* Specify where to log to
    - \* Defaults to .cardlog

- Each option is enter in this format

```
(set-option "option-name" "value")
```

-So for example

```
(set-option "output-dir" "./")
```