

# Procedural Plant Generation and Simulated Plant Growth

Massey University



Matthew Crankshaw

25 February 2019

# Acknowledgements

# Abstract

# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	Context and Background . . . . .	5
<b>2</b>	<b>Outline</b>	<b>6</b>
2.1	Outline . . . . .	6
<b>3</b>	<b>Introducing Lindenmayer Systems</b>	<b>7</b>
3.1	L-system grammars . . . . .	7
3.2	Interpreting L-systems . . . . .	8
3.3	Branching Filaments . . . . .	9
3.4	Basic 2D L-systems . . . . .	9
3.5	The Use of L-systems in 3D applications . . . . .	12
3.6	Parametric L-system . . . . .	13
3.6.1	Formalising Parametric L-system Grammar . . . . .	13
<b>4</b>	<b>Implementation</b>	<b>14</b>
4.1	Language and environment . . . . .	14
4.1.1	C/C++ Programming Language . . . . .	14
4.1.2	Standard Template Library (STL) . . . . .	15
4.1.3	Open Graphics Library (OpenGL) . . . . .	15
4.1.4	OpenGL Mathematics Library (GLM) . . . . .	15
4.1.5	Graphics Library Framework(GLFW) . . . . .	15
4.1.6	Git Version Control . . . . .	15
<b>5</b>	<b>Glossary</b>	<b>16</b>
<b>A</b>	<b>Appendix</b>	<b>18</b>
A.1	Appendix 1 . . . . .	18
A.2	Bibliography . . . . .	18

# List of Figures

3.1	Diagram showing a turtle interpreting simple L-system string. . . . .	9
3.2	Diagram showing a turtle interpreting an L-system incorporating branching. . . . .	9
3.3	Koch Curve. . . . .	10
3.4	Sierpinski Triangle. . . . .	10
3.5	Dragon Curve. . . . .	11
3.6	Fractal Plant. . . . .	11
3.7	Fractal Bush. . . . .	12

# Chapter 1

## Introduction

Here I will introduce the project and the thesis in general.

LaTeX latex

### 1.1 Context and Background

One of the most time consuming parts for digital artists and animators is creating differing variations of the same basic piece of artwork. In most games and other graphics applications environment assets such as trees, plants, grass, algae and other types of plant life make up the large majority of the assets within a game. Creating a tree asset can take a skilled digital artist more than an hour of work by hand, The artist will then have to create many variations of the same asset in order to obtain enough variation that a user of that graphics application would not notice that the asset has been duplicated. If you multiply this by the number of assets that a given artist will have to create and then modify, you are looking at an incredible number of hours that could potentially be put to use creating much more intricate and important assets.

The unique thing about plant life when compared with other types of graphics assets is that plant life is very random in the way it grows and it does not take an incredibly realistic model of a plant life to trick the human mind into believing that what it is seeing is some kind of plant. However what stands out like a sore thumb is when plants that are growing next to each other seemingly have no influence on the plant life around them.

## Chapter 2

# Outline

### 2.1 Outline

## Chapter 3

# Introducing Lindenmayer Systems

Aristid Lindenmayer is well known biologist who started work on what would become known as the Lindenmayer System or L-system for short. Originally they were intended to be used as a grammar for describing the development of simple organisms. However over the years they have been found to be useful in describing larger organisms and even non organic structures like music. [Worth and Stepney, 2005]

### 3.1 L-system grammars

According to Prusinkiewicz and Hanan a simple type of L-systems are those known as deterministic 0L systems, where the string refers to the sequence of cellular states and '0L system' abbreviating 'Lindenmayer system with zero-sided interactions'. With 0L systems there are only three major parts. There is a set of symbols (*alphabet*), the starting string (*Axiom*) and state transition rules (*rules*). The alphabet is a set of states. The starting string is a starting point containing one or more states. The transition rules are rules that dictate whether a state should remain the same or transition into a different state or even disappear. [Prusinkiewicz and Hanan, 2013].

An example of a deterministic 0L system is that a simplified model for the growth of algae:

We are given the *alphabet*: A, B

and the *axiom*: A

and the *rule* set:

$A \rightarrow AB$

$B \rightarrow A$

If we then apply the rules to the L-system we find it creates the following generation structure.

- 1.) A
- 2.) AB
- 3.) ABA
- 4.) ABAAB
- 5.) ABAABABA
- 6.) ABAABABAABAAB

This rewriting of initial string using a set of rules is ultimately the underlying concept behind L-systems. There are a number of improvements that can be made to this type of L-system in



order to accommodate for more complex and intricate structure. One of which is the inclusion of *constants*. Constants can be considered any state that does not have a rule associated with it or remains the same from generation to generation and therefore holds a consistent value or meaning. These constants are used when the L-system is interpreted and thus holds a constant value during string rewriting.

## 3.2 Interpreting L-systems

Once we have generated the set of rules that allow us to create the L-system we are left with a string of characters which represent that particular L-system. As with any grammar, there is a number of ways of interpreting the string that is generated by the L-systems rules. One method proposed by Przemyslaw Prusinkiewicz is "to generate a string of symbols using an L-system, and to interpret this string as a sequence of commands which control a 'turtle'". [Prusinkiewicz, 1986]

A two dimensional L-system string may hold the following commands in the form of symbols.

- F: Move forward by a specified distance whilst drawing a line
- f: Move forward by a specified distance without drawing a line
- +: Rotate to the right specified angle.
- -: Rotate to the left by a specified angle.
- [: Save the current position and angle.
- ]: Load a saved position and angle.

Similarly a three dimensional L-system string may hold the following commands in the form of symbols.

- F: Move forward by a specified distance whilst drawing a line
- f: Move forward by a specified distance without drawing a line
- +: Yaw to the right specified angle.
- -: Yaw to the left by a specified angle.
- /: Pitch up by specified angle.
- \: Pitch down by a specified angle.
- ^: Roll to the right specified angle.
- &: Roll to the left by a specified angle.
- [: Save the current position and angle.
- ]: Load a saved position and angle.




Figure 3.1: Diagram showing a turtle interpreting simple L-system string.

### 3.3 Branching Filaments

Explain how branching works and how it can be used for generating the L-systems




Figure 3.2: Diagram showing a turtle interpreting an L-system incorporating branching.

### 3.4 Basic 2D L-systems

There are a number of fractal geometry that have become well known particularly with regards to how they can seemingly imitate nature [Mandelbrot, 1982]. Particularly with the geometry such as the Koch snowflake which can be represented using the following L-system.

**Koch Curve:**

**Alphabet:** F

**Constants:** +, -

**Axiom:** F

**Angle:**  $90^\circ$

**Rules:**

$F \rightarrow F+F-F+F$




Figure 3.3: Koch Curve.

**Sierpinski Triangle:**

**Alphabet:** A, B

**Constants:** +, -

**Axiom:** A

**Angle:**  $60^\circ$

**Rules:**

$A \rightarrow B-A-B$

$B \rightarrow A+B+A$




Figure 3.4: Sierpinski Triangle.

**Dragon Curve:**

**Alphabet:** F, X, Y

**Constants:** +, -

**Axiom:** FX

**Angle:**  $90^\circ$

**Rules:**

$X \rightarrow X+YF+$

$Y \rightarrow -FX-Y$




Figure 3.5: Dragon Curve.

**Fractal Plant:**

**Alphabet:** X, F

**Constants:** +, -, [, ]

**Axiom:** X

**Angle:**  $25^\circ$

**Rules:**

$X \rightarrow F-[[X]+X]+F[+FX]-X$

$F \rightarrow FF$



Figure 3.6: Fractal Plant.


**Fractal Bush:****Alphabet:** F**Constants:** +, -, [, ]**Axiom:** F**Angle:**  $25^\circ$ **Rules:**
$$F \rightarrow FF+[+F-F-F]-[-F+F+F]$$


Figure 3.7: Fractal Bush.

### 3.5 The Use of L-systems in 3D applications

L-systems have been talked about and researched since its inception in 1968 by Aristid Lindenmayer. Over the years it's usefulness in modelling different types of plant life has been very clear, however its presence has been quite absent from any mainstream game engines for the most part, these engines relying either on digital artists skill to develop individual plants or on 3rd party software such as SpeedTree. These types of software use a multitude of different techniques however their methods are heavily rooted in Lindenmayer Systems.

## 3.6 Parametric L-system

### 3.6.1 Formalising Parametric L-system Grammar

$\langle \text{generations} \rangle \rightarrow n = \langle \text{integer} \rangle$   
 $\langle \text{definition} \rangle \rightarrow \# \text{define } \langle \text{name} \rangle \langle \text{unary} \rangle$   
 $\langle \text{axiom} \rangle \rightarrow \langle \text{name} \rangle (\langle \text{paramAx} \rangle \langle \text{paramAxList} \rangle)$   
 $\langle \text{paramAxList} \rangle \rightarrow \in | \langle \text{paramAx} \rangle \langle \text{paramAxList} \rangle$   
 $\langle \text{paramAx} \rangle \rightarrow [0-9]^+.[0-9] | [0-9]^+$   
  
 $\langle \text{production} \rangle \rightarrow \langle \text{name} \rangle : \langle \text{module} \rangle : \langle \text{condition} \rangle : \langle \text{successor} \rangle$   
 $\langle \text{name} \rangle \rightarrow [a-zA-Z]^+$   
 $\langle \text{module} \rangle \rightarrow \langle \text{modName} \rangle \in | (\langle \text{param} \rangle \langle \text{paramList} \rangle)$   
 $\langle \text{modName} \rangle \rightarrow [a-zA-Z]^+ | \langle \text{instruction} \rangle$   
 $\langle \text{instruction} \rangle \rightarrow + | - | / | \backslash | ^ | \& | !$   
 $\langle \text{param} \rangle \rightarrow \langle \text{name} \rangle | \langle \text{expression} \rangle | \langle \text{unary} \rangle$   
 $\langle \text{paramList} \rangle \rightarrow \in | \langle \text{param} \rangle \langle \text{paramList} \rangle$   
 $\langle \text{expression} \rangle \rightarrow \langle \text{expression} \rangle \langle \text{symbol} \rangle \langle \text{expression} \rangle | \langle \text{unary} \rangle | (\langle \text{expression} \rangle)$   
 $\langle \text{symbol} \rangle \rightarrow + | - | / | * | ^ | < | > | == | <= | >= | !=$   
 $\langle \text{unary} \rangle \rightarrow \langle \text{integer} \rangle | \langle \text{float} \rangle | \langle \text{bool} \rangle$   
 $\langle \text{integer} \rangle \rightarrow [0-9]^+$   
 $\langle \text{float} \rangle \rightarrow [0-9]^+.[0-9]^+$   
 $\langle \text{bool} \rangle \rightarrow 0 | 1$

# Chapter 4

## Implementation

Introduction to the implementation section

### 4.1 Language and environment

To understand what programming language and environment will be best suited for this project, I first provide the technical requirements that will need to be met. The programming language will need to be relatively fast when processing the rules of the L-systems and when rewriting these strings according to those rules.

The program will also need to interpret the strings generated by the L-system rules and be able to generate a 3 dimensional representation of that L-system. This representation will need to be intuitive and will have to allow me to examine it from different perspectives. In order to make the representation intuitive, the 3D representation should be rendered in real time at multiple frames per second. And the user should be able to use a computer mouse and keyboard to move around the 3D world.

Due to these demands have decided to use the C and C++ programming language. Due to its and thoroughly tested in built standard template library, I can count on it to be reliable and fast enough for the purpose of this project. It will also allow me to use other very useful libraries for 3D graphics such as OpenGL which is also written in C/C++. I will be speaking in more detail about these details of these libraries in later sections.

In order to create a window and provide the environment for writing pixels to the screen I will make use of the Graphics Library Framework (GLFW). Some useful mathematics functions and facilities can be found in the OpenGL Mathematics Library (GLM) and possibly the most important for rendering in 3D is the Open Graphics Library or OpenGL for short. All of these libraries together will provide me with a strong foundation of tools that I can use to approach the practical aspect of this project.

#### 4.1.1 C/C++ Programming Language

The C programming language developed by Dennis Richie and Bell Labs in 1972 has been one of the most popular programming languages for a number of decades now [Ritchie et al., 1975]. The

C language was then extended upon by Bjarne Stroustrup in 1985 to create the C++ programming language [Stroustrup, 2000]. I have included both C and C++ as the programming languages that I will be using, as they are very closely related and C code can be compiled using the C++ compiler. For the most part I will be writing C++ code and making use of its object oriented features. However, there are instances when it will be more convenient to write C code or make use of a C library.

#### **4.1.2 Standard Template Library (STL)**

The STL in C/C++ provides a number of useful functions, data structures and algorithms that have been extensively tested for both reliability and efficiency. The most common features I will be using are strings, vectors, stacks and input and output. It is possible that in some cases it may be more efficient to use custom data structures for the most part the STL functions will be more than good enough. [Horton, 2015]

#### **4.1.3 Open Graphics Library (OpenGL)**

OpenGL is a 2D and 3D graphics API [Movania et al., 2017]

#### **4.1.4 OpenGL Mathematics Library (GLM)**

#### **4.1.5 Graphics Library Framework (GLFW)**

#### **4.1.6 Git Version Control**



Chapter 5

Glossary

# Glossary

**LaTeX** test2. 5

**latex** is something about this thing. 5

## Appendix A

# Appendix

A.1 Appendix 1

A.2 Bibliography

# Bibliography

- [Horton, 2015] Horton, I. (2015). *Using the C++ Standard Template Libraries*. Apress.
- [Mandelbrot, 1982] Mandelbrot, B. B. (1982). *The fractal geometry of nature*, volume 2. WH freeman New York.
- [Movania et al., 2017] Movania, M. M., Lo, W. C. Y., Wolff, D., and Lo, R. C. H. (2017). *OpenGL – Build high performance graphics*. Packt Publishing Ltd, 1 edition.
- [Prusinkiewicz, 1986] Prusinkiewicz, P. (1986). Graphical applications of l-systems. In *Proceedings of graphics interface*, volume 86, pages 247–253.
- [Prusinkiewicz and Hanan, 2013] Prusinkiewicz, P. and Hanan, J. (2013). *Lindenmayer systems, fractals, and plants*, volume 79. Springer Science & Business Media.
- [Ritchie et al., 1975] Ritchie, D. M., Kernighan, B. W., and Lesk, M. E. (1975). *The C programming language*. Bell Laboratories.
- [Stroustrup, 2000] Stroustrup, B. (2000). *The C++ programming language*. Pearson Education India.
- [Worth and Stepney, 2005] Worth, P. and Stepney, S. (2005). Growing music: musical interpretations of l-systems. In *Workshops on Applications of Evolutionary Computation*, pages 545–550. Springer.