Networks and Systems

BSc Computer Science - Durham University

Matthew Emerson

October 2026

Contents

1 Module Introduction **1**
1.1 Assessment . . . 1
1.2 Timetable . . . 1

2 Cyber Security **1**
2.1 Introduction, Threat Modelling, and Applied Cryptography . . . 1
2.2 System Security . . . 4
2.3 Defence . . . 5

3 Networks **5**

4 Databases **6**
4.1 Enhanced Entity-Relationship Model . . . 6
4.2 Semistructured Databases (XML) . . . 6
4.3 XML Data Manipulation (XPath and XQuery) . . . 6
4.4 Transactions . . . 6
4.5 Concurrency Control . . . 6
4.6 Distributed Transactions . . . 6
4.7 Distributed Concurrency Control . . . 6

5 Distributed Systems **6**
5.1 Introduction to Distributed Systems . . . 6
5.2 Middleware and RMI Technologies . . . 6
5.3 Message-Oriented Middleware and Web Services . . . 6
5.4 Replication Models . . . 6
5.5 Concurrent Events and Consistency Control . . . 6
5.6 Fault Tolerance . . . 6
5.7 Load Distribution . . . 6

I Appendix **7**

6 Bibliography **7**
6.1 Module Professors . . . 7
6.2 References . . . 7
6.3 List of Figures . . . 7
6.4 Reading List . . . 7

1 Module Introduction

Networks and Systems has the module code COMP2211 and is led by Dr Wanqing Tu.

1.1 Assessment

This module is assessed through two pieces of summative coursework and two final exams, these can be seen in Table 1. Additional formatives are also shown in italics.

Title	Opening	Due	Feedback	Professor	Weight
Cyber Security	9th Oct	5th Nov	3rd Dec	Dr Carlton Shepherd	25%
Networks	23rd Oct	21st Jan	18th Feb	Dr Wanqing Tu	25%
Dist. Sys. & Databases	May Exam	-	-	Dr Vasantam	50%

Table 1: Assessments for Networks and Systems.

1.2 Timetable

This module is taught through one two-hour lecture and one two-hour computer class each week as seen below in Table 2.

Day	Time	Class Type	Location	Lecturer
Thursday	09:00 - 11:00	Lecture	CLC202	Dr Carlton Shepherd
Thursday	16:00 - 18:00	Computer Class	CC-0007	-

Table 2: Michaelmas Term Timetable for Networks and Systems.

2 Cyber Security

This section is taught by Dr Carlton Shepherd. The recommended reading for this module is as follows:

- Practical Cryptography for Developers (Nakov, Stefanov and Shideroff, 2018), specifically the section on "Encryption: Symmetric and Asymmetric".

2.1 Introduction, Threat Modelling, and Applied Cryptography

2.1.1 Basic Definitions

Definition 2.1.1.1: A system's security depends on the definition of the adversary: who they are, what they can do (or their capabilities) and their determination (time, money, resources). This is the adversary or threat model.

Definition 2.1.1.2: An asset is something that is worth protecting.

Definition 2.1.1.3: A threat is a person or program that may try and access/steal your assets.

Definition 2.1.1.4: An assumption is something you are relying on to be true/secure by default.

Definition 2.1.1.5: Your goal should be in terms of what needs to be secure, and how long for.

Definition 2.1.1.6: The controls are the things you can do to attempt to protect your assets.

The CIA triad are the three main security properties, these are:

- **Definition 2.1.1.7**: Confidentiality: The outcomes of different actions in the system are only visible by authorised subjects.
- **Definition 2.1.1.8**: Integrity: Actions modifying the system can only be performed by authorised subjects.

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

- **Definition 2.1.1.9**: Availability: Subjects can perform all actions they are authorised for.

In addition to these properties, it is also important to consider additional properties, such as:

- **Definition 2.1.1.10**: Authenticity: An entity is who they claim they claim to be.
- **Definition 2.1.1.11**: Non-Repudiation: An actor cannot easily deny that an action has occurred.
- **Definition 2.1.1.12**: Context-Binding: An action is valid only for a particular period of time, distance, location, and/or environment.

Definition 2.1.1.13: An exploit is a piece of code, a tool, or a technique that takes advantage of a flaw in software, hardware, or a network to cause unintended behaviour.

Definition 2.1.1.14: A vulnerability is a weakness or flaw in a system's design, implementation, operation, or human behaviour that an attacker can exploit to compromise security.

Definition 2.1.1.15: Risk is the probability or liklihood that a threat will exploit a vulnerability and cause harm, loss, or negative consequences to an asset.

2.1.2 STRIDE Modelling

Definition 2.1.2.1: One method of classifying security risks is STRIDE, which was first developed by Microsoft. It is separated as follows:

- **Definition 2.1.2.1**: **S**poofing is the act of using someone else's credentials to perform an operation and is a failure of identification and authentication.
- **Definition 2.1.2.2**: **T**ampering is the malicious modification of data and is a failure of integrity and authenticity.
- **Definition 2.1.2.3**: **R**epudiation is the act of denying having performed an operation and is a failure of accountability and identification.
- **Definition 2.1.2.4**: **I**nformation Dislosure is the exposure of information to unauthorised users and is a failure of confidentiality.
- **Definition 2.1.2.5**: **D**enial of Service is the act of denying service to legitimate users and is a failure of availability.
- **Definition 2.1.2.6**: **E**levation of Privilege is an instance of an unprivileged user gaining privileged access and is a failure of confinement and authentication.

This is a helpful model for structuring the analysis of potential system threats but it is not exhaustive or exclusive.

2.1.3 Applied Cryptography

Definition 2.1.3.1: To encode some given data, it is transformed from one format/domain to another. This is fully reversible, and does not provide any secrecy. The inverse procedure is called decoding.

- **Definition 2.1.3.2**: A subtype of encoding is steganography, where the existence of the secret message is concealed.

Definition 2.1.3.3: To hash some given data, it is transformed into a (usually) smaller, fixed-size. This is most commonly considered a one-way function. An example of this are SHA algorithms.

- A hashing algorithm works by taking a message m and applying a hashing algorithm $h = H(m)$. h can then be sent securely and the recipient can then take $h' = H(m')$ where $m = m'$, and if $h' = h$, then the message recieved is correct.

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

Definition 2.1.3.4: Non-secret data (plaintext) can be encrypted into ciphertext using a secret key. The output is $Enc(m, K) = c$. The inverse procedure, decryption, again uses a secret key to transform the ciphertext back to plaintext $Dec(c, K) = m$.

2.1.4 Cipher Examples

Definition 2.1.4.1: A substitution cipher works by taking each letter in the alphabet and replacing it with another one. This was purportedly created and used by Julius Caesar. These are weak though and can be broken by:

- **Definition 2.1.4.1**: A brute-force attack tries every possible key, which for substitution ciphers becomes trivial.
- **Definition 2.1.4.2**: A frequency analysis attack matches the ciphertext to the known frequency of English letters.

Definition 2.1.4.4: Another historical example of a cipher is a Vigenere cipher. This uses a sliding password, such that repeats of the same letter are coded differently. Attacks against this have to guess possible key lengths and then try all possibilities using frequency analysis. This is much harder to break.

Definition 2.1.4.5: Another encryption method is using one time pads. Here, you select a key as long as your message. Data is converted into binary and bitwise XORed with the key. To decode it, you then bitwise XOR the ciphertext with the key. This is considered theoretically secure as long as the key generation process is truly random, the key is never reused, and the key is kept secret.

Definition 2.1.4.6: Stream ciphers use a short secret key and a nonce - a use-once but public value - to generate a long pseudorandom sequence called a keystream. Only the short secret key must be kept private. We then XOR with the message and keystream.

- To encrypt, you take the secret key K and the nonce N and feed them through a keystream generator. The resulting keystream S is then XORed with the plaintext p to produce ciphertext C.
- To decrypt, the recipient takes the same secret key K and nonce N, feeds them through the keystream generator and then XOR the result with the ciphertext C to produce the original plaintext p.

Definition 2.1.4.7: Block ciphers transform a fixed-size block of plaintext into a ciphertext block of the same size, using a secret key. Encryption applies a keyed transformation to the plaintext block, and decryption reverses the transformation using the same key. An example of this is AES encryption. To encrypt longer messages, we use a mode of operation which specifies how to encrypt message blocks in sequence - this usually involves a nonce (initialisation vector).

- **Definition 2.1.4.7**: AES Electronic Code Book (ECB) mode works by taking the plaintext, splitting it into blocks, and then encrypting each of them separately. This is not secure.
- **Definition 2.1.4.8**: AES Cipher Block Chaining (CBC) mode splits the plaintext into blocks and encrypts the first one. The result is then XORed with the second plaintext block before it is encrypted, and so on.

2.1.5 Public Key Cryptography

Definition 2.1.5.1: Rivest, Shamir, Adelman (RSA) is an algorithm where person A computes the product of two prime numbers $n = p \times q$ and makes the value of n public. Person A then generates a public value e and a private value d using p and q. e can then be used to encrypt messages to send to person A, and d used to decrypt them. This is secure based on the computational difficulty of factorisation, but with the rise of quantum computing, is becoming less secure.

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

Definition 2.1.5.2: Digital signatures enables others to check that a message was signed using a private key and has not been altered. To sign a message, the sender uses their private key, and then sends the message and signature to the recipient. To verify the signature, the recipient uses the sender's public key and compares the result to the message.

2.2 System Security

2.2.1 Analysing the Security of Systems

Definition 2.2.1.1: A system is a set of components that interact to achieve a purpose. It generally consists of five components:

- **Definition 2.2.1.2**: Subjects are active entities with an identity and capabilities.
- **Definition 2.2.1.3**: Resources are passive entities with an identity and properties.
- **Definition 2.2.1.4**: Actions are interactions between subjects and resources.
- **Definition 2.2.1.5**: The purpose of a system is what it is used for, and so what security must preserve.
- **Definition 2.2.1.6**: A boundary defines what is inside (what you control), and what is outside.

When considering the security of a system, we should consider four questions:

- **What matters?** An asset and a security property (e.g., confidentiality).
- **Who could cause harm?** An adversary with stated capabilities.
- **Why could they succeed?** A weakness and the assumptions it violates.
- **What changes the outcome?** Controls and countermeasures. What is the remaining risk?

Definition 2.2.1.7: A trust boundary is where data or control passes between parties that trust each other differently (e.g., a phone to a ticketing service).

Definition 2.2.1.8: An attack surface is every entry point an adversary can reach.

Definition 2.2.1.9: A trusted computing base (TCB) is what must work correctly for the goal to hold. If any part fails, security fails.

Definition 2.2.1.10: A reference monitor sits between the subjects and objects. It recieves requests for the objects, compares them with the security policy, and if it passes, returns the requested objects. It is important when designing a system that this is always invoked, it is tamper-proof, and that the check is verifiable.

Actor	Motivation	Typical Capability	Example
Opportunists	Curiosity, notoriety, easy money.	Low: Off-the-shelf tools and mass scanning.	Mirai Botnet (2016).
Hacktivists	Publicity for a cause.	Low-to-Medium: DDoS, leaks, defacement.	Operation Payback (2010).
Organised Criminals	Money.	Medium-to-High: Ransomware, affiliates, access brokers.	Rhysida (2023).
Insiders	Grievance money, or simple mistakes.	High: They already have legitimate access.	Morrisons (2014).
Nation States	Espionage, sabotage, strategic advantage.	Very High: Custom tools, patience, zero-days.	SolarWinds (2020).

Table 3: Potential adversaries to a system.

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

Example 2.2.1.1: The Hezbollah pager attack was an attack where Hezbollah ordered thousands of new pagers for members across Lebanon and Syria. This consignment was intercepted by agents in a supply chain attack and 10 to 20 grams of military grade explosive was packed into each device. These pagers were then delivered to Hezbollah and handed out to members. The pagers then recieved a code, buzzed, and exploded in pockets, on belts, or in faces of users.

Definition 2.2.1.11: It can also be useful to consider system security from an adversarial perspective. To do this, people commonly use the kill chain model.

- Reconnaissance: Harvesting email addresses, conference information, etc.
- Weaponisation: Coupling an exploit with a backdoor into a deliverable payload.
- Delivery: Delivering a weaponised bundle to the victim via email, USB, etc.
- Exploitation: Exploiting a vulnerability to execute code on the victim's systems.
- Installation: Installing malware on an asset.
- Command and Control (C2): Setting up a control channel for remote manipulation of victims.
- Actions on Objectives: With "hands on keyboard" access, intruders can accomplish their original goals.

Definition 2.2.1.12: Reconnaissance can be split into a few types: passive gathering where attackers have no interaction with the target, active gathering where they do, and open-source intelligence (OSINT) where the attacker analyses data from publically available sources. They do this to identify potential attack vectors.

Example 2.2.1.2: The British Library attack in 2023 can be split into the categories shown in the Kill chain:

- Reconnaissance: Hostile reconnaissance on the 25th-26th October was detected and blocked, but treated as a one-off.
- Delivery and Exploitation: Most likely privileged credentials obtained by phishing or brute force, then used on a remote-access server without MFA. No software exploit was needed.
- Installation and C2: The attackers hijacked the network's own administration tools, and deleted log files to cover their tracks.
- Actions on Objectives: A "historically complex" legacy network let them reach well beyond the entry point and roughly 600 GB was copied. The servers were then encrypted or destroyed.

2.3 Defence

Definition 2.3.0.1: Asymmetry in security is the principle that finding a hole is much easier than securing all possible holes. However, an attack is a sequence of stages that are all opportunities to detect or stop it.

Definition 2.3.0.2: An attack tree is constructed such that: the root is the attackers' goal, the children are the different ways to achieve it, and the leaves are concrete actions. An OR node indicates that any of the children achieves the parent, while an AND node indicates that all children are required to achieve the parent. A set of leaves that satisfies the root is a complete attack.

When designing a system, it is important to consider the following principles: minimise the attack surface, split your defence across many layers, assign users as few privileges as necessary, deny requests as a default reponse unless explicitly allowed, attackers will always take the weakest link, and you should always assume there will be a breach, so monitor and plan for recovery.

3 Networks

This section is taught by Dr Wanqing Tu. Check for recommended reading.

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

4 Databases

This section is taught by Dr Vasantam. The recommended reading for this topic is:

- Connolly, T.M. and Begg, C.E. (2015). Database Systems: A practical approach to design, implementation, and management. 6th edn. Harlow, Essex, England: Pearson Education Limited.

4.1 Enhanced Entity-Relationship Model

4.2 Semistructured Databases (XML)

4.3 XML Data Manipulation (XPath and XQuery)

4.4 Transactions

4.5 Concurrency Control

4.6 Distributed Transactions

4.7 Distributed Concurrency Control

5 Distributed Systems

This section is taught by Dr Vasantam. The recommended reading for this topic is:

- Van Steen, M. and Tanenbaum, A.S. (2025). Distributed Systems. 4th edn. [online] Self-Published. Available at: https://www.distributed-systems.net/index.php/books/ds4/ [Accessed 5 Oct. 2026].

5.1 Introduction to Distributed Systems

5.2 Middleware and RMI Technologies

5.3 Message-Oriented Middleware and Web Services

5.4 Replication Models

5.5 Concurrent Events and Consistency Control

5.6 Fault Tolerance

5.7 Load Distribution

LaTeX File Template v.2.3.0: Copyright 2026, Matthew Emerson

Part I
Appendix

6 Bibliography

6.1 Module Professors

Module Lead: Doctor Wanqing Tu

- Focus: Computer networks and wireless communications.
- Email: wanqing.tu@durham.ac.uk
- Office Hours: Thursday 11:00 - 12:00.

Lecturer: Doctor Thirupathaiah Vasantam

- Focus: Applied probability and performance modelling.
- Email: thirupathaiah.vasantam@durham.ac.uk
- Office Hours: Monday 14:00 - 15:00.

Lecturer: Doctor Carlton Shepherd

- Focus: Cyber security.
- Email: carlton.g.shepherd@durham.ac.uk
- Office Hours: Email to make an appointment.

6.2 References

6.3 List of Figures

6.4 Reading List

6.4.1 Cyber Security

Nakov, S., Stefanov, M. and Shideroff, M. (2018). Practical Cryptography for Developers. [online] sec. Encryption: Symmetric and Asymmetric Available at: https://cryptobook.nakov.com/ [Accessed 9 Oct. 2026].

6.4.2 Databases

Connolly, T.M. and Begg, C.E. (2015). Database Systems: A practical approach to design, implementation, and management. 6th edn. Harlow, Essex, England: Pearson Education Limited.

6.4.3 Distributed Systems

Van Steen, M. and Tanenbaum, A.S. (2025). Distributed Systems. 4th edn. [online] Self-Published. Available at: https://www.distributed-systems.net/index.php/books/ds4/ [Accessed 5 Oct. 2026].