

Energy, expenditure, and consumption aspects of rebound,

Part II: Applications of the framework

Matthew Kuperus Heun^{1,2,3,*}, Gregor Semieniuk⁴, and Paul E. Brockway²

¹*Engineering Department, Calvin University, 3201 Burton St. SE, Grand Rapids, MI, 49546*

²*Sustainability Research Institute, School of Earth and Environment, University of Leeds, Woodhouse, Leeds, LS2 9JT, UK*

³*School for Public Leadership, Faculty of Economic and Management Science, Stellenbosch University, Private Bag X1, Matieland, 7602, Stellenbosch, South Africa*

⁴*Political Economy Research Institute and Department of Economics, University of Massachusetts Amherst, Amherst, MA, 01003*

*Corresponding author: mkh2@calvin.edu

Abstract

Widespread implementation of energy efficiency is a key greenhouse gas emissions mitigation measure, but rebound can “take back” energy savings. However, the absence of solid analytical foundations hinders empirical determination of the size of rebound. In Part I, we developed foundations of a rigorous analytical framework that is approachable for both energy analysts and economists. In this paper (Part II of two), we develop energy, expenditure, and consumption planes, a novel, mutually consistent, and numerically precise way to visualize and illustrate rebound. Further, we operationalize the macro factor for macroeconomic rebound. Using the framework and rebound planes, we calculate and show total rebound for two examples: energy efficiency upgrades of a car (56.2%) and an electric lamp (67.0%). We calculate rebound for a producer-sided extension to the framework, namely an energy price rebound effect. Finally, we provide information about new open source software tools for calculating magnitudes and visualizing rebound effects using the framework.




Fig. 1: Flowchart of rebound effects and decorations.

Keywords: Energy efficiency, Energy rebound, Energy services, Microeconomic rebound, Substitution and income effects, Macroeconomic rebound

JEL codes: O13, Q40, Q43

1 Introduction

In Part I of this two-part paper, we argued that improved clarity is needed about energy rebound. We said that

[a] description of rebound [is needed] that is (i) consistent across energy, expenditure, and consumption aspects, (ii) technically rigorous and (iii) approachable from both sides (economics and energy analysis). . . . In other words, the finance and human behavior aspects of rebound need to be presented in ways energy analysts can understand. And the energy aspects of rebound need to be presented in ways economists can understand.

To help improve clarity in the rebound field, we developed in Part I foundations for a rigorous analytical framework, one that is tractable for both energy analysts and economists. Three aspects of rebound are analyzed in the framework: energy, expenditure, and consumption. The framework contains both direct and indirect rebound and four rebound effects (emplacement, substitution, income, and macro) between five stages (\circ , $*$, \wedge , $-$, and \sim). Rebound terms and symbol decorations are shown in Fig. 1. (See Table 1 in Part I for details. See Appendix A for nomenclature.)

In this paper (Part II), we make further progress toward the goal of clarity with five contributions. First, we develop a new way to communicate components and mechanisms of rebound via mutually consistent and numerically precise visualizations of rebound effects in energy, expenditure, and consumption planes. Second, we calculate the macro rebound effect via a macro factor (k) selected

to be 3. Third, we apply the framework to two energy efficiency upgrades (EEUs) (a car and an electric lamp) with detailed explication of numerical results for the examples. Fourth, we apply the framework to calculate numerical values for the producer-sided energy price rebound extension to the framework. Finally, we provide information about new open source software tools for calculating and visualizing rebound for any energy efficiency upgrade.

The remainder of this paper is structured as follows. Section 2 describes data for the examples, our method of visualizing rebound, and open source software tools for calculating and visualizing rebound. Section 3 provides results for two examples: energy efficiency upgrades to a car and an electric lamp. Section 4 operationalizes the macro factor (k) and discusses results, and Section 5 concludes.

2 Data and methods

This section contains data for the examples (Section 2.1), an explication of our new method for visualizing rebound effects and magnitudes (Section 2.2), and a description of new open source software tools for rebound calculations and visualization (Section 2.3).

2.1 Data

To demonstrate application of the rebound analysis framework developed in Part I, we analyze two examples: energy efficiency upgrades to a car and an electric lamp. The examples are presented with much detail to support our goal of helping to advance clarity for the process of calculating the magnitude of rebound effects. Here, we collect parameter values for the equations to calculate nine rebound components: Re_{dempl} , Re_{emb} , Re_{OM} , Re_d , Re_{dsub} , Re_{isub} , Re_{dinc} , Re_{iinc} , and Re_{macro} . Total rebound (Re_{tot}) is given by the sum of the above components or equivalently by Eq. (35) of Part I.

2.1.1 Data for car example

For the first example, we consider the purchase of a more fuel efficient car, namely a gasoline-electric Ford Fusion Hybrid car, to replace a conventional gasoline Ford Fusion car. The cars are matched as closely as possible, except for the inclusion of an electric battery in the hybrid car. The car case

44 study features a larger initial capital investment ($\overset{\circ}{C}_{cap} \leftarrow \tilde{\overset{\circ}{C}}_{cap} \overset{\circ}{C}_{cap} \lessapprox \overset{*}{C}_{cap}$) for the long-term benefit
 45 of decreased energy service costs ($\overset{\circ}{C}_s \rightarrow \tilde{\overset{\circ}{C}}_s \overset{\circ}{C}_s \gtrapprox \overset{*}{C}_s$).

46 We require three sets of data. First, basic car parameters are summarized in Table 1. Second,
 47 we require several general economic parameters, mainly relating to the U.S. economy and personal
 48 finances of a representative U.S.-based user shown in Table 2. Third, we require elasticity parameters,
 49 as given in Table 3.

Table 1: Car example: Vehicle parameters.

Description Parameters [units]	Ford Fusion (gasoline)	Ford Fusion (hybrid EV)	Data sources and notes
Fuel economy $\eta^\circ, \tilde{\eta}, \eta^*$ [mpg]	25	42	Combined cycle mpg value taken from Thecarconnection.com (2020), for Titanium FWD 2020 model with Intercooled I-4, 2.0 L engine. Combined cycle mpg value taken from Thecarconnection.com (2020), for Titanium FWD 2020 model with Gas/Electric I-4, 2.0 L engine.
Undiscounted capital expenditure rate $\dot{C}_{cap}^\circ, \dot{C}_{cap}^*$ [\$ / yr]	2,533	2,518	Fourteen year annual, averaged capital costs = purchase cost / t_{life} . Ford Fusion gasoline costs from Edmunds.com (2020a). Ford Fusion Hybrid car costs from Edmunds.com (2020b).
Lifespan $t_{life}^\circ, t_{life}^*$ [yr]	14	14	Lifetime taken as 14 years, based on 13–17 years for U.S. cars from Berla.com (2016) and 14 years for UK cars from Society of Motor Manufacturers and Traders (2020).
Embodied energy E_{emb}°, E_{emb}^* [MJ]	34,000	40,000	34,000 MJ for conventional Ford Fusion gasoline car taken from Argonne National Laboratory, Energy Systems Division (2010). We assume an additional 6,000 MJ added for Ford Fusion Hybrid Electric Vehicle (HEV) battery, as HEV typically adds 10–25% to total LCA energy of vehicle manufacture (Onat et al., 2015). Battery lifetime assumed same as car lifetime, based on Nordelöf et al. (2014) and Onat et al. (2015).
Operations and maintenance expenditure rate $\dot{C}_{OM}^\circ, \dot{C}_{OM}^*$ [\$ / yr]	5,050	4,779	Lifetime (14 year) annual, averaged operation and maintenance (O&M) costs = sum of insurance, maintenance, repairs, taxes, and fees (excluding financing, depreciation, fuel). 5-year Ford Fusion O&M costs from Edmunds.com (2020a). 5-year Ford Fusion Hybrid O&M costs from Edmunds.com (2020b). Extrapolation of O&M costs for years 6–14 based on Djokic et al. (2015).
Disposal cost C_d°, C_d^* [\$]	−300	−300	Salvage value (negative cost) taken from Junk Car Medics (2024)
Ops., maint., and disposal expenditure rate, discounted $\dot{C}_{OMd}^\circ, \dot{C}_{OMd}^*$ [\$ / yr]	5,033	4,762	Sum of annualized operations, maintenance, and disposal costs.

Table 2: Car example: Economic parameters (2020).

Description Parameter [units]	Value	Data sources and notes
Distance driven prior to upgrade \dot{q}_s° [miles/yr]	12,416	Average U.S. vehicle miles/yr, calculated from Carinsurance.com (2019). This is slightly lower than the average driver miles/yr (13,476) (US Department of Transportation, 2018), as there are more registered U.S. vehicles than drivers.
Real median personal income U.S., in 2018 [\$/yr]	34,317	Taken from Federal Reserve Bank of St Louis (2019).
U.S. 2018 disposable income / real income (minus current taxes) [-]	0.88319	Taken from U.S. Bureau of Economic Analysis (BEA) National and Products Accounts (NIPA) Table 2.1. Personal Income and Its Disposition (US Bureau of Economic Analysis, 2020).
Share of savings from 2018 disposable income [-]	0.07848	Taken from U.S. Bureau of Economic Analysis (BEA) National and Products Accounts (NIPA) Table 2.1. Personal Income and Its Disposition (US Bureau of Economic Analysis, 2020).
Personal consumption in 2018 \dot{M} [\$/yr]	27,930	Calculation: $(\$34,317/\text{yr})(0.88319)(1 - 0.07848)$
Price of gasoline p_E [\$/gallon]	2.63	Source: US Energy Information Administration (2020b)
Fractional spend on original energy service $f_{C_s}^\circ$ [-]	0.066	Calculation: $\$1,306$ (spend on energy service) / $[\$19,115$ (other goods) + $\$1,306$ (energy service)] = 0.064, where spend on energy service = 12,416 miles / 25 mpg \times $\$2.63/\text{gallon}$ = $\$1,306$.
Real discount rate r [1/yr]	0.03	Taken from Federal Reserve St. Louis for 72 month car loan rate, which averaged 5% before the 2022 interest rate raises. Subtracting 2% inflation gives 3% real interest rate, by which we discount. (Board of Governors of the Federal Reserve System (US), 2024)
Macro factor k [-]	1.0	An initial value. See Section 4.1 for additional details.

Table 3: Car example: Elasticity parameters.

Description Parameter [units]	Value	Data sources and notes
Uncompensated own price elasticity of car use demand $\varepsilon_{q_s, p_s}^o [-]$	-0.2	We adopt -0.2 as our baseline value, based on U.S. studies including Gillingham (2020) who estimated a value of -0.1, Goetzke & Vance (2018) who estimated values between -0.05 and -0.23, and Parry & Small (2005) who estimated values between -0.1 and -0.3. For comparison, Borenstein (2015) uses values of -0.1 to -0.4 based on Parry & Small (2005).
Compensated price elasticity of car use demand $\varepsilon_{q_s, p_s, c}^o [-]$	-0.134	Calculated via the Slutsky Equation (Eq. (172) in Part I).
Compensated cross price elasticity of demand for other goods $\varepsilon_{q_o, p_s, c}^o \varepsilon_{q_g, p_o, c}^o [-]$	0.009	Calculated via Eq. (178) in Part I.
Income elasticity of demand for car use $\varepsilon_{q_s, M} [-]$	1.0	Follows from CES utility function.
Income elasticity of demand for other goods $\varepsilon_{q_o, M} \varepsilon_{q_g, M} [-]$	1.0	Follows from CES utility function.

2.1.2 Data for lamp example

For the second example, we consider purchasing a Light Emitting Diode (LED) electric lamp to replace a baseline incandescent electric lamp. Both lamps are matched as closely as possible in terms of energy service delivery (measured in lumen output per lamp), the key difference being the energy required to provide that service. The LED lamp has a low initial capital investment rate when spread out over the lifetime of the lamp (less than the incumbent incandescent lamp) and a long-term benefit of decreased direct energy expenditures at approximately the same energy service delivery rate ($\text{lm}\cdot\text{hr}/\text{yr}$).

Again, three sets of data are required. First, basic lamp parameters are summarized in Table 4. Second, several general economic parameters, mainly relating to the U.S. economy and personal finances of a representative U.S.-based user are given in Table 5. Third, we require the elasticity parameters, as shown in Table 6.

Table 4: Lamp example: Electric lamp parameters.

Description Parameters [units]	Incandescent lamp	LED lamp	Data sources and notes
Lamp efficiency $\eta^\circ, \tilde{\eta}, \eta^*$ [lm·hr/W·hr]	8.83	81.8	Incandescent: 530 lm output / 60 W energy input. LED: 450 lm output / 5.5 W energy input.
Undiscounted capital expenditure rate $\dot{C}_{cap}^\circ, \dot{C}_{cap}^*$ [\$ / yr]	1.044	0.121	Purchase costs: \$1.88 for incandescent lamp from HomeDepot.com (2020b), and \$1.21 for LED lamp from HomeDepot.com (2020a).
Lifespan $t_{life}^\circ, t_{life}^*$ [yr]	1.8	10	Based on assumed 3 hr/day from HomeDepot.com (2020b) and HomeDepot.com (2020a).
Life cycle analysis (LCA) embodied energy E_{emb}°, E_{emb}^* [MJ]	2.20	6.50	Base document: Table 4.5 Manufacturing Phase Primary Energy (MJ/20 million lm·hr), contained in U.S. DoE Life-cycle assessment of energy and environmental impacts of LED lighting products (US Department of Energy, 2012). Incandescent lamp: LCA energy = 42.2 MJ/20 million lm·hr. Lifetime output = 530 lm × 3 hr/day × 365 days/yr × 1.8 yr = 1,044,630 lm·hr. Thus LCA energy / lamp = 42.2 × 1.0446/20 = 2.20 MJ. LED lamp: LCA energy = 132 MJ/20 Million lm·hr for pack of 5 LED lamps. Lifetime output = 450 lm × 3 hr/day × 365 days/yr × 10 yr = 4,926,405 lm·hr. Thus LCA energy / lamp = 132 MJ/5 × 4.9264/20 = 6.5 MJ.
Operations and maintenance expenditure rate $\dot{C}_{OM}^\circ, \dot{C}_{OM}^*$ [\$ / yr]	0	0	Lifetime annual, averaged operations and maintenance (O&M) costs. Once installed assumed 0. Note: O&M costs exclude fuel (i.e., electricity) costs.
Disposal cost C_d°, C_d^* [\$]	0	0	Disposal cost assumed negligible (local/doorstep recycling facility).
Ops., maint., and disposal expenditure rate, discounted $\dot{C}_{OMd}^\circ, \dot{C}_{OMd}^*$ [\$ / yr]	0	0	Sum of annualized operations, maintenance, and disposal costs.

Table 5: Lamp example: Economic parameters (2020).

Description Parameter [units]	Value	Data sources and notes
Lighting consumption prior to upgrade \dot{q}_s° [lm·hr/yr]	580,350	Calculation: (530 lm) (3 hrs/day) (365 days/yr).
Real median personal income U.S. in 2018 [\$/yr]	34,317	Refer to Table 2.
U.S. 2018 disposable income / real income (minus current taxes) [-]	0.88319	Refer to Table 2.
Share of savings from 2018 disposable income [-]	0.07848	Refer to Table 2.
Personal consumption in 2018 \dot{M} [\$ /yr]	27,930	Calculation: (\$34,317/yr)(0.88319)(1 - 0.07848).
Price of electricity p_E [\$ /kW·hr]	0.1287	U.S. 2018 average U.S. household electricity price (US Energy Information Administration, 2020a).
Fractional spend on original energy service $f_{C_s}^\circ$ [-]	0.0003028	Calculation: \$8.5/yr (spend on energy service) / [\$27,920/yr (other goods) + \$8.5/yr (energy service)] = 0.0003028, where spend on energy service = 580,350 lm·hr/yr / 8.83 lm/W / 1000 W/kW \times \$0.1287/kW·hr = \$8.5/yr. Note: this is energy service from a single lamp.
Real discount rate r [1/yr]	0.03	Taken from Federal Reserve St. Louis for 72 month car loan rate, which averaged 5% before the 2022 interest rate raises. Subtracting 2% inflation gives 3% real interest rate, by which we discount. (Board of Governors of the Federal Reserve System (US), 2024)
Macro factor k [-]	1.0	An initial value. See Section 4.1 for additional details.

Table 6: Lamp example: Elasticity parameters.

Parameter [units]	Description	Value	Data sources and notes
$\varepsilon_{\dot{q}_s, p_s}^o$ [-]	Uncompensated own price elasticity of lighting demand	-0.4	We adopt -0.4 as our baseline value, as the average of last 50 years from Fouquet (2014, Fig. 4). For comparison, Borenstein (2015) uses a range of -0.4 to -0.8, based on Fouquet & Pearson (2011).
$\varepsilon_{\dot{q}_s, p_s, c}^o$ [-]	Compensated own price elasticity of lighting demand	-0.3997	Calculated via the Slutsky Equation (Eq. (172) in Part I).
$\varepsilon_{\dot{q}_o, p_s, c}^o$ [-]	Compensated cross price elasticity of demand for other goods	0.00012	Calculated via Eq. (178) in Part I.
$\varepsilon_{\dot{q}_s, \dot{M}}$ [-]	Income elasticity of lighting demand	1.0	Follows from CES utility function.
$\varepsilon_{\dot{q}_o, \dot{M}}$ [-]	Income elasticity of demand for other goods	1.0	Follows from CES utility function.

2.2 Visualization

A rigorous rebound analysis should track energy, expenditure, and consumption aspects of rebound at the device (direct rebound) and elsewhere in the economy (indirect rebound) across adjustments for all rebound effects (emplacement, substitution, income, and macro). Doing so involves many terms and much complexity.

To date, visualizing the energy, expenditure, and consumption aspects of rebound phenomena has not been done in a numerically precise manner with a set of mutually consistent graphs. ~~So we~~ We introduce *rebound planes* to help advance clarity of (direct and indirect) rebound and adjustments (via emplacement, substitution, income, and macro effects) across all aspects (energy, expenditure, and consumption). Each aspect is represented by a path in its own plane, showing adjustments in response to the EEU. ~~The order of presentation below is energy first, followed by expenditure, ending with consumption, because the EEU triggers rebound (the topic of this article and visible in the energy plane), but is caused by expenditures on the EEU and further monetary adjustments (visible in the expenditure plane), which are calculated via details about substitution (visible in the consumption plane).~~

Axes of the rebound planes represent direct and indirect effects, with direct effects shown on the x -axes, and indirect effects shown on the y -axes. ~~Specifically,~~

~~direct and indirect energy consumption rates (\dot{E}_{dir} , \dot{E}_{indir}) are placed on the x - and y -axes of the energy plane, respectively;~~

~~direct and indirect expenditure rates (\dot{C}_{dir} and \dot{C}_{indir} , discounted for beginning of life and end of life costs) are placed on the x - and y -axes of the expenditure plane, respectively; and~~

~~the indexed consumption rate of the energy service (\dot{q}_s) and the indexed expenditure rate of other consumption goods (\dot{C}_o) are placed on the x - and y -axes of the consumption plane, respectively.~~

Paths through energy, expenditure, and consumption planes consist of segments that represent changes due to the various rebound effects. ~~Table 9 provides the key for rebound path segments.~~ Effects that include both direct and indirect rebound will show displacement along both axes and create a path in the x - y plane. See ~~Appendix B for detailed mathematical descriptions for constructing paths on the rebound planes, and see~~ Section 3 for rebound ~~path graphs~~ planes for

EEU examples of a car and an electric lamp –

Segments in rebound planes: Segment Rebound-effect Symbol ————— Direct
emplacement Re_{dempt} ————— Embodied energy Re_{emb} ————— Ops.
maint. and disp. Re_{OMd} ————— Indirect substitution Re_{isub} ————— Direct substitution
 Re_{dsub} ————— Direct income Re_{dinc} ————— Indirect income Re_{inc} Macro Re_{macro}

Each rebound plane is described in the subsections below. Reference to the rebound planes in
Figs. 2–7 below will be beneficial.

2.2.1 The energy plane

The energy plane (see Figs. 2 and 5 below) shows the direct energy consumption rate (\dot{E}_{dir}) on the
 x -axis and the indirect energy consumption rate (\dot{E}_{indir}) on the y -axis.¹ Points \circ , $*$, \wedge , $—$, and \sim
represent stages between the rebound effects of Fig. 1. Points a , b , c , and d represent intermediate
stages. Lines with negative slope through points \circ , a , $*$, \wedge , $—$, and \sim indicate energy consumption
isoquants at key points. Note that segment appears only in the energy plane, because the framework
tracks energy consumption but not expenditures or consumption for the macro effect.

In the energy plane, point a lies on the $Re_{tot} = 0\%$ line indicating that point a (and the
 $Re_{tot} = 0\%$ line) is the point from which all rebound effects (Re_{empl} , Re_{sub} , Re_{inc} , and Re_{macro})
are measured. If rebound effects cause total energy demand to return to the original energy
consumption level (negative sloping line through the \circ point), all expected energy savings are
taken back by rebound effects. Thus, the line of constant energy consumption through the \circ point
is labeled $Re_{tot} = 100\%$. The contribution of each rebound effect to total rebound is represented by
the distance that each component's segment moves across the rebound isoquants. Total rebound
(Re_{tot}) is measured linearly between and beyond the $Re_{tot} = 0\%$ and $Re_{tot} = 100\%$ lines, with direct
rebound in the x direction and indirect rebound in the y direction. The region below and to the left
of the $Re_{tot} = 0\%$ line exhibits negative rebound, indicating hyperconservation. The region above
and to the right of the $Re_{tot} = 100\%$ line shows backfire, i.e., greater total energy consumption after
the EEU than before it.

¹A related, notional-only (not quantified as in Section 3), one-dimensional visualization of direct and
indirect energy rebound (but not on expenditure or consumption planes) can be found in Fig. 1 of
Exadaktylos & van den Bergh (2021).

Segment moves in the negative y direction by definition of the indirect substitution effect, and segment moves in the positive x direction by the definition of the direct substitution effect. Both income effect segments (and) show more energy consumption, because net savings are spent on goods and services that rely on at least some energy consumption.¹ Segment always moves in the positive y direction, because macro effects lead to additional indirect energy consumption.

2.2.1 The expenditure plane

The expenditure plane (see Figs. 3 and 6 below) shows the direct expenditure rate on the energy service (\dot{C}_{dir}) on the x -axis and the indirect expenditure rate (\dot{C}_{indir} , discounted when appropriate) on the y -axis. Lines with negative slope through points \circ , a , $*$, and \wedge indicate expenditure isoquants. The line through the \circ point is an isoquant for the cost of purchasing the original consumption bundle at the original prices. The line through the $*$ point is an isoquant for the cost of purchasing the original consumption bundle at the new prices. Segments and could both move in the positive y direction, they could both move in the negative y direction, or they could move in opposite directions, depending on the results of the independent analyses for embodied energy and capital cost rates. The substitution effect along segments and will together, by definition, lead to lower expenditure due to the energy service price decline and the budget-reducing compensating variation (CV). The income effect (segments and) must bring expenditure back to the original expenditure line (equal to the budget constraint set by income in dollar or nominal terms) by assumptions about non-satiation and utility maximization in the device user's decision function.

2.2.1 The consumption plane

The consumption plane (Figs. 4 and 7 below) shows the indexed rate of energy service consumption ($\dot{q}_s/\dot{q}_s^\circ$) on the x -axis and the indexed rate of other goods consumption ($\dot{C}_o/\dot{C}_o^\circ$) on the y -axis. Iso-expenditure loci of indexed energy service and other goods demand, i.e. budget constraints, are shown as lines with negative slope (lines , , and). Note that budget constraints and intersect at the y -axis (i.e., where $x = 0$), because the prices of other goods and services do not change

¹We exclude the case of an inferior good, whose consumption decreases as real income increases, but we note here the possibility of such behavior. This behavior would however require a different utility model besides the CES utility model, which we use throughout this analysis.

as a result of the EEU. Emplacement (by itself) does not alter consumption patterns, so the rate of energy service consumption and the rate of other goods consumption are unchanged across the emplacement effect ($\dot{q}_s^\circ = \dot{q}_s^*$ and $\dot{C}_o^\circ = \dot{C}_o^*$, respectively). Thus, only movements after the $*$ point are visible as a path in the consumption plane, and points \circ , a , b , and $*$ collapse to the same location in the consumption plane.

Indifference curves for the CES utility model are denoted by \sim and represent lines of constant utility through the \circ and Λ points. Prior to the EEU, the consumption basket (of the energy service and other goods) is represented by the \circ point. The budget constraint, here in real terms, i.e., the capacity to purchase either the energy service or other goods and services, is shown as isoquant \bar{C} . The original budget constraint line (\bar{C}°) is tangent to the original indifference curve (\sim°) at point \circ , the optimal consumption bundle prior to the EEU. The real budget line indicates the (higher) capacity to purchase combinations of energy services and other goods and services using the same money needed to purchase the old consumption bundle but at the new, lower price for the energy service, thanks to the EEU.

The substitution effect leads to the cheaper, optimal CES-utility-preserving consumption bundle at the Λ point. The substitution effect is shown by segments $\Lambda\bar{C}$ (the indirect component, which represents the decrease in other goods consumption) and $\Lambda\bar{C}^\circ$ (the direct component, which represents the increase in energy service consumption). Although the substitution effect is calculated in the consumption plane, its impact can be seen in the energy and expenditure [Appendix B for detailed mathematical descriptions for constructing paths on the rebound](#) planes.

In the consumption plane, the income expansion path under the CES utility model is a ray \bar{C}° from the origin through the Λ point in the consumption plane. The pre- and post-income-effect points (Λ and \bar{C}° , respectively) lie along the ray, due to homotheticity. The increased consumption rate of the energy service is represented by segment $\bar{C}^\circ\bar{C}$, and the increased consumption rate of other goods and services is represented by segments $\Lambda\bar{C}$.

Under non-homothetic utility models, the income expansion path will be closer to vertical in the consumption plane, as the device owner spends more net income (\hat{N}) on other goods and less on the energy service. In the limit, consumption of the energy service is already satiated, so net income is spent completely on other goods, resulting in a vertical income expansion path.

2.3 Software tools

We developed an open source R package called `ReboundTools` to standardize and distribute the methods for calculating rebound magnitudes in our framework. `ReboundTools` can be found at <https://github.com/MatthewHeun/ReboundTools>. (See Heun (2023).) `ReboundTools` provides functions for (i) reading input data from a spreadsheet, (ii) performing rebound calculations, and (iii) generating rebound tables and rebound planes. `ReboundTools` was used for all calculations and all rebound planes in this paper.

To find the path to an example spreadsheet bundled with the package, users of `ReboundTools` can call the function `ReboundTools::sample_eeu_data_path()`. After filling the example spreadsheet with parameters for an EEU, users can call two functions (`ReboundTools::load_eeu_data()` and `ReboundTools::rebound_analysis()`) to perform all rebound calculations described in this paper. The function `ReboundTools::path_graphs()` creates rebound paths in the energy, expenditure, and consumption planes. Extensive documentation for `ReboundTools` can be found at <https://matthewheun.github.io/ReboundTools/>.

In addition, an Excel workbook that performs identical rebound calculations using the framework of this paper **** will be stored at the Research Data Leeds Repository if this submission is accepted. The spreadsheet file is included with the submission of this paper. **** (See Brockway et al. (2023).)

3 Results

In this section we present rebound calculation results for two examples: energy efficiency upgrades of a car (Section 3.1) and an electric lamp (Section 3.2). Univariate sensitivity studies for both examples (car and lamp) can be found in Appendix C.

3.1 Example 1: Purchase of a new car

3.1.1 Numerical results: Car example

Armed with the data in Tables 1–3, and the equations in Section 2 of Part I, we calculate important values at each rebound stage, as shown in Table 7. Note that Table 7 applies to the car user. Across

the macro effect (segment — \sim in Fig. 2), changes occur only in the macroeconomy. For the car user, no changes are recorded across the macro effect. Thus, the ~~—(bar) and \sim (tilde) columns of column is absent from Table 7 are identical.~~ Rebound components for the car upgrade are shown in Table 8. ~~Figs. 2–4 show energy, expenditure, and consumption planes for the car example.~~

Table 7: Results for car example with macro factor (k) assumed to be 1. There is no change for the consumer across across the macro effect, so the last stage (\sim) is not shown. Blanks indicate unchanged values relative to previous or later values in the same row.

		Original (\circ)	After empl ($*$)	After sub (\wedge)	After inc ($-$)
Income rate	\dot{M} [\$ / yr]	27,930	27,930	27,930	27,930
Energy price	p_E [\$ / MJ]	0.0208	0.0208	0.0208	0.0208
Device lifetime	t_{life} [yr]	14	14	14	14
TVM factor (BOL)	τ_α [—]	1.203	1.203	1.203	1.203
TVM factor (EOL)	τ_ω [—]	0.796	0.796	0.796	0.796
Efficiency (engineering units)	η [mile / gal]	25	42	42	42
Efficiency	η [mile / MJ]	0.197	0.332	0.332	0.332
Energy service price	p_s [\$ / mile]	0.105	0.063	0.063	0.063
Embodied energy rate	\dot{E}_{emb} [MJ / yr]	2,429	2,857	2,857	2,857
Capital cost rate	\dot{C}_{cap} [\$ / yr]	2,533	2,518	2,518	2,518
	$\tau_\alpha \dot{C}_{cap}$ [\$ / yr]	3,048	3,030	3,030	3,030
Ops. & maint. cost rate	\dot{C}_{OM} [\$ / yr]	5,050	4,779	4,779	4,779
Disposal cost	C_d [\$]	−300	−300	−300	−300
Disposal cost rate	\dot{C}_d [\$ / yr]	−21	−21	−21	−21
	$\tau_\omega \dot{C}_d$ [\$ / yr]	−17	−17	−17	−17
Ops. & maint. and disposal cost rate	\dot{C}_{OMd} [\$ / yr]	5,033	4,762	4,762	4,762
Energy consumption rate	\dot{E}_s [MJ / yr]	62,885	37,432	40,167	41,903
Energy cost rate	\dot{C}_s [\$ / yr]	1,306	777	834	870
Net income rate	\dot{N} [\$ / yr]	0	817	835	0
Energy service consumption rate	\dot{q}_s [mile / yr]	12,416	12,416	13,323	13,899
Other goods cost rate	\dot{C}_g [\$ / yr]	18,543	18,543	18,469	19,267

Table 8: Car example: rebound results with macro factor (k) assumed to be 1.

Rebound term	Value [%]
Re_{dempl}	0.0
Re_{emb}	1.7
Re_{OMd}	−3.4
Re_{dsub}	10.7
Re_{isub}	−0.9
Re_{dinc}	6.8
Re_{iinc}	10.2
Re_{macro}	10.4
Re_{tot}	35.4

The energy plane for the car example. Macro factor (k) is assumed to be 1. See Table 9 for meanings of path segments.

The expenditure plane for the car example. CV is compensating variation, the increase in consumption of the energy service and decrease in consumption of other goods and services to

~~maintain constant utility. See Table 9 for meanings of path segments.~~

~~The consumption plane for the car example. See Table 9 for meanings of path segments.~~

The **emplacement effect** has three components: the direct emplacement effect, the embodied energy effect, and the combined operations, maintenance, and disposal effects. Rebound from the direct emplacement effect (Re_{dempl}) is 0.0% always, because energy takeback (and, therefore, rebound) occurs after the upgraded device is emplaced. Indirect rebound due to the embodied energy effect (Re_{emb}) is 1.7%, due to the higher embodied energy rate ($\Delta \dot{E}_{emb}^* = 429$ MJ/yr) stemming from the electric battery in the hybrid EV car. Rebound due to the operations, maintenance, and disposal effects (Re_{OMd}) is small and negative (-3.4%), because of the slightly lower operations, maintenance, and disposal costs for the hybrid EV car.

The **substitution effect** has two components: direct and indirect substitution effect rebound. Rebound from direct substitution (Re_{dsub}) is positive, as expected (10.7%). The car user will, on average, prefer more driving purely from the change in relative prices because of the fuel economy enhancements (42 mpg > 25 mpg). In other words, due the relative price change, the more fuel-efficient car is driven 7.3% further each year. Conversely, the indirect substitution effect (Re_{isub}) is slightly negative (-0.9%) to achieve the same level of utility after increased driving. Indeed, across the substitution effect, less money is spent on other goods ($\Delta \hat{C}_o = -74$, $\Delta \hat{C}_g = -74$ \$/yr). In Appendix C.7, we show how the displacement along an indifference curve alters the price elasticities, and in particular, that the uncompensated own price elasticity declines in magnitude. The decline slows the rate of additional consumption of energy-intensive driving, and attenuates the microeconomic rebound relative to assuming constant price elasticities.

The **income effect** also has two components: direct and indirect income effect rebound. The direct income effect (Re_{dinc}) is positive (6.8%), because the car user allocates some net savings to additional driving. Rebound from the indirect income effect (Re_{iinc}) is positive (10.2%) due to higher spending on other goods. Thus, the net savings after the substitution effect ($\hat{N} = 835$ \$/yr) translates into positive direct and indirect income rebound at the microeconomic level. Total microeconomic rebound (emplacement, substitution, and income effects) sums to $Re_{micro} = 25.0\%$.

Finally, in Part I we noted that the link between macroeconomic and microeconomic rebound is largely unexplored, so we assume a value of $k = 1$ for both examples, initially. We return to




Fig. 2: The energy plane for the car example. Macro factor (k) is assumed to be 1. See Table 9 for meanings of path segments.

the value for k in the Discussion (Section 4.1). With k assumed to be 1, the **macro effect** leads to macroeconomic rebound (Re_{macro}) of 10.4% for the car example, due to economic expansion caused by productivity enhancements arising from the more-efficient provision of the energy service (transportation).

3.1.2 Rebound visualizations: Car example

Fig. 2 shows the energy plane for the car example, assuming $k = 1$. The energy plane shows the direct energy consumption rate (\dot{E}_{dir}) on the x -axis and the indirect energy consumption rate (\dot{E}_{indir}) on the y -axis.¹ Points \circ , $*$, \wedge , $-$, and \sim represent stages between the rebound effects of Fig. 1. Points a , b , c , and d represent intermediate stages. Table 9 provides the key for rebound path segments. Note that segment $- \text{ } \text{---} \text{ } \sim$ appears only in the energy plane, because the framework tracks energy consumption but not expenditures or consumption for the macro effect.

¹A related, notional-only (not quantified), one-dimensional visualization of direct and indirect energy rebound (but not on expenditure or consumption planes) can be found in Fig. 1 of Exadaktylos & van den Bergh (2021).

Table 9: Segments in rebound planes.

Segment	Rebound effect	Symbol
	Direct emplacement Embodied energy Ops. maint. and disp.	Re_{dempl} Re_{emb} Re_{OMd}
	Indirect substitution Direct substitution	Re_{isub} Re_{dsub}
	Direct income Indirect income	Re_{dinc} Re_{iinc}
	Macro	Re_{macro}

In the energy plane, lines with negative slope through points o , a , $*$, \wedge , $-$, and \sim indicate energy consumption isoquants at key points. Point a lies on the $Re_{tot} = 0\%$ line indicating that point a (and the $Re_{tot} = 0\%$ line) is the point from which all rebound effects (Re_{empl} , Re_{sub} , Re_{inc} , and Re_{macro}) are measured. If rebound effects cause total energy demand to return to the original energy consumption level (negative sloping line through the o point), all expected energy savings are taken back by rebound effects. Thus, the line of constant energy consumption through the o point is labeled $Re_{tot} = 100\%$. The contribution of each rebound effect to total rebound is represented by the distance that each component's segment moves across the rebound isoquants. Total rebound (Re_{tot}) is measured linearly between and beyond the $Re_{tot} = 0\%$ and $Re_{tot} = 100\%$ lines, with direct rebound in the x direction and indirect rebound in the y direction. The region below and to the left of the $Re_{tot} = 0\%$ line exhibits negative rebound, indicating hyperconservation. The region above and to the right of the $Re_{tot} = 100\%$ line shows backfire, i.e., greater total energy consumption after the EEU than before it.

Segment $*c$ moves in the negative y direction by definition of the indirect substitution effect, and segment $c\wedge$ moves in the positive x direction by the definition of the direct substitution effect. Both income effect segments ($\wedge d$ and $d-$) show more energy consumption, because net savings are spent on goods and services that rely on at least some energy consumption.² Segment $- \sim$ always moves in the positive y direction, because macro effects lead to additional indirect energy consumption.

Note that rebound values from Table 8 are indicated on Fig. 2 as sums of direct and indirect

²We exclude the case of an inferior good, whose consumption decreases as real income increases, but we note here the possibility of such behavior. This behavior would however require a different utility model besides the CES utility model, which we use throughout this analysis.




Fig. 3: The expenditure plane for the car example. CV is compensating variation, the increase in consumption of the energy service and decrease in consumption of other goods and services to maintain constant utility. See Table 9 for meanings of path segments.

components for each effect: emplacement, substitution, income, and macro. Total rebound is also shown.

Fig. 3 shows the expenditure plane for the car example. The expenditure plane shows the direct expenditure rate on the energy service (\dot{C}_{dir}) on the x -axis and the indirect expenditure rate (\dot{C}_{indir} , discounted when appropriate) on the y -axis. Lines with negative slope through points o , a , $*$, and \wedge indicate expenditure isoquants. The line through the o point is an isoquant for the cost of purchasing the original consumption bundle at the original prices. The line through the $*$ point is an isoquant for the cost of purchasing the original consumption bundle at the new prices. Segments $a \cdots b$ and $b \rightarrow *$ could both move in the positive y direction, they could both move in the negative y direction, or they could move in opposite directions, depending on the results of the independent analyses for embodied energy and capital cost rates. The substitution effect along segments $* \rightarrow c$ and $c \rightarrow \wedge$ will together, by definition, lead to lower expenditure due to the energy service price decline and the budget-reducing compensating variation (CV). The income effect (segments $\wedge \rightarrow d$ and $d \rightarrow o$)




Fig. 4: The consumption plane for the car example. See Table 9 for meanings of path segments.

must bring expenditure back to the original expenditure line (equal to the budget constraint set by income in dollar or nominal terms) by assumptions about non-satiation and utility maximization in the device user's decision function.

Fig. 4 shows the consumption plane for the car example. The consumption plane shows the indexed rate of energy service consumption ($\dot{q}_s/\dot{q}_s^\circ$) on the x -axis and the indexed rate of other goods consumption ($\dot{C}_g/\dot{C}_g^\circ$) on the y -axis. Iso-expenditure loci of indexed energy service and other goods demand, i.e. budget constraints, are shown as lines with negative slope (lines $\circ-\circ$, $*-*$, $\wedge-\wedge$, and $- - -$). Note that budget constraints $\circ-\circ$ and $- - -$ intersect at the y -axis (i.e., where $x = 0$), because the prices of other goods and services do not change as a result of the EEU. As defined in this framework, emplacement (by itself) does not alter consumption patterns, so the rate of energy service consumption and the rate of other goods consumption are unchanged across the emplacement effect ($\dot{q}_s^\circ = \dot{q}_s^*$ and $\dot{C}_g^\circ = \dot{C}_g^*$, respectively). Thus, only movements after the $*$ point are visible as a path in the consumption plane, and points o , a , b , and $*$ collapse to the same location in the consumption plane.

Indifference curves for the CES utility model are denoted by $i^\circ - i^\circ$ and $\bar{i} - \bar{i}$ and represent lines of constant utility through the \circ and $-$ points. Prior to the EEU, the consumption basket (of the energy service and other goods) is represented by the \circ point. The budget constraint, here in real terms, i.e., the capacity to purchase either the energy service or other goods and services, is shown as isoquant $\circ - \circ$. The original budget constraint line ($\circ - \circ$) is tangent to the original indifference curve ($i^\circ - i^\circ$) at point \circ , the optimal consumption bundle prior to the EEU. The real budget line $* - *$ indicates the (higher) capacity to purchase combinations of energy services and other goods and services using the same money needed to purchase the old consumption bundle but at the new, lower price for the energy service, thanks to the EEU.

The substitution effect leads to the cheaper, optimal CES-utility-preserving consumption bundle at the \wedge point. The substitution effect is shown by segments $* - c$ (the indirect component, which represents the decrease in other goods consumption) and $c - \wedge$ (the direct component, which represents the increase in energy service consumption). Although the substitution effect is calculated in the consumption plane, its impact can be seen in the energy and expenditure planes.

In the consumption plane, the income expansion path under the CES utility model is a ray ($r - r$) from the origin through the \wedge point in the consumption plane. The pre- and post-income-effect points (\wedge and $-$, respectively) lie along the $r - r$ ray, due to homotheticity. The increased consumption rate of the energy service is represented by segment $\wedge - d$, and the increased consumption rate of other goods and services is represented by segments $d - -$.

Under non-homothetic utility models, the income expansion path will be closer to vertical in the consumption plane, as the device owner spends more net income (\hat{N}) on other goods and less on the energy service. In the limit, consumption of the energy service is already satiated, so net income is spent completely on other goods, resulting in a vertical income expansion path.

3.2 Example 2: Purchase of a new electric lamp

3.2.1 Numerical results: Lamp example

With the data in Tables 4–6 and the equations in Section 2 of Part I in hand, we calculate important values at each rebound stage, as shown in Table 10. ~~Similar to Table 7, Table 10 applies to the lamp~~

317 user, so no changes are recorded across the macro effect, and the $\bar{}$ (bar) and \sim (tilde) columns of
318 Table 10 are identical. Rebound components for the lamp upgrade are shown in Table 11. Figs. 5–7
319 show energy, expenditure, and consumption planes for the lamp example.

Table 10: Results for lamp example with macro factor (k) assumed to be 1. There is no change for the consumer across across the macro effect, so the last stage (\sim) is not shown. Blanks indicate unchanged values relative to previous or later values in the same row.

		Original (\circ)	After empl ($*$)	After sub (\wedge)	After inc ($-$)
Income rate	\dot{M} [\$ / yr]	27,930	27,930	27,930	27,930
Energy price	p_E [\$ / MJ]	0.0358	0.0358	0.0358	0.0358
Device lifetime	t_{life} [yr]	2	10	10	10
TVM factor (BOL)	τ_α [–]	1.012	1.138	1.138	1.138
TVM factor (EOL)	τ_ω [–]	0.959	0.847	0.847	0.847
Efficiency (engineering units)	η [lm·hr/kW·hr]	8,833	81,800	81,800	81,800
Efficiency	η [lm·hr/MJ]	2,454	22,722	22,722	22,722
Energy service price	p_s [\$ / lm·hr]	0.00001457	0.00000157	0.00000157	0.00000157
Embodied energy rate	\dot{E}_{emb} [MJ / yr]	1.222	0.650	0.650	0.650
Capital cost rate	\dot{C}_{cap} [\$ / yr]	1.04	0.12	0.12	0.12
	$\tau_\alpha \dot{C}_{cap}$ [\$ / yr]	1.06	0.14	0.14	0.14
Ops. & maint. cost rate	\dot{C}_{OM} [\$ / yr]	0.00	0.00	0.00	0.00
Disposal cost	C_d [\$]	0.00	0.00	0.00	0.00
Disposal cost rate	\dot{C}_d [\$ / yr]	0.00	0.00	0.00	0.00
	$\tau_\omega \dot{C}_d$ [\$ / yr]	0.00	0.00	0.00	0.00
Ops. & maint. and disposal cost rate	\dot{C}_{OMd} [\$ / yr]	0.00	0.00	0.00	0.00
Energy consumption rate	\dot{E}_s [MJ / yr]	236.5	25.5	62.2	62.2
Energy cost rate	\dot{C}_s [\$ / yr]	8.46	0.91	2.22	2.22
Net income rate	\dot{N} [\$ / yr]	0.00	8.46	11.30	0.00
Energy service consumption rate	\dot{q}_s [lm·hr / yr]	580,350	580,350	1,412,867	1,413,439
Other goods cost rate	\dot{C}_g [\$ / yr]	27,920	27,920	27,916	27,927

Table 11: Lamp example: rebound results with macro factor (k) assumed to be 1.

Rebound term	Value [%]
Re_{dempl}	0.0
Re_{emb}	−0.3
Re_{OMd}	0.0
Re_{dsub}	17.4
Re_{isub}	−6.4
Re_{dinc}	0.0
Re_{iinc}	17.3
Re_{macro}	13.0
Re_{tot}	41.1

320 The **emplacement effect** rebound components start with the direct emplacement effect (Re_{dempl}),
321 which is always 0.0%. Indirect rebound due to the embodied energy effect (Re_{emb}) is −0.3%.
322 Although the LED lamp has higher embodied energy ($E_{emb}^* = 6.50$ MJ) than the incandescent lamp
323 ($E_{emb}^\circ = 2.20$ MJ), the LED lamp has a much longer lifetime, meaning that the LED embodied energy
324 rate ($\dot{E}_{emb}^* = 0.65$ MJ / yr) is less than the incandescent embodied energy rate ($\dot{E}_{emb}^\circ = 1.22$ MJ / yr).

Thus, the change in embodied energy rate ($\Delta \dot{E}_{emb}^*$) is -0.57 MJ/yr, and embodied energy rebound is negative ($Re_{emb} = -0.3\%$). Rebound due to the combined operations, maintenance, and disposal effects (Re_{OMd}) is 0.0% , because we assume no difference in operations, maintenance, or disposal costs between the incandescent lamp and the LED lamp.³

Direct **substitution effect** rebound (Re_{dsub}) is 17.4% due to the much higher LED lamp efficiency ($\tilde{\eta} = 81.8 \eta^* = 81.8$ lm/W) compared to the incandescent lamp ($\eta^\circ = 8.83$ lm/W), leading to increased demand for lighting (from $\dot{q}_s^* = 580,350$ lm·hr/yr to $\hat{\dot{q}}_s = 1,412,867$ lm·hr/yr) as shown by segment $c \rightarrow \wedge$ in Fig. 7. To maintain constant utility, consumption of other goods is reduced ($\Delta \hat{C}_o = -4.15 \Delta \hat{C}_g = -4.15$ \$/yr), ~~as shown by segment in Fig. 7,~~ yielding indirect substitution effect rebound (Re_{isub}) of -6.4% .

Income effect rebound arises from spending net energy cost savings associated with converting from the incandescent lamp to the LED lamp ($\hat{N} = 11.30$ \$/yr). Direct income effect rebound (Re_{dinc}) is 0.01% , positive but small, as the lamp user allocates some of the net savings to additional demand for lighting. The indirect income effect rebound is large ($Re_{iinc} = 17.3\%$), due to the energy implications of increased spending on other goods. Total microeconomic level rebound (emplacement, substitution, and income effects) sums to $Re_{micro} = 28.1\%$.

Finally, **macro effect** rebound (Re_{macro}) is 13.0% with k assumed to be 1, due to economic expansion caused by productivity enhancements arising from the more-efficient provision of the energy service (lighting).

3.2.2 Rebound visualizations: lamp example

Figs. 5–7 show energy, expenditure, and consumption planes for the lamp example.

³Maintenance cost rates for both incandescent and LED lamps are likely to be equal and negligible; lamps are usually installed and forgotten. Real-world disposal cost differences between the incandescent and LED technologies are also likely to be negligible. However, if “disposal” includes recycling processes, cost rates may be different between the two technologies due to the wide variety of materials in LED lamps compared to incandescent lamps.




Fig. 5: The energy plane for the lamp example. Macro factor (k) is assumed to be 1. See Table 9 for meanings of path segments.




Fig. 6: Expenditure plane for the lamp example. CV is compensating variation, the increase in consumption of the energy service and decrease in consumption of other goods and services to maintain constant utility. See Table 9 for meanings of path segments.

or GDP growth. While the idea of scale economies from larger markets for particular products have a long history in economic thought dating back at least to Smith (1776), data from input-output tables and recent advances in network theory allowed formalization of the spill-overs from sectoral to aggregate growth. First results ~~show that~~ from the literature show that three quarters of U.S. aggregate output growth may have been up to 3 times as large as the growth of the sector in which growth originated (Foerster et al., 2022). ~~And industrial policy to encourage technology adoption in certain sectors was found to pay back up to 5 times its cost in India, but with wide variation across sectors (?). Since our problem also concerns technology adoption, one that features energy augmenting technical change, we take the value from the ? study, where the majority of multipliers cluster around 3. Thus, we~~ originates from sectoral shocks, which are amplified through the production and investment network where one sector's output is used as intermediate inputs and capital goods in others (Foerster et al., 2022). Durable goods are estimated by the authors to have the largest sectoral multiplier, and their effect on aggregate output is more than three times their sectoral growth. Since we are also considering durable goods, we adopt the value of $k = 3$ to represent the long-run growth effect, fully aware that this can ~~only be~~ be only a first approximation.

After setting $k = 3$, we can recalculate all rebound components in our framework. Emplacement (Re_{empl}), substitution (Re_{sub}), and income (Re_{inc}) rebound magnitudes are unchanged after setting $k = 3$. However, we see that choosing a placeholder value of $k = 1$ resulted in a low value for Re_{macro} and, therefore, Re_{tot} in Section 3. In Figs. 2 and 5, the macro effect segments ($- \text{---} \sim$) should be three times longer than they appear. In Tables 8 and 11, the values of macro rebound (Re_{macro}) should triple to 31.2% and 39.0%, and the values of total rebound (Re_{tot}) should increase to 56.2% and 67.0% for the car and lamp examples, respectively. For the remainder of this paper, we use $k = 3$.

4.2 Comparison between the car and lamp case studies

Tables 8 and 11 and selection of $k = 3$ in Section 4.1 enable fuller comparisons between the car and lamp examples. Several points can be made.

First, the magnitude of every rebound effect is different between the two examples, the exception

387 being direct emplacement rebound (Re_{dempl}) which is always 0.0% by definition. The implication is
388 that every EEU needs to be analyzed separately. The magnitudes of the rebound effects for one
389 EEU should never be assumed to apply to a different EEU.

390 Second, one cannot know *a-priori* which rebound effects will be large and which will be small for
391 a given EEU. Furthermore, some rebound effects are dependent upon economic parameters, such as
392 energy intensity (I_E). Thus, it is important to calculate the magnitude of all rebound effects for
393 each EEU in each economy.

394 Third, the two examples illustrate the fact that embodied energy rebound (Re_{emb}) can be positive
395 or negative, as discussed in Section 2.5.1 of Part I. The car's embodied energy rebound is positive
396 (1.7%) because of the high embodied energy of the hybrid's battery relative to the internal combustion
397 engine vehicle. Although the LED lamp's embodied energy is larger than the incandescent lamp's
398 embodied energy, the LED lamp's embodied energy rebound is small but negative (-0.3%), due to
399 the longer life of the LED lamp compared to the incandescent lamp. Thus, each EEU should be
400 analyzed independently for its embodied energy rebound.

401 Fourth, macro effect rebound is different between the two examples, owing to differences in
402 net income (\dot{N}^*) relative to expected savings (\dot{S}_{dev}). (For the car, Re_{macro} is 31.2%. For the lamp,
403 Re_{macro} is 39.0%.) The efficiency gain for the lamp is far greater than the efficiency gain for the car,
404 leading to much different rates of net income (\dot{N}^*) and different macro rebound values.

405 4.3 Comparison to previous rebound estimates

406 Tables 12 and 13 compare car and lamp results (with $k = 3$) to results from previous studies. The
407 suite of comparison studies is neither comprehensive nor definitive of car and lamp EEU's; rather,
408 they are examples that show the sort of calculations and estimations carried out in the general
409 literature using a variety of methods. That said, many of the studies are highly cited, thereby
410 carrying sufficient academic weight for our purposes. Tables 12 and 13 and their associated references
411 enable two types of observations, comparing (i) coverage of rebound components and (ii) magnitudes
412 and associated calculation or estimation methods.

Table 12: Rebound magnitude comparisons for the car example. All numbers in %. $k = 3$ is assumed. Note that $Re_{tot} = Re_{empl} + Re_{sub} + Re_{inc} + Re_{macro}$, $Re_{tot} = Re_{micro} + Re_{macro}$, and $Re_{tot} = Re_{dir} + Re_{indir}$.

	Rebound study	Coverage	Analysis method	Re_{empl}	$\frac{Re_{micro}}{Re_{sub}}$	Re_{inc}	Re_{macro}	Re_{dir}	Re_{indir}	Re_{tot}
	This paper (2024)	U.S., 2020	Energy, expenditure, and consumption planes	-1.8	9.8	17.0	31.2	17.6	38.6	56.2
1	Small & Van Dender (2007)	U.S., 1967–2001	Elasticity of VMT w.r.t. fuel cost per mile					4.5 (short run, 1967–2001) 22.2 (long run, 1967–2001) 2.2 (short run, 1997–2001) 10.7 (long run, 1997–2001)		
2	Greene (2012)	U.S., 1966–2007	Elasticities of transport fuel w.r.t. price & efficiency					4 (short run) 16 (long run)		
3	Koesler (2013)	Germany, 2009	Static CGE model, 10% efficiency shock					≤ 64	≤ 16	56
4	Thomas & Azevedo (2013)	U.S., 2004	Expenditure/cross price elasticities of personal transport fuels, using household spending survey data					10	6	
5	Borenstein (2015)	U.S., 2012	Microeconomic framework		13 (6–28)	11				
6	Chitnis & Sorrell (2015)	UK, 1964–2014	Estimated own/cross price elasticities of transport fuels, uses household spending survey data		72	5		55	23	86
7	Gillingham et al. (2015)	Pennsylvania, 2000–2010	Estimation of gasoline price elasticity of driving demand, from dataset of 75 million vehicle inspection records, including odometer data					10 (short run)		
8	Stapleton et al. (2016)	UK 1970–2011	Elasticity of VMT w.r.t. fuel cost/prices					9–36		
9	Moshiri & Aliyev (2017)	Canada, 1997–2009	Price elasticity of transport fuel, using household spending survey data					82–88		
10	Duarte et al. (2018)	Spain, 2010–2030	Dynamic CGE model, efficiency shock							26 (short run) 52 (long run)

Table 13: Rebound magnitude comparisons for the lamp example. All numbers in %. $k = 3$ is assumed. Note that $Re_{tot} = Re_{empl} + Re_{sub} + Re_{inc} + Re_{macro}$, $Re_{tot} = Re_{micro} + Re_{macro}$, and $Re_{tot} = Re_{dir} + Re_{indir}$.

	Rebound study	Coverage	Analysis method	Re_{empl}	Re_{micro} Re_{sub}	Re_{inc}	Re_{macro}	Re_{dir}	Re_{indir}	Re_{tot}
	This paper (2024)	U.S., 2020	Energy, expenditure, and consumption planes	−0.3	11.0	17.4	39.0	17.4	49.7	67.0
1	Guertin et al. (2003)	Canada, 1993	Econometric residential energy demand model based on Canadian household data					32–49		
2	Freire-González (2011)	Catalonia, Spain, 2000–2008	Input-output based energy model, utilising expenditure/cross price elasticities					49	16	
3	Thomas & Azevedo (2013)	U.S., 2004	Expenditure/cross price elasticities of home electricity use, using household spending survey data					10	10	
4	Schleich et al. (2014)	Germany, 2012	Survey of electricity consumption in 6409 German households					6		
5	Borenstein (2015)	U.S., 2012	Microeconomic framework		14 (6–37)	6				
6	Chitnis & Sorrell (2015)	UK, 1964–2014	Estimated own/cross price elasticities of transport fuels, uses household spending survey data		14	35		41	8	49
7	Duarte et al. (2018)	Spain, 2010–2030	Dynamic CGE model, efficiency shock							12 (short run) 51 (long run)
8	Barkhordar (2019)	Iran, 2018–2040	Dynamic CGE model					28 (average)		43 (average)
9	Chitnis et al. (2020)	UK, 1964–2015	Household demand analysis via Linear approximation to the Almost Ideal Demand System (LAIDS)					95	−41	54
10	Shojaeddini & Gilbert (2022)	U.S., 2009	Price elasticity of lighting from cross sectional data from the 2009 Residential Energy Consumption Survey (RECS)					18–29		

First, we see that none of the comparison studies report all rebound effects considered in this paper. Also, no previous studies report either emplacement rebound ($Re_{empl} = Re_{emb} + Re_{OMd}$) or include all of direct and indirect, substitution and income microeconomic rebound effect combinations. In addition, none of the other studies report macro rebound (Re_{macro}) by itself. In fact, only 4 and 5 of the 10 studies in each category (car and lamp, respectively) report total rebound (Re_{tot}). Therefore, by carefully including all rebound components in the framework and elucidating all rebound components in Part II, we are (i) helping to advance conceptual clarity in the field of energy rebound, which (ii) may enable future studies to estimate a broader range of rebound components.

We also observe that studies which provide total rebound are based on a top-down calculation of overall, economy-wide rebound, rather than the bottom-up “sum-of-components” approach that we employ. That finding is instructive. It supports the view that a rigorous analysis framework that sets out individual rebound components has been missing, which informed the objective for Part I of this paper. Further, the finding means that comparisons between top-down estimations or calculations of total, economy-wide rebound may also be of limited value, because the rebound effects included or excluded may not be clear, giving an appearance of a “black box” calculation approach.⁴

Second, helpful insights can be gained from comparison of rebound magnitudes and calculation methods. Greatest alignment between our values and earlier values appears within the direct (microeconomic) rebound (Re_{dir}) column in Tables 12 and 13. Our car (17.6%) and lamp (17.4%) values are in the lower half of the comparison studies for both cases (10% to 49% for the car and 10% to 55% for the lamp). This alignment may be due to the easier determination of direct rebound, from either empirical data (e.g., Small & Van Dender (2007)) or via own price elasticities (e.g., Chitnis & Sorrell (2015)).⁵

For indirect rebound (Re_{indir}), there is little agreement on the magnitude of rebound effects. Our values for car (38.6%) and lamp (49.7%) indirect rebound magnitudes are higher than those found in the comparison studies for either the car (6% to 23%) or the lamp (8% to 16%) cases. The most

⁴That said, without the top-down approaches, we would have few values to compare with our total rebound (Re_{tot}).

⁵Also worthy of note is that direct (microeconomic) rebound of personal transport may be the most-studied subfield in the rebound literature and likely the only topic with enough studies to enable meta-reviews such as Sorrell et al. (2009), Dimitropoulos et al. (2018), and Gillingham (2020).

likely cause of our larger indirect rebound values is that we include both micro and macro rebound levels, whereas the comparison studies focus mainly on microeconomic rebound only (commonly via cross price elasticities). In other words, comparisons of our indirect rebound values with the studies in Tables 12 and 13 may be too simple and not very meaningful, as we (alone) include macro-level effects in indirect rebound. If we exclude Re_{macro} from Re_{indir} , our indirect microeconomic rebound values become 7.5% (car) and 10.7% (lamp), which fit within the ranges reported by the car (6% to 23%) and lamp (−41% to 16%) comparison studies.

For total rebound (Re_{tot}), our values of 56.2% (car) and 67.0% (lamp) are close to those in the comparison studies for both the car (49% to 51%) and lamp (43% to 51%) examples. Beyond that, comparisons (as noted earlier) are inhibited by methodological differences between previous studies (top-down methods) and our bottom-up approach for calculating total rebound.

4.4 Sensitivity of rebound to $\varepsilon_{q_s, p_s}^{\circ}$

The effect of the uncompensated own price elasticity of energy service consumption ($\varepsilon_{q_s, p_s}^{\circ}$) on rebound deserves additional consideration, because it dictates the magnitude of direct substitution rebound and thereby affects other rebound components that follow. $\varepsilon_{q_s, p_s}^{\circ}$ is important, because it models device owner behavior with respect to additional consumption of the energy service. As $\varepsilon_{q_s, p_s}^{\circ}$ becomes more negative, the device owner increases consumption of the energy service after the EEU. We illustrate with the lamp example.

Because the microeconomic portion of this framework is focused on adjustments caused by a single EEU (in this example, replacing a single incandescent lamp with a single LED), $\varepsilon_{q_s, p_s}^{\circ}$ should account for only the behavioral adjustment of using a lamp for more hours per day. The device owner installing additional lamps with the savings generated by the EEU would fall under the income effect in our framework. Installing additional lamps elsewhere in the economy would fall under the macro effect.

Fouquet & Pearson (2011, Table 3) estimate $\varepsilon_{q_s, p_s}^{\circ} = -0.6$ for the most recent decade of their study (2000–2010). As with most historical lighting rebound studies, the Fouquet & Pearson estimate applies to the whole economy and will include emplacement of additional lamps. Thus,

the value $\varepsilon_{q_s, p_s}^{\circ} = -0.6$ is not entirely applicable to our framework, which is focused on single-device replacement. The value applicable to single-device replacements (and appropriate for this framework) is expected to be less negative. Like us, Borenstein (2015) focuses on single-device replacements and uses a range: $-0.8 < \varepsilon_{q_s, p_s}^{\circ} < -0.4$. We select $\varepsilon_{q_s, p_s}^{\circ} = -0.4$ (Table 6), acknowledging that the single-device elasticity is expected to be less negative than the economy-wide value from Fouquet & Pearson (-0.6). With $\varepsilon_{q_s, p_s}^{\circ} = -0.4$, Table 13 indicates that consumption of illumination from the single lamp increases by a factor of 2.4 from 3.0 hr/day originally to 7.3 hr/day after the substitution effect. This may mean that the more efficient lamp isn't switched off when the device owner leaves a room or the house for a period of time.

To our knowledge, the only study that focuses on single-device rebound and differentiates between “burn time” rebound and “luminosity” rebound is Schleich et al. (2014). Their methodology to determine burn time rebound relies on surveys and self-reported estimates rather than in-home measurements of the additional burn time per day for an LED lamp compared to an incandescent lamp. Because of this shortcoming, we prefer the value of $\varepsilon_{q_s, p_s}^{\circ} = -0.4$, as motivated above.

Regardless, Schleich et al. (2014) and Fouquet & Pearson (2011) can be used to assess the sensitivity of total rebound to the value of $\varepsilon_{q_s, p_s}^{\circ}$. Indeed, a value for $\varepsilon_{q_s, p_s}^{\circ}$ can be back-calculated from the estimate of burn time rebound, given as 4% (Schleich et al., 2014, p. 40, Table 2, “All bulbs, IL to LED” row). Burn time rebound is equivalent to our direct substitution rebound (Re_{dsub}) and implies a value for uncompensated own price elasticity of energy service consumption of $\varepsilon_{q_s, p_s}^{\circ} = -0.13$.⁶ Our value of $\varepsilon_{q_s, p_s}^{\circ} = -0.4$ lies between Fouquet & Pearson (-0.6) and the implied elasticity from Schleich et al. (-0.13).

Fig. 8 shows the univariate sensitivity to $\varepsilon_{q_s, p_s}^{\circ}$ for the lamp example and enables estimation of total rebound in our framework using the implied elasticity from Schleich et al. (2014) and the recent value from Fouquet & Pearson (2011). (See Appendix C for additional univariate sensitivity analyses.) Specifically, total rebound for the lamp example is 55.2% (with $\varepsilon_{q_s, p_s}^{\circ} = -0.13$, the implied value from Schleich et al.), 67.0% (with $\varepsilon_{q_s, p_s}^{\circ} = -0.4$, our preferred value), or 81.7% (with $\varepsilon_{q_s, p_s}^{\circ} = -0.6$, from Fouquet & Pearson).

⁶The value of $\varepsilon_{q_s, p_s}^{\circ} = -0.13$ was obtained via iteration: values for $\varepsilon_{q_s, p_s}^{\circ}$ were guessed until Eq. 23 of Part I gave $Re_{dsub} = 4\%$.




Fig. 8: Sensitivity of rebound components to uncompensated own price elasticity of energy service demand (ε_{q_s, p_s}^o) in the lamp example. The macro factor, $k = 3$. The line for Re_{dinc} is behind the line for Re_{dempl} . (Note reversed x -axis scale.)

4.5 Comparison of CES with satiated and constant price elasticity (CPE) utility models

In Section 2.5.3 of Part I, we showed income-effect rebound expressions under the limiting condition of already-satiated consumption of the energy service such that the income expansion path is a vertical line in the consumption plane of Figs. 4 and 7. Here, we discuss the numerical impact of the different utility models.

Table 14 compares income-effect rebound under the CES utility model, the bounding condition of satiated consumption of the energy service, and the constant price elasticity (CPE) utility model.⁷

In the car example, income effect rebound (Re_{inc}) reduces from 17.0% to 10.6% when moving from the CES utility model to the bounding condition of already-satiated consumption of the energy service. Total rebound (Re_{tot}) goes from 56.2% to 49.8%. On the other hand, the lamp example shows negligible change in total rebound (Re_{tot}), moving from 67.04% to 67.03%.

The reason for the nearly unchanged value for total rebound (Re_{tot}) in the lamp example is evident in the consumption plane of Fig. 7. In the CES (homothetic) utility model shown in Fig. 7, there is almost no income-effect spending on more of the energy service. Almost all spending of net income (\hat{N}) is on other goods. The path between the \wedge and $-$ points is nearly vertical already. In contrast, the path from \wedge to $-$ in the car example (Fig. 4) is decidedly *not* vertical and a reduction in income-effect rebound (Re_{inc}) is observed when moving from the CES utility model to the bounding condition of already satiated energy service consumption. Reality is probably somewhere in between.

Calculation of substitution rebound under the constant price elasticity (CPE) utility model, which approximates the substitution and income effects using only the uncompensated own price elasticity of energy service consumption ($\varepsilon_{q_s p_s}$), systematically overestimates substitution effect rebound and underestimates income effect rebound. That's by construction since income, not utility, is held constant when calculating substitution of the energy service for other goods consumption with the CPE model. And the income effect, in the CPE utility model, allows spending on other goods only, which leads to a lower income rebound than in the satiated model, since the absence of

⁷The constant price elasticity (CPE) utility model in Table 14 follows Borenstein (2015) who holds income constant, not utility, when calculating the substitution effect. Furthermore, Borenstein's income effect assumes all post-emplacement freed cash (\hat{N}^*) is spent at the energy intensity of the economy (I_E).

Table 14: Comparison of substitution effects (Re_{dsub} , Re_{isub} , Re_{sub}), income effects, (Re_{dinc} , Re_{iinc} , and Re_{inc}), and total (Re_{tot}) rebound for the CES utility model, satiated consumption of the energy service, and the CPE utility model for both car and lamp examples.

Rebound term	Car example			Lamp example		
	CES	Satiated	CPE	CES	Satiated	CPE
Re_{dsub} [%]	10.7	10.7		17.37	17.37	
Re_{isub} [%]	-0.9	-0.9		-6.37	-6.37	
Re_{sub} [%]	9.8	9.8	15.0	11.00	11.00	15.37
Re_{dinc} [%]	6.8	0.0		0.01	0.00	
Re_{iinc} [%]	10.2	10.6		17.35	17.35	
Re_{inc} [%]	17.0	10.6	10.4	17.36	17.35	12.99
Re_{tot} [%]	56.2	49.8		67.04	67.03	

compensating variation leaves less income to spend. Once again, the specific case determines the deviation of the sum of substitution and income rebound from an exact (in our case, CES) model. Table 14 shows that while the sum of substitution and income effects is 1.4% smaller for the CPE utility model relative to the CES utility model, they are nearly the same in the lamp example.

4.6 Energy price rebound

~~Appendix F of Part I~~, Section 3.2, ~~and~~ Eq. (36), and Appendix F of Part I provide an extension to the framework involving energy price rebound (Re_{pE}). This section quantifies energy price rebound for the car and lamp examples.

To quantify energy price rebound, data are needed for personal consumption (\dot{E}°) of the type of energy used by the device, including energy for the upgraded device and all other devices. For the car example, there is typically little other household gasoline consumption besides for cars, so we assume \dot{E}° equal to $\dot{E}_s^\circ/0.95$. For the lamp example, a median U.S. household consumes about 10,000 kW·hr/yr of electricity (U.S. Energy Information Agency, 2023). Given that there are 2.5 persons per U.S. household (Statista, 2024), an individual consumes electricity at a rate of $\dot{E}^\circ = 4000$ kW·hr/yr.

We also need data for the price elasticity of energy supply ($\varepsilon_{\dot{Q}_{E,pE}}$). For the car case, we take the price elasticity of gasoline supply to be 0.29 from Coyle et al. (2012). For the lamp case, we adopt the value of 0.33 from Ghoddusia & Roy (2017, Table 3).

Parameterizing on the fraction of all devices in the economy that are upgraded (f_{EEU}) and the




Fig. 9: Energy price rebound (Re_{p_E}) as a function of the fraction of all devices replaced by higher-efficiency versions (f_{EEU}). Black lines represent the nominal energy price elasticity of energy supply ($\varepsilon_{\dot{Q}_{E,PE}}$). Gray bands provide ± 0.1 range in $\varepsilon_{\dot{Q}_{E,PE}}$.

energy price elasticity of energy supply ($\varepsilon_{\dot{Q}_{E,PE}}$) yields Figure 9. As expected, price-effect rebound (Re_{p_E}) grows as more devices are upgraded, i.e., as f_{EEU} increases. Furthermore, inelastic energy supply (smaller $\varepsilon_{\dot{Q}_{E,PE}}$) leads to higher price-effect rebound.

In these examples, the car upgrade yields little additional freed cash beyond the (slightly) cheaper fuel for the car, so there is limited spending on other goods and services and little additional indirect energy demand. In contrast, the upgrade of the electric lamp is much more likely to provide energy price rebound, because electricity for the upgraded lamp is a small fraction of total electricity consumption by the consumer. *All* electricity purchased by the consumer becomes cheaper when the price of electricity falls due to widespread lamp upgrades throughout the economy, leading to freed cash spent on other goods and services which, themselves, demand energy at the energy intensity of the economy.

At 100% penetration of LED lamps ($f_{EEU} = 1$) and at the nominal energy price elasticity of supply ($\varepsilon_{\dot{Q}_{E,PE}} = 0.33$), energy price rebound is $Re_{p_E} = 60.9\%$. Combined with consumer sided

rebound of 67.0% from Section 4.1, the sum of consumer-sided and supply-side rebound is 127.9%, demonstrating that backfire could occur under conditions of full penetration of the lamp EEU.

5 Conclusions

In this paper (Part II [of two](#)), we help to advance clarity in the field of energy rebound by (i) developing mutually consistent and numerically precise visualizations of rebound effects in energy, expenditure, and consumption planes, (ii) operationalizing the macro factor, (iii) documenting in detail new calculations of rebound for car and lighting upgrades, (iv) showing the extensibility of our framework by applying it to estimate energy price rebound, and (v) providing information about new open source software tools for calculating and visualizing rebound for any energy efficiency upgrade. We encourage energy analysts and economists to use visualizations like the energy, expenditure, and consumption planes to document [and visualize](#) rebound calculations going forward. Our hope is that additional clarity will (i) narrow the gap between economists and energy analysts, (ii) lead to deeper interdisciplinary understanding of rebound phenomena, and (iii) enable energy and climate policy that takes full account of rebound.

From the application of the framework in Part II, we draw two important conclusions. First, the car and lamp examples (Section 3) show that the framework enables quantification of rebound magnitudes at microeconomic and macroeconomic levels, including energy, expenditure, and consumption aspects of direct and indirect rebound for emplacement, substitution, income, and macro effects. Second, the examples show that magnitudes of all rebound effects vary with the type of EEU performed. Thus, values for rebound effects for one EEU should never be assumed to apply to a different EEU, and it is important to calculate the magnitude of all rebound effects for each EEU in each economy.

Further work could be pursued in several areas. (i) Additional empirical studies could be performed to calculate the magnitude of different rebound effects for a variety of real-life EEUs. (ii) Deeper study of macro rebound is needed, including improved determination of the value of the macro factor (k). (iii) The framework could be used to study the distribution of rebound values across socioeconomic and demographic groups (Carroll et al., 2017). (iv) The rebound effects of

578 fossil-energy taxes could be studied, especially for the web of interconnected dynamic effects among
579 rebound components that are functions of the energy intensity of the economy (I_E). (v) Sensitivities
580 of rebound components to model parameters could be investigated more fully than in Appendix C,
581 although this will be challenging work because many rebound parameters are covariant. For example,
582 post-EEU efficiency ($\tilde{\eta}^*$) is unlikely to be independent of post-EEU capital cost (\tilde{C}_{cap}^*). (vi) The
583 framework could be extended to encompass fuel-switching EEUs, such as the move from a gasoline
584 car to an all-electric car. (vii) This framework could be embedded in energy-economy models to
585 better include rebound effects in discussions of macro energy modeling, energy policy, and CO₂
586 emissions mitigation.

587 Competing interests

588 Declarations of interest: none.

589 Author contributions

590 Author contributions for this paper (Part II of the two-part paper) are shown in Table 15.

Table 15: Author contributions.

	MKH	GS	PEB
Conceptualization	●	●	
Methodology	●	●	●
Software	●		●
Validation	●		●
Formal analysis	●	●	
Investigation	●	●	●
Resources	●	●	●
Data curation			●
Writing—original draft	●	●	
Writing—review & editing	●	●	●
Visualization	●	●	
Supervision	●		
Project administration	●		
Funding acquisition			●

591 Data repository

592 **** Data and example calculations in spreadsheet format will be stored at the Research Data Leeds
593 Repository if this submission is accepted. The spreadsheet file is included with the submission of
594 this paper. ****

595 Acknowledgements

596 Paul Brockway's time was funded by the UK Research and Innovation (UKRI) Council, supported
597 under EPSRC Fellowship award EP/R024254/1. The authors benefited from discussions with
598 Daniele Girardi (University of Massachusetts at Amherst) and Christopher Blackburn (Bureau
599 of Economic Analysis). The authors are grateful for comments from internal reviewers Becky
600 Haney and Jeremy Van Antwerp (Calvin University); Nathan Chan (University of Massachusetts at
601 Amherst); and Zeke Marshall (University of Leeds). The authors appreciate the many constructive
602 comments on a working paper version of this article from Jeroen C.J.M. van den Bergh (Vrije
603 Universiteit Amsterdam), Harry Saunders (Carnegie Institution for Science), and David Stern
604 (Australian National University). Finally, the authors thank the students of MKH's Fall 2019
605 Thermal Systems Design course (ENGR333) at Calvin University who studied energy rebound for
606 many energy conversion devices using an early version of this framework.

607 References

- 608 Argonne National Laboratory, Energy Systems Division (2010). Energy-consumption and carbon-emission analysis of vehicle and component
609 manufacturing. Tech. Rep. ANL/ESD/10-6, Argonne National Laboratory, Oak Ridge, TN.
610 URL https://greet.es.anl.gov/files/vehicle_and_components_manufacturing/
- 611 Barkhordar, Z. A. (2019). Evaluating the economy-wide effects of energy efficient lighting in the household sector of Iran. *Energy Policy*,
612 127, 125–133.
- 613 Berla.com (2016). Average lifespan for U.S. vehicles.
614 URL <https://berla.co/average-us-vehicle-lifespan/>
- 615 Board of Governors of the Federal Reserve System (US) (2024). Finance rate on consumer installment loans at commercial banks, new
616 autos 72 month loan (rflpbcianm72nm). Retrieved from FRED, Federal Reserve Bank of St. Louis [https://fred.stlouisfed.org/](https://fred.stlouisfed.org/series/RIFLPBCIANM72NM)
617 [series/RIFLPBCIANM72NM](https://fred.stlouisfed.org/series/RIFLPBCIANM72NM).
- 618 Borenstein, S. (2015). A microeconomic framework for evaluating energy efficiency rebound and some implications. *The Energy Journal*,
619 36(1), 1–21.

620 Brockway, P. E., Heun, M. K., & Semieniuk, G. (2023). Calculation data sheets for the rebound case study examples used in the journal
621 working paper “Advancing the necessary foundations for empirical energy rebound estimates: A partial equilibrium analysis framework”.
622 <https://doi.org/10.5518/1201>.

623 Bundesministerium für Wirtschaft und Energie (2018). Alle Tarife mengengewichteter Elektrizitätspreis für Haushaltskunden.
624 URL <https://www.bmwi.de/Redaktion/DE/Infografiken/Energie/strompreisbestandteile.html>

625 Carinsurance.com (2019). Average miles driven per year by state.
626 URL <https://www.carinsurance.com/Articles/average-miles-driven-per-year-by-state.aspx>

627 Carroll, C., Slacalek, J., Tokuoka, K., & White, M. N. (2017). The distribution of wealth and the marginal propensity to consume.
628 *Quantitative Economics*, 8(3), 977–1020.

629 Chitnis, M., Fouquet, R., & Sorrell, S. (2020). Rebound effects for household energy services in the UK. *The Energy Journal*, 41(4).

630 Chitnis, M., & Sorrell, S. (2015). Living up to expectations: Estimating direct and indirect rebound effects for UK households. *Energy*
631 *Economics*, 52, S100–S116.

632 [Coyle, D., DeBacker, J., & Prisinzano, R. \(2012\). Estimating the supply and demand of gasoline using tax data. *Energy Economics*, \(pp. 195–200\).](#)

633

634 Dimitropoulos, A., Oueslati, W., & Sintek, C. (2018). The rebound effect in road transport: A meta-analysis of empirical studies. *Energy*
635 *Economics*, 75, 163–179.

636 [Djokic, I., Lazic, L., Pavlovic, A., & Aydic, A. \(2015\). Simulation based life-cycle analysis of a vehicle fleet. *Proceedings of the 2nd Logistics International Conference \(LOGIC\)*, Belgrade, Serbia, pp. 216-221.](#)

637

638 URL <https://logic.sf.bg.ac.rs/wp-content/uploads/ONLINE-LOGIC-2015-Proceedings.pdf>

639 Duarte, R., Sánchez-Chóliza, J., & Sarasa, C. (2018). Consumer-side actions in a low-carbon economy: A dynamic CGE analysis for Spain.
640 *Energy Policy*, 118, 199–210.

641 Edmunds.com (2020a). 2020 Ford Fusion cost to own.
642 URL <https://www.edmunds.com/ford/fusion/2020/cost-to-own/#style=401757616/>

643 Edmunds.com (2020b). 2020 Ford Fusion Hybrid cost to own.
644 URL <https://www.edmunds.com/ford/fusion-hybrid/2020/cost-to-own/>

645 Exadaktylos, F., & van den Bergh, J. (2021). Energy-related behaviour and rebound when rationality, self-interest and willpower are
646 limited. *Nature Energy*, 6(12), 1104–1113.

647 Federal Reserve Bank of St Louis (2019). Real median personal income in the united states. Tech. rep., One Federal Reserve Bank Plaza,
648 St. Louis, MO 63102, USA.
649 URL <https://fred.stlouisfed.org/series/MEPAINUSA672N/>

650 finanzen.net (2021). Super Benzin. <https://www.finanzen.net/rohstoffe/super-benzinpreis/historisch>. Accessed 15 March 2021.

651 [Foerster, A. T., Hornstein, A., Sarte, P.-D. G., & Watson, M. W. \(2022\). Aggregate Implications of Changing Sectoral Trends. *Journal of Political Economy*, 130\(12\), 3286–3333.](#)

652

653 Fouquet, R. (2014). Long-run demand for energy services: Income and price elasticities over two hundred years. 8(2), 186–207.

654 Fouquet, R., & Pearson, P. J. G. (2011). The long run demand for lighting: Elasticities and rebound effects in different phases of economic
655 development. BC3 Working paper series 2011-06.

656 Freire-González, J. (2011). Methods to empirically estimate direct and indirect rebound effect of energy-saving technological changes in
657 households. *Ecological Modelling*, 223(1), 32–40.

658 [Ghoddusia, H., & Roy, M. \(2017\). Supply elasticity matters for the rebound effect and its impact on policy comparisons. *Energy Economics*, \(pp. 111–120\).](#)

659

660 Gillingham, K., Jenn, A., & Azevedo, I. M. (2015). Heterogeneity in the response to gasoline prices: Evidence from Pennsylvania and
661 implications for the rebound effect. *Energy Economics*, 52, S41–S52.

662 Gillingham, K. T. (2020). The rebound effect and the proposed rollback of U.S. fuel economy standards. *Review of Environmental*

663 *Economics and Policy*, 14(1), 136–142.

664 Goetzke, F., & Vance, C. (2018). *Is gasoline price elasticity in the United States increasing? Evidence from the 2009 and 2017 national*

665 *household travel surveys*. 765. Ruhr Economic Papers.

666 URL http://www.rwi-essen.de/media/content/pages/publikationen/ruhr-economic-papers/rep_18_765.pdf

667 Greene, D. L. (2012). Rebound 2007: Analysis of U.S. light-duty vehicle travel statistics. *Energy Policy*, 41, 14–28.

668 Guertin, C., Kumbhakar, S. C., & Duraiappah, A. K. (2003). *Determining demand for energy services: investigating income-driven*

669 *behaviours*. Winnipeg, Manitoba, Canada: International Institute for Sustainable Development.

670 Heun, M. K. (2023). ReboundTools: An R package that provides functions to analyze energy rebound. V0.1.36.

671 URL <https://doi.org/10.5281/zenodo.7514249>

672 HomeDepot.com (2020a). 40-watt equivalent A19 non-dimmable LED light bulb soft white 8-pack.

673 URL [https://www.homedepot.com/p/EcoSmart-40-Watt-Equivalent-A19-Non-Dimmable-LED-Light-Bulb-Soft-White-8-Pack-1001015802/](https://www.homedepot.com/p/EcoSmart-40-Watt-Equivalent-A19-Non-Dimmable-LED-Light-Bulb-Soft-White-8-Pack-1001015802/303714669?modalType=drawer/)

674 [303714669?modalType=drawer/](https://www.homedepot.com/p/EcoSmart-40-Watt-Equivalent-A19-Non-Dimmable-LED-Light-Bulb-Soft-White-8-Pack-1001015802/303714669?modalType=drawer/)

675 HomeDepot.com (2020b). 60-watt double life A15 incandescent light bulb 2-pack.

676 URL [https://www.homedepot.com/p/Sylvania-60-Watt-Double-Life-A15-Incandescent-Light-Bulb-2-Pack-11969/303762187?](https://www.homedepot.com/p/Sylvania-60-Watt-Double-Life-A15-Incandescent-Light-Bulb-2-Pack-11969/303762187?modalType=drawer/)

677 [modalType=drawer/](https://www.homedepot.com/p/Sylvania-60-Watt-Double-Life-A15-Incandescent-Light-Bulb-2-Pack-11969/303762187?modalType=drawer/)

678 [Junk Car Medics \(2024\). Scrap car prices in 2024.](#)

679 URL <https://www.junkcarmedics.com/prices/>

680 Koesler, S. (2013). Catching the rebound: Economy-wide implications of an efficiency shock in the provision of transport services by

681 households. Discussion Paper 13-082, Leibniz Centre for European Economic Research, Mannheim, Germany.

682 Moshiri, S., & Aliyev, K. (2017). Rebound effect of efficiency improvement in passenger cars on gasoline consumption in Canada. *Ecological*

683 *Economics*, 131, 330–341.

684 Nordelöf, A., Messagie, M., Tillman, A.-M., Söderman, M. L., & Van Mierlo, J. (2014). Environmental impacts of hybrid, plug-in hybrid,

685 and battery electric vehicles—what can we learn from life cycle assessment? *The International Journal of Life Cycle Assessment*,

686 19(11), 1866–1890.

687 Onat, N. C., Kucukvar, M., & Tatari, O. (2015). Conventional, hybrid, plug-in hybrid or electric vehicles? State-based comparative carbon

688 and energy footprint analysis in the United States. *Applied Energy*, 150, 36–49.

689 Parry, I. W. H., & Small, K. A. (2005). Does Britain or the United States have the right gasoline tax? *American Economic Review*,

690 95(4), 1276–1289.

691 Schleich, J., Mills, B., & Dütschke, E. (2014). A brighter future? Quantifying the rebound effect in energy efficient lighting. *Energy*

692 *Policy*, 72, 35–42.

693 Shojaeddini, E., & Gilbert, B. (2022). Heterogeneity in the rebound effect: Evidence from efficient lighting subsidies. *Environmental and*

694 *Resource Economics*.

695 Small, K. A., & Van Dender, K. (2007). Fuel efficiency and motor vehicle travel: The declining rebound effect. *Energy Journal*, 28(1),

696 25–51.

697 Smith, A. (1776). *An Inquiry into the Wealth of Nations*. London: Strahan.

698 Society of Motor Manufacturers and Traders (2020). 2020 automotive sustainability report—average vehicle age.

699 URL <https://www.smmt.co.uk/industry-topics/sustainability/average-vehicle-age/>

700 Sorrell, S., Dimitropoulos, J., & Sommerville, M. (2009). Empirical estimates of the direct rebound effect: A review. *Energy Policy*, 37(4),

701 1356–1371.

702 Stapleton, L., Sorrell, S., & Schwanen, T. (2016). Estimating direct rebound effects for personal automotive travel in Great Britain.

703 *Energy Economics*, 54, 313–325.

704 [Statista \(2024\). Average number of people per household in the United States from 1960 to 2023.](#)

705 URL <https://www.statista.com/statistics/183648/average-size-of-households-in-the-us/>

706 Thecarconnection.com (2020). 2020 Ford Fusion Specifications.
707 URL https://www.thecarconnection.com/specifications/ford_fusion_2020/
708 Thomas, B. A., & Azevedo, I. L. (2013). Estimating direct and indirect rebound effects for U.S. households with input–output analysis.
709 Part 2: Simulation. *Ecological Economics*, 86, 188–198.
710 US Bureau of Economic Analysis (2020). National and products accounts (NIPA) Table 2.1: Personal income and its disposition. Tech.
711 rep., 4600 Silver Hill Road, Suitland, MD 20746, USA.
712 URL https://apps.bea.gov/iTable/index_nipa.cfm/
713 US Department of Energy (2012). Life-cycle assessment of energy and environmental impacts of LED lighting products: Part I: Review
714 of the life-cycle energy consumption of incandescent, compact fluorescent, and LED lamps. Tech. rep., Forrestal Building, 1000
715 Independence Avenue, SW, Washington, DC 20585, USA.
716 URL https://www1.eere.energy.gov/buildings/publications/pdfs/ssl/2012_LED_Lifecycle_Report.pdf
717 US Department of Transportation (2018). Average annual miles per driver by age group. Tech. rep.
718 URL <https://www.fhwa.dot.gov/ohim/onh00/bar8.htm/>
719 US Energy Information Administration (2020a). Average price (cents/kilowatthour) by state by provider, 1990-2019. Tech. rep., 1000
720 Independence Avenue, SW, Washington, DC 20585, USA.
721 URL https://www.eia.gov/electricity/data/state/avgprice_annual.xlsx
722 US Energy Information Administration (2020b). U.S. regular gasoline prices. Tech. rep., 1000 Independence Avenue, SW, Washington,
723 DC 20585, USA.
724 URL <https://www.eia.gov/petroleum/gasdiesel/>
725 [U.S. Energy Information Agency \(2023\). Use of energy explained: Energy use in homes \(electricity\).](https://www.eia.gov/energyexplained/use-of-energy/electricity-use-in-homes.php)
726 URL <https://www.eia.gov/energyexplained/use-of-energy/electricity-use-in-homes.php>

Table A.1: Symbols and abbreviations.

Symbol	Meaning [example units]
a	a point in the emplacement effect in rebound planes or the share parameter in the CES utility model [-]
b	a point in the emplacement effect in rebound planes
C	cost [\$]
c	a point in the substitution effect in rebound planes
d	a point in the income effect on rebound planes
E	final energy [MJ]
f	expenditure share [-]
G	freed cash [\$]
I	energy intensity of economic activity [MJ/\$]
k	macro factor [-]
M	income [\$]
N	net savings [\$]
p	price [\$]
Q	quantity <u>at the macroeconomic level</u> [-]
Q	multiplicative term that accounts for discounting <u>quantity</u> [-]
Re	rebound [-]
r	real discount rate [1/yr]
S	energy cost savings [\$]
t	energy conversion device lifetime [yr]
u	utility [utils]
x	the abscissa coordinate
y	the ordinate coordinate

Appendices

A Nomenclature

Presentation of the rigorous analytical framework is aided by a nomenclature that describes energy stages and rebound effects. Table A.1 shows symbols and abbreviations, their meanings, and example units. Table A.2 shows Greek letters, their meanings, and example units. Table ~~?? shows~~ ~~abbreviations~~ A.3 shows initialisms and acronyms. Table A.4 shows symbol decorations and their meanings. Table A.5 shows subscripts and their meanings.

Differences are indicated by the Greek letter Δ and always signify subtraction of a quantity at an earlier stage of Fig. 1 from the same quantity at the next later stage of Fig. 1. E.g., $\Delta\bar{X} \equiv \bar{X} - \hat{X}$, and $\Delta\tilde{X} \equiv \tilde{X} - \bar{X}$. Lack of decoration on a difference term indicates a difference that spans all stages of Fig. 1. E.g., $\Delta X \equiv \tilde{X} - X^\circ$. ΔX is also the sum of differences across each stage in Fig. 1, as shown below.

Table A.2: Greek letters.

Greek letter	Meaning [example units]
α	subscript that indicates capital cost payments at beginning of life
Δ	difference (later quantity less earlier quantity, see Fig. 1)
ε	price or income elasticity [-]
$\varepsilon_{\dot{q}_s, \dot{M}}$	income (\dot{M}) elasticity of energy service demand (\dot{q}_s) [-]
$\varepsilon_{\dot{q}_o, \dot{M}}$	income (\dot{M}) elasticity of other goods demand (\dot{q}_o) [-]
$\varepsilon_{\dot{q}_s, p_s}$	uncompensated energy service price (p_s) elasticity of energy service demand (\dot{q}_s) [-]
$\varepsilon_{\dot{q}_o, p_s}$	uncompensated energy service price (p_s) elasticity of other goods demand (\dot{q}_o) [-]
$\varepsilon_{\dot{q}_s, p_s, c}$	compensated energy service price (p_s) elasticity of energy service demand (\dot{q}_s) [-]
$\varepsilon_{\dot{q}_o, p_s, c}$	compensated energy service price (p_s) elasticity of other goods demand (\dot{q}_o) [-]
η	final-energy-to-service efficiency [vehicle-km/MJ]
ω	subscript that indicates disposal cost at end of life
ρ	exponent in the CES utility function, $\rho \equiv (\sigma - 1)/\sigma$ [-]
σ	elasticity of substitution between the energy service (\dot{q}_s°) and other goods (\dot{q}_o°) [-]
τ	multiplicative term that accounts for discounting [-]

Table A.3: AbbreviationsInitialisms and acronyms.

Abbreviation	Meaning
APF	aggregate production function
<u>BOL</u>	<u>beginning of life</u>
CES	constant elasticity of substitution
CGE	computable general equilibrium
CPE	constant price elasticity
CV	compensating variation
EEU	energy efficiency upgrade
<u>EOL</u>	<u>end of life</u>
EPSRC	engineering and physical sciences research council
EV	electric vehicle
GDP	gross domestic product
LAIDS	linear approximation to almost ideal demand system
LED	light emitting diode
<u>MPC</u>	<u>marginal propensity to consume</u>
mpg	miles per U.S. gallon
RECS	residential energy consumption survey
<u>TVM</u>	<u>time value of money</u>
UK	United Kingdom
UKRI	UK research and innovation
U.S.	United States
VMT	vehicle miles traveled
w.r.t.	with respect to

Table A.4: Decorations.

Decoration	Meaning [example units]
X°	X originally (before the emplacement effect)
X^*	X after the emplacement effect (before the substitution effect)
\hat{X}	X after the substitution effect (before the income effect)
\bar{X}	X after the income effect (before the macro effect)
\tilde{X}	X after the macro effect
\dot{X}	rate of X [units of X /yr]
M'	effective income [\$]

Table A.5: Subscripts.

Subscript	Meaning
0	quantity at an initial time
1	a specific point on the consumption plane
<i>c</i>	compensated
<i>cap</i>	capital costs
<i>dev</i>	device
<i>dempl</i>	direct emplacement effect
<i>dinc</i>	direct income effect
<i>dir</i>	direct effects (at the energy conversion device)
<i>dsub</i>	direct substitution effect
<i>E</i>	energy
<i>emb</i>	embodied
<i>empl</i>	emplacement effect
<i>g</i>	<u>other expenditures (besides energy) by the device user</u>
<i>iempl</i>	indirect emplacement effects
<i>iinc</i>	indirect income effect
<i>inc</i>	income effect
<i>indir</i>	indirect effects (beyond the energy conversion device)
<i>isub</i>	indirect substitution effect
<i>life</i>	lifetime
<i>macro</i>	macro effect
<i>md</i>	maintenance and disposal
<i>o</i>	other expenditures (besides energy) by the device user
<i>own</i>	ownership duration
<i>s</i>	service stage of the energy conversion chain
<i>sub</i>	substitution effect
<i>tot</i>	sum of all rebound effects in the framework

$$\begin{aligned}
\Delta X &= \Delta \tilde{X} + \Delta \bar{X} + \Delta \hat{X} + \Delta X^* \\
\Delta X &= (\tilde{X} - \bar{X}) + (\bar{X} - \hat{X}) + (\hat{X} - X^*) + (X^* - X^\circ) \\
\Delta X &= (\tilde{X} - \bar{X}') + (\bar{X}' - \hat{X}') + (\hat{X}' - X^*) + (X^* - X^\circ) \\
\Delta X &= \tilde{X} - X^\circ
\end{aligned} \tag{1}$$

B Mathematical details of rebound planes

Rebound planes show the impact of direct and indirect rebound effects for energy, expenditure, and consumption aspects. Rebound planes for the car example can be found in Figs. 2–4. Rebound planes for the lamp example can be found in Figs. 5–7.

This appendix shows the mathematical details of rebound planes, specifically derivations of equations for lines and curves shown in Table B.1. The lines and curves enable construction of numerically precise and accurate paths in rebound planes as shown in Figs. 2–7.

Table B.1: Lines and curves for rebound planes.

Rebound plane	Lines and curves
Energy	Constant total energy consumption lines 0% and 100% rebound lines
Expenditure	Constant expenditure lines
Consumption	Constant expenditure lines Rays from origin to \wedge point Indifference curves

B.1 Energy planes

The energy plane shows direct (on the x -axis) and indirect (on the y -axis) energy consumption associated with the energy conversion device and the device user. Lines of total energy consumption isoquants provide a scale for total rebound. For example, the 0% and 100% rebound lines are constant total energy consumption lines which pass through the original point (\circ) and the post-direct-emplacement-effect point (a) in the energy plane.

The equation of a constant total energy consumption line is derived from

$$\dot{E}_{tot} = \dot{E}_{dir} + \dot{E}_{indir} \quad (2)$$

at any rebound stage. Direct energy consumption is energy consumed by the energy conversion device (\dot{E}_s), and indirect energy consumption is the sum of embodied energy, energy associated with maintenance and disposal, and energy associated with expenditures on other goods ($\dot{E}_{emb} + (\dot{C}_{OMd} + \dot{C}_o)I_E \dot{E}_{emb} + (\dot{C}_{OMd} + \dot{C}_g)I_E$).

For the energy plane, direct energy consumption is placed on the x -axis and indirect energy consumption is placed on the y -axis. To derive the equation of a constant energy consumption line, we first rearrange to put the y coordinate on the left of the equation:

$$\dot{E}_{indir} = -\dot{E}_{dir} + \dot{E}_{tot} . \quad (3)$$

Next, we substitute y for \dot{E}_{indir} , x for \dot{E}_{dir} , and $\dot{E}_s + \dot{E}_{emb} + (\dot{C}_{OMd} + \dot{C}_o)I_E \dot{E}_s + \dot{E}_{emb} + (\dot{C}_{OMd} + \dot{C}_g)I_E$ for \dot{E}_{tot} to obtain

$$y = -x + \dot{E}_s + \dot{E}_{emb} + (\dot{C}_{OMd} + \dot{C}_{og})I_E , \quad (4)$$

where all of \dot{E}_s , \dot{E}_{emb} , \dot{C}_{OMd} , and $\dot{C}_o \dot{C}_g$ apply at the same rebound stage.

763 The constant total energy consumption line that passes through the original point (\circ) shows
 764 100% rebound:

$$y = -x + \dot{E}_s^\circ + \dot{E}_{emb}^\circ + (\dot{C}_{OMd}^\circ + \dot{C}_{\overline{og}}^\circ)I_E . \quad (5)$$

765 The 0% rebound line is the constant total energy consumption line that accounts for expected
 766 energy savings (\dot{S}_{dev}) only:

$$y = -x + (\dot{E}_s^\circ - \dot{S}_{dev}) + \dot{E}_{emb}^\circ + (\dot{C}_{OMd}^\circ + \dot{C}_{\overline{og}}^\circ)I_E . \quad (6)$$

767 The above line passes through the a point in the energy plane.

768 B.2 Expenditure planes

769 The expenditure plane shows direct (on the x -axis) and indirect (on the y -axis) expenses associated
 770 with the energy conversion device and the device user. Lines of constant expenditure are important,
 771 because they provide budget constraints for the device user.

772 The equation of a constant total expenditure line is derived from the budget constraint

$$\dot{C}_{tot} = \dot{C}_{dir} + \dot{C}_{indir} \quad (7)$$

773 at any rebound stage. In the expenditure plane, indirect expenditures are placed on the y -axis
 774 and direct expenditures on energy for the energy conversion device are place on the x -axis. Direct
 775 expenditure is the cost of energy consumed by the energy conversion device ($\dot{C}_s = p_E \dot{E}_s$), and
 776 indirect expenses are the sum of capital costs, operations, maintenace, and disposal costs, and
 777 expenditures on other goods ($\cancel{R_\alpha \dot{C}_{cap}} + \cancel{\dot{C}_{OMd}} + \cancel{\dot{C}_o} \tau_\alpha \cancel{\dot{C}_{cap}} + \cancel{\dot{C}_{OMd}} + \cancel{\dot{C}_g}$). Rearranging to put the
 778 y -axis variable on the left side of the equation gives

$$\dot{C}_{indir} = -\dot{C}_{dir} + \dot{C}_{tot} . \quad (8)$$

779 Substituting y for \dot{C}_{indir} , x for \dot{C}_{dir} , and $\cancel{\dot{C}_s} + \cancel{R_\alpha \dot{C}_{cap}} + \cancel{\dot{C}_{OMd}} + \cancel{\dot{C}_o} \cancel{\dot{C}_s} + \tau_\alpha \cancel{\dot{C}_{cap}} + \cancel{\dot{C}_{OMd}} + \cancel{\dot{C}_g}$ for
 780 \dot{C}_{tot} gives

$$y = -x + \dot{C}_s + \textcolor{red}{R}\textcolor{blue}{\tau}_\alpha \dot{C}_{cap} + \dot{C}_{OMd} + \dot{C}_{\textcolor{red}{o}\textcolor{blue}{g}} , \quad (9)$$

781 where all of \dot{C}_s , $\textcolor{red}{R}\textcolor{blue}{\tau}_\alpha$, \dot{C}_{cap} , \dot{C}_{OMd} , and $\textcolor{red}{\dot{C}}_{\textcolor{red}{o}}\textcolor{blue}{\dot{C}}_{\textcolor{blue}{g}}$ apply at the same rebound stage.

782 The constant total expenditure line that passes through the original point (o) shows the budget
783 constraint for the device user:

$$y = -x + \dot{C}_s^\circ + \tau_\alpha^\circ \dot{C}_{cap}^\circ + \dot{C}_{OMd}^\circ + \dot{C}_{\textcolor{red}{o}\textcolor{blue}{g}}^\circ , \quad (10)$$

784 into which Eq. (78) of Part I can be substituted with $\dot{C}_s^\circ = p_E \dot{E}_s^\circ$ and $\dot{N}^\circ = 0$ to obtain

$$y = -x + \dot{M} . \quad (11)$$

785 The constant total expenditure line that accounts for expected energy savings (\dot{S}_{dev}) and freed
786 cash ($\dot{G} = p_E \dot{S}_{dev}$) only is given by:

$$y = -x + (\dot{C}_s^\circ - \dot{G}) + \tau_\alpha^\circ \dot{C}_{cap}^\circ + \dot{C}_{OMd}^\circ + \dot{C}_{\textcolor{red}{o}\textcolor{blue}{g}}^\circ , \quad (12)$$

787 or

$$y = -x + \dot{M} - \dot{G} . \quad (13)$$

788 The line given by the equation above passes through the a point in the expenditure plane.

789 B.3 Consumption planes

790 The consumption plane shows expenditures in the $\textcolor{red}{\dot{C}}_{\textcolor{red}{o}}/\textcolor{red}{\dot{C}}_{\textcolor{red}{o}}^\circ\textcolor{blue}{\dot{C}}_{\textcolor{blue}{g}}/\textcolor{blue}{\dot{C}}_{\textcolor{blue}{g}}^\circ$ vs. $\dot{q}_s/\dot{q}_s^\circ$ plane, according to the
791 utility model. (See Appendix C of Part I.) Consumption planes include (i) constant expenditure lines
792 given prices, (ii) a ray from the origin through the \wedge point, and (iii) indifference curves. Derivations
793 for each are shown in the following subsections.

794 B.3.1 Constant expenditure lines

795 There are four constant expenditure lines in the consumption planes of Figs. 4 and 7. The constant
796 expenditure lines pass through the original point (line o—o), the post-emplacement point (line

797 *—*), the post-substitution point (line \wedge — \wedge), and the post-income point (line — — —). Similar to
 798 the expenditure plane, lines of constant expenditure in the consumption plane are derived from the
 799 budget constraint of the device user at each of the four points.

800 Prior to the EEU, the budget constraint is given by Eq. (78) of Part I. Substituting $p_s^\circ \dot{q}_s^\circ$ for
 801 $p_E \dot{E}_s^\circ$ and recognizing that there is no net savings before the EEU ($\dot{N}^\circ = 0$) gives

$$\dot{M} = p_s^\circ \dot{q}_s^\circ + \tau_\alpha^\circ \dot{C}_{cap}^\circ + \dot{C}_{OMd}^\circ + \dot{C}_{\overline{og}}^\circ . \quad (14)$$

802 To create the line of constant expenditure in the consumption plane, we allow \dot{q}_s° and \dot{C}_g° and
 803 to vary in a compensatory manner: when one increases, the other must decrease. To show that
 804 variation along the constant expenditure line, we remove the notation that ties \dot{q}_s° and \dot{C}_g° to the
 805 original point (\circ) to obtain

$$\dot{M} = p_s^\circ \dot{q}_s + \tau_\alpha^\circ \dot{C}_{cap}^\circ + \dot{C}_{OMd}^\circ + \dot{C}_{\overline{og}} , \quad (15)$$

806 where all of \dot{M} , p_s° , $\tau_\alpha^\circ \dot{C}_{cap}^\circ$, and \dot{C}_{OMd}° apply at the same rebound stage, namely the original
 807 point (\circ) in this instance.

808 To derive the equation of the line representing the original budget constraint in $\dot{C}_g^\circ/\dot{C}_g^\circ$ vs.
 809 $\dot{q}_s/\dot{q}_s^\circ$ space (the \circ — \circ line through the \circ point in consumption planes), we solve for \dot{C}_g° to obtain

$$\dot{C}_{\overline{og}} = -p_s^\circ \dot{q}_s + \dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ . \quad (16)$$

810 Multiplying judiciously by $\dot{C}_g^\circ/\dot{C}_g^\circ$ and $\dot{q}_s/\dot{q}_s^\circ$ gives

$$\frac{\dot{C}_g^\circ}{\dot{C}_g^\circ} \dot{C}_{\overline{og}} = -p_s^\circ \frac{\dot{q}_s}{\dot{q}_s^\circ} \dot{q}_s^\circ + \dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ . \quad (17)$$

811 Dividing both sides by \dot{C}_g° yields

$$\frac{\dot{C}_g^\circ}{\dot{C}_g^\circ} = -\frac{p_s^\circ \dot{q}_s^\circ}{\dot{C}_g^\circ} \frac{\dot{q}_s}{\dot{q}_s^\circ} + \frac{1}{\dot{C}_g^\circ} (\dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ) . \quad (18)$$

812 Noting that $\dot{q}_s/\dot{q}_s^\circ$ and $\dot{C}_g^\circ/\dot{C}_g^\circ$ are the x -axis and y -axis, respectively, of the consumption
 813 plane gives

$$y = -\frac{\cancel{p_s^\circ \dot{q}_s^\circ}}{\cancel{\dot{C}_o^\circ}} \frac{p_s^\circ \dot{q}_s^\circ}{\dot{C}_g^\circ} x + \frac{1}{\cancel{\dot{C}_o^\circ}} \frac{1}{\dot{C}_g^\circ} (\dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ) . \quad (19)$$

814 A similar procedure can be employed to derive the equation of the $* \text{---} *$ line through the $*$ point
 815 after the emplacement effect. The starting point is the budget constraint at the $*$ point (Eq. (80)
 816 of Part I) with $\cancel{\dot{M}^\circ}$ replacing \dot{M}^* , $\cancel{\tilde{p}_s \dot{q}_s}$ replacing $\cancel{p_s^\circ \dot{q}_s^\circ}$, replacing $p_E \dot{E}_s^*$, and $\cancel{\dot{C}_o^\circ}$ replacing \dot{C}_o^* and \dot{C}_g
 817 replacing \dot{C}_g^* .

$$\dot{M} = \cancel{p_s^*} \dot{q}_s + \cancel{R^*} \tau_\alpha^* \dot{C}_{cap}^* + \dot{C}_{OMd}^* + \dot{C}_{\bar{o}g} + \dot{N}^* \quad (20)$$

818 Substituting Eq. (89) of Part I for \dot{N}^* , substituting Eq. (90) of Part I to obtain \dot{G} , multiplying
 819 judiciously by $\cancel{\dot{C}_o^\circ / \dot{C}_o^\circ} \cancel{\dot{C}_g / \dot{C}_g^\circ}$ and $\dot{q}_s^\circ / \dot{q}_s$, rearranging, and noting that $\dot{q}_s / \dot{q}_s^\circ$ is the x -axis and $\cancel{\dot{C}_o^\circ / \dot{C}_o^\circ}$
 820 $\cancel{\dot{C}_g / \dot{C}_g^\circ}$ is the y -axis gives

$$y = -\frac{\cancel{\tilde{p}_s \dot{q}_s^\circ}}{\cancel{\dot{C}_o^\circ}} \frac{p_s^\circ \dot{q}_s^\circ}{\dot{C}_g^\circ} x + \frac{1}{\cancel{\dot{C}_o^\circ}} \frac{1}{\dot{C}_g^\circ} (\dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ - \dot{G}) . \quad (21)$$

821 Note that the slope of Eq. (21) is less negative than the slope of Eq. (19), because $\tilde{p}_s < p_s^\circ$. The
 822 y -intercept of Eq. (21) is less than the y -intercept of Eq. (19), reflecting freed cash. Both effects are
 823 seen in the consumption planes (Figs. 4 and 7). The $\circ \text{---} \circ$ and $* \text{---} *$ lines intersect at the coincident
 824 \circ and $*$ points.

825 A similar derivation process can be used to find the equation of the line representing the budget
 826 constraint after the substitution effect (the $\wedge \text{---} \wedge$ line through the \wedge point). The starting point is
 827 Eq. (93) of Part I, and the equation for the constant expenditure line is

$$y = -\frac{\cancel{\tilde{p}_s \dot{q}_s^\circ}}{\cancel{\dot{C}_o^\circ}} \frac{p_s^\circ \dot{q}_s^\circ}{\dot{C}_g^\circ} x + \frac{1}{\cancel{\dot{C}_o^\circ}} \frac{1}{\dot{C}_g^\circ} (\dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ - \dot{G} + \cancel{p_s^*} \Delta \hat{q}_s + \Delta \hat{C}_{\bar{o}g}) . \quad (22)$$

828 Note that the $\wedge \text{---} \wedge$ line (Eq. (22)) has the same slope as the $* \text{---} *$ line (Eq. (21)) but a lower
 829 y -intercept.

830 Finally, the corresponding derivation for the equation of the constant expenditure line through
 831 the $-$ point (line $- \text{---} -$) starts with Eq. (102) of Part I and comes to

$$y = -\frac{\cancel{\tilde{p}_s \dot{q}_s^\circ}}{\cancel{\dot{C}_o^\circ}} \frac{p_s^\circ \dot{q}_s^\circ}{\dot{C}_g^\circ} x + \frac{1}{\cancel{\dot{C}_o^\circ}} \frac{1}{\dot{C}_g^\circ} (\dot{M} - \tau_\alpha^\circ \dot{C}_{cap}^\circ - \dot{C}_{OMd}^\circ - \Delta (\cancel{R_\alpha \dot{C}_{cap}^\circ})^* (\tau_\alpha \dot{C}_{cap})^* - \Delta \dot{C}_{OMd}^*) . \quad (23)$$

832 Simplification of Δ terms gives

$$y = -\frac{\tilde{p}_s \dot{q}_s^\circ}{\dot{C}_o^\circ} \frac{\tilde{p}_s \dot{q}_s^\circ}{\dot{C}_g^\circ} x + \frac{1}{\dot{C}_o^\circ} \frac{1}{\dot{C}_g^\circ} (\dot{M} - \mathbf{R}^* \mathbf{T}^*_{\alpha} \dot{C}_{cap}^* - \dot{C}_{OMd}^*) . \quad (24)$$

833 B.3.2 Ray from the origin to the \wedge point

834 In the consumption plane, the ray from the origin to the \wedge point (line $r-r$) defines the path along
 835 which the income effect (lines $\wedge-d$ and $d--$) operates. The ray from the origin to the \wedge point has
 836 slope $(\hat{C}_o/\hat{C}_o^\circ)/(\hat{q}_s/\hat{q}_s^\circ) = (\hat{C}_g/\hat{C}_g^\circ)/(\hat{q}_s/\hat{q}_s^\circ)$ and a y -intercept of 0. Therefore, the equation of line $r-r$ is

$$y = \frac{\hat{C}_o/\hat{C}_o^\circ}{\hat{q}_s/\hat{q}_s^\circ} \frac{\hat{C}_g/\hat{C}_g^\circ}{\hat{q}_s/\hat{q}_s^\circ} x . \quad (25)$$

837 B.3.3 Indifference curves

838 In the consumption plane, indifference curves represent lines of constant utility for the energy
 839 conversion device user. In the consumption plane $(\dot{C}_o/\dot{C}_o^\circ - \dot{C}_g/\dot{C}_g^\circ$ vs. $\dot{q}_s/\dot{q}_s^\circ$), any indifference curve is
 840 given by Eq. (??159) of Part I with $f_{\dot{C}_s}^\circ$ replacing the share parameter a , as shown in Appendix C of
 841 Part I. Recognizing that $\dot{C}_o/\dot{C}_o^\circ - \dot{C}_g/\dot{C}_g^\circ$ is on the y -axis and $\dot{q}_s/\dot{q}_s^\circ$ is on the x -axis leads to substitution
 842 of y for $\dot{C}_o/\dot{C}_o^\circ - \dot{C}_g/\dot{C}_g^\circ$ and x for $\dot{q}_s/\dot{q}_s^\circ$ to obtain

$$y = \left[\frac{1}{1 - f_{\dot{C}_s}^\circ} \left(\frac{\dot{u}}{\dot{u}^\circ} \right)^\rho - \frac{f_{\dot{C}_s}^\circ}{1 - f_{\dot{C}_s}^\circ} (x)^\rho \right]^{(1/\rho)} . \quad (26)$$

843 At any point on the $\dot{C}_o/\dot{C}_o^\circ - \dot{C}_g/\dot{C}_g^\circ$ vs. $\dot{q}_s/\dot{q}_s^\circ$ plane, namely $(\dot{q}_{s,1}/\dot{q}_s^\circ, \dot{C}_{o,1}/\dot{C}_o^\circ - \dot{C}_{g,1}/\dot{C}_g^\circ)$, indexed
 844 utility $(\dot{u}_1/\dot{u}^\circ)$ is given by Eq. (16) of Part I as

$$\frac{\dot{u}_1}{\dot{u}^\circ} = \left[f_{\dot{C}_s}^\circ \left(\frac{\dot{q}_{s,1}}{\dot{q}_s^\circ} \right)^\rho + (1 - f_{\dot{C}_s}^\circ) \left(\frac{\dot{C}_{o,1}}{\dot{C}_o^\circ} - \frac{\dot{C}_{g,1}}{\dot{C}_g^\circ} \right)^\rho \right]^{(1/\rho)} . \quad (27)$$

845 Substituting Eq. (27) into Eq. (26) for \dot{u}/\dot{u}° and simplifying exponents gives

$$y = \left\{ \frac{1}{1 - f_{\dot{C}_s}^\circ} \left[f_{\dot{C}_s}^\circ \left(\frac{\dot{q}_{s,1}}{\dot{q}_s^\circ} \right)^\rho + (1 - f_{\dot{C}_s}^\circ) \left(\frac{\dot{C}_{o,1}}{\dot{C}_o^\circ} - \frac{\dot{C}_{g,1}}{\dot{C}_g^\circ} \right)^\rho \right] - \frac{f_{\dot{C}_s}^\circ}{1 - f_{\dot{C}_s}^\circ} (x)^\rho \right\}^{(1/\rho)} . \quad (28)$$

846 Simplifying further yields the equation of an indifference curve passing through point $(\dot{q}_{s,1}/\dot{q}_s^\circ,$
 847 $\dot{C}_{o,1}/\dot{C}_o^\circ \dot{C}_{g,1}/\dot{C}_g^\circ)$:

$$y = \left\{ \left(\frac{f_{\dot{C}_s}^\circ}{1 - f_{\dot{C}_s}^\circ} \right) \left[\left(\frac{\dot{q}_{s,1}}{\dot{q}_s^\circ} \right)^\rho - (x)^\rho \right] + \left(\frac{\dot{C}_{o,1}}{\dot{C}_o^\circ} \frac{\dot{C}_{g,1}}{\dot{C}_g^\circ} \right)^\rho \right\}^{(1/\rho)}. \quad (29)$$

848 Note that if x is $\dot{q}_{s,1}/\dot{q}_s^\circ$, y becomes $\dot{C}_{o,1}/\dot{C}_o^\circ \dot{C}_{g,1}/\dot{C}_g^\circ$, as expected.

849 C Univariate sensitivity analyses

850 Sensitivity analyses show the effect of independently varied parameters on total rebound and rebound
 851 components. In the context of this framework, sensitivity analyses can show important trends,
 852 tendencies, and relationships between rebound parameters and rebound magnitudes. Key rebound
 853 parameters include post-EEU efficiency ($\tilde{\eta}\eta^*$), post-EEU capital cost ($\tilde{C}_{cap}C_{cap}^*$), energy price (p_E),
 854 pre-EEU uncompensated price elasticity of energy service demand ($\varepsilon_{\dot{q}_s, p_s}^\circ$), the macro factor (k), and
 855 post-EEU energy service price ($\tilde{p}_s p_s^*$). Univariate sensitivity analyses (the kind shown here) should
 856 be interpreted carefully, because some rebound parameters are not expected to be independent from
 857 others.

858 C.1 Effect of post-EEU efficiency ($\tilde{\eta}\eta^*$) on rebound terms

859 Fig. C.1 shows that both the energy takeback rate and expected energy savings (\dot{S}_{dev}) increase with
 860 post-EEU efficiency ($\tilde{\eta}\eta^*$), but the relationship is asymptotic. Each unit increase of fuel economy
 861 or lighting efficiency is less effective than the previous unit increase of fuel economy or lighting
 862 efficiency for saving energy. At very high levels of fuel economy or lighting efficiency, a unit increase
 863 leads to almost no additional energy savings. Thus, we can say there are diminishing returns of fuel
 864 economy and lighting efficiency, leading to saturation of energy savings at very high levels of fuel
 865 economy and lighting efficiency. A simple example illustrates. A $\eta^\circ = 25$ mpg car drives $q_s^\circ = 100$
 866 miles using $E_s^\circ = 4$ gallons of gasoline. A more-efficient car ($\tilde{\eta} = 30$ $\eta^* = 30$ mpg) is expected to use
 867 $E_s^* = 3.33$ gallons to drive the same distance, a savings of $\dot{S}_{dev} = 0.67$ gallons. Another 5 mpg boost
 868 in efficiency (to $\tilde{\eta} = 35$ $\eta^* = 35$ mpg) will use $E_s^* = 2.86$ gal to drive 100 miles, a further expected




Fig. C.1: Expected energy savings rate (\dot{S}_{dev} , solid line) and takeback rate (dashed line) sensitivity to post-EEU efficiency ($\tilde{\eta}\eta^*$). The macro factor, $k = 3$. (Note different x - and y -axis scales.)

savings of only $\dot{S}_{dev} = 0.47$ gallons. Each successive 5 mpg boost in fuel economy saves less energy than the previous 5 mpg boost in fuel economy.

Saturation can be seen mathematically, too. Taking the limit as $\tilde{\eta} \rightarrow \infty$ $\eta^* \rightarrow \infty$ in Eq. (12) of Part I gives $\dot{S}_{dev} = \dot{E}_s^\circ$, not ∞ . Thus, efficiency saturation must occur. Fig. C.1 shows that this framework correctly replicates expected efficiency saturation trends.

Saturation is especially noticeable in the lamp example compared to the car example, the difference being that the LED lamp is already much more efficient than the incandescent lamp ($9.26\times$), whereas the hybrid car is only $1.68\times$ more efficient than the conventional gasoline car. Thus, at $\tilde{\eta} = 81.8$ $\eta^* = 81.8$ lm·hr/W·hr, the energy efficient LED is far closer to efficiency saturation than the hybrid vehicle (at $\tilde{\eta} = 42$ $\eta^* = 42$ mpg). As a result, further increases in the LED lamp's efficiency are less effective than further increases in the hybrid car's efficiency.

That said, actual savings is the difference between the expected energy savings line (solid line) and the takeback line (dashed line) in Fig. C.1. Because the gap between the lines grows, higher efficiency yields greater energy savings, even after accounting for rebound effects. But the actual

883 savings are always less than expected savings, due to takeback.

884 Fig. C.1 shows that expected energy savings (\dot{S}_{dev}) increase faster than takeback as $\tilde{\eta}\eta^*$ increases.
885 Thus, total rebound (Re_{tot} , the ratio of takeback rate to expected energy savings rate in Eq. (3) of
886 Part I), decreases as efficiency grows. The lamp exhibits a relatively smaller rebound decline with
887 efficiency, because the lamp example is closer to saturation than the car example.

888 Fig. C.2 shows the variation of all rebound components with post-EEU efficiency ($\tilde{\eta}\eta^*$). In
889 the car and lamp examples, direct substitution rebound (Re_{dsub}) is the rebound component most
890 sensitive to changes in post-EEU efficiency ($\tilde{\eta}\eta^*$).

891 Note that the sensitivity analysis on post-upgrade efficiency ($\tilde{\eta}\eta^*$, Fig. C.2) is the only sensitivity
892 analysis that requires careful explication of both the numerator and denominator of Eq. (3) in
893 Part I, as in Fig. C.1, because both the numerator and denominator of Eq. (3) in Part I change
894 when post-upgrade efficiency ($\tilde{\eta}\eta^*$) changes. The denominator of Eq. (3) in Part I doesn't change
895 for the sensitivity analyses of Figs. C.3–C.6. Thus, for the remaining sensitivity analyses, when the
896 rebound percentage increases (decreases), the energy takeback rate in the numerator of Eq. (3) in
897 Part I increases (decreases) proportionally, and the actual energy savings rate decreases (increases)
898 accordingly.

899 C.2 Effect of capital cost ($\tilde{C}_{cap}C_{cap}^*$) on rebound terms

900 The sensitivity of energy rebound to capital cost ($\tilde{C}_{cap}C_{cap}^*$) is shown in Fig. C.3. All other things
901 being equal, as capital cost of the EEU rises, less net savings result from the emplacement effect,
902 leading to smaller income, macro, and total rebound. The same effects would be observed with
903 increasing maintenance operations and maintenance (\dot{C}_{OM}^*) and disposal cost rate (\tilde{C}_{md}) (\dot{C}_d^*) rates.

904 C.3 Effect of energy price (p_E) on rebound terms

905 The effect of energy price on rebound is shown in Fig. C.4. Increasing energy prices lead to larger
906 total rebound (Re_{tot}), because higher energy prices lead to more net savings (\hat{N}) to be spent by the
907 device user. All other things being equal, more net savings leads to more spending on other goods
908 and services that demand energy.




Fig. C.2: Sensitivity of rebound components to post-EEU efficiency ($\tilde{\eta}^*$). The macro factor, $k = 3$.




Fig. C.3: Sensitivity of rebound components to capital cost ($\tilde{C}_{cap}^* C_{cap}^*$). The macro factor, $k = 3$.




Fig. C.4: Sensitivity of rebound components to energy price (p_E). German energy prices denoted by vertical lines. The macro factor, $k = 3$.

Fig. C.4 also shows the effect of energy price (p_E) on all rebound components. Most rebound components increase with energy price, with the car and lamp examples exhibiting different sensitivities. Substitution effects (Re_{dsub} and Re_{isub}) are the only rebound components that decrease with energy price (p_E). Substitution effects decrease with energy price, because at high energy price, less behavior adjustment is needed to re-equilibrate after emplacement of the efficient device.

In Fig. C.4, German energy prices⁸ are shown as vertical lines, providing an indication of possible energy price variations. All other things being equal, if U.S. residents paid Germany's energy prices, total energy rebound (Re_{tot}) would be 93.0% for the car example and 148.0% for the lamp example.

C.4 Effect of original uncompensated own price elasticity ($\varepsilon_{\dot{q}_s p_s}^o$) on rebound terms

⁸For the car example, the gasoline price in Germany is taken as 1.42 €/liter for the average “super gasoline” (95 octane) price in 2018 (finanzen.net, 2021). For the lamp example, the electricity price in Germany is taken as 0.3 €/kW·hr for the 2018 price of a household using 3.5 MWh/yr, an average value for German households (Bundesministerium für Wirtschaft und Energie, 2018). Converting currency (at 1 € = \$1.21) and physical units gives 6.5 \$/US gallon and 0.363 \$/kW·hr.




Fig. C.5: Sensitivity of rebound components to uncompensated own price elasticity of energy service demand ($\varepsilon_{q_{s,p_s}}^o$). The macro factor, $k = 3$. [The lamp portion of this figure appears as Fig. 8.](#) (Note reversed x -axis scale.)

Fig. C.5 shows the variation of total rebound (Re_{tot}) with the original uncompensated price elasticity of energy service demand ($\varepsilon_{q_{s,p_s}}^o$). The effect is exponential, and total rebound increases with larger negative values of $\varepsilon_{q_{s,p_s}}^o$, as expected. The lamp example also shows stronger exponential variation than the car example. The main reason that total rebound values are different between the two examples is the larger absolute value of original uncompensated own price elasticity ($\varepsilon_{q_{s,p_s}}^o$) for the lamp (-0.4) compared to the car (-0.2). Were the car to have the same original uncompensated own price elasticity as the lamp (i.e., -0.4), total rebound would be closer for both examples (73.4% for the car and 67.0% for the lamp). Fig. C.5 shows that direct substitution rebound (Re_{dsub}) is the most sensitive rebound component to changes in $\varepsilon_{q_{s,p_s}}^o$. For the lamp example, indirect income rebound (Re_{iinc}) also increases substantially with $\varepsilon_{q_{s,p_s}}^o$, because net savings increases substantially with $\varepsilon_{q_{s,p_s}}^o$.




Fig. C.6: Sensitivity of rebound components to the macro factor (k).

C.5 Effect of macro factor (k) on rebound terms

The sensitivity of energy rebound to the macro factor (k) is shown in Fig. C.6. The macro factor has a linear effect on total rebound (Re_{tot}) through the macro rebound component (Re_{macro}). All other rebound components are constant when k is varied independently.

C.6 Effect of discount rate (r) on rebound terms

The effect of discount rate on rebound is shown in Fig. C.7. Discounting has little effect on rebound terms compared to other parameters such as upgraded efficiency ($\tilde{\eta}_L^*$, Fig. C.2), capital cost ($\tilde{C}_{cap} C_{cap}^*$, Fig. C.3), energy price (p_E , Fig. C.4), and own price elasticity of energy service demand ($\varepsilon_{\dot{q}_s p_s}^o$, Fig. C.5).

C.7 Effect of energy service price ($\tilde{p}_s p_s^*$) on price elasticities ($\hat{\varepsilon}$)

The sensitivity of post-substitution effect price elasticities ($\hat{\varepsilon}$) to post-upgrade energy service price (\tilde{p}_s) is shown in Fig. C.8 for the CES utility model described in Section 2.5.2 and Appendix C of




Fig. C.7: Sensitivity of rebound components to discount rate (r).

Part I. Note that the left side of each graph ($\tilde{p}_s = \theta p_s^* = 0$) represents unattainable infinite efficiency ($\tilde{\eta}_s \rightarrow \infty$, $\eta_s^* \rightarrow \infty$), i.e., delivery of the energy service without energy consumption.

First, note the sign of the elasticities. As expected, both of the uncompensated price elasticities ($\hat{\epsilon}_{\dot{q}_s, p_s}$ and $\hat{\epsilon}_{\dot{q}_s, p_s, c}$, dashed lines in Fig. C.8) are negative, regardless of the energy service price (\tilde{p}_s): a lower price means more consumption of both goods, all other things being equal. The compensated own price elasticity ($\hat{\epsilon}_{\dot{q}_s, p_s, c}$) is negative and the compensated cross price elasticity ($\hat{\epsilon}_{\dot{q}_s, p_s, c}$) is positive. As \tilde{p}_s declines, the consumers substitutes the energy service for other goods.

Second, the magnitude of price elasticities varies. Fig. C.8 shows that the car example exhibits more variation of price elasticities ($\hat{\epsilon}$) with energy service price (\tilde{p}_s) than the lamp example, because the expenditure share ($f_{C_s}^0$) for the lamp example is very small compared to the car example. Using the constant price elasticity (CPE) utility model may be a good enough approximation in the lamp example. However, for the car example, using the CES utility function will be necessary to eliminate errors that will be present in the CPE approximation. This result is an important finding that should encourage analysts implementing analytical rebound calculations with substitution and




Fig. C.8: Sensitivity of post substitution effect price elasticities ($\hat{\varepsilon}$) to post-EEU energy service price (\tilde{p}_s) for the CES utility model. This graph is a visualization of Eqs. [??\(200\)](#), [??\(203\)](#), [\(192\)](#), and [\(202\)](#) of Part I. The solid vertical line indicates the original energy service price (p_s°), and the dashed vertical line indicates the upgraded energy service price ($p_s^* = \hat{p}_s = \bar{p}_s = \tilde{p}_s$) for the two examples. See Tables 7 and 10 for p_s in different units.

957 income effects to prefer the CES utility model over the CPE approximation.

958 Fig. C.8 shows that as efficiency increases (and $\tilde{p}_s - p_s^*$ decreases), the absolute value of the
959 uncompensated price elasticities ($\hat{\varepsilon}_{\dot{q}_s, p_s}$ and $\hat{\varepsilon}_{\dot{q}_o, p_s} - \hat{\varepsilon}_{\dot{q}_g, p_s}$) decreases, a change that exceeds the slightly
960 increasing (in absolute value terms) compensated own price elasticity ($\hat{\varepsilon}_{\dot{q}_s, p_s, c}$). Thus, direct rebound
961 is attenuated as efficiency increases, relative to a constant price elasticity model. (See also the
962 patterns of lines of Fig. C.2, which show a declining trend.)