

6/7/8T (Low Profile) Dump Series

Specifications									
•	G.V.W.R 12,000#	Axle - (2) 6,000# Cambered Electric Brake							
•	G.A.W.R. (Each Axle) - 6,000#	•	Suspension - Multi-Leaf Spring w/ Equalizer						
•	Coupler - 2-5/16" - Adjustable Type	•	Tires - ST235/80R16 Load Range E						
•	Safety Chain - 3/8" Grade 30 w/ Hooks	•	Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)						
•	Jack - Bolt-On 7K Top Wind Drog Leg	Deck - 10 Ga. 1 Piece Smooth Steel w/ Tube Fr							
<u> •</u>	Tongue - Wrapped 6" Channel	•	Lights - L.E.D. Stop, Tail, & Turn						
•	Frame - All Tubing Construction	•	Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal						
•	Sides - 24" 12 Ga. Smooth Steel w/ Tarp	•	Paint Prep - 5-Stage Super Blast Treatment						
•	Crossmembers - All Tube w/ 16" Centers	•	Paint - Super Durable Powdercoat						
•	Fenders - 9x72" - Diamond Plate w/ Steel Backs	•	Gate - Combo: Barn Door/3-Position Spreader						
•	Tie Down - (4) Corner Mounted D-Rings	•	Ramps - 5' Slide-In Runner Style						
Hydraulic Pump - 12-Volt Self-Contained Unit w/ Remote and Inline Truck Charger									
	Hydraulic Lifting Hoist - Scissor Hoist: 5" Cylinder w/ Gravity Down Vent Port								



	Optional Features							
•	Surge Brake Upgrade	•	Battery Charger Options					
•	Metal Tarp Protector	•	42" High Sides					
•	Spare Tire Mount	•	TieDown/Wheel Options					
•	Wet Line (No Pump)	•	Gas Powered Pump					
•	7K or 8K Axle Upgrades	•	Gooseneck Model					



Dimensions												
Weight/Length	A	В	С	D	Е	F						
3,600# - 10'	120"	79"	45"	29"	80"	17"						
3,900# - 12'	144"	90"	45"	29"	80"	17"						
4,500# - 14'	168"	101"	45"	29"	80"	17"						
4,800# - 16'	192"	122"	45"	29"	80"	17"						



