

# Forensics Subversion and Covert Channels

Aaron Sedlacek  
Branden Clark

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
push    0Dh
call    sub_31411B
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
; -----
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# Agenda

- Access Token Manipulation
- IRP Handling and Filter Drivers
- Forensics Countermeasures
- Covert Channels
- Out-Of-Band

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Windows Authorization Tokens

- User logs on
  - OS generates a “Primary” access token based on:
    - The user’s account
    - The user’s security groups
    - Privileges granted by the administrator
- All processes launched on behalf of the user will be given a copy of this token

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
mov     [ebp+arg_0], ebx
short loc_31306E
mov     eax, [ebp+var_74]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
mov     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
; sub_312FD8+55
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
; -----
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# Windows Authorization Tokens

- The OS uses the access token to authorize a process when it attempts to
  - Perform an action that requires special privileges
  - Access a securable object
- **Securable Object** - Any object that has a security descriptor
- **Security Descriptor**
  - Determines an object's owner, primary security group, and discretionary access control list (DACL)

# Windows Authorization Tokens

- List of access control entries (ACEs)
  - each ACE identifies a user, or security group, and the operations that they're allowed to perform on an object
- 34 different privileges
  - SeDebugPrivilege
  - SeShutdownPrivilege
  - SeLoadDriverPrivilege
  - ...



# Modifying Tokens

- Two ways to modify access tokens:
  - a. Windows API:
    - `OpenProcessToken()`
    - `AdjustTokenPrivileges()`
    - `AdjustTokenGroups()`
  - b. DKOM
    - **EPROCESS** struct contains a pointer to the token object

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
call    [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_31306D: ; CODE XREF: sub_312FD8+55
; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D: ; CODE XREF: sub_312FD8+49
; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D: ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C: ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Agenda

- Access Token Manipulation
- **IRP Handling and Filter Drivers**
- Forensics Countermeasures
- Covert Channels
- Out-Of-Band

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F

loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
push    0Dh
call    sub_31411B

loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# Drivers and Device Stacks

- Drivers add themselves to the chain of drivers

- Create a device

- `IoCreateDevice()`

- Insert device into group of devices

- `IoAttachDevice()`

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
mov     [ebp+arg_0], ebx
mov     eax, [ebp+var_70]
mov     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_314623
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```


```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```





# Drivers and Device Stacks



# IRP Lifecycle Example



- Read request made to read keystroke

## IRP




# IRP Lifecycle Example


- IRP Makes its way down the device stack



# IRP Lifecycle Example



# IRP Lifecycle Example



# IRP Forwarding and Completion

- **IoCallDriver(gNextDevice, theIRP)**
  - Calls the next device in the stack
- **IoSkipCurrentStackLocation(theIRP)**
  - If this function is called, **IoCallDriver()** calls the next driver with the **IO\_STACK\_LOCATION** of the current driver
  - This trick allows the lower-level driver to use any arguments or completion routines supplied
- **IoCompleteRequest(theIRP)**
  - Returns the given IRP to the I/O Control Manager



# Completion Routines

- IoSetCompletionRoutine(theIRP, completionRoutine, ...)
  - Registers a routine to be executed when the next lowest driver has completed the IRP

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_314623
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
mov     esi, eax
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Agenda

- Access Token Manipulation
- IRP Handling and Filter Drivers
- **Forensics Countermeasures**
- Covert Channels
- Out-Of-Band

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Hooking Countermeasures

- There are certain ranges of addresses that most call table entries should contain

| Call Table | Red Flag Condition   |
|------------|--|
| IAT        | An entry lies outside of its designated DLL address range                    |
| IDT        | The address of the 0x2E handler lies outside of ntoskrnl.exe                 |
| MSR        | The contents of IA32_SYSENTER_EIP lie outside of ntoskrnl.exe                |
| SSDT       | Pointers to the Nt*() routines lie outside of ntoskrnl.exe                   |
| IRP        | The addresses of dispatch routines lie outside of the driver's address range |

# Patching Countermeasures

- Byte Scanning
  - Scan the first few and last few lines of each routine for a telltale jump instruction
- Checksum Calculations

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# DKOM Countermeasures

- Cross-View Detection

- There are usually multiple ways to collect the same information
- Some may be under the control of the rootkit, but not all
- Typically, Cross-view Detection uses high-level and low-level methods

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+var_4]
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jnz     short loc_31306F
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
push    0Dh
call    sub_31411B
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# DKOM Countermeasures

- Cross-View Enumerations
  - High-Level Enumeration
    - `CreateToolHelp32Snapshot()`
    - PID Bruteforce
  - Low-level Enumeration
    - Walk the Process list
    - Walk the Thread list
- Rootkit Detection Tools
  - RootkitRevealer (Sysinternals tool)
  - HackerDefender, Vanquish, AFX, Blacklight, Volatility

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```



# Counter-Countermeasures

- Authors have three options:
  1. Starve the Opposition
    - a. The Grugq's 'Data Contraception' philosophy
  2. Stepping out of the two-ring model
    - a. Rogue Hypervisors (Ring -1)
    - b. System Management Mode Rootkits (Ring -2)
    - c. Lights-Out Management Facilities (Ring -3)
    - d. Bootkits
    - e. Onboard Flash Storage and Circuit-Level
  3. Covert Channels

```
push edi
call sub_314623
test eax, eax
jz short loc_31306D
cmp [ebp+arg_0], ebx
mov short loc_313066, eax
mov eax, [ebp+var_70]
cmp eax, [ebp+var_84]
jb short loc_313066
sub eax, [ebp+var_84]
push esi
```

```
push esi
push eax
push edi
mov [ebp+arg_0], eax
call sub_31486A
test eax, eax
jz short loc_31306D
push esi
lea eax, [ebp+arg_0]
push eax
push esi
push [ebp+arg_4]
call sub_3140F3
test eax, eax
jz short loc_31306D
cmp [ebp+arg_0], esi
jz short loc_31308F
```

```
loc_31306D: ; CODE XREF: sub_312FD8+7
; sub_312FD8+55
```

```
loc_31306D: ; CODE XREF: sub_312FD8+7
; sub_312FD8+49
```

```
call sub_3140F3
test eax, eax
jz short loc_31307D
call sub_3140F3
jmp short loc_31308C
```

```
loc_31307D: ; CODE XREF: sub_312FD8+7
```

```
call sub_3140F3
and eax, 0FFFFFFh
or eax, 80070000h
```

```
loc_31308C: ; CODE XREF: sub_312FD8+7
```

```
mov [ebp+var_4], eax
```

# Agenda

- Access Token Manipulation
- IRP Handling and Filter Drivers
- Forensics Countermeasures
- Covert Channels
- Out-Of-Band

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Covert Channels

- Why?

- If an analyst can't find a rootkit on the victim machine, they can still watch all network traffic
- What good is a rootkit if you can't talk to it or use it to retrieve data?

- How?

- Covert Channel - A network connection that disguises its byte stream as normal traffic
- Doesn't need to be fancy, just needs to be unanticipated

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
mov     esi, 1D0h
push    esi
push    [ebp+var_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
; CODE XREF: sub_312FD8
; sub_312FD8+55
```

```
push    2Dh
call    sub_31411B
```

```
loc_31306D:
; CODE XREF: sub_312FD8
; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:
; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:
; CODE XREF: sub_312FD8
```

# Common Malware Channels

- 1980's - Listen on an obscure port
  - Firewalls
- Late 1980's - IRC
  - Malware connects back to the attacker, does not leave an obscure port hanging around
  - Now stands out like a sore thumb
- 1990's - Peer-to-peer
  - P2P protocols aren't necessarily inconspicuous

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
mov     short loc_313066, ebx
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    esi
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_314118
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Common Malware Channels

- Now - HTTP

- Web traffic is everywhere, supports a myriad of higher-level protocols
- with TCP, can be considered reliable

- Malware will stick to strictly legitimate URLs

- Malware has started using things like Google Groups as C2 servers
- Difficult to filter, lends itself to steganography

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
mov     short loc_313066, ebx
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+var_84], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```



# Common Malware Channels

- HTTP provides an endless variety of places to hide data
  - Particularly, mixed into the content of seemingly legitimate HTTP requests/replies
- Using HTTPS can be useful, but it can imply that some data is being hidden
  - Rootkits will commonly encrypt segments of the HTTP content instead

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
mov     short loc_313066, ebx
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31308F
mov     eax, [ebp+arg_0]
```

```
loc_31306E:                                     ; CODE XREF: sub_312FD8
; sub_312FD8+55
```

```
push    0Dh
call    sub_3140F3
loc_31306D:                                     ; CODE XREF: sub_312FD8
; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```



# Protocol Tunneling

- Stash our data in the nooks and crannies of an otherwise mundane protocol
- The goal is to bore the forensic analyst to death
- Covert data stream must:
  - Make it past the perimeter firewall
  - Blend in with existing traffic

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Protocol Tunneling

- **HTTP**
  - Reliable and flexible, but noisy
  - Typically used for Data exfiltration
- **DNS**
  - Not suited for data transfer
  - Typically used for WAN-based C2
  - Ubiquitous
- **ICMP**
  - Often blocked at the perimeter
  - Typically used for LAN-based C2
  - Often Ignored by forensic analysts

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Protocol Tunneling

- ICMP example
  - [RC3 CTF Forensics 400](#)

```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
    
```

```

loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
    
```

```

push    0Dh
call    sub_31411B
    
```

```

loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
    
```

```

call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
    
```

```

loc_31307D:                                     ; CODE XREF: sub_312FD8
    
```

```

call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
    
```

```

loc_31308C:                                     ; CODE XREF: sub_312FD8
    
```

```

mov     [ebp+var_4], eax
    
```

# Protocol Tunneling

- ICMP example
  - [RC3 CTF Forensics 400](#)
- scapy example
  - [Kit kappa icmp transfer](#)

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
;
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Protocol Tunneling

- IPv4

```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi

```

IPv4 Header Format

| Octet | 0                      |   |   |     |   |   |   | 1    |          |   |    |    |     |    | 2            |                 |    |    |                 |    |    | 3  |    |    |    |    |    |    |    |    |    |    |
|-------|------------------------|---|---|-----|---|---|---|------|----------|---|----|----|-----|----|--------------|-----------------|----|----|-----------------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Bit   | 0                      | 1 | 2 | 3   | 4 | 5 | 6 | 7    | 8        | 9 | 10 | 11 | 12  | 13 | 14           | 15              | 16 | 17 | 18              | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 |
| 0     | Version                |   |   | IHL |   |   |   | DSCP |          |   |    |    | ECN |    | Total Length |                 |    |    |                 |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 32    | Identification         |   |   |     |   |   |   |      |          |   |    |    |     |    |              | Flags           |    |    | Fragment Offset |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 64    | Time To Live           |   |   |     |   |   |   |      | Protocol |   |    |    |     |    |              | Header Checksum |    |    |                 |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 96    | Source IP Address      |   |   |     |   |   |   |      |          |   |    |    |     |    |              |                 |    |    |                 |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 128   | Destination IP Address |   |   |     |   |   |   |      |          |   |    |    |     |    |              |                 |    |    |                 |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 160   | Options (if IHL > 5)   |   |   |     |   |   |   |      |          |   |    |    |     |    |              |                 |    |    |                 |    |    |    |    |    |    |    |    |    |    |    |    |    |

```

call    sub_31411B
; -----
loc_31306D:                                     ; CODE XREF: sub_312FD8
; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax

```

# Protocol Tunneling

- IPv4
  - ID field - 16 bpp (bits per packet)
  - DF flag - 1 bpp
  - TTL - 8 bpp
  - many more

```
push edi
call sub_314623
test eax, eax
jz short loc_31306D
cmp [ebp+arg_0], ebx
jnz short loc_313066
mov eax, [ebp+var_70]
cmp eax, [ebp+var_84]
jb short loc_313066
sub eax, [ebp+var_84]
push esi
push esi
push eax
push edi
mov [ebp+arg_0], eax
call sub_31486A
test eax, eax
jz short loc_31306D
push esi
lea eax, [ebp+arg_0]
push eax
mov esi, 1D0h
push esi
push [ebp+arg_4]
push edi
call sub_314623
test eax, eax
jz short loc_31306D
cmp [ebp+arg_0], esi
jz short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push 0Dh
call sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call sub_3140F3
test eax, eax
jg short loc_31307D
call sub_3140F3
jmp short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call sub_3140F3
and eax, 0FFFFh
or eax, 80070000h
```


```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov [ebp+var_4], eax
```



# Protocol Tunneling

- IPv6



```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
    
```

XREF: sub\_312FD8  
312FD8+55

XREF: sub\_312FD8  
312FD8+49

XREF: sub\_312FD8

```

and     eax, 0FFFFh
or      eax, 80070000h

loc_31308C:
mov     [ebp+var_4], eax
    
```

: CODE XREF: sub\_312FD8

# Protocol Tunneling

- IPv6
  - Much simpler...but...

```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F

```

```

loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55

```

```

push    0Dh
call    sub_31411B

```

```

loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49

```

```

call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

```

```

loc_31307D:                                     ; CODE XREF: sub_312FD8

```

```

call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

```

```

loc_31308C:                                     ; CODE XREF: sub_312FD8

```

```

mov     [ebp+var_4], eax

```

# Protocol Tunneling

- IPv6
  - Much simpler...but...
  - Has extension headers!

| Extension Header                                       | Type | Description   |
|--|------|---|
| <i>Hop-by-Hop Options</i>                              | 0    | Options that need to be examined by all devices on the path.                          |
| <i>Destination Options</i> (before routing header)     | 60   | Options that need to be examined only by the destination of the packet.               |
| <i>Routing</i>   | 43   | Methods to specify the route for a datagram (used with <a href="#">Mobile IPv6</a> ). |
| <i>Fragment</i>  | 44   | Contains parameters for fragmentation of datagrams.                                   |
| <i>Authentication Header (AH)</i>                      | 51   | Contains information used to verify the authenticity of most parts of the packet.     |
| <i>Encapsulating Security Payload (ESP)</i>            | 50   | Carries encrypted data for secure communication.                                      |
| <i>Destination Options</i> (before upper-layer header) | 60   | Options that need to be examined only by the destination of the packet.               |
| <i>Mobility</i> (currently without upper-layer header) | 135  | Parameters used with <a href="#">Mobile IPv6</a> .                                    |

# Protocol Tunneling

- IPv6
  - Much simpler...but...
  - Has extension headers!

```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
    
```

*Hop-by-Hop Options and Destination Options extension header format*

| Offsets | Octet | 0                                      |   |   |   |   |   |   |   | 1           |   |    |    |    |    |    |    | 2                   |    |    |    |    |    |    |    | 3  |    |    |    |    |    |    |    |
|---------|-------|--|---|---|---|---|---|---|---|-------------|---|----|----|----|----|----|----|---------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Octet   | Bit   | 0                                      | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8           | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16                  | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 |
| 0       | 0     | Next Header                            |   |   |   |   |   |   |   | Hdr Ext Len |   |    |    |    |    |    |    | Options and Padding |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 4       | 32    | Options and Padding                    |   |   |   |   |   |   |   |             |   |    |    |    |    |    |    |                     |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 8       | 64    | Optional: more Options and Padding ... |   |   |   |   |   |   |   |             |   |    |    |    |    |    |    |                     |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 12      | 96    |  |   |   |   |   |   |   |   |             |   |    |    |    |    |    |    |                     |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |

## Next Header (8 bits)

Specifies the [type](#) of the next header.

## Hdr Ext Len (8 bits)

Length of this header in 8-octet units, not including the first 8 octets.

## Options (variable)

Contains one or more options, and optional padding fields to align options and to make the total header length a multiple of 8 octets. Options are [TLV](#)-coded.

```

jmp     short loc_31308C
; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
    
```

# Protocol Tunneling

- IPv6
  - Much simpler...but...
  - Has extension headers!
  - The extension headers add a LOT of variability to each packet
    - Plenty of opportunities for crazy covert channels

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    esi
push    esi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jnz     short loc_31308F

loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
push    0Dh
call    sub_31411B

loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# Protocol Tunneling

- Finding covert channels
  - Read the RFCs
  - ...that's about it

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```



```
push    edi
call    sub_314623
test    eax, eax
jz       short loc_31306D
cmp     [ebp+arg_0], ebx
jg       short loc_31306E
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb       short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

- API but easy to detect
- and, protocol-specific
- cification (NDIS)
- ow network-based
- ert
- 39

# Passive Covert Channels

- You're still generating new packets
  - That may be enough for an analyst to find a rootkit
- Instead, make subtle modifications to existing packets.
  - Steganography at the packet level
- Extra **STEALTH** but additional **EFFORT**
  - Requires a foothold on a device that has access to all network traffic (like a router)

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_313066
push    esi
lea     eax, [ebp+arg_0]
mov     esi, ebx
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+55
push    esi
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                                ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# Agenda

- Access Token Manipulation
- IRP Handling and Filter Drivers
- Forensics Countermeasures
- Covert Channels
- Out-Of-Band

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Additional Processor Modes

- The IA-32 architecture supports 3 modes:
  - Real mode (kernel mode)
  - Protected mode (user mode)
  - System management mode
- Intel processors that support virtualization have 2 more modes:
  - Root mode
  - Non-root mode

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
inc     eax, loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31466A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
push    [ebp+arg_0]
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F

loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
push    0Dh
call    sub_31411B

loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```

# System Management Mode

- Operating mode provided for handling:
  - Power management
  - System hardware control
  - Proprietary OEM designed code
- SMM provides a way to execute instructions in a manner that's hidden from the targeted OS!

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    esi
mov     esi, [ebp+arg_0], eax
call    sub_314623
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
jnz     short loc_313066
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F

loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
push    0Dh
call    sub_31411B


loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

; -----
loc_31307D:                                     ; CODE XREF: sub_312FD8
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

loc_31308C:                                     ; CODE XREF: sub_312FD8
mov     [ebp+var_4], eax
```



# Switching to SMM



```
push edi
call sub_314623
test eax, eax
jz short loc_31306D
cmp [ebp+arg_0], ebx
jnz short loc_313066
mov eax, [ebp+var_70]
cmp eax, [ebp+var_84]
jb short loc_313066
sub eax, [ebp+var_84]
push esi
```

```
push esi
push eax
push edi
[ebp+arg_0], eax
sub_31486A
eax, eax
short loc_31306D
esi
eax, [ebp+arg_0]
eax
esi, 1D0h
esi
push [ebp+arg_4]
push edi
```

```
call test
jz
cmp
jz
loc_313066:
push
call sub_31411B
```

```
loc_31306D:
call sub_3140F3
test eax, eax
jg short loc_31307D
call sub_3140F3
jmp short loc_31308C
; CODE XREF: sub_312FD8
; sub_312FD8+49
```

```
call sub_3140F3
and eax, 0FFFFh
or eax, 80070000h
loc_31308C:
mov [ebp+var_4], eax
; CODE XREF: sub_312FD8
```



# Switching to SMM

- System Management Interrupt (SMI)
  - Normal Hardware Interrupt
  - No hardware-agnostic way to generate an SMI
  - Most researchers generate an SMI by using Programmed Input/Output (PIO)
    - Talk to the hardware and get it to do something to cause an SMI
- SMRAM
  - 64 KB in size, all code and data the SMI Handler is composed of is here

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
call    sub_314623
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+var_10]
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+var_10], eax
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_3140F3:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# SMM Operations

- No such things as privilege levels or address mappings
  - Just the handler and memory
- The handler can arbitrarily modify anything in physical memory
- SMM is controlled by flags in the **SMRAMC** Register
  - the **SMRAMC** register can be manipulated by PIO
  - Contains the D\_LCK and D\_OPEN flags

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_1], eax
call    sub_31466A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8+55
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8+49
; sub_312FD8+49
```

```
call    sub_3140F3
; sub_3140F3
jg      short loc_31307D
call    sub_3140F3
; sub_3140F3
short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# SMM Operations

- D\_LCK Flag
  - When set, **SMRAMC** is read-only and D\_OPEN is cleared
- D\_OPEN Flag
  - When set, SMRAM can be accessed by non-SMM code
  - Until 2008, vendors used to leave this flag set by accident
  - Bypass found in 2009

- [http://invisiblethingslab.com/resources/misc09/smm\\_cache\\_fun.pdf](http://invisiblethingslab.com/resources/misc09/smm_cache_fun.pdf)

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```


```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Rogue Hypervisors

- Hypervisor/Virtual Machine Monitor (VMM)
  - Low-level layer of software that allows a computer to share its resources between multiple operating systems



# Rogue Hypervisors

- Blue Pill proof-of-concept
  - Developed by Joanna Rutkowska, Alexander Tereshkin, and Rong Fan

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```



# Lights-Out Management

- OEM's have put more and more functionality at the motherboard level
  - Machines can be accessed and managed without an OS or **without even being turned on**
- Intel's Active Management Technology (AMT)
  - Has an independent processor to execute AMT code
    - Even supports a stand-alone web server
  - Researchers have demonstrated how to modify the code that AMT executes
    - **Essentially construct a ring -3 rootkit**



# Bootkits

- Subvert the boot process so that an attacker's code is executed first
- The next major development in malware
- Mostly used to bypass Microsoft Patchguard
- Unfortunately, outside of the scope of this course

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     [ebp+var_70], eax
push    esi
push    [ebp+arg_4]
push    [ebp+var_70]
call    sub_314623
test    eax, eax
jz      short loc_31306D
mov     [ebp+var_84], eax
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```


```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# Bootkits



```

push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F

```

```

; CODE XREF: sub_312FD8
; sub_312FD8+55

```

```

push    0Dh
call    sub_31411B

```

```

; CODE XREF: sub_312FD8
; sub_312FD8+49

```

```

call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C

```

```

; CODE XREF: sub_312FD8

```

```

call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h

```

loc\_31308C:

```

; CODE XREF: sub_312FD8

```

```

mov     [ebp+var_4], eax

```

# Questions?

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
push    esi
push    eax
push    edi
mov     [ebp+arg_0], eax
call    sub_31486A
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     esi, 1D0h
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```

# References

1. Blunden, Bill. The Rootkit Arsenal Escape and Evasion in the Dark Corners of the System, Second Edition. 2nd ed. Burlington, Mass.: Jones & Bartlett Learning, 2013. Print.
1. Hoglund, Greg, and James Butler. Rootkits: Subverting the Windows Kernel. Upper Saddle River, NJ: Addison-Wesley, 2006. Print.

```
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], ebx
jnz     short loc_313066
mov     eax, [ebp+var_70]
cmp     eax, [ebp+var_84]
jb      short loc_313066
sub     eax, [ebp+var_84]
push    esi
```

```
push    esi
push    eax
mov     [ebp+arg_0], eax
test    eax, eax
jz      short loc_31306D
push    esi
lea     eax, [ebp+arg_0]
push    eax
mov     [ebp+var_4], esi
push    esi
push    [ebp+arg_4]
push    edi
call    sub_314623
test    eax, eax
jz      short loc_31306D
cmp     [ebp+arg_0], esi
jz      short loc_31308F
```

```
loc_313066:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+55
```

```
push    0Dh
call    sub_31411B
```

```
loc_31306D:                                     ; CODE XREF: sub_312FD8
                                              ; sub_312FD8+49
```

```
call    sub_3140F3
test    eax, eax
jg      short loc_31307D
call    sub_3140F3
jmp     short loc_31308C
```

```
loc_31307D:                                     ; CODE XREF: sub_312FD8
```

```
call    sub_3140F3
and     eax, 0FFFFh
or      eax, 80070000h
```

```
loc_31308C:                                     ; CODE XREF: sub_312FD8
```

```
mov     [ebp+var_4], eax
```