COMP108 Data Structures and Algorithms

Divide-and-Conquer Algorithms (Part I)

Professor Prudence Wong

pwong@liverpool.ac.uk

2022-23

Outline

Divide-and-Conquer algorithms


- Basic idea
- Learn a few examples

Learning outcomes:

- Able to describe the principle of divide-and-conquer algorithms
- ▶ Able to design divide-and-conquer algorithm for some simple problems

Triomino Puzzle

- ▶ Input: 2ⁿ-by-2ⁿ chessboard with one missing square & many L-shaped tiles of 3 adjacent squares
- Question: Cover the chessboard with L-shaped tiles without overlapping



Divide-and-conquer algorithms

One of the best-known algorithm design techniques

ldea:


- A problem instance is divided into several smaller instances of the same problem, ideally of about same size
- The smaller instances are solved, typically recursively
- The solutions for the smaller instances are combined to get a solution to the large instance

Finding the sum of all numbers in an array

Suppose we have 8 numbers:

```
4 6 3 2 8 7 5 1
```

- Suppose we have 8 numbers:
- 4 6 3 2 8 7 5 1
- Divide: let's divide them into two halves



```
Iterative version:  \begin{aligned} & \text{sum} \leftarrow 0 \\ & \text{i} \leftarrow 1 \\ & \text{while i} \leq \text{n do} \\ & \text{begin} \\ & \text{sum} \leftarrow \text{sum} + A[i] \\ & \text{i} \leftarrow \text{i} + 1 \\ & \text{end} \\ & \text{output sum} \end{aligned}
```

- Suppose we have 8 numbers:
 - 4 6 3 2 8 7 5 1
- Divide: let's divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the sum of each half, then we can simply add these two sums


```
Iterative version:  \begin{aligned} & \text{sum} \leftarrow 0 \\ & \text{i} \leftarrow 1 \\ & \text{while i} \leq \text{n do} \\ & \text{begin} \\ & \text{sum} \leftarrow \text{sum} + A[i] \\ & \text{i} \leftarrow \text{i} + 1 \\ & \text{end} \\ & \text{output sum} \end{aligned}
```


- Suppose we have 8 numbers:
 - 4 6 3 2 8 7 5 1
- Divide: let's divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the sum of each half, then we can simply add these two sums
- Recursively: How to find the sum of each half? Apply divide-and-conquer on each half


```
Iterative version:  \begin{aligned} & \text{sum} \leftarrow 0 \\ & \text{i} \leftarrow 1 \\ & \text{while i} \leq \text{n do} \\ & \text{begin} \\ & \text{sum} \leftarrow \text{sum} + A[i] \\ & \text{i} \leftarrow \text{i} + 1 \\ & \text{end} \\ & \text{output sum} \end{aligned}
```


- Suppose we have 8 numbers:
 - 4 6 3 2 8 7 5 1
- Divide: let's divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the sum of each half, then we can simply add these two sums
- Recursively: How to find the sum of each half? Apply divide-and-conquer on each half
- When to stop: When there is only one number left, simply return this number (sum of one number is the number itself)


4 6 3 2 8 7 5 1



















































































For simplicity, assume n is a power of 2

We can call the following algorithm by RecSum(A, 1, n)

Algorithm RecSum(A[], p, q)


```
p is index of entry of first element in the current call \mathbf{q} ... last ...
```

```
Iterative version:  \begin{aligned} & \text{sum} \leftarrow 0 \\ & \text{i} \leftarrow 1 \\ & \text{while i} \leq \text{n do} \\ & \text{begin} \\ & \text{sum} \leftarrow \text{sum} + A[i] \\ & \text{i} \leftarrow \text{i} + 1 \\ & \text{end} \\ & \text{output sum} \end{aligned}
```

end

```
For simplicity, assume n is a power of 2
We can call the following algorithm by RecSum(A, 1, n)
Algorithm RecSum(A[], p, q)
    if p == q then
         return A[p]
    else
    begin
```

For simplicity, assume n is a power of 2



Finding the minimum over all numbers in an array

Suppose we have 8 numbers:

4 6 3 2 8 7 5 1

```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin if A[i] \leq \min then \min \leftarrow A[i] i \leftarrow i + 1 end output min
```

Finding the minimum over all numbers in an array

Suppose we have 8 numbers:

4 6 3 2 8 7 5 1

Divide: divide them into two halves

4 6 3 2 **AND** 8 7 5 1

```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin if A[i] \leq \min then \min \leftarrow A[i] i \leftarrow i + 1 end output min
```

Finding the minimum over all numbers in an array

- Suppose we have 8 numbers:
- 4 6 3 2 8 7 5 1
- Divide: divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the minimum of each half, then we can compare these two numbers and return the smaller one

```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin if A[i] \leq \min then \min \leftarrow A[i] i \leftarrow i + 1 end output min
```

Finding the minimum over all numbers in an array


- Suppose we have 8 numbers:
 - 4 6 3 2 8 7 5 1
- Divide: divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the minimum of each half, then we can compare these two numbers and return the smaller one
- Recursively: How to find the minimum of each half? Apply divide-and-conquer on each half


```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin \text{if } A[i] \leq \min \text{ then } \min \leftarrow A[i] i \leftarrow i+1 end output \min
```


Finding the minimum over all numbers in an array


- Suppose we have 8 numbers:
 - 4 6 3 2 8 7 5 1
- Divide: divide them into two halves
 - 4 6 3 2 **AND** 8 7 5 1
- Conquer: If we know the minimum of each half, then we can compare these two numbers and return the smaller one
- Recursively: How to find the minimum of each half? Apply divide-and-conquer on each half
- When to stop: When there is only one number left, simply return this number (the minimum of one number is the number itself)


```
Iterative version:  \min \leftarrow A[1]   i \leftarrow 2   \text{while } i \leq n \text{ do}   \text{begin}   \text{if } A[i] \leq \min \text{ then}   \min \leftarrow A[i]   i \leftarrow i+1   \text{end}   \text{output min}
```























































































What about the maximum?



```
For simplicity, assume n is a power of 2 
We can call the following algorithm by RecMin(A, 1, n) 
Algorithm RecMin(A[], p, q)
```

```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin if A[i] \leq \min then \min \leftarrow A[i] i \leftarrow i + 1 end output min
```

```
For simplicity, assume n is a power of 2 
We can call the following algorithm by RecMin(A, 1, n) 
Algorithm RecMin(A[], p, q) 
if p == q then 
return A[p] 
else begin
```

```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 while i \leq n do begin if A[i] \leq \min then \min \leftarrow A[i] i \leftarrow i + 1 end output min
```

end

```
For simplicity, assume n is a power of 2
We can call the following algorithm by RecMin(A, 1, n)
     Algorithm RecMin(A[], p, a)
            if p == a then
                 return A[p]
            else begin
                 answer1 \leftarrow RecMin(A, p, \frac{p+q-1}{2})
answer2 \leftarrow RecMin(A, \frac{p+q+1}{2}, q)
```


```
Iterative version: \min \leftarrow A[1] i \leftarrow 2 \text{while } i \leq n \text{ do} \text{begin} \text{if } A[i] \leq \min \text{ then} \min \leftarrow A[i] i \leftarrow i+1 \text{end} \text{output min}
```

end


```
For simplicity, assume n is a power of 2
We can call the following algorithm by RecMin(A, 1, n)
     Algorithm RecMin(A[], p, q)
           if p == a then
                return A[p]
           else begin
                answer1 \leftarrow RecMin(A, p, \frac{p+q-1}{2})
answer2 \leftarrow RecMin(A, \frac{p+q+1}{2}, q)
                if answer1 < answer2 then
                      return answer1
                else return answer2
           end
```

```
Iterative version:  \min \leftarrow A[1]   i \leftarrow 2   \text{while } i \leq n \text{ do}   \text{begin}   \text{if } A[i] \leq \min \text{ then }   \min \leftarrow A[i]   i \leftarrow i+1   \text{end}   \text{output min}
```

Time complexity analysis



Time complexity analysis



Summary

Summary: Basic Divide-and-Conquer algorithms

Next: Merge Sort Algorithm

For note taking