

COMP108

Data Structures and Algorithms

Pseudo code (Part I)

Professor Prudence Wong

pwong@liverpool.ac.uk

2022-23

Outline

Describing algorithms using pseudo code

- ▶ Algorithm vs Program
- ▶ Pseudo code
 - ▶ Trace pseudo code
 - ▶ Develop simple pseudo code

Learning outcome:

- ▶ Able to use pseudo code to describe algorithm

What is an algorithm

- ▶ A sequence of **precise and concise** instructions that guide you (or a computer) to solve a **specific** problem in a **finite** amount of time



- ▶ Daily life examples: cooking recipe, furniture assembly manual
 - ▶ What are input / output in each case?

Algorithm vs Program

An algorithm is a sequence of precise and concise instructions that guide a person/computer to solve a specific problem

Algorithms are free from grammatical rules

- ▶ **Content** is more important than form
- ▶ Acceptable as long as it tells people how to perform a task

Programs must follow some syntax rules

- ▶ **Form** is important
- ▶ Even if the idea is correct, it is still not acceptable if there is syntax error

Compute the n -th power

Input: a number x & a non-negative integer n

Output: the n -th power of x

Algorithm:

1. Set a temporary variable p to 1
2. Repeat the multiplication $p \leftarrow p * x$ for n times
3. Output the result p .

n is 3
 x is 2 \rightarrow 8

$p \leftarrow 1$

$p * x$

Pseudo code

Pseudo code:

```
p ← 1
for i ← 1 to n
  p ← p * x
output p
```

Python:

```
p = 1
for i in range(n):
    p = p * x
print p
```

C:

```
p = 1;
for (i=1; i<=n; i++)
    p = p * x;
printf("%d\n", p);
```

Pascal:

```
p := 1;
for i := 1 to n
    p := p * x;
writeln(p);
```

C++:

```
p = 1;
for (i=1; i<=n; i++)
    p = p * x;
cout << p << endl;
```

Java

```
p = 1;
for (i=1; i<=n; i++)
    p = p * x;
System.out.println(p);
```

Pseudo Code

One way to describe algorithm is by pseudo code

```
p ← 1  
for i ← 1 to n  
  p ← p * x  
output p
```

more like English

similar to programming language

Pseudo code uses combination of both

Control flow

Expectations (refer to COMP101 / COMP122)

► if-then-else

```
if <condition> then  
    <statement>  
else  
    <statement>
```

index variable
i

► for-loop

```
for <variable>  $\leftarrow$  <value1> to <value2> do  
    <statement>
```

► while-loop

```
while <condition> do  
    <statement>
```


Control flow

Expectations (refer to COMP101 / COMP122)

► if-then-else

```
if <condition> then
    <statement>
else
    <statement>
```

► for-loop

```
for <variable>  $\leftarrow$  <value1> to <value2> do
    <statement>
```

► while-loop

```
while <condition> do
    <statement>
```

► block of statements

```
begin
    <statement1>
    <statement2>
    ⋮
end
```

OR

```
{
    <statement1>
    <statement2>
    ⋮
}
```

Loops

- Sum of first n +ve integers

```
sum  $\leftarrow$  0  
i  $\leftarrow$  1  
while  $i \leq n$  do  
  begin  
    sum  $\leftarrow$  sum + i  
    i  $\leftarrow$  i + 1  
  end  
output sum
```

i $1 \rightarrow 2 \rightarrow 3 \rightarrow 4 \rightarrow 5 \dots$

Sum 1 3 6 10 15

Loops

- Sum of first n +ve integers

```
sum  $\leftarrow$  0  
i  $\leftarrow$  1  
while  $i \leq n$  do  
begin  
    sum  $\leftarrow$  sum + i  
    i  $\leftarrow$  i + 1  
end  
output sum
```

Trace table - how variables change

- suppose $n = 4$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5

Loops

- Sum of first n +ve integers

```

sum ← 0
i ← 1
while i ≤ n do
begin
    sum ← sum + i
    i ← i + 1
end
output sum

```

Trace table - how variables change

- suppose $n = 4$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5

- suppose $n = 6$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5
5	5	15	6
6	6	21	7

Loops

- Sum of first n +ve integers

```

sum ← 0
i ← 1
while i ≤ n do
begin
    sum ← sum + i
    i ← i + 1
end
output sum
  
```

Handwritten annotations: A blue circle around '0', a blue circle around 'sum + i' with an arrow pointing to it from a blue asterisk, and a blue circle around 'i' in 'i ← i + 1'.

How to find product?

Trace table - how variables change

- suppose $n = 4$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5

- suppose $n = 6$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5
5	5	15	6
6	6	21	7

Loops

- Sum of first n +ve integers

```

sum ← 0
i ← 1
while i ≤ n do
begin
    sum ← sum + i
    i ← i + 1
end
output sum

```

How to find product?

(i) 0 change to 1 (ii) + i change to * i

Trace table - how variables change

- suppose $n = 4$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5

- suppose $n = 6$

iteration	i before	sum	i after
before loop	1	0	1
1	1	1	2
2	2	3	3
3	3	6	4
4	4	10	5
5	5	15	6
6	6	21	7

Example — What is being computed?

Trace table

Suppose $0 < x < y$ & both are +ve integers

```

i ← 1
while i ≤ x do
  begin
    if  $x \% i == 0$  AND  $y \% i == 0$  then
      output i
    i ← i + 1
  end
end
  
```

- Operator % finds remainder:
 $a \% b$ gives remainder of a divided by b

mod

$$6 \% 4 = 2$$

$$6 \% 3 = 0$$

Example — What is being computed?

Suppose $0 < x < y$ & both are +ve integers

```

i ← 1
while i ≤ x do
begin
  if x%i == 0 AND y%i == 0 then
    output i
  i ← i + 1
end
  
```

Trace table

► suppose $x = 4, y = 12$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	2	3
3	3	-	4
4	4	4	5

- Operator % finds remainder:
 $a \% b$ gives remainder of a divided by b

Example — What is being computed?

Suppose $0 < x < y$ & both are +ve integers

```

i ← 1
while i ≤ x do
begin
  if x%i == 0 AND y%i == 0 then
    output i
  i ← i + 1
end

```

- ▶ Operator % finds remainder:
a%b gives remainder of a divided by b

Trace table

- ▶ suppose $x = 4, y = 12$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	2	3
3	3	-	4
4	4	4	5

- ▶ suppose $x = 6, y = 15$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	-	3
3	3	3	4
4	4	-	5
5	5	-	6
6	6	-	7

Example — What is being computed? common factors

Trace table

► suppose $x = 4, y = 12$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	2	3
3	3	-	4
4	4	4	5

► suppose $x = 6, y = 15$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	-	3
3	3	3	4
4	4	-	5
5	5	-	6
6	6	-	7

Suppose $0 < x < y$ & both are +ve integers

```

i ← 1
while i ≤ x do
begin
  if x%i == 0 AND y%i == 0 then
    output i
  i ← i + 1
end

```

i ≤ y

- Operator % finds remainder:
 $a \% b$ gives remainder of a divided by b

Example — What is being computed? common factors

Trace table

- suppose $x = 4, y = 12$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	2	3
3	3	-	4
4	4	4	5

- suppose $x = 6, y = 15$

iteration	i before	output	i after
	1	-	1
1	1	1	2
2	2	-	3
3	3	3	4
4	4	-	5
5	5	-	6
6	6	-	7

Suppose $0 < x < y$ & both are +ve integers

```

i ← 1
while i ≤ x do
begin
  if x%i == 0 AND y%i == 0 then
    output i
  i ← i + 1
end
  
```

- Operator % finds remainder:
 $a \% b$ gives remainder of a divided by b

What happen if we change to "else i ← i+1"?

Example 2 — What is being computed?

HCF
GCD

highest common factors
greatest common divisors

Suppose $0 < x < y$ & both are +ve integers

```

i ← x
found ← false
while i ≥ 1 AND found ≠ true do
  begin
    if x%i == 0 AND y%i == 0 then
      found ← true
    else
      i ← i - 1
  end
output i
  
```

- ▶ found is a **flag** variable
- ▶ What value is output?
- ▶ Questions:
 - ▶ What value of **found** makes the loop stop?
 - ▶ When does **found** change to such value?

Example 2 — What is being computed? HCF/GCD

Suppose $0 < x < y$ & both are +ve integers

```
i ← x
found ← false
while i ≥ 1 AND found ≠ true do
  begin
    if x%i == 0 AND y%i == 0 then
      found ← true
    else
      i ← i - 1
  end
output i
```

- ▶ found is a **flag** variable
- ▶ What value is output?
- ▶ Questions:
 - ▶ What value of **found** makes the loop stop?
 - ▶ When does **found** change to such value?

Example 2 — What is being computed? HCF/GCD

Suppose $0 < x < y$ & both are +ve integers

```

i ← x
found ← false
while i ≥ 1 AND found ≠ true do
  begin
    if x%i == 0 AND y%i == 0 then
      found ← true
    else
    i ← i - 1
  end
  output i

```

Handwritten notes: "OK" with an arrow pointing to the loop condition, and a blue circle around "output i".

► found is a **flag** variable

► What value is output?

► Questions:

- What value of **found** makes the loop stop?
- When does **found** change to such value?
- What happens if we change the relational operator of the if-then-else from AND to OR? **only x will be**

removing else => HCF-1 will be output

output

Example 3

Consider the following algorithm.

```
// Assume  $x < y$  are two integers  
 $r \leftarrow y$   
 $q \leftarrow 0$   
while  $r \geq x$  do  
begin  
     $r \leftarrow r - x$   
     $q \leftarrow q + 1$   
end  
output  $r$  and  $q$ 
```

What is computed?

Trace table

Example 3

Consider the following algorithm.

```
// Assume  $x < y$  are two integers
 $r \leftarrow y$ 
 $q \leftarrow 0$ 
while  $r \geq x$  do
begin
     $r \leftarrow r - x$ 
     $q \leftarrow q + 1$ 
end
output  $r$  and  $q$ 
```

What is computed?

Trace table

► Suppose $x=4, y=14$

(@ end of) iteration	r	q
	14	0
1	10	1
2	6	2
3	2	3

Example 3

Consider the following algorithm.

```
// Assume  $x < y$  are two integers
 $r \leftarrow y$ 
 $q \leftarrow 0$ 
while  $r \geq x$  do
begin
     $r \leftarrow r - x$ 
     $q \leftarrow q + 1$ 
end
output  $r$  and  $q$ 
```

What is computed?

Trace table

► Suppose $x=4, y=14$

(@ end of) iteration	r	q
	14	0
1	10	1
2	6	2
3	2	3

► Suppose $x=5, y=14$

(@ end of) iteration	r	q
	14	0
1	9	1
2	4	2

Example 3

Consider the following algorithm.

```
// Assume  $x < y$  are two integers
 $r \leftarrow y$ 
 $q \leftarrow 0$ 
while  $r \geq x$  do
begin
     $r \leftarrow r - x$ 
     $q \leftarrow q + 1$ 
end
output  $r$  and  $q$ 
```

What is computed?

Trace table

- Suppose $x=4, y=14$

(@ end of) iteration	r	q
	14	0
1	10	1
2	6	2
3	2	3

- Suppose $x=5, y=14$

(@ end of) iteration	r	q
	14	0
1	9	1
2	4	2

- Suppose $x=7, y=14$

(@ end of) iteration	r	q
	14	0
1	7	1
2	0	2

Example 3

Consider the following algorithm.

```
// Assume  $x < y$  are two integers
 $r \leftarrow y$ 
 $q \leftarrow 0$ 
while  $r \geq x$  do
begin
     $r \leftarrow r - x$ 
     $q \leftarrow q + 1$ 
end
output  $r$  and  $q$ 
```

What is computed?

remainder & quotient

Trace table

► Suppose $x=4, y=14$

(@ end of) iteration	r	q
	14	0
1	10	1
2	6	2
3	2	3

► Suppose $x=5, y=14$

(@ end of) iteration	r	q
	14	0
1	9	1
2	4	2

► Suppose $x=7, y=14$

(@ end of) iteration	r	q
	14	0
1	7	1
2	0	2

Summary

Summary: Understanding and tracing pseudo code

Next: Developing pseudo code

For note taking

