
Efficient Renaming in Conflict-Free Replicated Data Types (CRDTs)

Case Study of a Sequence CRDT: LogootSplit

Matthieu Nicolas (matthieu.nicolas@inria.fr), Gérald Oster, Olivier Perrin


CRDTs [1]

- Replicated data structure
- Updates performed without coordination
- Strong Eventual Consistency [1]




Limits

- Attach an identifier to each element
- Size of identifiers not bounded
- Overhead of the data structure increasing over time



Reassign shorter identifiers in a fully distributed manner



Rename operation

- Reassign shorter identifiers to whole current state
- Can be performed without coordination

Rewriting rules

- Can not apply concurrent insert or delete as such
- Define rewriting rules to handle concurrent updates

Concurrent *rename* operations

- Proposed *rename* operation not commutative
- Define a total order on *rename* operations
- Pick a "winner" operation between concurrent renames
- Add rewriting rules to *undo* effects of "losing" ones

Propose a fully distributed renaming mechanism for LogootSplit [2]



- Designed the rename operation
- Defined rewriting rules to deal with concurrent updates



- Implementing in MUTE (https://coedit.re/)
- Designing the strategy to trigger the renaming



- Prove formally the correctness of the renaming mechanism
- Benchmark its performances (Memory, CPU, Bandwidth, ...)

[1] M. Shapiro, N. M. Preguiça, C. Baquero, and M. Zawirski. *Conflict-free replicated data types.*In *Proceedings of the 13th International Symposium on Stabilization, Safety, and Security of Distributed Systems*, SSS 2011.

[2] L. André, S. Martin, G. Oster, and C.-L. Ignat. Supporting adaptable granularity of changes for massive-scale collaborative editing. In International Conference on Collaborative Computing: Networking, Applications and Worksharing - CollaborateCom 2013.







