

Efficient renaming in Conflict-free Replicated Data Types (CRDTs)

Matthieu Nicolas


COAST team

Supervised by Gérald Oster and Olivier Perrin

November 29, 2018




Conflict-free Replicated Data Types (CRDTs) [3]




- Replicated data structure

Conflict-free Replicated Data Types (CRDTs) [3]




- Replicated data structure
- Updates performed without coordination

Conflict-free Replicated Data Types (CRDTs) [3]




- Replicated data structure
- Updates performed without coordination

Conflict-free Replicated Data Types (CRDTs) [3]



- Replicated data structure
- Updates performed without coordination

Conflict-free Replicated Data Types (CRDTs) [3]



- Replicated data structure
- Updates performed without coordination
- Strong Eventual Consistency [3]

Identifier-based CRDTs

Main idea

- Attach an identifier to each inserted element

Allow to achieve commutative updates

- By identifying uniquely elements
- By ordering them relatively to each other

- State of the art of *Sequence CRDTs*
- Relies on *identifiers* to ensure convergence, noted here as letters and words
- Elements are ordered by their identifier

- State of the art of *Sequence CRDTs*
- Relies on *identifiers* to ensure convergence, noted here as letters and words
- Elements are ordered by their identifier



Figure 1: The state of a sequence which contains the elements "helo" and their corresponding identifiers

LogootSplit [1]

- State of the art of *Sequence CRDTs*
- Relies on *identifiers* to ensure convergence, noted here as letters and words
- Elements are ordered by their identifier



Figure 1: The state of a sequence which contains the elements "helo" and their corresponding identifiers



Figure 2: The state of a sequence which contains the block "helo"

Example




Figure 3: Example of concurrent *insert* operations

Example




Figure 3: Example of concurrent *insert* operations

Example




Figure 3: Example of concurrent *insert* operations

Example




Figure 3: Example of concurrent *insert* operations

Example




Figure 3: Example of concurrent *insert* operations

Declining performances

- Operations performed may lead to an inefficient internal representation




Figure 4: Example of inefficient internal representation

- The more blocks we have:
 - The more metadata we store
 - The longer it takes to browse the sequence to *insert* or *delete* an element

How to reduce the footprint of the metadata ?

Renaming mechanism

- Introduce a *rename* operation




Figure 5: Example of renaming

Renaming mechanism

- Introduce a *rename* operation



Figure 5: Example of renaming

- Generates a new identifier to the first element, based on its previous identifier

Renaming mechanism

- Introduce a *rename* operation



Figure 5: Example of renaming

- Generates a new identifier to the first element, based on its previous identifier
- Then generates contiguous identifiers for all following elements

Renaming mechanism

- Introduce a *rename* operation



Figure 5: Example of renaming

- Generates a new identifier to the first element, based on its previous identifier
- Then generates contiguous identifiers for all following elements

Renaming mechanism

- Introduce a *rename* operation




Figure 5: Example of renaming

- Generates a new identifier to the first element, based on its previous identifier
- Then generates contiguous identifiers for all following elements

Renaming mechanism

- Introduce a *rename* operation




Figure 5: Example of renaming

- Generates a new identifier to the first element, based on its previous identifier
- Then generates contiguous identifiers for all following elements
- Each *rename* marks the beginning of a new *epoch*

Handling concurrent operations

- Others can perform updates concurrently to a *rename* operation




Figure 6: Example of inconsistency

Handling concurrent operations

- Others can perform updates concurrently to a *rename* operation




Figure 6: Example of inconsistency

Handling concurrent operations

- Others can perform updates concurrently to a *rename* operation




Figure 6: Example of inconsistency

- Apply them as such could lead to inconsistencies

Rewriting concurrent operations

- Define rewriting rules to transform identifiers from one *epoch* to another
- Upon reception of concurrent operations, rewrite identifiers before applying them




Figure 7: Example of rewriting

Rewriting concurrent operations

- Define rewriting rules to transform identifiers from one *epoch* to another
- Upon reception of concurrent operations, rewrite identifiers before applying them




Figure 7: Example of rewriting

Handling concurrent rename

- Define a total order between *rename* operations
- Pick a "winner" operation between concurrent *renames*
- Define additional rewriting rules to *undo* the effect of "losing" ones

- Propose a fully distributed renaming mechanism for *LogootSplit*
- Allows to reinitialize the footprint of the CRDT without coordination
- Implemented in MUTE [2], our P2P collaborative text editor

Provide a formal proof

- Need to ensure the correctness of our algorithm

Benchmark the mechanism

- Measure its impact on the performances
- Compare different strategies

Generalize the approach to other CRDTs

Thanks for your attention, any questions?



- [1] L. André, S. Martin, G. Oster, and C.-L. Ignat.

Supporting adaptable granularity of changes for massive-scale collaborative editing.

In International Conference on Collaborative Computing: Networking, Applications and Worksharing - CollaborateCom 2013, pages 50–59, Austin, TX, USA, Oct. 2013. IEEE Computer Society.

- [2] M. Nicolas, V. Elvinger, G. Oster, C.-L. Ignat, and F. Charoy.

MUTE: A Peer-to-Peer Web-based Real-time Collaborative Editor.

In ECSCW 2017 - 15th European Conference on Computer-Supported Cooperative Work, volume 1 of *Proceedings of 15th European Conference on Computer-Supported Cooperative Work - Panels, Posters and Demos*, pages 1–4, Sheffield, United Kingdom, Aug. 2017. EUSSET.

- [3] M. Shapiro, N. M. Preguiça, C. Baquero, and M. Zawirski.
Conflict-free replicated data types.
In *Proceedings of the 13th International Symposium on Stabilization, Safety, and Security of Distributed Systems, SSS 2011*, pages 386–400, 2011.