

CRASH CAPTURE GUIDE

LogDump

Capture a crash dump of a C•CURE 9000 service and collect the logs that explain it — from one file, with no installer.

Audience: Integrators, customers and L3 engineers · Platform: Windows Server · Version 1.0

What this tool does

When a C•CURE 9000 service crashes, the evidence needed to explain it exists only in the instant it fails. LogDump waits for that instant and captures it.

It does two jobs, and you can use either on its own:

- **Watch and capture.** Point it at a process or service. It installs a Windows Scheduled Task that waits — through reboots, for as long as it takes — and captures a full memory dump the moment the target crashes, hangs, or crosses a CPU or memory threshold.
- **Collect.** Gather C•CURE application, web, installer and event logs into one timestamped bundle you can send to support.

It is a single executable. Nothing is installed, no runtime is required, and nothing about C•CURE is modified.

Which half do you need? If a service is crashing and nobody knows why, you need **Part 1**. If support has asked you for logs, you only need **Part 2** — skip ahead, it takes about a minute.

Before you start

You need	Detail
LogDump.exe	Supplied by your Johnson Controls engineer. A single file.
procdump64.exe	Microsoft Sysinternals ProcDump, from learn.microsoft.com/sysinternals/downloads/procdump . Not included — dump capture cannot work without it. Not needed for log collection.
Administrator	On the server itself. LogDump requests elevation automatically.
Disk space	A full dump is roughly the size of the target's memory use — commonly 400 MB to 1 GB for a C•CURE service. Allow several GB.

Match ProcDump to the target, or you get nothing

Procdump ships as `procdump.exe` (32-bit) and `procdump64.exe` (64-bit), and the two are not interchangeable. A 32-bit ProcDump **cannot capture a 64-bit process at all** — it produces no dump and no obvious error, and you discover this only after the crash you were waiting for.

LogDump works out which one is correct and tells you. Step 3 is where you confirm it. Copy in **both** ProcDump binaries if you have them; copy `procdump64.exe` at minimum.

Part 1 — Capture a crash dump

1. Put both files in one folder

On the server, create a folder such as `C:\LogDump` and copy in:

```
C:\LogDump\  
  LogDump.exe  
  procdump64.exe
```

Give it its own folder. LogDump writes its settings (`config.json`), its status file (`health.json`) and its log next to itself. Do not run it from a network share, from removable media, or from inside `C:\Program Files`.

2. Run it as Administrator

Double-click `LogDump.exe`. Windows shows a User Account Control prompt — that is expected; choose **Yes**. It opens on the **ProcDump** page.

The ProcDump page on first run. Everything needed to arm a capture is here: target at the top, triggers in the middle, live status above the buttons.

3. Choose the target, then check the line underneath

The Target row. **Refresh** re-reads the machine if the service started after you opened LogDump.

Open **Process or service** and pick the service that is crashing. Running processes appear as **Proc:** and Windows services as **Svc:** . For the main C•CURE server that is:

```
Proc: SoftwareHouse.CrossFire.Server.exe
```

If the target is not running right now, tick **Include stopped services** to see stopped ones. LogDump can arm a capture for something that is not running yet — it waits for the process to start.

Now read the small line directly beneath the dropdown. **This is the most important line in the application.** It must name the 64-bit binary:

```
64-bit process -> procdump64.exe (via PE header)
```


Stop if that line says anything else

If it reads `No ProcDump binary found`, ProcDump is not in the folder — go back to step 1. If it reads `could not determine target bitness`, or names `procdump.exe` for a target you expect to be 64-bit, do not continue: send your Johnson Controls engineer a photo of the window. Continuing produces an empty or unusable dump.

Why this check exists. Most C•CURE services are .NET assemblies built as *AnyCPU*. Their file header reports 32-bit while Windows actually runs them 64-bit, so the obvious check gives the wrong answer. LogDump reads the CLR header to resolve it properly. On a reference C•CURE server, eight of ten Software House processes share an identical 32-bit file header and split evenly between 32- and 64-bit at runtime — which is exactly why this is worth ten seconds of your attention.

4. Choose what counts as a failure

Open **Preset** and pick how the target is failing.



The screenshot shows the LogDump configuration window. The 'Preset' dropdown menu is open, displaying the following options: 'Crash capture' (selected), 'Crash capture', 'Hang capture', 'Crash + hang capture', 'High CPU spike capture', 'Memory threshold capture', 'Low impact full dump', and 'Custom'. The other fields in the window are 'Dump type:', 'CPU% / Low% / Dur / Max:', and 'ProcDump path:'.

Presets are one-click shortcuts. Picking one resets every trigger and applies that combination.

Preset	Captures when	Use it when
Crash capture	Unhandled exception, or the process exits	The service disappears
Hang capture	The window stops responding	It freezes but stays running
Crash + hang capture	Any of the above	You are not sure which — the usual choice
High CPU spike capture	CPU over 90% for 10s	It pins a core
Memory threshold capture	Memory commit over 2048 MB	You suspect a leak
Low impact full dump	Immediately, once	You want a snapshot right now

Leave **Dump type** on **Full**. Anything smaller usually cannot be analysed.

The preset list is not the limit. Presets are shortcuts, not the only path. Tick any combination of **-e**, **-h**, **-t**, the CPU fields and **MB (-m)** directly and the dropdown moves to **Custom**, keeping everything you ticked. Use the dropdown to snap back to a preset.

5. Say where dumps go

Set **Dump directory** to a folder on a drive with room — for example `D:\CCURE-Dumps`. Avoid `C:\Windows`, the desktop, and anything inside a user profile. Filling the system drive on a C•CURE server causes its own outage.

Leave **ProcDump path** blank if `procdump64.exe` sits beside `LogDump.exe`; it is found automatically.

6. Arm it

Click **Create Task**, then **Run Now**. The **Monitor status** rows above the buttons should change to show the scheduled task installed and the monitor running. That panel refreshes itself every few seconds and reads the real state of the machine — trust it over anything in this guide.

That is it. You can close the window.

The capture keeps running without it and starts again by itself if the server reboots. Leave C•CURE alone and carry on as normal until the fault happens again.

Part 2 — Collect the evidence and send it

7. Get the dump

Reopen LogDump and click **Open Dumps** at the bottom. Look for a `.dmp` file stamped around the time of the failure.

If nothing is there, click **View Logs** — that is LogDump's own log, and it is the first thing support will ask for.

8. Collect the log bundle

In the sidebar under **LOG COLLECTOR**, click **Data Collection**. The ticked defaults are the right starting point; add the C•CURE log components relevant to the fault. Click **Start collection**, then **Open last output** when it finishes.

Save path (blank = Desktop):

Extra collections

☒ System information
☒ Installed applications (all)

☒ Installed updates (if any)
☒ InstallHistory.xml

☒ Event logs (Application + System)
☐ Full export (default: last 7 days)

☐ Bulk updates (if any)
☒ SWHSystem settings

☒ LogDump logs, dumps & task state

Log components (install-dir based)

☐ CCure Portal logs
☐ CCure Web logs

☐ CrossFire Logging (System Trace)
☐ Security Intelligence Datacache logs

☐ VictorWeb Logs
☐ VictorWebServices auth logs

☐ VictorWebServices Website Logs

Status: Idle

Data Collection. The upper group gathers system state; the lower group gathers C•CURE component logs from the install directory. Collection runs on a background thread, so the window stays responsive.

Output is a timestamped run folder — `<base>\YYYY-MM-DD\Run_HHMMSS\` — containing the collected trees, a transcript and a `Collection_Summary.txt`, plus a zip you can send.

The other two collector pages are narrower: **Install Logs** gathers installer artifacts and `InstallHistory.xml`; **System Health** takes a point-in-time snapshot of the machine.

9. Send them, then stand the capture down

Send your engineer the `.dmp` file and the collection zip. Dumps are large — expect to use a file transfer link rather than email.

Afterwards


Open LogDump, click **Stop**, then **Remove Task** to take the scheduled task off the server. Then delete any leftover `.dmp` files. A crash dump contains a copy of everything that was in the process's memory at the moment it failed, which can include credentials and cardholder data. Treat dumps as sensitive and do not leave copies on the server.

Reference

If something looks wrong

What you see	What it means
No ProcDump binary found	<code>procdump64.exe</code> is not beside <code>LogDump.exe</code> . Copy it in and reopen LogDump.
could not determine target bitness	The target could not be resolved — commonly a service hosted inside <code>svchost</code> . Do not continue; contact your engineer.
Line names <code>procdump.exe</code> unexpectedly	The wrong target is selected, or it genuinely is 32-bit. Confirm against Task Manager → Details → Platform.
Status panel stays empty	LogDump is not elevated. Close it and reopen as Administrator.
Crash happened, no <code>.dmp</code>	Click View Logs and send the log to your engineer.

The buttons along the bottom



The action row. It appears only on the ProcDump page — switching to a collector page hides it.

Button	What it does
Create Task	Saves settings and installs the Scheduled Task. The main action.
Run Now	Starts the monitor immediately instead of waiting for a reboot.
Stop	Stops the monitor, leaving the task installed.
Remove Task	Removes the Scheduled Task from the server.
Save Config	Writes <code>config.json</code> without touching Task Scheduler.
Open Dumps	Opens the dump folder in Explorer.
View Logs	Opens LogDump's own log.
Copy Args	Copies the full ProcDump command line to the clipboard.
Task Scheduler	Launches <code>taskschd.msc</code> .

Command line

Every action in the interface has a command-line equivalent, for integrators scripting a deployment. Verbs also accept a leading `--`.

```
LogDump.exe                                launch the interface
LogDump.exe collect                        collect all log workflows to the Desktop
LogDump.exe collect --out D:\Case12345 --workflows data,health
LogDump.exe install --config <path>        install the Scheduled Task
LogDump.exe start | stop | status | uninstall
LogDump.exe monitor --config <path>        the loop the Scheduled Task runs
```

`--config` defaults to `config.json` beside the executable. Exit codes: `0` success, `1` failure, `2` bad arguments.

What it touches

What	
Writes	Its own folder (<code>config.json</code> , <code>health.json</code> , <code>Logs\</code>), the dump folder you choose, and the collection output folder you choose.
Creates	One Windows Scheduled Task, running as SYSTEM, started at boot. Removed by Remove Task .
Reads	The target's file header, service configuration, Windows event logs, and C•CURE log directories.
Does not	Modify C•CURE, change how any service runs, or send anything anywhere unless you configure email or webhook notifications yourself.

Capturing a dump briefly suspends the target while the file is written — typically under a second for a clone-based capture.