Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

SP Signal Processing

Nils Heine

Real-Time Automatic Gain Control for Singing Voice Applications

University of Hamburg
Department of Informatics

March 20, 2018

Outline

1. Motivation
2. Algorithm
3. Optimization
4. Results
5. Future Implementations

Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

SP
Signal Processing

Motivation

Motivation

Motivation

- compressor to fast

Motivation

- compressor to fast
- factor in human perception

Motivation



- compressor to fast
- factor in human perception
- save time

Dummy UI


RMS Window
60 ms
Expand Time
1500 ms
Compress Time
150 ms
Lookahead
100 ms
Loudness Goal
-23 dB
Gain Range
6.0 dB
MLS Gate
-33.0 dB
Alpha
1000 α
Current Gain
0.0 dB
Write
AutoVocalCtrl

Algorithm

Algorithm

Algorithm: Filter



[1]

[1] **Figure from DAFX: Digital Audio Effects by Udo Zoelzer.**

Algorithm: Filter



- lowcut (38 Hz), highshelf (1681 Hz)[2]

[2] **from Recommendation ITU-R BS.1770-4**.

Algorithm: RMS

Root Mean Square (RMS):

```
void AutoVocalCtrlAudioProcessor::updateRMS(int channel)
{
    rms[channel] = (1. - rmsCo) * rms[channel] +
                   rmsCo * (filterSample[channel] * filterSample[channel]);
}
```

[3]

Time Constants:

```
float AutoVocalCtrlAudioProcessor::getTimeConstant(float ms)
{
    if (ms > 0.f)
        return 1.f - exp(-2.2*(1./currentSampleRate)/(ms/1000.));
    else
        return 1.f;
}
```

[2]

[3] **Based on Book: Digital Audio Signal Processing by Udo Zoelzer.**

Algorithm: Gate

Algorithm: Gain

```
void AutoVocalCtrlAudioProcessor::updateGain(int channel)
{
    const double g = *loudnessGoal - mls[channel];
    const double co = g < gain[channel] ? compressTCo:expandTCo;
    gain[channel] = clipRange.clipValue((1 - co) * gain[channel] + co * g);
    updateAutomation();
    ...
}
```

Algorithm: Gain: Loudness Goal Adaption

```
void AutoVocalCtrlAudioProcessor::updateGain(int channel)
{
    ...
    alphaGain[channel] = (1 - alphaCo) * alphaGain[channel] + alphaCo * gain[channel];
    if (channel == getTotalNumInputChannels() - 1)
    {
        ...
        updateLoudnessGoal();
    }
}
```

Algorithm: Gain: Write Automation



Algorithm: Lookahead

per ringbuffer



Optimization

Optimization

```
...
res = optmze.brute(compareGainCurve, bnds, full_output=True, finish=optmze.fmin)
...
res = optmze.minimize(compareGainCurve, x0, bounds=bnds, options={'disp': True, 'eps': 0.5})
...
x1 = np.array([-28.22, 5.65, 110.14, 2044.41, -33.94, 0.])
...
```

Optimization: Results



Results

Audio Examples

- Original:
- Gain Control:

Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

SP
Signal Processing

Future Implementations

Future Implementations

- side chain backtrack
- offline loudness goal calculation
- set parameters ➜ simplify UI
- improve writing of automation
- idle time?
- wet / dry?

Outline

1. Motivation
2. Algorithm
3. Optimization
4. Results
5. Future Implementations