

About AWS, Why AWS

AWS Management Console Introduction

Launching First EC2 Instance (Virtual Machine) (Elastic Compute Cloud)

How to take remote of that Instance using various methods?

Benefits of Cloud Computing

Linux Operating System (Amazon Linux similar to RHEL)

4 Sessions to complete Linux OS

Virtualization

Virtual Machine

Containerization

Container Vs Virtual Machine

AWS Journey

AWS Global Infrastructure (Regions, AZs, Edge Locations, Local & Wavelength Zone)

AWS List of Services


for Introduction

Launching First EC2 Instance (Virtual Machine) (Elastic Compute Cloud)

Launching First Virtual Machine in AWS

Methods to Connect EC2 Instance


1 Core = 2 vCPU



EC2 (In Free Tier A/C)

750 Hrs/mo Free of cost using **t2.micro** instance
EBS Volume Size <= 30GB

If the Key is lost



Why AWS?

more than 200 fully featured services

total major or minor services > 1500

AWS is agile.

AWS Global Cloud Infrastructure

Region (geolocation) = 27 Live Regions

> 86 Availability zones => group of data centers

> 400 Edge locations

Direct connect


AWS Free Tier Account

Performance


Deployment Speed


Security

Virtualization



Virtualization





Type of Hypervisors

Type 1 Hypervisor

Directly install on Hardware layer


We use Type 1 hypervisors in Data Center

Examples: VMWare ESXi, Citrix XEN, AWS Nitro Hypervisor


Type-2 Hypervisors

Type2 Hypervisor installed on OS

Examples: Virtual Box, VMWare Workstation etc.





Data Center




Data Center Features

- Load Balancing
- DRS: Distributed Resource Scheduling
- High Resiliency
- High Availability
- Fault Tolerance

Containerization



Container shares underlying OSs and has applications with all dependencies to run it independently




AWS Global Cloud Infrastructure

Region & Availability Zones

Region is an independent and separate geographic location.

Within a Region we have at least 2 or 3 isolated locations called Availability Zones



17 Local Zones
28 Wavelength Zones
for ultralow latency applications


245 Countries and Territories Served

115 Direct Connect Locations

Local Zone

Local Zones are creating near to large populations, or IT & Industrial Hub.

Region: N.Virginia



Wavelength Zone


AWS Wavelength is an infrastructure offering optimized for mobile edge computing applications.

This is basically meant for 5G mobile technology.

Direct Connect

It provides connectivity between physical data center with AWS Cloud

Hybrid Cloud



AWS Direct Connect makes it easy to establish a dedicated network connection from your **premises to AWS**. Using AWS Direct Connect, you can establish private connectivity between **AWS and your datacenter**, office, or colocation environment.

AWS EC2 (Elastic Compute Cloud)

EC2 is a compute service

You can Create and Manage Virtual Machines (EC2 Instances)

AMI (Amazon Machine Image)

Instance Types

EBS Volume (Elastic Block Store)

Security Group

EIP (Elastic IP)

Key Pairs

Snapshot

Bootstrapping

Bastion Host

IAM & AWS CLI

Identity and Access Management

Users

Roles

Policies

AWS CLI

EC2 (Elastic Compute Cloud)

AMI (Amazon Machine Image)

Template of OS, Image of OS


It contains OS + Configuration of OS + Applications + User Data

Quick Start

My AMI

AWS Marketplace

LAB



Instance Type

configuration of Instance: contains vCPUs, RAM, Network Interface Capabilities, & EBS Volume throughput etc.

Number of Families within the Instance Type

- 1 **General Purpose** provides a balance of compute, memory and networking resources. m5n.8xlarge
- 2 **Compute Optimized**
- 3 **Memory Optimized**
- 4 **Storage Optimized**
- 5 **Accelerated Computing**

Instance Plans: (Scheme)

On Demand (you will pay for every hour)

Reserved Instance: (for either 1 entire year or 3 year time)

you will get good discount, it could be approx 30-40%


**Spot Instances: created on free resources of AWS Data Centers
getting upto 80% discount**

Amazon EBS Volume Types

	SSD					HDD		Previous Generation
	General Purpose SSD		Provisioned IOPS SSD			Throughput Optimized HDD	Cold HDD	Magnetic
Volume type	gp3	gp2	io2 Block Express ‡	io2	io1	st1	sc1	standard
Durability	99.8% - 99.9% durability (0.1% - 0.2% annual failure rate)	99.8% - 99.9% durability (0.1% - 0.2% annual failure rate)	99.999% durability (0.001% annual failure rate)		99.8% - 99.9% durability (0.1% - 0.2% annual failure rate)	99.8% - 99.9% durability (0.1% - 0.2% annual failure rate)	99.8% - 99.9% durability (0.1% - 0.2% annual failure rate)	
Use cases	Low-latency interactive apps Development and test environments		Workloads that require sub-millisecond latency, and sustained IOPS performance or more than 64,000 IOPS or 1,000 MiB/s of throughput	Workloads that require sustained IOPS performance or more than 16,000 IOPS I/O-intensive database workloads		Big Data Data Warehouse Log Processing	Throughput-oriented storage for data that is infrequently accessed Scenarios where the lowest storage cost is important	Workloads where data is infrequently accessed
Volume size	1 GiB - 16 TiB		4 GiB - 64 TiB	4 GiB - 16 TiB		125 GiB - 16 TiB	125 GiB - 16 TiB	1 GiB-1 TiB
Max IOPS per volume (16 KiB I/O)	3 IOPS/GiB 16,000		2,56,000	up to 50 IOPS/GiB 64,000 †		500	250	40-200
Max throughput per volume	1,000 MiB/s	250 MiB/s	4,000 MiB/s	1,000 MiB/s †		500 MiB/s	250 MiB/s	40-90 MiB/s
Amazon EBS Multi-attach	Not supported		Not supported	Supported		Not supported	Not supported	Not supported
Boot volume	Supported					Not supported	Not supported	Supported

Provisioned IOPs

IOPs= Input/Output Operations/sec (these are number of thread to read/write data with any volume)



General Purpose

SSD Volume

Capacity of Volume (1 GB to 16 TB)

Example: 100 GB = $3 \times 100 = 300$ IOPs
1500 GB = $3 \times 1500 = 4500$ IOPs

min no. of IOPs = 100
max. no. of IOPs = 16000

Multi-Attach EBS Volume

condition to attach volume with multiple instances

Volume Type: io1/io2


All instances & the volume should be in the same Availability Zone

Use only Nitro Based Instance

A1, C5, C5a, C5ad, C5d, C5n, C6a, C6g, C6gd, C6gn, C6i, C6id, D3, D3en, DL1, G4, G4ad, G5, G5g, Hpc6a, I3en, I4i, Im4gn, Inf1, Is4gen, M5, M5a, M5ad, M5d, M5dn, M5n, M5zn, M6a, M6g, M6gd, M6i, M6id, p3dn.24xlarge, P4, R5, R5a, R5ad, R5b, R5d, R5dn, R5n, R6g, R6gd, R6i, R6id, T3, T3a, T4g, u-3tb1.56xlarge, u-6tb1.112xlarge, u-9tb1.112xlarge, u-12tb1.112xlarge, VT1, X2gd, X2id n, X2iedn, X2iezn, and z1d

LAB

Availability Zone



Conditions and Requirements to configure multi attach volumes.

LAB

How to create an additional volume to connect with EC2 Instance

How to connect it with instance?

How to configure the volume for the instance?

- Attach the volume
- Create a partition in the volume
- Provide File System
- Mount the partition

Elastic IP Address (EIP)

EIP is a Fixed or static public IPv4 address

Chargeable but in AWS Free Tier A/c One EIP is Free

Max 5 EIPs can be allocated to your AWS Account Region

EIPs are needed for DNS (Domain Name System) reverse entry or EIP is required for NAT(Network address translation) Gateway


EIPs are also needed for Global Accelerators

if you need fixed or non changeable IP address in that case EIP will be used.

By default VMs (instances) will have dynamic public IP address

To provide public Static IP (EIP) is a two step process.

1. Allocate an EIP to your AWS Account
2. Associate the EIP with your EC2 Instance or Global Accelerator or NAT G/W



Procedure/steps to disassociate the EIP from the Instance

1. Disassociate the EIP from the Instance
2. Release the EIP from your AWS Account.

Security Group (External F/W for Instance)

Snapshot (method to take backup of EBS)

Configuration/concept of Bastion Host/Jump Server

Bootstrapping (method to configure VM at launch time using a script)

EFS (NAS)

Que: What is the need of EIP? When it is required?

Calculate EBS Volume Price:

type : io2
size : 1000 GB
IoPs : 5000

\$ 450/mo
\$ 471/mo

Security Group: External Firewall to be attached with EC2 Instance

Its a bunch of firewall rules

You would write rules in Security Group to allow or restrict traffic

You can connect multiple security groups with one instance.

Max 5 security groups can be connected with one instance

Max 2500 security groups can be created per region/VPC

You find rules written in Security Group are **permissive** in nature, it means you cannot create rules that deny access. Security Group are **stateful in nature**. In stateful, when you send a request from your instance, acknowledgement traffic for that request is allowed.

Security Group Sections

Inbound: to filter incoming traffic

Max 60 rules can be written in Inbound

It does filter the traffic on the basis of **Protocol, Port Number** and **IP address/NID**


By default, in inbound, **all traffic is denied**, therefore you will write rules to allow traffic

Outbound: to filter outgoing traffic

Max 60 rules can be written in Outbound

It does filter the traffic on the basis of Protocol, Port Number and IP address/NID

By Default, in outbound, **all traffic is allowed**



EC2 Key Pair:


Public Key Cryptography

Public Key

It is used to encrypt the information, and it belongs to AWS

Private Key

It is used to decrypt the encrypted information, and we download it.



You can also use third party tools to create and use your own key pairs

AWS generated key used **2048** bit and **SSH-2 RSA** Algorithm


AWS account can have upto 5000 keys pairs per region

finds keys both in .pem or .ppk format

.pem is used for OpenSSH tools

.ppk is used to puTTY

Important: you can also launch an Instance without a key pair



Snapshot


Snapshot is a backup and recovery method for EBS volume

The snapshot is a **point in time** backup of an EBS Volume


EBS Snapshots are incremental and cost effective solution

if multiple backups are taken of a volume, they are incremental

EBS Volume




Snapshots are stored in **S3 storage space**




Region-A

Snapshot is a Region Specific




Region-B

Copy



Note:


Snapshots can be shared privately or publicly



Bootstrapping: It is a method to configure EC2 Instance at launch time using either Shell Script (Linux) or Power shell script for Windows


Let's configure Apache Server using Bootstrapp

```
#!/bin/bash
sudo su -
yum install httpd -y
systemctl start httpd
systemctl enable httpd
cd /var/www/html
echo "This is my First Bootstrap Server" > index.html
```



Bastion Host / Jump Server

Windows Instance supports both RDP & SSH protocol



IAM (Identity and Access Management)

Users
Groups
Roles
Permissions

IAM can be controlled through:

AWS Management Console
AWS Command Line Interface (CLI)
AWS SDKs

Some Technical Concepts:

Principals

Three Principals

IAM Root Users

IAM User

Roles or Temporary Security Tokens

Users

Programmatic Access User (AWS CLI, AWS SDKs, or with other development Tools)

In this you will have **access key** and **secret access key** for the user

AWS Management Console User

You will use user interface for login, need username and password

Team (IT)

User: John

Production

Training

EC2 Read Only Access


VM

S3 Read Only Access

Service

Cloudwatch Full Access

Configuration



AWS CLI (Command Line Interface)

How to install AWS CLI in your host machine (laptop)?

Launching Instance using cli:

```
aws ec2 run-instances --image-id ami-xxxxxxx --count 1 --instance-type t2.micro --  
key-name MyKeyPair --security-group-ids sg-903004f8 --subnet-id subnet-6e7f829e
```

```
aws ec2 run-instances --image-id ami-0de5988cb74e68c72 --count 1 --instance-type  
t2.micro --key-name BarclaysKey --security-group-ids sg-0191124cc71ae8a6a --subnet-  
id subnet-0cd2381d2ad7a0321
```

Permissions: (Policies) >850

JSON to write policies

Visual Editor Tool


Scenario: need to create a user with very limited access over EC2 Service, and for that you need to write a policy in Visual Editor

how to login as a root account in AWS CLI?


Root credentials:

IAM Role:

it is an identity to provide access to one AWS Service to access another AWS Service




Create a Role EC2 Service with S3 access Permission



Understanding AWS S3 (Simple Storage Service)

Sanjay Sharma




S3

1. Creating Bucket
 2. Uploading Files (Objects)
 3. Sharing Objects
 4. Access Objects over the Internet
 5. Deleting S3 Bucket
- Storage Class
Web Site Hosting

In S3 5GB Space is Free of Cost in Free Tier

Static Web Site Hosting

Pre-Requisite: Template of static Website



Versioning

To maintain multiple variants on an object is called versioning


Versioning is disabled by default on buckets

Once you enable it, can't be disabled, it can only be suspended.

if the object is deleted accidentally, can be restored because of versioning

Storage Class

Use case of data



In One zone, data is stored in single AZ
while in Standard-IA data is stored in multiple AZs


S3 Pricing

Standard Storage Class (Default)	\$0.023 per GB/mo
S3 Intelligent Tiering	\$0.023 per GB
S3 Standard - IA (Infrequent Access)	\$0.0125 per GB
S3 One Zone - IA	\$0.01 per GB
Glacier Instant Retrieval	\$0.004 per GB
S3 Glacier Flexible Retrieval	\$0.0036 per GB

Life Cycle Management

Transition Action (From one storage class to another storage Class)


Expiration Action (or need to delete objects after a certain period of time)



Replication

Same Region Replication

Cross Region Replication



Pre-Requisites for the replication

Buckets must be in different Regions

Enable Versioning on both buckets

CloudFormation

Stack

Elastic Beanstalk

it's good example of PaaS

It is used to deploy application in AWS

Lambda

AWS Lambda Functions


Lambda is a serverless service to run code

Where Lambda can be used?


Lambda functions and triggers are the core components of building applications on AWS Lambda. A Lambda function is the code and runtime that process events, while a trigger is the AWS service or application that invokes the function. To illustrate, consider the following scenarios:

1. **File processing** – Suppose you have a photo sharing application. People use your application to upload photos, and the application stores these user photos in an Amazon S3 bucket. Then, your application creates a thumbnail version of each user's photos and displays them on the user's profile page. In this scenario, you may choose to create a Lambda function that creates a thumbnail automatically. Amazon S3 is one of the supported AWS event sources that can publish object-created events and invoke your Lambda function. Your Lambda function code can read the photo object from the S3 bucket, create a thumbnail version, and then save it in another S3 bucket.
2. **Data and analytics** – Suppose you are building an analytics application and storing raw data in a DynamoDB table. When you write, update, or delete items in a table, DynamoDB streams can publish item update events to a stream associated with the table. In this case, the event data provides the item key, event name (such as insert, update, and delete), and other relevant details. You can write a Lambda function to generate custom metrics by aggregating raw data.
3. **Websites** – Suppose you are creating a website and you want to host the backend logic on Lambda. You can invoke your Lambda function over HTTP using Amazon API Gateway as the HTTP endpoint. Now, your web client can invoke the API, and then API Gateway can route the request to Lambda.
4. **Mobile applications** – Suppose you have a custom mobile application that produces events. You can create a Lambda function to process events published by your custom application. For example, you can configure a Lambda function to process the clicks within your custom mobile application.
5. **Orchestration** (Task Administration)

File Processing:



LAB:



Memory (MB)	Price per 1ms
128	\$0.0000000021
512	\$0.0000000083

Duration:
12017.01
ms

Billed
Duration:
12018 ms

Total Price = 12018 x 0.0000000021 =

I need to run this lambda function
daily on a specific time

Memory
Size: 512
MB

Max
Memory
Used: 95
MB

AWS EventBridge

Lambda Function



Lambda Function

Serverless Service to run code

It runs code in a serverless manner without provisioning any Instance

Serverless service has some characteristics

1. No Server management
2. Flexible Scaling
3. No Idle Capacity
4. High Availability

Serverless Applications have several components and layers:

Compute

API

Storage (we have ephemeral storage (temp storage))


Interprocess Messaging

Orchestration

Let's say if TTL = 40 sec, and program takes 10 sec to complete, 10 sec is execution time.
Lambda will charge for 10 sec, not for 40 sec.

Lambda provide compute resources to run program.

Use of memory(RAM) and CPU Power are proportionate in Lambda



Lambda can also provide TTL (Time to Live), time in which Lambda Function should be completed. **TTL is the max amount of time in which program must be completed.**

Eg: if you allocate some TTL = 40 seconds, it means program must be completed within 40 seconds, otherwise lambda function will die.

AWS Lambda will not charge for the TTL, lambda will charge only to execution time.

Pricing in Lambda depends on two factors:

1. Amount of RAM is consumed to run the Program, not allocated RAM

*eg: if you allocate 512 MB RAM, and program takes only **128 MB** to execute the program, you will pay only for 128 MB RAM, not for 512 MB.*

2. Lambda charges in milliseconds not in seconds

eg: you consume 10 sec to run the program, it means you will pay for 10000 ms

1 second = 1000 milliseconds

Example: for 128 MB RAM and 10000 ms Lambda charges \$0.0000000021

and you consume 10 sec to run the program

= 10000 x 0.0000000021 =

VPC (Virtual Private Gateway)

An Isolated network within a Region.
Every VPC (Network) will have its CIDR Block (Network ID)
IP Addresses
Within VPC we have some components as below:

Internet Gateway

Subnets

RouteTables

NAT Gateways

EIP

NACL (Network Access Control List)

IP Addresses

IPv4

IPv6

Class A,B,C,D and E


We are using Class A,B and C in AWS VPC

Public IPs

Private IPs


We you create a VPC Generally select Ranges from Private IP Address

Class A	10.0.0.0-10.255.255.255
CLASS B	172.16.0.0 - 172.31.255.255
Class C	192.168.0.0- 192.168.255.255



CIDR (Classless Inter Domain Routing)

	ClassFull	
Class-A	10.0.0.0/8	10.0.0.0/20, 10.0.0.0/24
Class-B	172.31.0.0/16	10.0.0.0/16, 172.16.10.0/24




In every region you will find a default VPC with CIDR 172.31.0.0/16


Creating a simple VPC

VPC (NID:CIDR) 10.10.10.0/24

Public Subnets

- Subnet1 10.10.10.0/25
- Subnet2 10.10.10.128/25






Peering connection provides connectivity between two VPCs
 These VPCs can be in same Region same AWS A/C or VPCs
 can be in different accounts.

How to delete Peering connection?

How to delete VPCs?

Assignment



Task:

Assignment

Elastic Beanstalk Work:

<https://docs.aws.amazon.com/elasticbeanstalk/latest/dg/tutorials.html>

Download Application —————> **nodejs.zip**

Deploy it in Elastic Beanstalk, with with load balancing enabled

and also allows Private key enabled on ec2 launched by ElasticBeanstalk

Assignment

<https://aws.amazon.com/lambda/getting-started/>

[Products](#) / [Compute](#) / [AWS Lambda](#)

AWS Lambda Getting Started

AWS Lambda is a serverless compute service that runs your code in response to events and automatically manages the underlying compute resources for you, making it easier to build applications that respond quickly to new information.

No matter whether you are new to AWS Lambda or you already have a use case in mind, choose your own path and follow the curated learning steps to get started on AWS Lambda.

Assignment

<https://serverlessland.com/getting-started/lambda/>

Getting Started with Lambda HTTP

CDK (Cloud Development Kit)

RDS (Relational Database Service): SQL Database

Aurora (Serverless)

DynamoDB: NoSQL Database Server; DynamoDB is Serverless

Elasticache

API

What is CDK?

Cloud Development Kit

Infrastructure as Code

TypeScript, JavaScript, Python, Java, C#/.net and Go

About CDK

Lab/Exercise:

Install and configure the CDK CLI

Create your first CDK Project

Deploy your first infrastructure

Install and configuration of AWS CLI

Some important files

bin/**cdk-demo.ts**: This is the entry point to your CDK application

lib/**cdk-demo-stack.ts**: This is where your main CDK application stack is defined

package.json This is where you define your project dependencies etc

cdk.json: This file tells the toolkit how to run your application

lib/cdk-demo-stack.ts

```
import * as cdk from 'aws-cdk-lib';
import { Construct } from 'constructs';
import * as ec2 from 'aws-cdk-lib/aws-ec2';
// import * as sqs from 'aws-cdk-lib/aws-sqs';

export class CdkDemoStack extends cdk.Stack {
  constructor(scope: Construct, id: string, props?: cdk.StackProps) {
    super(scope, id, props);

    new ec2.Vpc(this, 'mainVPC', {
      maxAzs: 2,
      subnetConfiguration: [
        {
          cidrMask: 24,
          name: 'public-subnet',
          subnetType: ec2.SubnetType.PUBLIC,
        }
      ]
    });

    // The code that defines your stack goes here

    // example resource
    // const queue = new sqs.Queue(this, 'CdkDemoQueue', {
    //   visibilityTimeout: cdk.Duration.seconds(300)
    // });
  }
}
```


Assignment

Creating an AWS Fargate service using the AWS CDK

https://docs.aws.amazon.com/cdk/v2/guide/ecs_example.html

AWS RDS (Relational Database Service)

Amazon Aurora



Oracle, MySQL, Postgresql, MS-SQL,

RDBMS

RDS

Redshift

Datwarehouse

DynamoDB

NoSQL Database

AWS Database Services

RDBMS

NoSQL

In-memory Caching Service

About RDS:

1


Assignment

Create a web server and an Amazon RDS DB instance

https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/TUT_WebAppWithRDS.html

This document helps you install an Apache web server with PHP and create a MySQL database. The web server runs on an Amazon EC2 instance using Amazon Linux, and the MySQL database is a MySQL DB instance. Both the Amazon EC2 instance and the DB instance run in a virtual private cloud (VPC) based on the Amazon VPC service

RDS Read Replica



DynamoDB

Unstructured and semi structured Database

No SQL Database use alternate models for data management such as key-value pairs or document storage

Examples of Unstructured database:

- Weather Data
- Employees Emails
- Surveillance Data IOT
- Stock Market Data
- Gaming Data

DynamoDB is fully Managed, multiregion, mulimaster, durable database with built in security

It can handle 10 trillion requests per day
20 million requests per second

DynamoDB is a Serverless Service

You can store any amount of data in DynamoDB Tables

You can scale up or scale down your **tables throughput** capacity with any downtime.

DynamoDB provides on-demand backup capabilities

Backup of tables is possible

Max retention period is 35 days

it delete expire items from tables automatically .


TTL allows you to define a per-item timestamp.

High Availability and Durability

Tables are replicated in multi-AZs in the Region

Where to use DynamoDB

DynamoDB Table Structure



DynamoDB supports two different kind of Primary Keys

Partition Key

Partition Key and Sort Key (Composite Primary Key)

S.No.
Country

DynamoDB Features:

It allows rapid replication of your data among multiple AZs in a Region.

Read/Write Capacity Mode

1. On-Demand
2. Provisioned (default, free tier eligible)

On-Demand

it is good if you create new tables with unknown workloads.

it is good if you have unpredictable application traffic

it is good if you prefer the ease of paying for only what you use.

Provisioned

it is good if you have predictable traffic

it is good if you run applications whose traffic is consistent and ramps gradually

it is good if you can forecast capacity requirement to control costs.

DynamoDB Read Capacity Unit (RCU)

Eventually Consistent (Fast and cheaper) (1 RCU = 8 KB/sec)

Strongly consistent (little slow but expensive)(1 RCU = 4 KB/sec)

Transactional (ACID: Atomicity, Consistency, isolation and durability)

DynamoDB Write Capacity Unit (WCU) (1 WCU= 1 KB/Sec)

Pricing: it charges for reading, writing and for storing data.

DynamoDB Limits

Quota of 256 tables per AWS Region

Size: no practical limit

AWS DynamoDB

25GB

Free of Cost

Assignment

Amplify, Lambda & DynamoDB

Build a Basic Web Application

<https://aws.amazon.com/getting-started/hands-on/build-web-app-s3-lambda-api-gateway-dynamodb/>

In this tutorial, you will create a simple web application. You will first build a static web app that renders "Hello World." Then you will learn how to add functionality to the web app so the text that displays is based on a custom input you provide.

AWS ElastiCache

Memcached or Redis Protocol-compliant server nodes
nodes, shards and clusters.

Glue/Kinesis/Cloudwatch/ECS/CodePipeline+/APIGateways/

SAM (Serverless Application Model)

Components

AWS SAM Template Specification

AWS SAM CLI


Benefits using SAM

Single-Deployment Configuration

Extensions of AWS CloudFormation

Built in Best Practices


Local Debug and Testing




Introduction with AWS ELB

Elastic Load Balancer

Elastic Load Balancing automatically distributes incoming application traffic across multiple targets, such as Amazon EC2 instances, containers, IP addresses, Lambda functions, and virtual appliances. It can handle the varying load of your application traffic in a single Availability Zone or across multiple Availability Zones.




Types of ELB in AWS


ALB Application Load Balancer 80/443 with http/https it works on Layer 7 Application Layer	NLB Network Load Balancer it does support all logical ports (1-65535), it works on layer 4, Transport Layer	Classic Load Balancer  Previous Generation Load Balancer It does support both Layer 4 and Layer 7	GWLB Gateway Load Balancer Gateway Load Balancer makes it easy to deploy, scale, and manage your third-party virtual appliances. It gives you one gateway for distributing traffic across multiple virtual appliances, while scaling them up, or down, based on demand.
--	---	--	---

Elastic Load Balancer

Type of ELB (Architectural Point of View)




Assignment




Task

Just Open Lightweight Service and create an Instance, verify & delete.

Cross Region Load Balancing



LAB:



Important Facts about ELB:

Traffic Distribution

Continuous Health Check

ELB can be Public or Private

Target Instances must be in diff AZs

Algorithm by default: **Round Robin**

Every ELB can be accessed using its end-point (DNS name of ELB)

But if ELB is used with **Global Accelerator**, GA will/can use EIPs

End Point of ELB and also be mapped with a Domain Name using Route53 to open website using a Domain Name.

ELB can also be integrated with Auto Scaling to manage traffic load at backend.


ELB is highly available and Scalable

ELB will connect with Security Group in order to filter traffic

ELB can also be connected with WAF (**Web Application Firewall**)


Internal ELB uses Private IP address to distribute the load within the VPC

We can set **SSL Certificate** to allow/configure https traffic




Instances
IP addresses >> ENI
Lambda Functions
Application Load Balancer

Auto Scaling



Auto Scaling Group: Its a logical group of EC2 Instances participating in Auto Scaling



Benefits of Auto Scaling

Improved Fault Tolerance

Important: Auto scaling, it either terminates the instance or it launches the instance it never stops or starts the instance.

Improved Availability

Improved Cost Management

Component of Auto Scaling Group

- 1 **Auto Scaling Group:** Min & Max Size and Desired Capacity, and condition to increase or decrease number of instances on the basis of Metrics.
- 2 **Launch Configuration:**

We specify **AMI ID**, Instance Type, Key Pair, Security Group, Block Storage (EBS), User Data (to configure instance)

AMI ID

Target Tracking Scaling Policy

Avg. CPU Utilization


if Avg CPU Utilization $\geq 35\%$, an addition instance will join the group.
and it can go up to max size of auto scaling group.

Avg CPU Utilization of multiple instance

50%	40%
Instance1	Instance2
Avg CPU Utilization = 45%	
50%	Avg CPU Utilization = 50%
Instance1	

$99\%/35\% = 2.8$ Approx
3 More instance will
join the group

Integration of Auto Scaling with ELB



Create ELB

condition to trigger action is CPU Util $\geq 35\%$

Current usage is 95%

Number of instances expected = $95/35$

=Approx 3 More instances

AWS SDK

AWS SNS -- Simple Notification Server

SNS is push based system

and it pushes notifications to Google, FireOS, Windows, Apple and Anroid devices

You can push messages to SMS Text message system, emails, SQS queues.


SNS can trigger Lambda Functions also.

AWS SQS -- Simple Queue Service



it can contain upto 256 KB in any format json, xml etc.

Standard Queues (Default) FIFO Queues



Default Visibility Timeout=30sec

Visibility Timeout can be changed

Max Visibility Timeout can be 12 Hours

But messages can be kept in queues from 1 min to 14 days, and default retention period is 4 days.

Send Messages Between Distributed Applications with Amazon Simple Queue Service (SQS)

<https://aws.amazon.com/getting-started/hands-on/send-messages-distributed-applications/?ref=gsrchandson>

AWS CloudWatch


Resource/Service Monitoring Service

Basic Monitoring

Its Free, Polls data in every 5 min, works with limited metrics, Ingest only 5 GB data

Detailed Monitoring

Chargeable, data poll time to monitor service can be reduced < 5min



AWS CloudWatch measures the performance on the basis of Metrics.

AWS EC2 Metrics

CPUUtilization
DiskReadOps
NetworkIn
NetworkOut
NetworkPacketIn etc.

AWS Billing and Cost Metrics

Estimated Charges
ServiceName
LinkedAccount etc.

AWS EBS Metrics

EBSReadOps
EBSWriteOps
EBSReadBytes
EBSWriteBytes etc.

Benefits of CloudWatch Monitoring

- AWS Resource Monitoring**
- EC2 Instance Monitoring**
- Setting Alarm and Actions**
- Viewing Graphical Representation**
- Viewing Statistics**
- Monitoring and Storing Logs**

Task

Create 2 EC2 Instances, and generate some traffic on these instances by sending packets continuously.

```
c:/> ping <ip_address_Instance> -l 1024 -t
```

Stay for 5 minutes to have some output in CloudWatch and Create CloudWatch DashBoard and create multiple widgets.

Task

Alarms:

Create an alarm for an EC2 instance's CPU Utilization, if CPU Utilization $\geq 70\%$ one time in 5 minutes, in that case the Instance must be stopped automatically.

Task

Using CloudWatch to create a Bill Alarm by enabling estimated charges for AWS Account. Create a Billing Alarm to Monitor Your Estimated AWS Account Charges.

AWS Glue

(Glue is ETL(Extract, Transform and Load) Service), and it is Serverless


AWS Glue is a serverless data integration service that makes it easy for analytics users to discover, prepare, move, and integrate data from multiple sources. You can use it for analytics, machine learning, and application development. It also includes additional productivity and data ops tooling for authoring, running jobs, and implementing business workflows.

With AWS Glue, you can discover and connect to more than 70 diverse data sources and manage your data in a centralized data catalog. You can visually create, run, and monitor extract, transform, and load (ETL) pipelines to load data into your data lakes. Also, you can immediately search and query cataloged data using Amazon Athena, Amazon EMR, and Amazon Redshift Spectrum.

AWS Glue consolidates major data integration capabilities into a single service. These include data discovery, modern ETL, cleansing, transforming, and centralized cataloging. It's also serverless, which means there's no infrastructure to manage. With flexible support for all workloads like ETL, ELT, and streaming in one service, AWS Glue supports users across various workloads and types of users.

Also, AWS Glue makes it easy to integrate data across your architecture. It integrates with AWS analytics services and Amazon S3 data lakes. AWS Glue has integration interfaces and job-authoring tools that are easy to use for all users, from developers to business users, with tailored solutions for varied technical skill sets.

With the ability to scale on demand, AWS Glue helps you focus on high-value activities that maximize the value of your data. It scales for any data size, and supports all data types and schema variances. To increase agility and optimize costs, AWS Glue provides built-in high availability and pay-as-you-go billing.



Glue Data Catalog

Each AWS account has one AWS Glue Data Catalog per AWS Region. Each Data Catalog is a highly scalable collection of tables organized into databases. A table is metadata representation of a collection of structured or semi-structured data stored in sources such as Amazon RDS, Apache Hadoop Distributed File System, Amazon OpenSearch Service, and others. The AWS Glue Data Catalog provides a uniform repository where disparate systems can store and find metadata to keep track of data in data silos. You can then use the metadata to query and transform that data in a consistent manner across a wide variety of applications.

Glue Crawler


An AWS Glue crawler connects to a data store, progresses through a prioritized list of classifiers to extract the schema of your data and other statistics, and then populates the Glue Data Catalog with this metadata. Crawlers can run periodically to detect the availability of new data as well as changes to existing data, including table definition changes. Crawlers automatically add new tables, new partitions to existing table, and new versions of table definitions. You can customize Glue crawlers to classify your own file types.

2

Assignment: Submit

Steps to work in Glue

- 1 Create IAM Role for Glue with `AWSGlueServiceRole` & `S3FullAccess` Permission
- 2 Create Directory Structure ins S3




- 3 Glue: Configure DataBase information

Table Information

Manage Glue Studio to declare Jobs

ECS (Elastic Container Service)



3

Assignment: Submit

Creating a container image for use on Amazon ECS

<https://docs.aws.amazon.com/AmazonECS/latest/userguide/create-container-image.html>

CI/CD Pipeline CodePipeline

Continuous Delivery and Continuous Integration

Code Pipeline does:

- It establishes a consistent release process

- Use to automate application release process

- It speeds up delivery while improving quality

- You can view Pipeline history, progress at a glance, and can use your favorite tools.

Security and Encryption

- how to secure infrastructure or applications

- Security Group, NACL, VPN

- WAF Service, Guard Duty,

- Firewall Manager, Inspector, Shield

- GWLB with third party appliances such as IDS/IPS

- Encryption : KMS (Key Management Service)

