Commercial Products Master Prices

30XV
140 - 500
50 & 60 Hz

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE
SHIPPING POINT: CHARLOTTE, NC
NEAREST PORT OF EMBARKATION: SAVANNAH, GA

TYPE OF SALE: 1604 140-500 (NA & Export)

F.O.B. SHIPPING POINT
FREIGHT PREPAID

30X Two Piece Shipment, CONDENSER COIL CORROSION PROTECTION OPTION **CHILLERS**

, Condenser and Evaporator Option tables are currently filled in by hand.

And Hydronic Kit Option
And Refrigerant

09FC Startup Warranties must be added to table by hand



These air-cooled packaged chiller units are fully piped and charged with HFC-134a refrigerant. Weatherproof construction, lightweight distribution and small footprint make them ideal for rooftop or ground level installation. Upward discharge airflow minimizes directional sound and carries heat away from surrounding areas (Notes 1, 2, 3, 4 & 5).

FEATURES AND ACCESSORIES

Refrigeration Circuit	30XV 140 – 500
Full R-134a Refrigerant Charge (not orderable from the factory)	FIOP
Full R-513A Refrigerant Charge	Std
Full Load Factory Run Test and Run Test Report	Std
Independent Refrigeration Circuits	Std
Variable Speed Rotary Screw Compressors	Std
Compressor Protection (Note 6)	Std
~3600 Step Electronic Expansion Valve (EXV – Note 7)	Std
Two-Pass Flooded Shell-and-Tube Evaporator with Heater (Note 8)	Std
Two-Pass Flooded Shell-and-Tube Evaporator for Brine Operation with heater	FIOP
One-Pass Flooded Shell-and-Tube Evaporator	FIOP
Three-Pass Flooded Shell-and-Tube Evaporator with Heater	FIOP
Three-Pass Flooded Shell-and-Tube Evaporator for Brine Operation with heater	FIOP
One-Pass Flooded Shell-and-Tube Process Brine Evaporator	FIOP
Remote Two-Pass Flooded Shell-and-Tube Evaporator with Heater	FIOP & Accy
Remote Evaporator Assembly Kit	Accy
Evaporator Insulation (Note 9)	Std
Filter Drier	Std
Moisture Indicating Sight Glass	Std
AeroAcoustic Condenser Fans	Std
AeroAcoustic High-Static Condenser Fans	FIOP
Low-Sound Kit	FIOP
Sound Optimization	FIOP
Micro Channel Condenser Coil	Std
Condenser Coil Options	
E-Coated Micro Channel	FIOP
Al/Cu Fins	FIOP
E-Coated Al/Cu Condenser Coils	FIOP
Isolation Valve Option	FIOP
Suction Line Insulation	FIOP
Liquid Service Valve per Circuit (& Discharge Service Valve on Flooded Evaporator Models)	Std

PC 903 FORM NO. 30XV-24PPG
SUPERSEDES
PRICE SECTION 30XA

Chilled Water Circuit	30XV 140 – 500
300 psig (2068 kPa) Fluid Side Rated (150 psig for units with optional hydronic system)	Std
Electronic Flow Switch (thermal dispersion – Note 10)	Std
Freeze Protection (Note 11) – Evaporator Heaters (Note 12)	Std
Hydronic Kit – sizes 140-325 (available only for certain sizes, voltages and tiers)	FIOP

Controls / Communication	30XV 140-500
Microprocessor 7-inch TOUCHPILOT (touch screen) Display	Std
Control Box Hinged Access Panels	Std
Temperature & Pressure Display	Std
Energy Management Module (EMM) + GFI	FIOP / Accy
Chilled Water Temperature Reset (from return fluid – Note 13)	Std
Chilled Water Temperature Reset Sensor (via 4-20 mA signal; EMM required)	FIOP / Accy
Demand Limit, 1-step (via switch, field supplied)	Std
Demand Limit (via 4-20 mA signal, 2 additional steps; EMM required)	FIOP / Accy
Load Shedding Capability (BMS required, via CCN(std) or BACnet Communication)	Std
Low Water Temp Protection	Std
High Pressure Protection	Std
Low Pressure Protection	Std
Compressor Lead/Lag Control (cycles & run-time – Note 14)	Std
Unit Mounted Control Panel	Std
Variable Speed Condenser Fans (for Std-Tier units - Note 15)	FIOP
High-Static Variable Speed Condenser Fans	FIOP
Electronically Commutated Motor (ECM) for the condenser Fans	FIOP
Anti-Cycling Protection	Std
CCN Communication	Std
BACnet Translator (MS/TP)	FIOP
LONworks Translator	FIOP / Accy
External Pump Control Capability (no variable speed pump capability)	Std
Dual Chiller Accessory Kit	Accy
Display Heater for Control Panel	Accy
Datacenter Option	FIOP

Electrical	30XV 140 – 500
Single Point Primary Power Entry	Std
Dual Point Primary Power Entry	FIOP
Control Transformer (line power voltage to 115VAC)	FIOP
Unit Mounted Main Disconnect, Non-fused	FIOP
115V GFI Convenience Outlet (included on EMM option)	FIOP/Accy
Compressor Soft Start with VFD	Std
Permanent Magnet (PM) Compressor Motor	FIOP
SCCR – 10kA	Std
High SCCR (25kA – 575V / 65kA – all other voltages)	FIOP

Packaging / Security	30XV140 – 500
Coil Face Shipping Protection	Std
Condenser Coil Trim Panels	FIOP / Accy
Security Grilles	FIOP / Accy
Security Grilles (Sides) & Hail Guard (End)	FIOP
Full Hail Guard	FIOP / Accy
Skid and Bag	FIOP
Two-Piece Shipment (for Certain Sizes)	FIOP

Std — Standard Feature
FIOP — Factory-Installed Option
Accy — Field-Installed Accessory
N/A — Not Available

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

MODEL NUMBER NOMENCLATURE

Position	1-4	5	6-8	9	10	11	12	13	14	15	16	17
Description	**30XV**	**-**	**200**	**6**	**S**	**L**	**-**	**0**	**-**	**-**	**C**	**L**

Air-Cooled AquaForce Chiller

Design Series

Nominal Capacity

140	250	400	50A
160	275	40A	
180	300	450	
200	325	45A	
225	350	500	

Voltage Options

1 = 575-3-60
2 = 380-3-60
5 = 208/230-3-60
6 = 460-3-60
9 = 400-3-50
G = 400-3-60
H = 380-3-50
J = 415-3-50
K = 440-3-50

Product Tiers & Evaporator Configuration

S = Standard
M = Medium
H = High

Condenser Options

Evaporator & Hydronic Kit Options

Low Ambient & Sound Options

Valve & Insulation Options

Electrical Options

Controls Options

Packaging Options

MODEL NUMBER NOMENCLATURE DEFINITION

Two-Piece Shipment (Position 8)

0 = Single Piece Shipment
5 = Single Piece Shipment
A = Two Piece Shipment

Product Tier Configuration (Position 10)

S = Standard Tier
M = Mid Tier
H = High Tier

Condenser and PM Motor Options (Position 11)

- = Al Fin / Cu Tube, R-134a
0 = Cu Fin / Cu Tube, R-134a
2 = Al Fin / Cu Tube, E-Coat, R-134a
3 = Cu Fin / Cu Tube, E-Coat, R-134a
4 = Micro Channel, R-134a
5 = Micro Channel, E-Coat, R-134a
6 = Al Fin / Cu Tube, PM Compressor Motor, R-134a
7 = Cu Fin / Cu Tube, PM Compressor Motor, R-134a
9 = Al Fin / Cu Tube, E-Coat, PM Compressor Motor, R-134a
B = Cu Fin / Cu Tube, E-Coat, PM Compressor Motor, R-134a
C = Micro Channel, PM Compressor Motor, R-134a
D = Micro Channel, E-Coat, PM Compressor Motor, R-134a
F = Al Fin / Cu Tube, R-513A Refrigerant
G = Cu Fin / Cu Tube, R-513A Refrigerant
J = Al Fin / Cu Tube, E-Coat, R-513A Refrigerant
K = Cu Fin / Cu Tube, E-Coat, R-513A Refrigerant
L = Micro Channel , R-513A Refrigerant
M = Micro Channel, E-Coat, R-513A Refrigerant
N = Al Fin / Cu Tube, PM Compressor Motor, R-513A Refrigerant
P = Cu Fin / Cu Tube, PM Compressor Motor, R-513A Refrigerant
T = Al Fin / Cu Tube, E-Coat, PM Compressor Motor, R-513A Refrigerant
V = Cu Fin / Cu Tube, E-Coat, PM Compressor Motor, R-513A Refrigerant
W = Micro Channel, PM Compressor Motor, R-513A Refrigerant
X = Micro Channel, E-Coat, PM Compressor Motor, R-513A Refrigerant

Evaporator and Hydronic Kit Options (Position 12)

- = Flooded Evaporator, 2 pass, w/o Heater, no pump
0 = Flooded Evaporator, 2 pass, w/ Heater, no pump
1 = Flooded Evaporator, 1 pass, w/ Heater, no pump
2 = Flooded Evaporator, 2 pass for Brine Application, w/ Heater, no pump
3 = Flooded Evaporator, 1 pass for Process Brine Application, w/ Heater, no pump
B = Flooded Evaporator, 3 pass, w/ Heater, no pump
C = Flooded Evaporator, 3 pass for Brine Application, w/ Heater, no pump
R = Remote Evaporator, 2 pass (requires to be processed via ETO) , no pump

Condenser Fans and Sound Options (Position 13)

- = Fixed Speed Condenser Fans (Std Tier) / Variable Speed Fans (Mid and High-Tier), Std Sound
0 = Variable Speed Condenser Fans (Std Tier only), Std Sound
1 = Fixed Speed Condenser Fans (Std Tier) / Variable Speed Fans (Mid and High-Tier), Low Sound Kit
2 = Variable Speed Condenser Fans (Std Tier only), Low Sound Kit
3 = Fixed Speed Condenser Fans (Std Tier) / Variable Speed Fans (Mid and High-Tier), Std Sound, Sound Optimization
4 = Variable Speed Condenser Fans (Std Tier only), Std Sound, Sound Optimization
5 = Fixed Speed Condenser Fans (Std Tier) / Variable Speed Fans (Mid and High-Tier), Low Sound Kit, Sound Optimization
6 = Variable Speed Condenser Fans (Std Tier only), Low Sound Kit, sound Optimization
7 = Variable Speed High Static Fans, Std Sound
8 = Variable Speed High Static Fans, Low Sound Kit
C = ECM Fans, Std Sound
D = ECM Fans, Low Sound Kit
F = ECM Fans, Std Sound, Sound Optimization
G = ECM Fans, Low Sound Kit, Sound Optimization

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

Valve and Insulation Options (Position 14)

- = No suction service valve, Actuated discharge valves (Flooded evaporator), No suction line insulation, R-134a or R-513A Refrigerant
0 = Suction service valve, Actuated discharge valves (Flooded evaporator), No suction line insulation, R-134a or R-513A Refrigerant
1 = No suction service valve, Manual discharge valves (Flooded evaporator, Middle East only), No suction line insulation, R-134a or R-513A Refrigerant
2 = Suction service valve, Manual discharge valves (Flooded evaporator, Middle East only), No suction line insulation, R-134a or R-513A Refrigerant
5 = No suction service valve, Actuated discharge valves (Flooded evaporator), Suction line insulation, R-134a or R-513A Refrigerant
6 = Suction service valve, Actuated discharge valves (Flooded evaporator), Suction line insulation, R-134a or R-513A Refrigerant
7 = No suction service valve, Manual discharge valves (Flooded evaporator, Middle East only), Suction line insulation, R-134a or R-513A Refrigerant
8 = Suction service valve, Manual discharge valves (Flooded evaporator, Middle East only), Suction line insulation, R-134a or R-513A Refrigerant
9 = No suction service valve, Actuated discharge valves (Brine evaporator), No suction line insulation, R-134a Refrigerant
B = Suction service valve, Actuated discharge valves (Brine evaporator), No suction line insulation, R-134a Refrigerant
C = No suction service valve, Manual discharge valves (Brine evaporator, Middle East only), No suction line insulation R-134a Refrigerant
D = Suction service valve, Manual discharge valves (Brine evaporator, Middle East only), No suction line insulation R-134a Refrigerant
F = No suction service valve, Actuated discharge valves (Brine evaporator), Suction line insulation, R-134a Refrigerant
G = Suction service valve, Actuated discharge valves (Brine evaporator), Suction line insulation, R-134a Refrigerant
H = No suction service valve, Manual discharge valves (Brine evaporator, Middle East only), Suction line insulation R-134a Refrigerant
J = Suction service valve, Manual discharge valves (Brine evaporator, Middle East only), Suction line insulation, R-134a Refrigerant
K = No suction service valve, Actuated discharge valves (Brine evaporator), No suction line insulation, R-513A Refrigerant
L = Suction service valve, Actuated discharge valves (Brine evaporator), No suction line insulation, R-513A Refrigerant
M = No suction service valve, Manual discharge valves (Brine evaporator, Middle East only), No suction line insulation R-513A Refrigerant
N = Suction service valve, Manual discharge valves (Brine evaporator, Middle East only), No suction line insulation R-513A Refrigerant
P = No suction service valve, Actuated discharge valves (Brine evaporator), Suction line insulation, R-513A Refrigerant
Q = Suction service valve, Actuated discharge valves (Brine evaporator), Suction line insulation, R-513A Refrigerant
R = No suction service valve, Manual discharge valves (Brine evaporator, Middle East only), Suction line insulation R-513A Refrigerant
S = Suction service valve, Manual discharge valves (Brine evaporator, Middle East only), Suction line insulation, R-513A Refrigerant
T = No suction service valve, Actuated discharge valves (Process Brine Evaporator), Suction line insulation, R-134a Refrigerant
V = Suction service valve, Actuated discharge valves (Process Brine Evaporator), Suction line insulation, R-134a Refrigerant
W = No suction service valve, Actuated discharge valves (Process Brine Evaporator), Suction line insulation, R-513A Refrigerant
X = Suction service valve, Actuated discharge valves (Process Brine Evaporator), Suction line insulation, R-513A Refrigerant

Electrical Options (Position 15)

- = Single Point Power, No control transformer, Std
0 = Single Point Power w/ disconnect, No control transformer, Std SCCR
1 = Dual Point Power, No control transformer, Std SCCR
2 = Dual Point Power w/ disconnect, No control transformer, Std SCCR
3 = Single Point Power, Control transformer, Std SCCR
4 = Single Point Power w/ disconnect, Control transformer, Std SCCR
5 = Dual Point Power, Control transformer, Std SCCR
6 = Dual Point Power w/ disconnect, Control transformer, Std SCCR
7 = Single Point Power, No control transformer, High SCCR
8 = Single Point Power w/ disconnect, No control transformer, High SCCR
9 = Dual Point Power, No control transformer, High SCCR
B = Dual Point Power w/ disconnect, No control transformer, High SCCR
C = Single Point Power, Control transformer, High SCCR
D = Single Point Power w/ disconnect, Control transformer, High SCCR
F = Dual Point Power, control transformer, High SCCR
G = Dual Point Power w/ disconnect, Control transformer, High SCCR

Control Options (Position 16)

C = 7" touchpilot, Remote Connectivity
D = 7" touchpilot, K, GFI, Remote Connectivity
F = 7" touchpilot, BACnet (MS/TP) Translator, Remote Connectivity
G = 7" touchpilot, EMM, GFI, BACnet (MS/TP) Translator, Remote Connectivity
H = 7" touchpilot, LON Translator, Remote Connectivity
J = 7" touchpilot, EMM, GFI, LON Translator, Remote Connectivity
K = 7" touchpilot, Remote Connectivity, Datacenter
L = 7" touchpilot, EMM, GFI, Remote Connectivity, Datacenter
M = 7" touchpilot, BACnet (MS/TP) Translator, Remote Connectivity, Datacenter
N = 7" touchpilot, EMM, GFI, BACnet (MS/TP) Translator, Remote Connectivity, Datacenter
P = 7" touchpilot, LON Translator, Remote Connectivity, Datacenter
Q = 7" touchpilot, EMM, GFI, LON Translator, Remote Connectivity, Datacenter

Packaging Options (Position 17)

L = Coil Face Shipping Protection (CFSP)
0 = CFSP, Coil Trim Panels
1 = CFSP, Coil Trim Panels, Security Grilles
2 = CFSP, Coil Trim Panels, Security Grilles (Sides), Hail Guards (End)
3 = Full Hail Guard
9 = Coil Trim Panels, Skid + Bag
B = Coil Trim Panels, Security Grilles, Skid + Bag
C = Coil Trim Panels, Security Grilles (Sides), Hail Guards (End), Skid + Bag
D = Full hail Guard, Skid, Bag

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

30XV AIR COOLED LIQUID CHILLING PACKAGES
BASE UNIT WITH NO CRATING

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-1401M4-0--CL	575-3-60*	366,001
30XV-1401H4-0--CL	575-3-60*	396,530
30XV-1402S4----CL	380-3-60*	308,067
30XV-1402M4-0--CL	380-3-60*	339,464
30XV-1402H4-0--CL	380-3-60*	368,897
30XV-1406S4----CL	460-3-60	307,078
30XV-1406M4-0--CL	460-3-60	336,576
30XV-1406H4-0--CL	460-3-60	366,750
30XV-1405S4----CL	208/230-3-60	381,947
30XV-1405M4-0--CL	208/230-3-60	427,637
30XV-1405H4-0--CL	208/230-3-60	458,777
30XV-1409M4----CL	400-3-50*	339,464
30XV-1409H4----CL	400-3-50*	368,897
30XV-140GS4----CL	400-3-60*	308,067
30XV-140GM4----CL	400-3-60*	339,464
30XV-140GH4----CL	400-3-60*	368,897
30XV-140HM4----CL	380-3-50*	339,464
30XV-140HH4----CL	380-3-50*	368,897
30XV-140JM4----CL	415-3-50*	339,464
30XV-140JH4----CL	415-3-50*	368,897
30XV-140KM4----CL	440-3-50*	339,464
30XV-140KH4----CL	440-3-50*	368,897
30XV-1601S4-0--CL	575-3-60*	356,321
30XV-1601M4-0--CL	575-3-60*	385,124
30XV-1601H4-0--CL	575-3-60*	418,783
30XV-1602S4----CL	380-3-60*	317,200
30XV-1602M4-0--CL	380-3-60*	359,219
30XV-1602H4-0--CL	380-3-60*	391,147
30XV-1606S4----CL	460-3-60	316,212
30XV-1606M4-0--CL	460-3-60	356,398
30XV-1606H4-0--CL	460-3-60	389,002
30XV-1605S4----CL	208/230-3-60	391,082
30XV-1605M4-0--CL	208/230-3-60	445,291
30XV-1605H4-0--CL	208/230-3-60	481,029
30XV-1609S4-0--CL	400-3-50*	330,683
30XV-1609M4----CL	400-3-50*	359,219
30XV-1609H4----CL	400-3-50*	391,147
30XV-160GS4----CL	400-3-60*	316,212
30XV-160GH4----CL	400-3-60*	391,147
30XV-160GM4----CL	400-3-60*	359,219
30XV-160HS4-0--CL	380-3-50*	330,683
30XV-160HM4----CL	380-3-50*	359,219
30XV-160HH4----CL	380-3-50*	391,147
30XV-160JS4-0--CL	415-3-50*	330,683
30XV-160JM4----CL	415-3-50*	359,219

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-160JH4----CL	415-3-50*	391,147
30XV-160KS4-0--CL	440-3-50*	330,683
30XV-160KM4-0--CL	440-3-50*	359,219
30XV-160KH4----CL	440-3-50*	391,147
30XV-1801S4----CL	575-3-60*	351,812
30XV-1801M4-0--CL	575-3-60*	399,368
30XV-1801H4-0--CL	575-3-60*	435,300
30XV-1802S4----CL	380-3-60*	325,491
30XV-1802M4-0--CL	380-3-60*	373,464
30XV-1802H4-0--CL	380-3-60*	407,665
30XV-1806S4----CL	460-3-60	324,503
30XV-1806M4-0--CL	460-3-60	370,644
30XV-1806H4-0--CL	460-3-60	405,520
30XV-1805S4----CL	208/230-3-60	399,370
30XV-1805M4-0--CL	208/230-3-60	459,536
30XV-1805H4-0--CL	208/230-3-60	497,546
30XV-1809S4-0--CL	400-3-50*	338,974
30XV-1809M4----CL	400-3-50*	373,464
30XV-1809H4----CL	400-3-50*	407,665
30XV-180GS4----CL	400-3-60*	325,491
30XV-180GM4----CL	400-3-60*	373,464
30XV-180GH4----CL	400-3-60*	407,665
30XV-180HS4-0--CL	380-3-50*	338,974
30XV-180HM4----CL	380-3-50*	373,464
30XV-180HH4----CL	380-3-50*	407,665
30XV-180JS4-0--CL	415-3-50*	338,974
30XV-180JM4----CL	415-3-50*	373,464
30XV-180JH4----CL	415-3-50*	407,665
30XV-180KS4-0--CL	440-3-50*	338,974
30XV-180KM4----CL	440-3-50*	373,464
30XV-180KH4----CL	440-3-50*	407,665
30XV-2001S4-0--CL	575-3-60*	391,158
30XV-2001M4-0--CL	575-3-60*	420,182
30XV-2001H4-0--CL	575-3-60*	454,762
30XV-2002S4----CL	380-3-60*	350,584
30XV-2002M4-0--CL	380-3-60*	393,349
30XV-2002H4-0--CL	380-3-60*	425,103
30XV-2006S4----CL	460-3-60	349,447
30XV-2006M4-0--CL	460-3-60	391,754
30XV-2006H4-0--CL	460-3-60	423,708
30XV-2005S4----CL	208/230-3-60	424,461
30XV-2005M4-0--CL	208/230-3-60	482,348
30XV-2005H4-0--CL	208/230-3-60	520,220
30XV-2009S4-0--CL	400-3-50*	366,133
30XV-2009M4----CL	400-3-50*	393,349
30XV-2009H4----CL	400-3-50*	425,103
30XV-200GS4----CL	400-3-60*	350,584

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-200GM4----CL	400-3-60*	393,349
30XV-200GH4----CL	400-3-60*	425,103
30XV-200HS4-0--CL	380-3-50*	366,133
30XV-200HM4----CL	380-3-50*	393,349
30XV-200HH4----CL	380-3-50*	425,103
30XV-200JS4-0--CL	415-3-50*	366,133
30XV-200JM4----CL	415-3-50*	393,349
30XV-200JH4----CL	415-3-50*	425,103
30XV-200KS4-0--CL	440-3-50*	366,133
30XV-200KM4----CL	440-3-50*	393,349
30XV-200KH4----CL	440-3-50*	425,103
30XV-2251S4-0--CL	575-3-60*	410,411
30XV-2251M4-0--CL	575-3-60*	441,846
30XV-2251H4-0--CL	575-3-60*	467,828
30XV-2252S4----CL	380-3-60*	378,663
30XV-2252M4-0--CL	380-3-60*	423,050
30XV-2252H4-0--CL	380-3-60*	449,576
30XV-2256S4----CL	460-3-60	368,800
30XV-2256M4-0--CL	460-3-60	411,934
30XV-2256H4-0--CL	460-3-60	437,875
30XV-2259S4-0--CL	400-3-50*	392,678
30XV-2259M4----CL	400-3-50*	423,050
30XV-2259H4----CL	400-3-50*	449,576
30XV-225GS4----CL	400-3-60*	378,663
30XV-225GM4----CL	400-3-60*	423,050
30XV-225GH4----CL	400-3-60*	449,576
30XV-225HS4-0--CL	380-3-50*	392,678
30XV-225HM4----CL	380-3-50*	423,050
30XV-225HH4----CL	380-3-50*	449,576
30XV-225JS4-0--CL	415-3-50*	392,678
30XV-225JM4----CL	415-3-50*	423,050
30XV-225JH4----CL	415-3-50*	449,576
30XV-225KS4-0--CL	440-3-50*	392,678
30XV-225KM4----CL	440-3-50*	423,050
30XV-225KH4----CL	440-3-50*	449,576
30XV-2501S4-0--CL	575-3-60*	445,326
30XV-2501M4-0--CL	575-3-60*	473,961
30XV-2501H4-0--CL	575-3-60*	501,274
30XV-2502S4----CL	380-3-60*	413,998
30XV-2502M4-0--CL	380-3-60*	456,691
30XV-2502H4-0--CL	380-3-60*	486,105
30XV-2506S4----CL	460-3-60	398,676
30XV-2506M4-0--CL	460-3-60	440,325
30XV-2506H4-0--CL	460-3-60	467,224
30XV-2509S4-0--CL	400-3-50*	429,259
30XV-2509M4----CL	400-3-50*	456,691
30XV-2509H4----CL	400-3-50*	486,105

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-250GS4----CL	400-3-60*	413,998
30XV-250GM4----CL	400-3-60*	456,691
30XV-250GH4----CL	400-3-60*	486,105
30XV-250HS4-0--CL	380-3-50*	429,259
30XV-250HM4----CL	380-3-50*	456,691
30XV-250HH4----CL	380-3-50*	486,105
30XV-250JS4-0--CL	415-3-50*	429,259
30XV-250JM4----CL	415-3-50*	456,691
30XV-250JH4----CL	415-3-50*	486,105
30XV-250KS4-0--CL	440-3-50*	429,259
30XV-250KM4----CL	440-3-50*	456,691
30XV-250KH4----CL	440-3-50*	486,105
30XV-2751S4-0--CL	575-3-60*	468,571
30XV-2751M4-0--CL	575-3-60*	495,270
30XV-2751H4-0--CL	575-3-60*	520,049
30XV-2752S4----CL	380-3-60*	437,641
30XV-2752M4-0--CL	380-3-60*	478,657
30XV-2752H4-0--CL	380-3-60*	505,746
30XV-2756S4----CL	460-3-60	422,686
30XV-2756M4-0--CL	460-3-60	462,915
30XV-2756H4-0--CL	460-3-60	487,942
30XV-2759S4-0--CL	400-3-50*	452,905
30XV-2759M4----CL	400-3-50*	478,657
30XV-2759H4----CL	400-3-50*	505,746
30XV-275GS4----CL	400-3-60*	437,641
30XV-275GM4----CL	400-3-60*	478,657
30XV-275GH4----CL	400-3-60*	505,746
30XV-275HS4-0--CL	380-3-50*	452,905
30XV-275HM4----CL	380-3-50*	478,657
30XV-275HH4----CL	380-3-50*	505,746
30XV-275JS4-0--CL	415-3-50*	452,905
30XV-275JM4----CL	415-3-50*	478,657
30XV-275JH4----CL	415-3-50*	505,746
30XV-275KS4-0--CL	440-3-50*	452,905
30XV-275KM4----CL	440-3-50*	478,657
30XV-275KH4----CL	440-3-50*	505,746
30XV-3001S4-0--CL	575-3-60*	500,382
30XV-3001M4-0--CL	575-3-60*	528,239
30XV-3001H4-0--CL	575-3-60*	549,728
30XV-3002S4----CL	380-3-60*	468,687
30XV-3002M4-0--CL	380-3-60*	513,934
30XV-3002H4-0--CL	380-3-60*	536,004
30XV-3006S4----CL	460-3-60	452,914
30XV-3006M4-0--CL	460-3-60	496,137
30XV-3006H4-0--CL	460-3-60	517,244
30XV-3009S4-0--CL	400-3-50*	483,773
30XV-3009M4----CL	400-3-50*	513,934

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-3009H4----CL	400-3-50*	536,004
30XV-300GS4----CL	400-3-60*	468,687
30XV-300GM4----CL	400-3-60*	513,934
30XV-300GH4----CL	400-3-60*	536,004
30XV-300HS4-0--CL	380-3-50*	483,773
30XV-300HM4----CL	380-3-50*	513,934
30XV-300HH4----CL	380-3-50*	536,004
30XV-300JS4-0--CL	415-3-50*	483,773
30XV-300JM4----CL	415-3-50*	513,934
30XV-300JH4----CL	415-3-50*	536,004
30XV-300KS4-0--CL	440-3-50*	483,773
30XV-300KM4----CL	440-3-50*	513,934
30XV-300KH4----CL	440-3-50*	536,004
30XV-3251S4-0--CL	575-3-60*	548,547
30XV-3251M4-0--CL	575-3-60*	567,799
30XV-3251H4-0--CL	575-3-60*	590,906
30XV-3252S4----CL	380-3-60*	506,255
30XV-3252M4-0--CL	380-3-60*	553,384
30XV-3252H4-0--CL	380-3-60*	575,928
30XV-3256S4----CL	460-3-60	489,692
30XV-3256M4-0--CL	460-3-60	533,692
30XV-3256H4-0--CL	460-3-60	557,466
30XV-3259S4-0--CL	400-3-50*	533,573
30XV-3259M4----CL	400-3-50*	553,384
30XV-3259H4----CL	400-3-50*	575,928
30XV-325GS4----CL	400-3-60*	506,255
30XV-325GM4----CL	400-3-60*	553,384
30XV-325GH4----CL	400-3-60*	575,928
30XV-325HS4-0--CL	380-3-50*	533,573
30XV-325HM4----CL	380-3-50*	553,384
30XV-325HH4----CL	380-3-50*	575,928
30XV-325JS4-0--CL	415-3-50*	533,573
30XV-325JM4----CL	415-3-50*	553,384
30XV-325JH4----CL	415-3-50*	575,928
30XV-325KS4-0--CL	440-3-50*	533,573
30XV-325KM4----CL	440-3-50*	553,384
30XV-325KH4----CL	440-3-50*	575,928
30XV-3501H4----CL	575-3-60*	683,679
30XV-3501M4----CL	575-3-60*	669,897
30XV-3501S4-0--CL	575-3-60*	626,368
30XV-3502H4----CL	380-3-60*	661,421
30XV-3502M4----CL	380-3-60*	649,487
30XV-3502S4----CL	380-3-60*	581,005
30XV-3506H4----CL	460-3-60	653,878
30XV-3506M4----CL	460-3-60	624,302
30XV-3506S4----CL	460-3-60	559,591
30XV-3509S4-0--CL	400-3-50*	603,236

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-3509M4----CL	400-3-50*	649,487
30XV-3509H4----CL	400-3-50*	661,421
30XV-350GS4----CL	400-3-60*	581,005
30XV-350GM4----CL	400-3-60*	649,487
30XV-350GH4----CL	400-3-60*	661,421
30XV-350HS4-0--CL	380-3-50*	603,236
30XV-350HM4----CL	380-3-50*	649,487
30XV-350HH4----CL	380-3-50*	661,421
30XV-350JS4-0--CL	415-3-50*	603,236
30XV-350JM4----CL	415-3-50*	649,487
30XV-350JH4----CL	415-3-50*	661,421
30XV-350KS4-0--CL	440-3-50*	603,236
30XV-350KM4----CL	440-3-50*	649,487
30XV-350KH4----CL	440-3-50*	661,421
30XV-4001H4----CL	575-3-60*	800,951
30XV-4001M4----CL	575-3-60*	761,789
30XV-4001S4-0--CL	575-3-60*	755,561
30XV-4002H4----CL	380-3-60*	800,542
30XV-4002M4----CL	380-3-60*	729,979
30XV-4002S4----CL	380-3-60*	695,225
30XV-4006H4----CL	460-3-60	727,243
30XV-4006M4----CL	460-3-60	688,081
30XV-4006S4----CL	460-3-60	655,045
30XV-4009S4-0--CL	400-3-50*	724,411
30XV-4009M4----CL	400-3-50*	729,979
30XV-4009H4----CL	400-3-50*	800,542
30XV-400GS4----CL	400-3-60*	695,225
30XV-400GM4----CL	400-3-60*	729,979
30XV-400GH4----CL	400-3-60*	800,542
30XV-400HS4-0--CL	380-3-50*	724,411
30XV-400HM4----CL	380-3-50*	729,979
30XV-400HH4----CL	380-3-50*	800,542
30XV-400JS4-0--CL	415-3-50*	724,411
30XV-400JM4----CL	415-3-50*	729,979
30XV-400JH4----CL	415-3-50*	800,542
30XV-400KS4-0--CL	440-3-50*	724,411
30XV-400KM4----CL	440-3-50*	729,979
30XV-400KH4----CL	440-3-50*	800,542
30XV-4501H4----CL	575-3-60*	870,351
30XV-4501M4----CL	575-3-60*	807,570
30XV-4501S4-0--CL	575-3-60*	787,247
30XV-4502H4----CL	380-3-60*	871,412
30XV-4502M4----CL	380-3-60*	775,576
30XV-4502S4----CL	380-3-60*	723,952
30XV-4506H4----CL	460-3-60	794,451
30XV-4506M4----CL	460-3-60	731,670
30XV-4506S4----CL	460-3-60	681,763

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30XV-4509S4-0--CL	400-3-50*	753,889
30XV-4509M4----CL	400-3-50*	775,576
30XV-4509H4----CL	400-3-50*	871,412
30XV-450GS4----CL	400-3-60*	723,952
30XV-450GM4----CL	400-3-60*	775,576
30XV-450GH4----CL	400-3-60*	871,412
30XV-450HS4-0--CL	380-3-50*	753,889
30XV-450HM4----CL	380-3-50*	775,576
30XV-450HH4----CL	380-3-50*	871,412
30XV-450JS4-0--CL	415-3-50*	753,889
30XV-450JM4----CL	415-3-50*	775,576
30XV-450JH4----CL	415-3-50*	871,412
30XV-450KS4-0--CL	440-3-50*	753,889
30XV-450KM4----CL	440-3-50*	775,576
30XV-450KH4----CL	440-3-50*	871,412
30XV-5001M4----CL	575-3-60*	875,530
30XV-5001S4-0--CL	575-3-60*	854,158
30XV-5002M4----CL	380-3-60*	841,833
30XV-5002S4----CL	380-3-60*	789,817
30XV-5006M4----CL	460-3-60	797,670
30XV-5006S4----CL	460-3-60	746,545
30XV-5009S4-0--CL	400-3-50*	820,492
30XV-5009M4----CL	400-3-50*	841,833
30XV-500GS4----CL	400-3-60*	789,817
30XV-500GM4----CL	400-3-60*	841,833
30XV-500HS4-0--CL	380-3-50*	820,492
30XV-500HM4----CL	380-3-50*	841,833
30XV-500JS4-0--CL	415-3-50*	820,492
30XV-500JM4----CL	415-3-50*	841,833
30XV-500KS4-0--CL	440-3-50*	820,492
30XV-500KM4----CL	440-3-50*	841,833

* 208/230-3-60 & 460-3-60 Configurations are the only ones available from Carrier Mexico

FACTORY-INSTALLED OPTIONS (FIOP)

POSITION 8

TWO-PIECE SHIPMENT

DESCRIPTION	MASTER PRICE	
	400-High 450-Mid 500-Std	**450-High 500-Mid**
Two-Piece shipment: Includes unit being split into 2 pieces and connections (shipped loose) to assemble unit in the field. It does not include labor to put the modules together A	10,947	11,351

* The two-piece shipment is indicated by the letter “A” in position 8 of the model number. Not available for US, Canada and Mexico.

POSITION 11

CONDENSER COIL CORROSION PROTECTION OPTION

DESCRIPTION	MASTER PRICE (Pricing done based on the # of V’s)						
	4V	**5V**	**6V**	**7V**	**8V**	**9V**	**10V**
	Where used	Where used	Where used	Where used	Where used	Where used	Where used
	140-Std* 140-Mid 160-Std 180-Std	140-High 160-Mid 180-Mid 200-Std 225-Std	160-High 180-High 200-Mid 225-Mid 250-Std 275-Std	200-High 225-High 250-Mid 275-Mid 300-Std	250-High 275-High 300-Mid 325-Std 350-Std	300-High 325-Mid 350-Mid 400-Std	325-High 350-High 400-Mid 450-Std
Micro Channel 4,C,L,W	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Micro Channel, E-Coat 5,D,M,X 1F 1N	30XV_COIL_001 20,287	30XV_COIL_007 25,358	30XV_COIL_013 30,431	30XV_COIL_019 35,504	30XV_COIL_025 40,575	30XV_COIL_031 45,647	30XV_COIL_037 50,719
Al Fin/Cu Tube* -,6,F,N 1 1G	30XV_COIL_002 10,727	30XV_COIL_008 13,408	30XV_COIL_014 16,089	30XV_COIL_020 18,768	30XV_COIL_026 21,450	30XV_COIL_032 24,131	30XV_COIL_038 26,813
Cu Fin/Cu Tube* 0,7,G,PC 1A 1H	30XV_COIL_004 24,460	30XV_COIL_010 30,573	30XV_COIL_016 26,288	30XV_COIL_022 42,804	30XV_COIL_028 48,920	30XV_COIL_034 55,034	30XV_COIL_040 61,149
Al Fin/Cu Tube, E-Coat* 2,9,J,T 1C 1K	30XV_COIL_005 34,450	30XV_COIL_011 43,062	30XV_COIL_017 51,676	30XV_COIL_023 60,289	30XV_COIL_029 68,900	30XV_COIL_035 77,513	30XV_COIL_041 86,127
Cu Fin/Cu Tube, E-Coat* 3,B,K,V 1L, 1D	30XV_COIL_006 47,740	30XV_COIL_012 59,675	30XV_COIL_018 71,611	30XV_COIL_024 83,545	30XV_COIL_030 95,481	30XV_COIL_036 107,414	30XV_COIL_042 119,352

*Al/Cu coils not available for 30XV140 Std-tier unit (only exception)

** Cu-Cu and Cu-Cu E-Coat option not available for quote or ordering in any region and only available for the Middle East for SASO documentation purpose only

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

CONDENSER COIL CORROSION PROTECTION OPTION

DESCRIPTION	MASTER PRICE (Pricing done based on the # of V's)	
	11V	**12V**
	Where used	Where used
	400-High 450-Mid 500-Std	450-High 500-Mid
Micro Channel 4,C,L,W	Std.	Std.
Micro Channel, E-Coat 5,D,M,X	30XV_COIL_043 55,792	30XV_COIL_049 60,864
Al Fin/Cu Tube* -,6,F,N	30XV_COIL_044 29,494	30XV_COIL_050 32,178
Cu Fin/Cu Tube* 0,7,G,P	30XV_COIL_046 67,264	30XV_COIL_052 N/A
Al Fin/Cu Tube, E-Coat* 2,9,J,T	30XV_COIL_047 94,738	30XV_COIL_053 103,350
Cu Fin/Cu Tube, E-Coat* 3,B,K,V	30XV_COIL_048 131,288	30XV_COIL_054 N/A

*Al/Cu coils not available for Std-tier units with fixed speed fans

** Cu-Cu and Cu-Cu E-Coat option not available for quote or ordering in any region and only available for the Middle East for SASO documentation purpose only

PERMANENT MAGNET COMPRESSOR MOTOR*

DESCRIPTION	MASTER PRICE				
	Voltage	140-200	225	250-325	350-500
No PM Motor - ,0,2,3,4,5,F,G,J,K,L,M	All	Std.	Std.	Std.	Std.
Permanent Magnet Compressor Motor 6,7,9,B,C,D,N,P,T,V,W,X	380-3-60	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	460-3-60	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	400-3-50	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	400-3-60	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	380-3-50	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	415-3-50	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	440-3-50	30XV_COMPR_001 17,659	30XV_COMPR_002 18,339	30XV_COMPR_003 19,020	30XV_COMPR_004 19,270
	208/230-3-60	-	-	-	-
	575-3-60	-	-	-	-

* Not available with Fixed Speed or High-Static Fans and not available with fixed speed fans

REFRIGERANT

DESCRIPTION	MASTER PRICE					
	140-Std	**140-Mid 140-High 160-Std**	**160-Mid 160-High 180-Std 180-Mid 200-Std**	**180-High 200-Mid 200-High**	**225-Std 225-Mid 225-High 250-Std**	**250-Mid 250-High 275-Std 275-Mid 275-High 300-Std**
R-134a - MCHX and RTPF Coils - ,0,2,3,4,5,6,7,9,B,C,D	Std.	Std.	Std.	Std.	Std.	Std.
R-513A – MCHX Coils L,M,W,X 1M,1N	30XV_COIL_055 1,175	30XV_COIL_056 1,347	30XV_COIL_057 1,544	30XV_COIL_058 1,659	30XV_COIL_059 1,945	30XV_COIL_060 2,174
R-513A – RTPF Coils F,G,J,K,N,P,T,V 1H,1K,1L,1G	30XV_COIL_061 1,768	30XV_COIL_062 2,090	30XV_COIL_063 2,439	30XV_COIL_064 2,699	30XV_COIL_065 2,985	30XV_COIL_066 3,416

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

DESCRIPTION	MASTER PRICE					
	300-Mid 300-High 325-Std 325-Mid 325-High	**350-Std**	**350-Mid 350-High**	**400-Std 400-Mid 400-High 450-Std**	**450-Mid 450-High 500-Std**	**500-Mid**
R-134a - MCHX and RTPF Coils - ,0,2,3,4,5,6,7,9,B,C,D	Std.	Std.	Std.	Std.	Std.	Std.
R-513A – MCHX Coils L,M,W,X	30XV_COIL_067 2,376	30XV_COIL_068 2,548	30XV_COIL_069 2,917	30XV_COIL_070 3,203	30XV_COIL_071 3,432	30XV_COIL_072 4,131
R-513A – RTPF Coils F,G,J,K,N,P,T,V	30XV_COIL_073 3,864	30XV_COIL_074 3,864	30XV_COIL_075 4,404	30XV_COIL_076 4,529	30XV_COIL_077 5,216	30XV_COIL_078 5,502

POSITION 12

EVAPORATOR OPTION

DESCRIPTION	MASTER PRICE					
	140-Std	**140-Mid 140-High 160-Std**	**160-Mid**	**160-High 180-Std**	**180-Mid 180-High**	**200-Std**
Flooded Evaporator, 2 pass, without heater* -	Std.	Std.	Std.	Std.	Std.	Std.
Flooded Evaporator, 2 pass, with heater 0	30XV_COOLER_001 1,456	30XV_COOLER_001 1,456	30XV_COOLER_001 1,456	30XV_COOLER_001 1,456	30XV_COOLER_001 1,456	30XV_COOLER_003 1,834
Flooded Evaporator, with heater, one pass 1	30XV_COOLER_002 5,437	30XV_COOLER_002 5,437	30XV_COOLER_002 5,437	30XV_COOLER_002 5,437	30XV_COOLER_002 5,437	30XV_COOLER_004 5,437
Flooded Evaporator, 2 pass, with heater for Brine Application** 2	30XV_COOLER_007 1,456	30XV_COOLER_007 1,456	30XV_COOLER_007 1,456	30XV_COOLER_007 1,456	30XV_COOLER_007 1,456	30XV_COOLER_008 1,834
Flooded Evaporator, one pass for Process Brine Application 3	-	-	30XV_COOLER_2D_160_M 40,165	-	-	-
Flooded Evaporator, 3 pass, with heater B	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_014 12,270
Flooded Evaporator, 3 pass, with heater for Brine Application** C	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_013 8,548	30XV_COOLER_014 12,270
Remote Evaporator ‡ R	(38,736)	(40,242)	(44,590)	(44,590)	(45,798)	(45,798)

DESCRIPTION	MASTER PRICE					
	200-Mid	**200-High**	**225-Std**	**225-Mid 225-High**	**250-Std**	**250-Mid**
Flooded Evaporator, 2 pass, without heater* -	Std.	Std.	Std.	Std.	Std.	Std.
Flooded Evaporator, 2 pass, with heater 0	30XV_COOLER_003 1,834	30XV_COOLER_003 1,834	30XV_COOLER_003 1,834	30XV_COOLER_003 1,834	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076
Flooded Evaporator, with heater, one pass 1	30XV_COOLER_004 5,437	30XV_COOLER_004 5,437	30XV_COOLER_004 5,437	30XV_COOLER_004 5,437	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437
Flooded Evaporator, 2 pass, with heater for Brine Application** 2	30XV_COOLER_008 1,834	30XV_COOLER_008 1,834	30XV_COOLER_008 1,834	30XV_COOLER_008 1,834	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076
Flooded Evaporator, one pass for Process Brine Application 3	30XV_COOLER_2D_200_M 40,165	-	-	-	-	30XV_COOLER_2D_250_M 51,374

DESCRIPTION	MASTER PRICE					
	200-Mid	**200-High**	**225-Std**	**225-Mid 225-High**	**250-Std**	**250-Mid**
Flooded Evaporator, 3 pass, with heater B	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270
Flooded Evaporator, 3 pass, with heater for Brine Application** C	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270	30XV_COOLER_014 12,270
Remote Evaporator ‡ R	(49,609)	(49,609)	(52,433)	(53,853)	(55,253)	(61,156)

DESCRIPTION	MASTER PRICE					
	250-High	**275-Std**	**275-Mid 275-High 300-Std**	**300-Mid**	**300-High 325-Std**	**325-Mid 325-High**
Flooded Evaporator, 2 pass, without heater* -	Std.	Std.	Std.	Std	Std	Std
Flooded Evaporator, 2 pass, with heater 0	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076	30XV_COOLER_005 2,076
Flooded Evaporator, with heater, one pass 1	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437	30XV_COOLER_006 5,437
Flooded Evaporator, 2 pass, with heater for Brine Application** 2	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076	30XV_COOLER_009 2,076
Flooded Evaporator, one pass for Process Brine Application 3	-	-	-	30XV_COOLER_2D_300_M 51,374	-	-
Flooded Evaporator, 3 pass, with heater B	30XV_COOLER_014 12,270	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247
Flooded Evaporator, 3 pass, with heater for Brine Application** C	30XV_COOLER_014 12,270	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247
Remote Evaporator ‡ R	(61,156)	(61,156)	(62,259)	(64,034)	(64,034)	(66,063)

DESCRIPTION	MASTER PRICE						
	350-Std	**350-Mid 350-High**	**400-Std**	**400-Mid**	**400-High 450-Std**	**450-Mid 450-High 500-Std**	**500-Mid**
Flooded Evaporator, 2 pass, without heater* -	Std	Std	Std.	Std.	Std.	Std.	Std
Flooded Evaporator, 2 pass, with heater 0	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076	30XV_COOLER_010 2,076
Flooded Evaporator, with heater, one pass 1	30XV_COOLER_017 5,437	30XV_COOLER_017 5,437	30XV_COOLER_011 7,596	30XV_COOLER_011 7,596	30XV_COOLER_011 7,596	30XV_COOLER_011 7,596	30XV_COOLER_011 7,596
Flooded Evaporator, 2 pass, with heater for Brine Application** 2	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076	30XV_COOLER_012 2,076
Flooded Evaporator, one pass for Process Brine Application 3	-	-	-	30XV_COOLER_2D_400_M 55,477	-	-	30XV_COOLER_2D_500_M 85,640
Flooded Evaporator, 3 pass, with heater B	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378
Flooded Evaporator, 3 pass, with heater for Brine Application** C	30XV_COOLER_015 15,247	30XV_COOLER_015 15,247	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378	30XV_COOLER_016 16,378
Remote Evaporator ‡ R	(73,196)	(81,729)	(86,512)	(88,492)	(88,492)	(97,697)	(105,941)

*Cannot be offered for North America (US & Canada)

****The Evaporator for Brine Application is intended for comfort cooling, not process applications**

‡ ETO required to validate option. Unit will be shipped from the factory without the Evaporator and no R-134a refrigerant (Nitrogen charge only). Refrigerant will need to be purchased locally and it is not included in the price of the unit and/or option. Additionally, the following accessories are required: Remote Evaporator & Remote Evaporator Installation Kit

POSITION 13

SOUND OPTIONS

DESCRIPTION	MASTER PRICE			
	140-200	225	250-325	350-500
Standard Sound - No compressor sound enclosures -,0,3,4,7,C,F 4	Std.	Std.	Std.	Std.
Low Sound Kit - Includes full compressor sound enclosure and muffler for each compressor 1,2,5,6,8,D,G 4A	30XV_SOUND_002 16,608 30XV_SOUND_003 +	30XV_SOUND_005 19,444 30XV_SOUND_006 +	30XV_SOUND_008 21,792 30XV_SOUND_009 +	30XV_SOUND_011 21,792 30XV_SOUND_012 +

SOUND/CAPACITY OPTIMZATION OPTION*

DESCRIPTION	MASTER PRICE			
	140-200	225	250-325	350-500
Off -,0,1,2,7,8,C,D 15	Std.	Std.	Std.	Std.
Sound/Capacity Optimization - customized programming for lower sound target or specific capacity requirement 3,4,5,6,F,G 15A	30XV_SOUND_001 3,141	30XV_SOUND_004 3,141	30XV_SOUND_007 3,141	30XV_SOUND_010 3,141

***Notes:**

Sound optimization is only available through ECat selections imported through Quote Builder (orders being processed through HVACPartners order or manual entry of model # through Quote Builder will have to process Sound Optimization via ETO).

Sound optimization is not available with high-static fan option.

CONDENSER FANS

DESCRIPTION	MASTER PRICE							
	Voltage	140-Std	160-Std 180-Std	200-Std	225-Std	250-Std 275-Std	300-Std	325-Std
Fixed Speed Condenser Fans (Std) – This configuration does not offer low ambient head pressure control -,1,3,5	All 60Hz Except 575V	Std.	Std.	Std.	Std.	Std.	Std.	Std.
	575-3-60	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	All 50Hz	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variable Speed Condenser Fans * ‡ 0,2,4,6 3A	208/230	n/a	30XV_CONDFAN_001 15,794	30XV_CONDFAN_005 26,049	n/a	n/a	n/a	n/a
	380/400	n/a	30XV_CONDFAN_002 13,483	30XV_CONDFAN_006 15,548	30XV_CONDFAN_009 14,015	30XV_CONDFAN_012 15,263	30XV_CONDFAN_015 15,086	30XV_CONDFAN_018 27,319
	460	n/a	30XV_CONDFAN_003 12,405	30XV_CONDFAN_007 13,488	30XV_CONDFAN_010 13,103	30XV_CONDFAN_013 14,514	30XV_CONDFAN_016 15,086	30XV_CONDFAN_019 25,164
	575	n/a	30XV_CONDFAN_004 Std.	30XV_CONDFAN_008 Std.	Std.	Std.	Std.	Std.
	All 50Hz	Std	Std	Std	Std	Std	Std	Std
Variable Speed High Static Condenser Fans. It also allows External Static Pressure up to 100Pa. * ‡ 7,8 3B	208/230	n/a	30XV_CONDFAN_001 15,794	30XV_CONDFAN_005 26,049	n/a	n/a	n/a	n/a
	380/400	n/a	30XV_CONDFAN_002 13,483	30XV_CONDFAN_006 15,548	30XV_CONDFAN_009 14,015	30XV_CONDFAN_033 15,263	30XV_CONDFAN_015 15,086	30XV_CONDFAN_036 27,319
	460	n/a	30XV_CONDFAN_003 12,405	30XV_CONDFAN_007 13,488	30XV_CONDFAN_010 13,103	30XV_CONDFAN_034 14,514	30XV_CONDFAN_016 15,086	30XV_CONDFAN_037 25,164
	575	n/a	30XV_CONDFAN_004 12,799	30XV_CONDFAN_008 14,273	30XV_CONDFAN_011 13,314	30XV_CONDFAN_035 14,548	30XV_CONDFAN_017 16,132	30XV_CONDFAN_038 25,950
	All 50Hz	NC	NC	NC	NC	NC	NC	NC
Electronically Commuted Motor (ECM) Fans * ‡ C,D,F,G 3C	208/230 575	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	380/400 All 50HZ	n/a	30XV_CONDFAN_039 9,235	30XV_CONDFAN_041 12,234	30XV_CONDFAN_043 13,993	30XV_CONDFAN_045 17,622	30XV_CONDFAN_047 22,393	30XV_CONDFAN_049 22,393
	460	n/a	30XV_CONDFAN_040 10,650	30XV_CONDFAN_042 14,673	30XV_CONDFAN_044 15,371	30XV_CONDFAN_046 18,961	30XV_CONDFAN_048 23,172	30XV_CONDFAN_050 23,172

* (includes providing the function of Low Ambient Head Pressure Control) - This option permits start-up at 0°F (-18°C) and operation of the 30XV units to -20°F (-29°C) outdoor ambient temperature by controlling the speed of the condenser fans. Package includes sensor, control and hardware for operating the fans in each circuit. With pump control or glycol in loop; without pump control or glycol, minimum operating ambient temperature is 0° F

‡ May require installation of field-supplied wind baffles (not included)

CONDENSER FANS (cont)

DESCRIPTION	Voltage	MASTER PRICE 140-Mid	140-High 160-Mid 180-Mid	160-High 180-High 200-Mid	200-High 225-Mid 225-High	250-Mid 250-High 275-Mid 275-High 300-Mid	300-High 325-Mid	325-High
Variable Speed Condenser Fans * ‡ -,2,4,6 3,3A	All 60Hz All 50Hz	Std	Std	Std	Std	Std	Std	Std
Variable Speed High Static Condenser Fans. It also allows External Static Pressure up to 100Pa. * ‡ 7,8 3B	All 60Hz All 50Hz	NC	NC	NC	NC	NC	NC	NC
Electronically Commuted Motor (ECM) Fans * ‡ C,D,F,G 3A	208/230 575	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	380/400 All 50HZ	30XV_CONDFAN_051 9,235	30XV_CONDFAN_053 12,234	30XV_CONDFAN_055 16,298	30XV_CONDFAN_057 21,163	30XV_CONDFAN_059 22,287	30XV_CONDFAN_061 22,287	30XV_CONDFAN_063 25,069
	460	30XV_CONDFAN_052 10,650	30XV_CONDFAN_054 14,673	30XV_CONDFAN_056 17,617	30XV_CONDFAN_058 21,942	30XV_CONDFAN_060 23,172	30XV_CONDFAN_062 24,656	30XV_CONDFAN_064 27,823

* (includes providing the function of Low Ambient Head Pressure Control) - This option permits start-up at 0°F (-18°C) and operation of the 30XV units to -20°F (-29°C) outdoor ambient temperature by controlling the speed of the condenser fans. Package includes sensor, control and hardware for operating the fans in each circuit. With pump control or glycol in loop; without pump control or glycol, minimum operating ambient temperature is 0° F

‡ May require installation of field-supplied wind baffles (not included)

CONDENSER FANS (cont)

DESCRIPTION	MASTER PRICE Voltage	Std Tier 350	400	450	500	Mid & High Tiers All Sizes
Fixed Speed Condenser Fans (Std) – This configuration does not offer low ambient head pressure control -,1,3,5	All 60Hz Except 575V	Std.	Std.	Std.	Std.	n/a
	575-3-60	n/a	n/a	n/a	n/a	n/a
	All 50Hz	n/a	n/a	n/a	n/a	n/a
Variable Speed Condenser Fans * ‡ 0,2,4,6 3A	208/230	n/a	n/a	n/a	n/a	Std
	380-400	30XV_CONDFAN_021 22,232	30XV_CONDFAN_024 29,188	30XV_CONDFAN_027 29,934	30XV_CONDFAN_030 30,674	
	460	30XV_CONDFAN_022 20,664	30XV_CONDFAN_025 26,047	30XV_CONDFAN_028 28,111	30XV_CONDFAN_031 27,865	
	575	Std.	Std.	Std.	Std.	

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

DESCRIPTION	MASTER PRICE					Mid & High Tiers
		Std Tier				
	Voltage	350	400	450	500	All Sizes
	All 50Hz	Std	Std	Std	Std	Std
Variable Speed High Static Condenser Fans. It also allows External Static Pressure up to 100Pa. * ‡ 7,8 3B	208/230	n/a	n/a	n/a	n/a	NC
	380/400	30XV_CONDFAN_021 22,232	30XV_CONDFAN_024 29,188	30XV_CONDFAN_027 29,934	30XV_CONDFAN_030 30,674	
	460	30XV_CONDFAN_022 20,664	30XV_CONDFAN_025 26,047	30XV_CONDFAN_028 28,111	30XV_CONDFAN_031 27,865	
	575	30XV_CONDFAN_023 21,777	30XV_CONDFAN_026 27,225	30XV_CONDFAN_029 28,528	30XV_CONDFAN_032 28,679	
	All 50Hz	NC	NC	NC	NC	NC
Electronically Commuted Motor (ECM) Fans * ‡ C,D,F,G 3C	208/230 575	n/a	n/a	n/a	n/a	
	380/400 All 50HZ	30XV_CONDFAN_065 31,129	30XV_CONDFAN_066 33,359	30XV_CONDFAN_067 36,800	30XV_CONDFAN_068 41,906	
	460	30XV_CONDFAN_069 33,457	30XV_CONDFAN_070 35,446	30XV_CONDFAN_071 40,147	30XV_CONDFAN_072 47,295	

* (includes providing the function of Low Ambient Head Pressure Control) - This option permits start-up at 0°F (-18°C) and operation of the 30XV units to -20°F (-29°C) outdoor ambient temperature by controlling the speed of the condenser fans. Package includes sensor, control and hardware for operating the fans in each circuit. With pump control or glycol in loop; without pump control or glycol, minimum operating ambient temperature is 0° F

‡ May require installation of field-supplied wind baffles (not included)

CONDENSER FANS (cont)

DESCRIPTION	MASTER PRICE				
	Voltage	350-Mid	350-High 400-Mid	400-High 450-Mid	450-High 500-Mid
Variable Speed Condenser Fans * ‡ -,2,4,6	All 60Hz All 50Hz	Std	Std	Std	Std
Variable Speed High Static Condenser Fans. It also allows External Static Pressure up to 100Pa. * ‡ 7,8	All 60Hz All 50Hz	NC	NC	NC	NC
Electronically Commuted Motor (ECM) Fans * ‡ C,D,F,G	208/230 575	n/a	n/a	n/a	n/a
	380/400 All 50HZ	30XV_CONDFAN_073 33,172	30XV_CONDFAN_074 37,754	30XV_CONDFAN_075 41,906	30XV_CONDFAN_076 45,623
	460	30XV_CONDFAN_077 35,551	30XV_CONDFAN_078 41,337	30XV_CONDFAN_079 46,193	30XV_CONDFAN_080 51,669

* (includes providing the function of Low Ambient Head Pressure Control) - This option permits start-up at 0°F (-18°C) and operation of the 30XV units to -20°F (-29°C) outdoor ambient temperature by controlling the speed of the condenser fans. Package includes sensor, control and hardware for operating the fans in each circuit. With pump control or glycol in loop; without pump control or glycol, minimum operating ambient temperature is 0° F

‡ May require installation of field-supplied wind baffles (not included)

FACTORY-INSTALLED OPTIONS (cont)

POSTION 14

ISOLATION VALVE

DESCRIPTION	MASTER PRICE			
	140-200	225	250-325	350-500
No Additional Isolation Valve(s) (Std) -,1,5,7,9,C,F,H,K,M,P,R,T,W	Std.	Std.	Std.	Std.
Isolation Valve(s) - Provides additional refrigerant isolation capability, and specific details are dependent upon which cooler type is selected. Regardless of which cooler option is employed, the selection of the isolation valve option results in chillers which are equipped with a liquid line service valve, a discharge service valve, and a series of valves on or near the cooler, the net effect of which is to provide isolation capability in the condenser area, the cooler area and the compressor area. Please refer to the latest PD document for additional details. 0,2,6,8,B,D,G,J,L,N,Q,S,V,X 5A	30XV_ISOVALV_001 5,867	30XV_ISOVALV_002 6,508	30XV_ISOVALV_003 7,149	30XV_ISOVALV_004 8,438

HIGH AMBIENT VALVE CONFIGURATION OPTION *

DESCRIPTION	MASTER PRICE	
	140-325	350-500
No High Ambient	Std.	Std.
High Ambient Valve Configuration Option (Middle East Only) 1,2,7,8,C,D,H,J,M,N,R,S	30XV_HIAMB_001 (3,962)	30XV_HIAMB_002 (5,945)

* High ambient option includes a Manual Discharge Service Valve instead of motorized discharge service valve and it is available for Middle East region only. Not available with Process Brine Evaporator option.

SUCTION LINE INSULATION OPTION

DESCRIPTION	MASTER PRICE		
	140-200	225-325	350-500
No Suction Line Insulation (Std)	Std.	Std.	Std.
Suction Line Insulation - Insulation is tubular closed-cell insulation. This option is recommended for areas of high dew points where condensation may be a concern. * **5,6,7,8,F,G,H,J,P,R,S,T,V,W,X**	30XV_LINEINS_001 1,009	30XV_LINEINS_002 1,111	30XV_LINEINS_003 7,985

* Suction line insulation is valid for any operating condition. Required with process brine Evaporator.

REFRIGERANT *

DESCRIPTION	MASTER PRICE

R-134a	Std.
R-513A**	NC

* Position 12 must be considered for the proper evaporator type chosen for this position 14
** R-513A option must be chosen under option 11

POSITION 15

ELECTRICAL OPTIONS

POWER CONNECTION OPTION

DESCRIPTION	VOLTAGE	MASTER PRICE					
		140	160	180	200	225	250
Single Point - ,0,3,4,7,8,C,D	460-3-60	Std.	Std.	Std.	Std.	Std.	Std.
	575-3-60	Std.	Std.	Std.	Std.	Std.	Std.
	380-3-60 400-3-50 To 440-3-50	Std.	Std.	Std.	Std.	Std.	Std.
	208/230-3-60	Std.	Std.	Std.	Std.	-	-
Dual Point 1,2,5,6,9,B,F,G	460-3-60	30XV_PWRCON_001 (1,984)	30XV_PWRCON_005 (1,984)	30XV_PWRCON_009 (1,984)	13 (1,984)	17 (2,549)	20 (2,549)
	575-3-60	30XV_PWRCON_002 (1,984)	30XV_PWRCON_006 (1,984)	30XV_PWRCON_010 (1,984)	14 (1,984)	18 (2,549)	21 (2,549)
	380-3-60 400-3-50 To 440-3-50	30XV_PWRCON_003 (2,274)	30XV_PWRCON_007 (2,274)	30XV_PWRCON_011 (2,274)	15 (2,274)	19 (4,925)	22 (4,925)
	208/230-3-60	30XV_PWRCON_004 (6,797)	30XV_PWRCON_008 (6,797)	30XV_PWRCON_012 (6,797)	16 (6,797)	-	-

POWER CONNECTION OPTION (Cont)

DESCRIPTION	VOLTAGE	MASTER PRICE						
		275	300	325	350	400	450	500
Single Point - ,0,3,4,7,8,C,D	460-3-60	Std.	Std.	Std.	Std.	Std.	Std.	Std.
	575-3-60	Std.	Std.	Std.	Std.	Std.	Std.	Std.
	380-3-60 400-3-50 To 440-3-50	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Dual Point * 1,2,5,6,9,B,F,G	460-3-60	23 (2,549)	26 (2,549)	29 (2,549)	32 (773)	35 (773)	38 (773)	41 (773)
	575-3-60	24 (2,549)	27 (2,549)	30 (2,549)	33 (773)	36 (773)	39 (773)	42 (773)
	380-3-60 400-3-50 To 440-3-50	25 (4,925)	28 (4,925)	31 (4,925)	34 1,726	37 1,726	40 1,726	43 1,726

* Dual Point Power option not available for Carrier-Mexico units

CONTROL TRANSFORMER OPTION

DESCRIPTION	Voltage	MASTER PRICE		
		140-160	180-325	350-500
None -,0,1,2,7,8,9,B	575-3-60 To 460-3-60 400-3-60	Std.	Std.	Std.
	400-3-50 380-3-50 To 440-3-50	-	-	-
Control Transformer - Main power source supplies control circuit (line power voltage to 115VAC) 3,4,5,6,C,D,F,G	575-3-60 460-3-60	30XV_CNTLTRAN_001 3,392	30XV_CNTLTRAN_003 4,097	30XV_CNTLTRAN_005 4,097
	380-3-60 To 208/230-3-60 400-3-50 To 440-3-50	30XV_CNTLTRAN_002 4,530	30XV_CNTLTRAN_004 5,100	30XV_CNTLTRAN_006 5,100

UNIT-MOUNTED TERMINAL BLOCK / NON-FUSED DISCONNECT OPTION

DESCRIPTION	SCCR	VOLTAGE	MASTER PRICE		
			140-200	225-325	350-500
Terminal Block	Std	460-3-60	Std.	Std.	Std.
		575-3-60	Std.	Std.	Std.
		380-3-60 400-3-50 To 440-3-50	Std.	Std.	Std.
		208/230-3-60	Std.	-	-
Single Point Non-Fused Disconnect -,3,7,C	Std - ,0,1,2,3,4,5,6	460-3-60	30XV_NFD_001 5,336	30XV_NFD_007 8,625	30XV_NFD_017 7,915
		575-3-60	30XV_NFD_002 5,336	30XV_NFD_008 8,625	30XV_NFD_018 7,915
		380-3-60 400-3-50 To 440-3-50	30XV_NFD_003 4,983	30XV_NFD_009 8,078	30XV_NFD_019 19,696
	High 7,8,9,B,C,D,F,G	460-3-60	30XV_NFD_004 5,336	30XV_NFD_010 9,027	30XV_NFD_020 7,915
		575-3-60	30XV_NFD_005 5,336	30XV_NFD_011 9,027	30XV_NFD_021 7,915
		380-3-60 400-3-50 To 440-3-50	30XV_NFD_006 4,983	30XV_NFD_012 8,078	30XV_NFD_022 19,696

UNIT-MOUNTED TERMINAL BLOCK / NON-FUSED DISCONNECT OPTION (Cont.)

DESCRIPTION	SCCR	VOLTAGE	MASTER PRICE		
			140-200	225-325	350-500
Terminal Block	Std	460-3-60	Std.	Std.	Std.
		575-3-60	Std.	Std.	Std.
		380-3-60 400-3-50 To 440-3-50	Std.	Std.	Std.
		208/230-3-60	Std.	-	-

Dual Point Non-Fused Disconnect 9,F	Std - ,0,1,2,3,4,5,6	460-3-60	NC	NC	-
		575-3-60	NC	NC	-
		380-3-60 400-3-50 To 440-3-50	NC	30XV_NFD_015 (2,335)	-
		208/230-3-60 5	30XV_NFD_013 (4,153)	-	-
	High 7,8,9,B,C,D,F,G	460-3-60	NC	NC	-
		575-3-60	NC	NC	-
		380-3-60 2 400-3-50 To 440-3-50	NC	30XV_NFD_016 (2,335)	-
		208/230-3-60 5	30XV_NFD_014 (4,153)	-	-

SHORT CIRCUIT CURRENT RATING (SCCR) OPTION

DESCRIPTION			UNIT SIZE (Tier)					
Power Connection	**SCCR**	**Description**	**Voltage**	**SCCR RATING**	**140-200 (Std)**	**225-325 (Std)**	**140-200 (Mid/High)**	**225-325 (Mid/High)**
Single Point	Standard	Terminal Block (Single Point) Dual Disconnect Switch (Dual Point)	460-3-60	25kA	Std.	Std.	Std.	Std.
			575-3-60	10kA	Std.	Std.	Std.	Std.
			380-3-60 400-3-50 To 440-3-50	25kA	Std.	Std.	Std.	Std.
			208/230-3-60	25kA	Std.	-	Std.	-
Dual Point	Standard	Terminal Block	460-3-60	25kA	NC	NC	NC	NC
			575-3-60	18kA	NC	NC	NC	NC
			380-3-60 400-3-50 To 440-3-50	25kA	NC	NC	NC	NC
			208/230-3-60	25kA	NC	-	NC	-
Single Point 7,8,C,D 8A	High 10A	* Disconnect and breakers	460-3-60 6	65kA	30XV_SCCR_001 439	30XV_SCCR_008 1,568	30XV_SCCR_014 439	30XV_SCCR_021 1,568
			575-3-60 1	35kA	30XV_SCCR_002 439	30XV_SCCR_009 1,568	30XV_SCCR_015 439	30XV_SCCR_022 1,568
			380-3-60 2 400-3-50 To 440-3-50 9,G,J,K	65kA	30XV_SCCR_003 439	30XV_SCCR_010 1,568	30XV_SCCR_016 732	30XV_SCCR_023 1,568
			208/230-3-60 5	65kA	-	-	-	-
Dual Point 9,B,F,G 8B,8C	High 10A	** Disconnect and breakers	460-3-60 6	65kA	30XV_SCCR_004 439	30XV_SCCR_011 1,568	30XV_SCCR_017 439	30XV_SCCR_024 1,568
			575-3-60 1	35kA	30XV_SCCR_005 439	30XV_SCCR_012 1,568	30XV_SCCR_018 439	30XV_SCCR_025 1,568
			380-3-60 2 400-3-50 To 440-3-50 9,G,J,K	65kA	30XV_SCCR_006 439	30XV_SCCR_013 1,568	30XV_SCCR_019 732	30XV_SCCR_026 1,568
			208/230-3-60 5	65kA	30XV_SCCR_007 1,783	-	30XV_SCCR_020 1,783	-

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

***** Requires HSCCR Disconnect from above table and two HSCCR breakers

****** Requires two HSCCR breakers (that the field wires directly to) and breaker handles (dual power disconnect option from table above

SHORT CIRCUIT CURRENT RATING (SCCR) OPTION (Cont)

DESCRIPTION			UNIT SIZE (Tier)		
Power Connection	**SCCR**	**Description**	**Voltage**	**SCCR RATING**	**350-500 (all tiers)**
Single Point	Standard	Terminal Block	460-3-60	25kA	Std.
			575-3-60	10kA	Std.
			380-3-60 400-3-50 To 440-3-50	25kA	Std.
			208/230-3-60	25kA	-
Dual Point	Standard	Terminal Block	460-3-60	25kA	Std.
			575-3-60	10kA	Std.
			380-3-60 400-3-50 To 440-3-50	25kA	Std.
			208/230-3-60	25kA	-
Single Point 7,8,C,D 8A	High 10A	* Disconnect and breakers	460-3-60 6	65kA	30XV_SCCR_027 NC
			575-3-60 1	35kA	30XV_SCCR_028 NC
			380-3-60 2 400-3-50 To 440-3-50 9,G,J,K	65kA	30XV_SCCR_029 NC
			208/230-3-60 5	65kA	-
Dual Point 9,B,F,G 8B,8C	High 10A	** Breakers only (no disconnect) 9,F 8B	460-3-60 6	65kA	30XV_SCCR_030 18,975
			575-3-60 1	35kA	30XV_SCCR_031 18,975
			380-3-60 2 400-3-50 To 440-3-50 9,G,J,K,H	65kA	30XV_SCCR_032 18,975
			208/230-3-60 5	65kA	-

* Requires HSCCR Disconnect from above table and two HSCCR breakers
** Through the door disconnect handle available via ETO only

POSITION 16

CONTROLS OPTIONS

ENERGY MANAGEMENT MODULE

DESCRIPTION	UNIT	MASTER PRICE
None	All	Std.
Energy Management Module (EMM) - includes GFI convenience outlet D,G,J,L,N,Q	All	30XV_EMM_001 1,056

EXTERNAL INTERFACE OPTION

DESCRIPTION	VOLTAGE	MASTER PRICE	
		140-325	350-500
Standard - The Std Panel already includes: BACnet over IP & MSTP and Remote Connectivity	All	Std.	Std.
BACnet / Modbus Translator (Building automation system over BACnet or Modbus) F,M 12A	All	30XV_XINT_001 716	30XV_XINT_003 1,099
LONworks Translator H,P 12B	All	30XV_XINT_002 1,095	30XV_XINT_004 1,507

DATACENTER OPTION

DESCRIPTION	VOLTAGE	MASTER PRICE				
		140-275 All tiers	300 All tiers	325 All tiers	350-Std 350-Mid	350-High
No Datacenter	All	Std.	Std.	Std.	Std.	Std.
Datacenter Option: Allows chiller to operate with higher Entry and Leaving Water Temperatures at Higher Ambient Conditions K,L,M,N,P,Q 18A	208/230-3-60	-	-	-	-	-
	380-3-60 400-3-50 To 440-3-50	-	-	-	-	-
	460-3-60	30XV_DATA_CTR_01 1,178	30XV_DATA_CTR_02 8,544	30XV_DATA_CTR_03 8,544	30XV_DATA_CTR_04 1,178	30XV_DATA_CTR_05 1,178
	575-3-60	30XV_DATA_CTR_06 1,178	30XV_DATA_CTR_07 1,671	30XV_DATA_CTR_08 1,178	30XV_DATA_CTR_09 1,178	30XV_DATA_CTR_10 1,178

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

DESCRIPTION	VOLTAGE	MASTER PRICE			
		400 All tiers	450-Std 450-Mid	450-High	500 All tiers
No Datacenter	All	Std.	Std.	Std.	Std.
Datacenter Option: Allows chiller to operate with higher Entry and Leaving Water Temperatures at Higher Ambient Conditions K,L,M,N,P,Q	208/230-3-60	-	-	-	-
	380-3-60 400-3-50 To 440-3-50	-	-	-	-
	460-3-60	30XV_DATA_CTR_11 1,178	30XV_DATA_CTR_12 38,088	30XV_DATA_CTR_13 1,178	30XV_DATA_CTR_14 38,088
	575-3-60	30XV_DATA_CTR_15 1,178	30XV_DATA_CTR_16 1,178	30XV_DATA_CTR_17 1,178	30XV_DATA_CTR_18 1,167

POSITION 17

SECURITY GRILLES AND HAIL GUARD OPTIONS

DESCRIPTION	MASTER PRICE (Pricing done based on the # of V's)								
	4V	5V	6V	7V	8V	9V	10V	11V	12V
	Where used	Where used	Where used	Where used	Where used	Where used	Where used	Where used	Where used
	140-Std 140-Mid 160-Std 180-Std	140-High 160-Mid 180-Mid 200-Std 225-Std	160-High 180-High 200-Mid 225-Mid 250-Std 275-Std	200-High 225-High 250-Mid 275-Mid 300-Std	250-High 275-High 300-Mid 325-Std	300-High 325-Mid	325-High	400-High 450-Mid 500-Std	450-High 500-Mid
No Coil Panels L	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Coil Trim Panels ** **0,9 14A 14K**	30XV_SGHG_001 2,056	30XV_SGHG_005 2,631	30XV_SGHG_009 3,047	30XV_SGHG_013 3,516	30XV_SGHG_017 4,038	30XV_SGHG_021 4,559	30XV_SGHG_025 5,027	30XV_SGHG_029 5,496	30XV_SGHG_033 5,965
Coil Trim Panels + Security Grills 1,B 14B,14L	30XV_SGHG_002 4,106	30XV_SGHG_006 4,913	30XV_SGHG_010 5,560	30XV_SGHG_014 6,260	30XV_SGHG_018 7,013	30XV_SGHG_022 7,766	30XV_SGHG_026 8,464	30XV_SGHG_030 9,163	30XV_SGHG_034 9,862
Coil Trim Panels + Security Grills (Sides) + Hail Guards (End) 2,C 14C,14M	30XV_SGHG_003 5,063	30XV_SGHG_007 5,868	30XV_SGHG_011 6,517	30XV_SGHG_015 7,214	30XV_SGHG_019 7,967	30XV_SGHG_023 8,719	30XV_SGHG_027 9,420	30XV_SGHG_031 10,118	30XV_SGHG_035 10,818
Full Hail Guard 3,D 14D,14N	30XV_SGHG_004 12,404	30XV_SGHG_008 13,590	30XV_SGHG_012 15,245	30XV_SGHG_016 16,432	30XV_SGHG_020 18,088	30XV_SGHG_024 19,764	30XV_SGHG_028 21,909	30XV_SGHG_032 22,350	30XV_SGHG_036 23,773

* Full Hail Guard does not include Coil Trim Panels
** Coil Trim Panels option will include the panels only for the header side

PACKAGING OPTIONS

DESCRIPTION	MASTER PRICE (Pricing done based on the # of V's)								
	4V	5V	6V	7V	8V	9V	10V	11V	12V
	Where used	Where used	Where used	Where used	Where used	Where used	Where used	Where used	Where used
	140-Std 140-Mid 160-Std 180-Std	140-High 160-Mid 180-Mid 200-Std 225-Std	160-High 180-High 200-Mid 225-Mid 250-Std 275-Std	200-High 225-High 250-Mid 275-Mid 300-Std	250-High 275-High 300-Mid 325-Std	300-High 325-Mid	325-High	400-High 450-Mid 500-Std	400-High 500-Mi
None 3	NC	NC	NC	NC	NC	NC	NC	NC	NC
Coil Face Shipping Protection (CFSP) L,0,1,2	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Skid & Bag 9,B,C,D	30XV_PKG_001 3,538	30XV_PKG_002 3,927	30XV_PKG_003 4,316	30XV_PKG_004 4,791	30XV_PKG_005 5,183	30XV_PKG_006 5,799	30XV_PKG_007 6,415	30XV_PKG_008 7,057	30XV_PKG_009 7,699

* Skid & Bag option is recommended for regions where ocean freight is required.

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

FIELD-INSTALLED ACCESSORIES

CONTROL/COMMUNICATION ACCESSORIES

ORDERING NUMBER	DESCRIPTION	USAGE	MASTER PRICE	RCD LIST
30XV70000701	Energy Management Module Kit - Where External temperature reset is required by 4-20mA signal. Package also provides Demand Limiting and temperature set point.	All	1,696	
30XV70001701	BACnet/Modbus Translator	All	924	
30XV70001901	LonWorks Translator	All	1,185	
33ZCT55SPT	Space Temp. w/ Occupancy Override Button	All	¤	
HH79NZ014	Thermistor (5k Ohm) - 3 inch Water Temperature Sensor	All	54	*
HH79NZ029	Thermistor (5k Ohm) - 4 inch Water Temperature Sensor	All	73	*
10HB50106801	Thermistor Well - 3 inch	All	44	*
10HB50106802	Thermistor Well - 4 inch	All	41	*
00EFN900044000A	Dual Chiller Accessory Kit - Provides the additional hardware required to operate two chillers in parallel.	All	443	
30XV70001601	Display Heater for Control Panel	All	758	

***** RCD List Price - Subject to change on a quarterly basis and should be verified with RCD prior to quoting.
¤ See CCN System and Controls price page (catalog 500-059) or check SAP for current pricing.

ELECTRICAL ACCESSORIES

ORDERING NUMBER	DESCRIPTION	UNIT	SHIP WT (Lbs/Kgs)	MASTER PRICE
30XV70000801	Convenience Outlet - includes a 4-amp GFI (Ground Fault Interrupt) receptacle with independent fuse protection. Convenience outlet is 115V female receptacle. Not available with 380-400V & all 50Hz.	All	10/4.5	1,318

FIELD-INSTALLED ACCESSORIES (cont)

SECURITY GRILL ACCESSORIES *

ORDERING NUMBER	DESCRIPTION	USED ON	MASTER PRICE
30XV70000301	Security Grilles (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - Corrosion resistant wire grilles provide protection for chiller internal components. This item is sufficient for a 4V unit.	All units	5,885
30XV70000401	Security Grilles - 1V Module Kit For units with more than 4Vs, this module needs to be order as well. The quantity will depend on the amount of Vs the unit may have.	5V unit (will require Qty. 1) 6V unit (will require Qty. 2) 7V unit (will require Qty. 3) 8V unit (will require Qty. 4) 9V unit (will require Qty. 5) 10V unit (will require Qty. 6) 11V unit (will require Qty. 7) 12V unit (will require Qty. 8)	2,025

* Security Grilles require Coil Trim Panel option or accessory

HAIL GUARD ACCESSORIES

ORDERING NUMBER	DESCRIPTION	USED ON	MASTER PRICE
30XV70000501	Full Hail Guard (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - Louvered panels covering the ends of the chiller and designed to protect against harsh weather conditions and as privacy screen This item is sufficient for a 4V unit.	All units	17,659
30XV70000601	Full Hail Guard - 1V Module Kit For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	5V unit (will require Qty. 1) 6V unit (will require Qty. 2) 7V unit (will require Qty. 3) 8V unit (will require Qty. 4) 9V unit (will require Qty. 5) 10V unit (will require Qty. 6) 11V unit (will require Qty. 7) 12V unit (will require Qty. 8)	4,414

COIL TRIM PANEL ACCESSORIES

For units in the field **with no Coil Trim Panels** FIOP and customer requires coil trim panels on both sides, the following must be ordered:

ORDERING NUMBER	DESCRIPTION	MASTER PRICE	MASTER PRICE (Pricing done based on the # of V's) Where used and Quantity			
			4V	5V	6V	7V
			30XV140S 30XV140M 30XV160S 30XV180S	30XV140H 30XV160M 30XV180M 30XV200S 30XV225S	30XV160H 30XV180H 30XV200M 30XV225M 30XV250S 30XV275S	30XV200H 30XV225H 30XV250M 30XV275M 30XV300S
30XV70000101	End Coils (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - mounting hardware included. Provides aesthetic, finished appearance for the condenser coil ends and the evaporator/pump connection side of the unit. This item is sufficient for a 4V unit	4,873	1	1	1	1
30XV70000201	Center Coils - 1V Module Kit (Center Cover Panels - one for each side of unit) For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	1,838	0	1	2	3

ORDERING NUMBER	DESCRIPTION	MASTER PRICE	MASTER PRICE (Pricing done based on the # of V's) Where used and Quantity				
			8V	9V	10V	11V	12V
			30XV250H 30XV275H 30XV300M 30XV325S	30XV300H 30XV325M	30XV325H	30XV400H 30XV450M 30XV500S	30XV450H 30XV500M
30XV70000101	End Coils (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - mounting hardware included. Provides aesthetic, finished appearance for the condenser coil ends and the evaporator/pump connection side of the unit. This item is sufficient for a 4V unit	4,873	1	1	1	1	1
30XV70000201	Center Coils - 1V Module Kit (Center Cover Panels - one for each side of unit) For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	1,838	4	5	6	7	8

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

COIL TRIM PANEL ACCESSORIES

For units in the field **with Coil Trim Panels** FIOP (which includes header side only) but customer requires coil trim panels on both sides, the following must be ordered:

ORDERING NUMBER	DESCRIPTION	MASTER PRICE	MASTER PRICE (Pricing done based on the # of V's) Where used and Quantity			
			4V	5V	6V	7V
			30XV140S 30XV140M 30XV160S 30XV180S	30XV140H 30XV160M 30XV180M 30XV200S 30XV225S	30XV160H 30XV180H 30XV200M 30XV225M 30XV250S 30XV275S	30XV200H 30XV225H 30XV250M 30XV275M 30XV300S
30XV70000101*	End Coils (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - mounting hardware included. Provides aesthetic, finished appearance for the condenser coil ends and the evaporator/pump connection side of the unit. This item is sufficient for a 4V unit	4,873	1	1	1	1
30XV70000201	Center Coils - 1V Module Kit (Center Cover Panels - one for each side of unit) For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	1,838	0	0	0	1

ORDERING NUMBER	DESCRIPTION	MASTER PRICE	MASTER PRICE (Pricing done based on the # of V's) Where used and Quantity				
			8V	9V	10V	11V	12V
			30XV250H 30XV275H 30XV300M 30XV325S	30XV300H 30XV325M	30XV325H	30XV400H 30XV450M 30XV500S	30XV450H 30XV500M
30XV70000101*	End Coils (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - mounting hardware included. Provides aesthetic, finished appearance for the condenser coil ends and the evaporator/pump connection side of the unit. This item is sufficient for a 4V unit	4,873	1	1	1	1	1
30XV70000201	Center Coils - 1V Module Kit (Center Cover Panels - one for each side of unit) For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	1,838	1	2	2	3	3

* For units ordered with the Coil Trim Panels FIOP and customer wants coil trim panels on the non-header side as well, this accessory is needed and there will be an excess of 2 end coils, which can be discarded

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

REMOTE EVAPORATOR*

ORDERING NUMBER	DESCRIPTION	USED ON	MASTER PRICE
30XV70001101	Remote evaporator	140-Std	33,618
30XV70001102	Remote evaporator	140-Mid & High 160-Std	34,824
30XV70001103	Remote evaporator	160-Mid & High 180-Std	32,599
30XV70001104	Remote evaporator	180-Mid & High 200-Std	40,364
30XV70001105	Remote evaporator	200-Mid & High	44,513
30XV70001106	Remote evaporator	225-Std	45,732
30XV70001107	Remote evaporator	225-Mid & High	46,846
30XV70001108	Remote evaporator	250-Std	48,596
30XV70001109	Remote evaporator	250-Mid & High 275-Std	54,609
30XV70001110	Remote evaporator	275-Mid & High 300-Std	55,691
30XV70001111	Remote evaporator	300-Mid & High 325-Std	57,368
30XV70001112	Remote evaporator	325-Mid & High	59,416
30XV70001113	Remote evaporator	350-Std	64,329
30XV70001114	Remote evaporator	350-Mid & High	72,907
30XV70001115	Remote evaporator	400-Std	77,983
30XV70001116	Remote evaporator	400-Mid & High 450-Std	79,728
30XV70001118	Remote evaporator	450-Mid & High 500-Std	89,810
30XV70001119	Remote evaporator	500-Mid	98,803

REMOTE EVAPORATOR ASSEMBLY KIT*

ORDERING NUMBER	DESCRIPTION	USED ON	MASTER PRICE
30XV70001201	Remote evap piping/electrical	30XV 140-200	18,683
30XV70001202	Remote evap piping/electrical	30XV 225	20,409
30XV70001203	Remote evap piping/electrical	30XV 250-325	21,227
30XV70001204	Remote evap piping/electrical	30XV 350	23,090
30XV70001205	Remote evap piping/electrical	30XV 400-500	23,251

*FACTORY START UP & FIRST YEAR LABOR (USA & CANADA)

Order No.	DESCRIPTION	USAGE	NET PRICE
30XV-ST1	Start up, First Unit	30XV 140-350	2,628
30XV-STA	Start up, Each Additional Unit	30XV 140-350	1,772
30XV-ST2	Start up, First Unit	30XV 400-500	2,628
30XV-STB	Start up, Each Additional Unit	30XV 400-500	1,772

***Required for all 30XV and 09FC (when applicable) sales in USA and Canada**

GENERAL & APPLICATION NOTES

1. The units are designed for outdoor applications and, therefore, all electrical components are protected from the weather. All external sheet metal parts are painted with polyester baked enamel on galvanized steel. The frame is constructed of heavy-gage galvanized steel members zinc-dipped for superior corrosion protection.
2. All chillers are certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified units may be found in the AHRI Directory at www.ahridirectory.org.
3. All 208, 230, 380, 400, 460 and 575V 60 Hz and 380, 400, 415 and 440V 50Hz units are ETL and ETLc approved.
4. International Sales: F.O.B. Shipping Point. Freight prepaid to nearest point of embarkation.
5. Warranty Terms: APO, LAO, ETO Sales. Warranty terms and conditions determined by individual Carrier International Selling Company.
6. The compressors are electrically and mechanically protected by the VFDs and unit controls. Example of protection: electrical overload, over temperature, high pressure, low pressure/loss of charge, phase loss, phase reversal, etc.
7. The electronic expansion valve contains a linear stepper motor (~3600 steps) controlled by the unit's microprocessor to accurately meter refrigerant to the evaporator to maintain optimal operation of the system at all times
8. The evaporators, oil separators and mufflers (when order) are designed, constructed and tested in compliance with the ASME Code requirements for Unfired Pressure Vessels. The ASME stamping (U) is applied to the refrigerant side only.
9. Evaporators are insulated with ¾-inch closed-cell foam.
10. A factory-installed electronic thermal dispersion flow switch provides chilled water proof-of-flow.
11. Low temperature override is provided to prevent overshoot from the leaving water that could cause the unit to go out on evaporator freeze protection.
12. Insertion evaporator heaters are standard on flooded evaporators (except for Middle East Region). Whenever the unit is subject to temperatures below 33º F (1º C), an appropriate antifreeze solution must be added to the water in the evaporator to prevent freeze-up. The antifreeze should be properly inhibited to minimize corrosion.
13. Temperature reset from return, space temperature or outside air temperature may be performed with standard unit controls (requires accessory sensors). Reset via 4-20 mA signal requires the Energy Management Module.
14. Automatic lead/lag feature alternates lead compressor based on start cycles or run-time to ensure even wear for multiple compressor units.
15. Standard condenser head pressure control allows operation down to 32 F (0 C) on standard-tier units. Under many operating conditions, unit operation to as low as -20 F (-29 C) ambient temperature is achievable on all mid and high-tier units, and it is also achievable for standard-tier units which employ the variable-speed condenser fan option. For any operation below 32 F (0 C), pump control or the use of glycol in the system is required. Whenever a unit is expected to operate at ambient temperatures below 32 F (0 C), field-supplied and installed wind baffles must be added to the unit.

ETLc

ISO 9001

AHRI 550/590

ASME

OPTIONAL EXTENDED WARRANTIES ARE AVAILABLE. SEE CATALOG NO. 500-089 "COMMERCIAL START-UP AND OPTIONAL EXTENDED WARRANTY PRICING"