Commercial Products Master Prices

30CF
425-850
60 Hz

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE
SHIPPING POINT: CHARLOTTE, NC
NEAREST PORT OF EMBARKATION: SAVANNAH, GA

TYPE OF SALE: 1626 300-500 (NA & Export)

F.O.B. SHIPPING POINT
FREIGHT PREPAID

30CF AQUAFORCE WITH GREENSPEED INTELLIGENCE AIR-COOLED CENTRIFUGAL COMPRESSION LIQUID CHILLERS



These air-cooled packaged chiller units are fully piped and charged with HFC1234ze- refrigerant. Weatherproof construction, lightweight distribution and small footprint make them ideal for rooftop or ground level installation. Upward discharge airflow minimizes directional sound and carries heat away from surrounding areas (Notes 1, 2, 3, 4 & 5).

FEATURES AND ACCESSORIES

Refrigeration Circuit	30CF 425-850
Full R-1234ze Refrigerant Charge	Std
Full Load Factory Run Test and Run Test Report	Std
Single Refrigeration Circuit	Std
Variable Speed Centrifugal Compressors	Std
Compressor Protection (Note 6)	Std
~3600 Step Electronic Expansion Valve (EXV – Note 7)	Std
Two-Pass Flooded Shell-and-Tube Evaporator with Heater (Notes 8 and 12)	Std
Evaporator Insulation (Note 9)	Std
Filter Drier	Std
Moisture Indicating Sight Glass	Std
AeroAcoustic Condenser Fans	Std
~~Low-Sound Kit~~	~~FIOP~~
Micro Channel Condenser Coil	Std
Condenser Coil Options	
E-Coated Micro Channel	FIOP
Suction Service Valve	Std
Suction Line Insulation	Std
Liquid Service Valve per Circuit & Discharge Service Valve	Std
Waterside Economizer Coils with diverting valve	Std

PC 903 FORM NO. 30CF-1PPG
SUPERSEDES
PRICE SECTION 30CF

Chilled Water Circuit	30CF 425-850
300 psig (2068 kPa) Fluid Side Rated (150 psig for units with optional hydronic system)	Std
Electronic Flow Switch (thermal dispersion – Note 10)	Std
Freeze Protection (Note 11) – Evaporator Heaters (Note 12)	Std
Hydronic Kit	FIOP

Controls / Communication	30CF 425-850
Microprocessor 7-inch TOUCHPILOT (touch screen) Display	Std
Control Box Hinged Access Panels	Std
Temperature & Pressure Display	Std
~~Energy Management Module (EMM) + GFI Convenience Outlet~~	~~Std~~
Chilled Water Temperature Reset (from return fluid – Note 13)	Std
Demand Limit, 1-step (via switch, field supplied)	Std
Low Water Temp Protection	Std
High Pressure Protection	Std
Low Pressure Protection	Std
Unit Mounted Control Panel	Std
Variable Speed Condenser Fans	Std
Electronically Commutated Motor (ECM) for the condenser Fans	FIOP
Anti-Cycling Protection	Std
CCN Communication	Std
BACnet Translator (IP or MS/TP)	Std
~~LONworks Translator~~	~~Accy~~
External Pump Control Capability (no variable speed pump capability)	Std
Display Heater for Control Panel	Std
Datacenter Option	Std
Uninterrupted Power Supply (UPS)	Std
Remote Connectivity	Std

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

Electrical	30CF 425-850
Single Point Primary Power Entry	Std
Control Transformer (line power voltage to 115VAC)	Std
Unit Mounted Main Disconnect, Non-fused	Std
~~115V GFI Convenience Outlet and EMM~~	~~Std~~
Permanent Magnet (PM) Compressor Motor	Std
High SCCR (65kA – 460v)	Std
Line Reactor	FIOP
~~Auto Transfer Switch~~	~~FIOP~~
Harmonic Filter	FIOP
Evaporator Heater (120V)	FIOP
Evaporator Heater (208V)	FIOP

Packaging / Security	30CF 425-850
Coil Face Shipping Protection	Std
Condenser Coil Trim Panels	FIOP / Accy
Full Hail Guard	FIOP / Accy
Export Packaging	FIOP
Security Grilles	FIOP
Security Grilles and End Hail Guards	FIOP

Std — Standard Feature
FIOP — Factory-Installed Option
Accy — Field-Installed Accessory
N/A — Not Available

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

MODEL NUMBER NOMENCLATURE

Position	1-4	5	6-8	9	10	11	12	13	14	15	16	17
Description	**30CF**	**-**	**425**	**6**	**M**	**4**	**-**	**-**	**0**	**1**	**1**	**0**

Air-Cooled AquaForce Chiller

Design Series

Nominal Capacity

425
475
500
850

Voltage Options

6 = 460-3-60

Product Tiers & Evaporator Configuration

M = Medium
H = High

Condenser Options

Evaporator & Hydronic Kit Options

Low Ambient & Sound Options

Valve & Insulation Options

Electrical Options

Controls Options

Packaging Options

MODEL NUMBER NOMENCLATURE DEFINITION

Voltage Options (Position 9)

6 = 460-3-60

Product Tier Configuration (Position 10)

M = Mid Tier
H = High Tier

Condenser Coil Options (Position 11)

~~- = Micro Channel for R-1234ze~~
~~0 = Micro Channel, E-Coat for R-1234ze~~
4 = Micro Channel for R-1234ze
5 = Micro Channel, E-Coat for R-1234ze

Evaporator and Hydronic Kit Options (Position 12)

~~- = Flooded Evaporator, 2 pass, w/ Heater, no hydronic kit (120V Heater)~~
~~0 = Flooded Evaporator, 2-pass, w/ Heater, no hydronic kit (208V Heater)~~
5 = Flooded Evaporator, 2 pass, w/ Heater, high-head hydronic kit, End connections (120V Heater)
7 = Flooded Evaporator, 2-pass w/ Heater, no hydronic kit, center connectons (left side exit, 120V)
F = Flooded Evaporator, 2 pass, w/ Heater, high-head hydronic kit, center connections (left side, 120V)
K = Flooded Evaporator, 2-pass w/ Heater, high-head hydronic kit, center connections (right side, 120V)
~~L = Flooded Evaporator, 2-pass w/ Heater, high-head hydronic kit, end connections (208V Heater)~~

Condenser Fans and Sound Options (Position 13)

~~- = VFD Fans, Std Sound~~
0 = ECM Fans, Std Sound

Piping Valve, Seismic, and Free Cooling (Position 14)

~~- = Dual point power, suction service valve (SSV)~~
0 = Single point power, separate Heater Circuit (120V), SSV
~~1 = Dual point power, Seismic & Wind load Certified, SSV~~
~~2 = Single point power, Seismic & Wind load Certified, separate Heater Circuit (120V), SSV~~
~~3 = Dual point power, Free Cooling, SSV~~
4 = Single point power, separate Heater Circuit (120V), Free Cooling
~~5 = Dual point power, Seismic & Wind load Certified, Free Cooling, SSV~~
~~6 = Single point power, separate Heater Circuit (120V), Seismic & Wind load Certified, Free Cooling, SSV~~
~~7 = Single point power w/Heater Circuit, suction service valve (SSV)~~
~~8 = Single point power w/Heater Circuit, Seismic & Wind load Certified, SSV~~
~~9 = Single point power w/Heater Circuit, Free Cooling, SSV~~
~~B = Single point power w/Heater Circuit, Seismic & Wind load Certified, Free Cooling, SSV~~

Electrical Options (Position 15)

1 = NFD, High SCCR
5 = NFD, High SCCR, line reactor
9 = NFD, High SCCR, harmonic filter

Control Options (Position 16)

- = 7" Touchpilot Display, Remote Connectivity, Freeze Protection
0 = 7" Touchpilot Display, No Remote Connectivity, Freeze Protection
1 = 7" Touchpilot Display, Remote Connectivity, Freeze Protection, with Control Transformer
2 = 7" Touchpilot Display, No Remote connectivity, Freeze Protection, with Control Transformer
3 = 7" Touchpilot Display, Remote Connectivity, Separate Freeze Protection with Control Transformer
4 = 7" Touchpilot Display, No Remote Connectivity, Separate Freeze Protection, with Control Transformer
5 = 7" Touchpilot Display, Remote Connectivity, Separate Freeze Protection, Separate Pump Power
6 = 7" Touchpilot Display, No Remote Connectivity, Separate Freeze Protection, Separate Pump Power
7 = 7" Touchpilot Display, Remote Connectivity, Separate Pump Power, Freeze protection, with Control Transformer
8 = 7" Touchpilot Display, No Remote Connectivity, Separate Pump Power, Freeze Protection, with Control Transformer
9 = 7" Touchpilot Display, Remote Connectivity, Separate Freeze Protection, Separate Pump Power, with Control Transformer
B = 7" Touchpilot Display, No Remote Connectivity, Separate Freeze Protection, Separate Pump Power, with Control Transformer

Packaging Options (Position 17)

0 = CFSP, Coil Trim Panels,
~~1 = Coil Trim Panels, Security Grilles, Hail Guards (end)~~
3 = Full Hail Guard
~~9 = CFSP, Coil Trim Panels, Export Package~~
~~B = Coil trim panels, security grilles, export Package~~
~~D = Full hail guard, export package~~

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

30CF AIR COOLED LIQUID CHILLING PACKAGES
BASE UNIT WITH NO CRATING

ORDERING NUMBER	POWER SUPPLY	MASTER PRICE
30CF-4256M4--0110	460-3-60	1
30CF-4256H4--0110	460-3-60	1
30CF-4756M4--0110	460-3-60	1
30CF-4756H4--0110	460-3-60	1
30CF-5006H4--0110	460-3-60	$2,272,348
30CF-8506H4--0110	460-3-60	1

FACTORY-INSTALLED OPTIONS (FIOP)

POSITION 11

CONDENSER COIL CORROSION PROTECTION OPTION

DESCRIPTION	MASTER PRICE (Pricing done based on the # of V's)					
	9V	10V	12V	13V	14V	14V
	Where used	Where used	Where used	Where used	Where used	Where used
	425-Mid	425-High	475-Mid	475-High	500-High	850-High
Micro Channel R-1234ze ~~or R-515b~~ **1** 4	Std.	Std.	Std.	Std.	Std.	Std.
Micro Channel, E-Coat R-1234ze ~~or R-515b~~ **1A** 5	30CF_COIL_001 1	30CF_COIL_002 1	30CF_COIL_003 1	30CF_COIL_004 1	30CF_2MW_COIL_001 1	30CF_3MW_COIL_001 1

POSITION 12

EVAPORATOR OPTION

DESCRIPTION	425-Mid	425-High	475-Mid	475-High	500-High	850-High
Flooded Evaporator, 2 pass, with 120v heater for Brine Application	Std	Std	Std	Std	Std	Std

WATER CONNECTIONS

DESCRIPTION	425-Mid	425-High	475-Mid	475-High	500-High	850-High
Chiller End water connections 5 **16B 16J**	Std	Std	Std	Std	Std	Std
Chiller Center (left) water connections 7 F **16C 16E**	30CF_WC_001 1	30CF_WC_002 1	30CF_WC_003 1	30CF_WC_004 1	30CF_2MW_WC_001 $8,719	30CF_3MW_WC_001 1
Chiller Center (right) water connections K **16H**	30CF_WC_005 1	30CF_WC_006 1	30CF_WC_007 1	30CF_WC_008 1	30CF_2MW_WC_002 $11,338	30CF_3MW_WC_002 1

HYDRONIC KIT OPTION

DESCRIPTION	Voltage	425-Mid	425-High	475-Mid	475-High	500-High	850-High
No Pump	460	Std	Std.	Std.	Std.	Std.	Std
~~Low Head Pump (N+0)~~	~~460~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~
High Head Pump ~~(N+0)~~ 5 F K **16B 16E 16H 16J**	460	30CF_HYDRONIC_005 1	30CF_HYDRONIC_006 1	30CF_HYDRONIC_007 1	30CF_HYDRONIC_008 1	30CF_2MW_HYDRONIC_002 $33,568	30CF_3MW_HYDRONIC_002 1

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

POSITION 13

SOUND OPTIONS

DESCRIPTION	MASTER PRICE			
	425	475	500	850
Standard Sound - No compressor sound enclosures	Std.	Std.	Std.	Std.

CONDENSER FANS

DESCRIPTION	Voltage	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
Variable Speed Condenser Fans* - 3	460	Std	Std.	Std.	Std.	Std.	Std.
Electronically Commuted Motor (ECM) Fans * ‡ 0 3A	460	30CF_CONDENSER_001 1	30CF_CONDENSER_002 1	30CF_CONDENSER_003 1	30CF_CONDENSER_004 1	30CF_2MW_CONDENSER_001 $200,468	30CF_3MW_CONDENSER_001 1

* (includes providing the function of Low Ambient Head Pressure Control) - This option permits start-up at 0°F (-18°C) and operation of the 30CF units to -20°F (-29°C) outdoor ambient temperature by controlling the speed of the condenser fans. Package includes sensor, control and hardware for operating the fans in each circuit. With pump control or glycol in loop; without pump control or glycol, minimum operating ambient temperature is 0° F

‡ May require installation of field-supplied wind baffles (not included)

FACTORY-INSTALLED OPTIONS (cont)

POSTION 14

SUCTION SERVICE VALVE

DESCRIPTION	MASTER PRICE			
	425	475	500	850
Suction Service Valve(s) - Provides additional refrigerant isolation capability. Regardless of which cooler option is employed, the selection of the isolation valve option results in chillers which are equipped with a liquid line service valve, a discharge service valve, and a series of valves on or near the cooler, the net effect of which is to provide isolation capability in the condenser area, the cooler area and the compressor area. Please refer to the latest PD document for additional details.	Std.	Std.	Std.	Std.

SUCTION LINE INSULATION OPTION

DESCRIPTION	MASTER PRICE			
	425	475	500	850
Suction Line Insulation - Insulation is tubular closed-cell insulation.	Std.	Std.	Std.	Std.

* Suction line insulation is valid for any operating condition.

FREE COOLING

DESCRIPTION	MASTER PRICE			
	425	475	500	850
No Free Cooling (Direct Expansion)	Std.	Std.	Std.	Std.
Free Cooling (Direct Expansion)	30CF_FC_0011	30CF_FC_0021	30CF_2MW_FC_0011	30CF_3MW_FC_0011

POWER CONNECTION

DESCRIPTION	MASTER PRICE			
	425	475	500	850
~~Dual point~~	~~Std.~~	~~Std.~~	~~Std.~~	~~Std.~~
Single point, separate Heater Circuit 0 4 **7A**	30CF_POWER_0011	30CF_POWER_0021	30CF_2MW_POWER_001 52,971	30CF_3MW_POWER_0011
~~Single point with Heater Circut~~	~~1~~	~~1~~	~~1~~	~~1~~

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE
POSITION 15

F.O.B. SHIPPING POINT
FREIGHT PREPAID

ELECTRICAL OPTIONS

POWER CONNECTION OPTION

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
Non-fused disconnect and control transformer	460-3-60	Std.	Std.	Std.	Std.	Std.	Std.

SHORT CIRCUIT CURRENT RATING (SCCR) OPTION

DESCRIPTION	UNIT SIZE (Tier)					
SCCR	Voltage	SCCR RATING	425	475	500	850
High	460-3-60	65kA	Std.	Std.	Std.	Std.

ACTIVE HARMONIC FILTER*

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
No Harmonic Filter	460-3-60	Std.	Std.	Std.	Std.	Std.	Std.
Active Harmonic Filter – provides IEEE-519 compliance 9 **9B**	460-3-60	30CF_HARMONIC_0011	30CF_HARMONIC_0021	30CF_HARMONIC_0031	30CF_HARMONIC_0041	30CF_2MW_HARMONIC_001 $254,286	30CF_3MW_HARMONIC_0011

* Can not be ordered with line reactor

LINE REACTOR*

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
No Line Reactor	460-3-60	Std.	Std.	Std.	Std.	Std.	Std.
Line Reactor 5 **9A**	460-3-60	30CF_REACTOR_0011	30CF_REACTOR_0021	30CF_REACTOR_0031	30CF_REACTOR_0041	30CF_2MW_REACTOR_001 $19,391	30CF_3MW_REACTOR_0011

* Can not be ordered with harmonic filter

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE
POSITION 16

F.O.B. SHIPPING POINT
FREIGHT PREPAID

CONTROLS OPTIONS

~~ENERGY MANAGEMENT MODULE~~

~~DESCRIPTION~~	~~UNIT~~	~~MASTER PRICE~~
~~None~~	~~All~~	~~Std.~~
~~Energy Management Module (EMM) - includes GFI convenience outlet~~	~~All~~	~~1~~

EXTERNAL INTERFACE OPTION

DESCRIPTION	VOLTAGE	MASTER PRICE
		425-850
Standard Panel - No Remote Connectivity - Panel already includes: BACnet over IP & MS/TP, Modbus, and NO REMOTE CONNECTIVITY	All	Std.
Remote connectivity - the Panel includes: BACnet over IP & MS/TP, Modbus, and Remote Connectivity - 1 5 7 9 **11**	All	30CF_INTERFACE_001 $2830

UNINTERRUPTIBLE POWER SUPPLY (UPS)

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
Uninterruptible Power Supply (UPS)	All	Std.	Std.	Std.	Std.	Std.	Std.

CONTROL TRANSFORMER

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
Control Transformer	All	Std.	Std.	Std.	Std.	Std.	Std.
No Control Transformer - 0 5 6 **15**	All	30CF_TRANSF_001 1	30CF_TRANSF_002 1	30CF_TRANSF_003 1	30CF_TRANSF_004 1	30CF_2MW_TRANSF_001 1	30CF_3MW_TRANSF_001 1

PUMP POWER

DESCRIPTION	VOLTAGE	MASTER PRICE					
		425-Mid	425-High	475-Mid	475-High	500-High	850-High
No Pump/Integrated Pump Power	All	Std.	Std.	Std.	Std.	Std.	Std.
Separate Pump Power 7 8 9 B **17A**	All	30CF_PUMP_001 1	30CF_PUMP_002 1	30CF_PUMP_003 1	30CF_PUMP_004 1	30CF_2MW_PUMP_001 $20,016	30CF_3MW_PUMP_001 1

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE
F.O.B. SHIPPING POINT
FREIGHT PREPAID

POSITION 17

SECURITY GRILLES AND HAIL GUARD OPTIONS

DESCRIPTION	MASTER PRICE					
	425-Mid	425-High	475-Mid	475-High	500-High	850-High
Coil Trim Panels (includes Coil Face Shipping Protection (CFSP))*	Std.	Std.	Std.	Std.	Std.	Std.
Coil Trim Panels and Security Grilles (includes CFSP)* 1 B **14B 14F**	30CF_SGHG_001 1	30CF_SGHG_002 1	30CF_SGHG_003 1	30CF_SGHG_004 1	30CF_2MW_SGHG_001 1	1
~~Coil Trim Panels, Security Grilles and End Hail Guards *~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~
Full Hail Guards * 3 **14D 14H**	30CF_SGHG_009 1	30CF_SGHG_010 1	30CF_SGHG_011 1	30CF_SGHG_012 1	30CF_2MW_SGHG_003 $14,767	1

* Coil Trim Panels option will include the panels only for the header side

PACKAGING OPTIONS

DESCRIPTION	MASTER PRICE					
	425-Mid	425-High	475-Mid	475-High	500-High	850-High
Coil Face Shipping Protection (CFSP)	Std.	Std.	Std.	Std.	Std.	Std.
~~Skid & Bag*~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~	~~1~~

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

FIELD-INSTALLED ACCESSORIES

CONTROL/COMMUNICATION ACCESSORIES

ORDERING NUMBER	DESCRIPTION	USAGE	MASTER PRICE	RCD LIST
30XV70000701	Energy Management Module Kit - Where External temperature reset is required by 4-20mA signal. Package also provides Demand Limiting and temperature set point.	All	1,631	
30XV70001701	BACnet/Modbus Translator	All	888	
30XV70001901	LonWorks Translator	All	1,139	
33ZCT55SPT	Space Temp. w/ Occupancy Override Button	All	¤	
HH79NZ014	Thermistor (5k Ohm) - 3 inch Water Temperature Sensor	All	54	*
HH79NZ029	Thermistor (5k Ohm) - 4 inch Water Temperature Sensor	All	73	*
10HB50106801	Thermistor Well - 3 inch	All	44	*
10HB50106802	Thermistor Well - 4 inch	All	41	*
30XV70001601	Display Heater for Control Panel	All	729	

***** RCD List Price - Subject to change on a quarterly basis and should be verified with RCD prior to quoting.
¤ See CCN System and Controls price page (catalog 500-059) or check SAP for current pricing.

ELECTRICAL ACCESSORIES

ORDERING NUMBER	DESCRIPTION	UNIT	SHIP WT (Lbs/Kgs)	MASTER PRICE
30XV70000801	GFI Convenience Outlet - includes a 4-amp GFI (Ground Fault Interrupt) receptacle with independent fuse protection. Convenience outlet is 115V female receptacle. Not available with 380-400V & all 50Hz.	All	10/4.5	1,267

COIL TRIM PANEL ACCESSORIES

For units in the field **with no Coil Trim Panels** FIOP and customer requires coil trim panels on both sides, the following must be ordered:

ORDERING NUMBER	DESCRIPTION	MASTER PRICE	MASTER PRICE (Pricing done based on the # of V's) Where used and Quantity				
			8V	9V	10V	11V	12V
			30CF300M	30CF300H	30CF400M	30CF400H 30CF450M	30CF450H 30CF500M
30XV70000101	End Coils (2Vs for the ends + 2 center cover panels; 4 total Vs in this option) - mounting hardware included. Provides aesthetic, finished appearance for the condenser coil ends and the evaporator/pump connection side of the unit. This item is sufficient for a 4V unit	4,599	1	1	1	1	1
30XV70000201	Center Coils - 1V Module Kit (Center Cover Panels - one for each side of unit) For units with more than 4Vs, this module needs to be ordered as well. The quantity will depend on the amount of Vs the unit may have.	1,768	4	5	6	7	8

Carrier Corporation • Syracuse, N.Y. 13221
SUBJECT TO CHANGE WITHOUT NOTICE

F.O.B. SHIPPING POINT
FREIGHT PREPAID

***FACTORY START UP & FIRST YEAR LABOR (USA & CANADA)**

Order No.	DESCRIPTION	USAGE	NET PRICE
30CF-ST1	Start up, First Unit	All 30CF Models	2,628
30CF-STA	Start up, Each Additional Unit	All 30CF Models	1,772

***Required for all 30CF sales in USA and Canada**

GENERAL & APPLICATION NOTES

1. The units are designed for outdoor applications and, therefore, all electrical components are protected from the weather. All external sheet metal parts are painted with polyester baked enamel on galvanized steel. The frame is constructed of heavy-gage galvanized steel members zinc-dipped for superior corrosion protection.
2. All chillers are certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified units may be found in the AHRI Directory at www.ahridirectory.org.
3. All 460V 60 Hz are ETL and ETLc approved.
4. International Sales: F.O.B. Shipping Point. Freight prepaid to nearest point of embarkation.
5. Warranty Terms: APO, LAO, ETO Sales. Warranty terms and conditions determined by individual Carrier International Selling Company.
6. The compressors are electrically and mechanically protected by the VFDs and unit controls. Example of protection: electrical overload, over temperature, high pressure, low pressure/loss of charge, phase loss, phase reversal, etc.
7. The electronic expansion valve contains a linear stepper motor (~3600 steps) controlled by the unit's microprocessor to accurately meter refrigerant to the evaporator to maintain optimal operation of the system at all times
8. The evaporators, oil separators and mufflers ordered are designed, constructed and tested in compliance with the ASME Code requirements for Unfired Pressure Vessels. The ASME stamping (U) is applied to the refrigerant side only.
9. Evaporators are insulated with ¾-inch closed-cell foam.
10. A factory-installed electronic thermal dispersion flow switch provides chilled water proof-of-flow.
11. Low temperature override is provided to prevent overshoot from the leaving water that could cause the unit to go out on evaporator freeze protection.
12. Insertion evaporator heaters are standard on flooded evaporators. Whenever the unit is subject to temperatures below 33º F (1º C), an appropriate antifreeze solution must be added to the water in the evaporator to prevent freeze-up. The antifreeze should be properly inhibited to minimize corrosion.
13. Temperature reset from return, space temperature or outside air temperature may be performed with standard unit controls (requires accessory sensors). Reset via 4-20 mA signal requires the Energy Management Module.
14. Automatic lead/lag feature alternates lead compressor based on start cycles or run-time to ensure even wear for multiple compressor units.
15. Under many operating conditions, unit operation to as low as -20 F (-29 C) ambient temperature is achievable. For any operation below 32 F (0 C), pump control or the use of glycol in the system is required. Whenever a unit is expected to operate at ambient temperatures below 32 F (0 C), field-supplied and installed wind baffles must be added to the unit.

ETLc

ISO 9001

AHRI 550/590

ASME

OPTIONAL EXTENDED WARRANTIES ARE AVAILABLE. SEE CATALOG NO. 500-089 "COMMERCIAL START-UP AND OPTIONAL EXTENDED WARRANTY PRICING"