

1. Select the option that correctly completes the sentence:

1 point

Training a model using labeled data and using this model to predict the labels for new data is known as \_\_\_\_\_.

- ☐ Unsupervised Learning  
☐ Clustering  
☒ Supervised Learning  
☐ Density Estimation

2. Select the option that correctly completes the sentence:

1 point

Modeling the features of an unlabeled dataset to find hidden structure is known as \_\_\_\_\_.

- ☒ Unsupervised Learning  
☐ Classification  
☐ Supervised Learning  
☐ Regression

3. Select the option that correctly completes the sentence:

1 point

Training a model using categorically labelled data to predict labels for new data is known as \_\_\_\_\_.

- ☐ Clustering  
☐ Feature Extraction  
☒ Classification  
☐ Regression

4. Select the option that correctly completes the sentence:


1 point

Training a model using labelled data where the labels are continuous quantities to predict labels for new data is known as \_\_\_\_\_.

- ☐ Clustering  
☐ Feature Extraction  
☒ Regression  
☐ Classification

5. Using the data for classes 0, 1, and 2 plotted below, what class would a KNeighborsClassifier classify the new point as for  $k = 1$  and  $k = 3$ ?

1 point



- ☐
  - k=1: Class 0
  - k=3: Class 1
- ☐
  - k=1: Class 2
  - k=3: Class 1
- ☒
  - k=1: Class 1
  - k=3: Class 2
- ☐
  - k=1: Class 0
  - k=3: Class 2
- ☐
  - k=1: Class 1
  - k=3: Class 0

6. Which of the following would \*not\* be something you specify for a nearest neighbor classifier algorithm?

1 point

- ☐ A distance metric that finds neighbor points in the training set
- ☐ How many nearest neighbors to examine
- ☐ A method for pooling the classes of neighbor points to make a final classification decision
- ☐ An optional weighting function on the neighbor points
- ☒ The number of initial clusters to create from the training set

7. Why is it important to examine your dataset as a first step in applying machine learning? (Select all that apply):

1 point

- ☒ See what type of cleaning or preprocessing still needs to be done
- ☒ You might notice missing data
- ☒ Gain insight on what machine learning model might be appropriate, if any
- ☒ Get a sense for how difficult the problem might be
- ☐ It is not important

8. The key purpose of splitting the dataset into training and test sets is:

1 point

- ☐ To reduce the amount of labelled data needed for evaluating classifier accuracy
- ☐ To reduce the number of features we need to consider as input to the learning algorithm
- ☐ To speed up the training process
- ☒ To estimate how well the learned model will generalize to new data

9. The purpose of setting the random\_state parameter in train\_test\_split is: (Select all that apply)

1 point

- ☐ To split the data into similar subsets so that bias is not introduced into the final results
- ☒ To make experiments easily reproducible by always using the same partitioning of the data
- ☐ To avoid bias in data splitting
- ☐ To avoid predictable splitting of the data

10. Given a dataset with 10,000 observations and 50 features plus one label, what would be the dimensions of X\_train, y\_train, X\_test, and y\_test? Assume a train/test split of 75%/25%.

1 point

- ☒
  - X\_train: (7500, 50)
  - y\_train: (7500, )
  - X\_test: (2500, 50)
  - y\_test: (2500, )
- ☐
  - X\_train: (2500, )
  - y\_train: (2500, 50)
  - X\_test: (7500, )
  - y\_test: (7500, 50)
- ☐
  - X\_train: (10000, 28)
  - y\_train: (10000, )
  - X\_test: (10000, 12)
  - y\_test: (10000, )
- ☐
  - X\_train: (2500, 50)
  - y\_train: (2500, )
  - X\_test: (7500, 50)
  - y\_test: (7500, )

- ☐
- X\_train: (10000, 50)
  - y\_train: (10000,)
  - X\_test: (10000, 50)
  - y\_test: (10000,)

11. Which of the following statements about the effect of the number of neighbors parameter k is true?

1 point

- ☐ Nearest neighbor classifier accuracy is never significantly affected by the choice of k.
- ☒ For small values of k (e.g. k = 1), the classifier will tend to be much more sensitive to noise, mislabeled data, and other sources of variation for individual data points.
- ☒ For larger values of k (e.g. k = 10), the regions in feature space assigned to different classes generally become less fragmented and have smoother decision boundaries between the regions, compared to results using smaller values of k.
- ☐ For small values of k (e.g. k = 1), the classifier will tend to be much less sensitive to noise, mislabeled data, and other sources of variation for individual data points.