

Travel Booking Platform - Database Schema

Flights, Hotels, Cabs |

USERS

Column Name	Data Type	Constraint
user_id	INT	PK, NOT NULL
name	VARCHAR(100)	NOT NULL
email	VARCHAR(100)	UNIQUE, NOT NULL
password	VARCHAR(255)	NOT NULL
phone	VARCHAR(15)	NOT NULL
role	VARCHAR(20)	NOT NULL
provider_type	VARCHAR(20)	NULL
provider_company_name	VARCHAR(150)	NULL
created_at	DATETIME	NOT NULL

FLIGHTS

Column Name	Data Type	Constraint
flight_id	INT	PK, NOT NULL
provider_id	INT	FK (references USERS.user_id), NOT NULL
flight_number	VARCHAR(20)	UNIQUE, NOT NULL
source	VARCHAR(100)	NOT NULL
destination	VARCHAR(100)	NOT NULL
departure_time	DATETIME	NOT NULL
arrival_time	DATETIME	NOT NULL
price	DECIMAL(10,2)	NOT NULL
total_seats	INT	NOT NULL
available_seats	INT	NOT NULL
status	VARCHAR(20)	NOT NULL

HOTELS

Column Name	Data Type	Constraint
hotel_id	INT	PK, NOT NULL
provider_id	INT	FK (references USERS.user_id), NOT NULL
hotel_name	VARCHAR(150)	NOT NULL
location	VARCHAR(150)	NOT NULL
address	VARCHAR(255)	NOT NULL
phone	VARCHAR(15)	NOT NULL
room_type	VARCHAR(50)	NOT NULL
price_per_night	DECIMAL(10,2)	NOT NULL
capacity	INT	NOT NULL
rating	DECIMAL(2,1)	NOT NULL
available_rooms	INT	NOT NULL
status	VARCHAR(20)	NOT NULL

CABS

Column Name	Data Type	Constraint
cab_id	INT	PK, NOT NULL
provider_id	INT	FK (references USERS.user_id), NOT NULL
vehicle_number	VARCHAR(20)	UNIQUE, NOT NULL
cab_type	VARCHAR(50)	NOT NULL

Column Name	Data Type	Constraint
driver_name	VARCHAR(100)	NOT NULL
driver_phone	VARCHAR(15)	NOT NULL
price_per_km	DECIMAL(10,2)	NOT NULL
status	VARCHAR(20)	NOT NULL

BOOKINGS (CHILD TABLES FILLED)

Column Name	Data Type	Constraint
booking_id	INT	PK, NOT NULL
user_id	INT	FK (references USERS.user_id), NOT NULL
provider_id	INT	FK (references USERS.user_id), NOT NULL
flight_id	INT	FK → FLIGHTS.flight_id, NULL
hotel_id	INT	FK → HOTELS.hotel_id, NULL
cab_id	INT	FK → CABS.cab_id, NULL
booking_type	VARCHAR(20)	NOT NULL
booking_date	DATETIME	NOT NULL
total_amount	DECIMAL(10,2)	NOT NULL
booking_status	VARCHAR(30)	NOT NULL
payment_method	VARCHAR(30)	NULL
payment_amount	DECIMAL(10,2)	NULL
payment_status	VARCHAR(20)	NULL
transaction_id	VARCHAR(100)	UNIQUE, NULL
payment_date	DATETIME	NULL
cancelled_by	INT	FK (references USERS.user_id), NULL
cancellation_reason	VARCHAR(255)	NULL
refund_amount	DECIMAL(10,2)	NULL
cancellation_status	VARCHAR(20)	NULL
cancelled_at	DATETIME	NULL

ENTITY RELATIONSHIP DIAGRAM – RELATIONSHIP LIST

Parent Table	Relationship	Child Table
USERS	1 → N	BOOKINGS (as Customer)
USERS	1 → N	FLIGHTS (as Provider)
USERS	1 → N	HOTELS (as Provider)
USERS	1 → N	CABS (as Provider)
USERS	1 → N	BOOKINGS (as Provider)
FLIGHTS	1 → N	BOOKINGS
HOTELS	1 → N	BOOKINGS
CABS	1 → N	BOOKINGS