EPAM University Programs
DevOps external course
Module 4 Linux & Bash Essentials
TASK 4.6

1. *User management*. Here we suppose there are at least two users, namely, root and guest.
(i) Create a new user *user*
groupadd user (add group user)
useradd -g user -s /bin/bash -d /home/user -m user (added user "user with group user, with shell=bash, homedir /home/user will be created)
passwd user (change password for user)
id user (show "user" ID)
ls -ld /home/user (show permission for the folder of user)



(ii) Log in to the system as "user" (hint use **su**). (I connected directly and via su - user)



(ii) Edit **/etc/passwd** to prevent user *user* from logging in to the system. (I use vipw command to modify /etc/password and update /etc/shadow/in the same time and change shell to /usr/sbin/nologin)



2. *Content of* **/etc/passwd** and **/etc/group**.

(i) Look through **/etc/passwd** and **/etc/group** (hint: use **less** or **cat**).

(ii) Get data from **/etc/passwd** and **/etc/group** about users: *root*, *guest*, *user* (hint: filter by **grep**). (guest user is not present in my sysem)



(iii)Parse **/etc/passwd** and **/etc/group** with cut. (I used pipe to head to display 10 string only to reduce output in screenshots)

cut -f1 -d: /etc/passwd (show column 1 (username)-d: means delimiter is ":")

cut -f1,2 -d: /etc/passwd (show columns 1 and 2 (username and password (in shadow will be real hash, in passwd file – "x" only) -d: means delimiter is :)



cut -f1,7 -d: /etc/passwd (show username and shell of user)

cut -f1 -d: /etc/group (show group names)

cut -f1,2 -d: /etc/group (show group names and x like group password)


user@SmartHome: ~
mail
news
root@SmartHome:/home/user# cut -f1 -d: /etc/group | head
root
daemon
bin
sys
adm
tty
disk
lp
mail
news
root@SmartHome:/home/user# cut -f1,2 -d: /etc/group | head
root:x
daemon:x
bin:x
sys:x
adm:x
tty:x
disk:x
lp:x
mail:x
news:x
root@SmartHome:/home/user# man /etc/group
root@SmartHome:/home/user# man group
root@SmartHome:/home/user#



(iv) Try to call **less** on **/etc/shadow** and invoke

sudo less /etc/shadow

man -k shadow (display all command connected with shadow functionality)

man 5 shadow (5 means description and structure of the file shadow)

Analyze content of **/etc/shadow** based on what you've found in **man** 5 shadow. (second field is real hash of user password)



3. Dealing with **chmod**.

(i) An executable script. Open your favorite editor and put these lines into a file

#!/bin/bash

echo “Drugs are bad MKAY?”

Give name “script.sh” to the script and call to

chmod +x script.sh (add X “exec” perm (user group and other) to file)

Then you are ready to execute the script:

./**script.sh**



(ii) Suppose, you have logged in to the system as *guest*. (I used user pi) Create directory "testDir" in the **/tmp**; put some file into testDir and prohibit user *user* from visiting this directory (i.e. "testDir").



It is needed to set permission of directory=disable x bit for Other field (I used command chmod 744 testDir)



(iii) Test, if it possible to forbid an owner of some file to read to or write from this file.

Yes, it is possible read and write see screenshot with actions for details:


pi@SmartHome: /tmp/testDir
permitted by applicable law.
Last login: Fri Apr 24 07:32:18 2020 from 192.168.1.131
root@SmartHome:~# su - pi
pi@SmartHome:~ $ cd /tmp/
pi@SmartHome:/tmp $ ls -ld testDir/
drwxr--r-- 2 pi pi 4096 Apr 24 08:17 testDir/
pi@SmartHome:/tmp $ cd testDir/
pi@SmartHome:/tmp/testDir $ ls
pi@SmartHome:/tmp/testDir $ ls -la
total 12
drwxr--r-- 2 pi pi 4096 Apr 24 08:17 .
drwxrwxrwt 10 root root 4096 Apr 24 08:16 ..
-rw------- 1 pi pi 16 Apr 24 08:17 .bash_history
pi@SmartHome:/tmp/testDir $ echo "end of file" >> .bash_history
pi@SmartHome:/tmp/testDir $ chmod 500 .bash_history
pi@SmartHome:/tmp/testDir $ echo "end of file2" >> .bash_history
-bash: .bash_history: Permission denied
pi@SmartHome:/tmp/testDir $ cat .bash_history | head
sudo bash
exit
end of file
pi@SmartHome:/tmp/testDir $ chmod 600 .bash_history
pi@SmartHome:/tmp/testDir $ ls -la
total 12
drwxr--r-- 2 pi pi 4096 Apr 24 08:17 .
drwxrwxrwt 10 root root 4096 Apr 24 08:16 ..
-rw------- 1 pi pi 28 Apr 24 08:25 .bash_history
pi@SmartHome:/tmp/testDir $ chmod 300 .bash_history
pi@SmartHome:/tmp/testDir $ ls -la
total 12
drwxr--r-- 2 pi pi 4096 Apr 24 08:17 .
drwxrwxrwt 10 root root 4096 Apr 24 08:16 ..
--wx------ 1 pi pi 28 Apr 24 08:25 .bash_history
pi@SmartHome:/tmp/testDir $ cat .bash_history | head
cat: .bash_history: Permission denied
pi@SmartHome:/tmp/testDir $