



# UNIVERSITÀ DI TRENTO

## Formal Method Mod. 1 (Automated Reasoning) Laboratory 2

Giuseppe Spallitta  
[giuseppe.spallitta@unitn.it](mailto:giuseppe.spallitta@unitn.it)

Università degli studi di Trento

March 15, 2023

# Automating the encoding generation

---

- ▶ During the last lecture we spent a lot of time encoding the last problem, despite the low number of variables and constraints involved  
⇒ For harder tasks we would spend tons of hours simply in defining the DIMACS/SMT-LIB files!
- ▶ From now on we will **write some code to automate the generation of the input file and easily read the output in a human friendly style.**
- ▶ In the following examples I will use Python 3.x and the Python library **pysmt** for its simplicity and readability, but feel free to use any programming languages you are confident with (e.g. C, C++, Java and others).
- ▶ You can check all pysmt functionalities here:  
[https://pysmt.readthedocs.io/en/latest/api\\_ref.html#module-pysmt.shortcuts](https://pysmt.readthedocs.io/en/latest/api_ref.html#module-pysmt.shortcuts)

# Outline

---

## 1. Advanced SAT solving

Logic puzzles

Solving Sudoku

Nonogram

## 2. SAT incrementality and UNSAT core extraction

## 3. Homeworks



# Interview calendar

---

## Exercise 2.1: logic riddle

Bill has a series of job interviews this week (August 20th, 21st, 22nd and 23rd), each for a different type of position (copywriter, graphic design, sales rep and social media) at a different company (Alpha Plus, Laneplex, Sancode, Streeter Inc.). Using only the clues below, match each job position to its company, and determine the day for each interview and the town it will be held in. No option in any category can be used more than once.



# Interview calendar (cont.d)

## Exercise 2.1: logic riddle (cont.d)

Some clues are given to us to determine each assignment:

- ▶ The Alpha Plus interview is 2 days before the meeting for the copywriter position.
- ▶ The meeting for the graphic design position is sometime after the Sancode interview.
- ▶ Of the interview for the sales rep position and the Laneplex interview, one is on August 23rd and the other is on August 20th.
- ▶ The Streeter Inc. interview is 2 days after the Alpha Plus interview.
- ▶ On the 23rd there is no interview for social media roles

# How people usually solve it

		owners					breeds				
		Anita	Barbara	Douglas	Fernando	Ginger	beagle	bulldog	chow chow	great dane	maltese
years	2006	×		×	×				×		
	2007	×	×	×	●	×	×	×	●	×	×
	2008	●	×	×	×	×			×		
	2009	×			×				×		
	2010	×			×			×	×		×
dogs	Max					×					
	Molly	×	×	×	×	●					
	Riley			×		×					
	Samson	×				×					
	Shadow					×					

## 1. Advanced SAT solving

# Interview calendar: variables

---

As always, we first define the variables that efficiently describe the problem:

- ▶  $x_{ij}$  states if day  $i$  ( $i \in \{20\text{th}, 21\text{st}, 22\text{nd}, 23\text{rd}\}$ ) refers to a specific property, such as the company and the position available.
- ▶ For instance to store the status of August 20th we need 8 variables, one for each company and for each role. The same applies for the other 3 days, requiring  $8 * 4 = 32$  variables.
- ▶ We must define a simple function to map each variable into an indexed variable and store this mapping while generating the constraints!

Now we can encode the clues stated by the problem, one by one:

# Interview calendar: properties (1)

---

The Alpha Plus interview is 2 days before the meeting for the copywriter position.

- ▶ This means that either the Alpha Plus interview is on the 20th or the 21st of August and then the copywriter interview respectively on the 22nd or the 23rd.

$$(x_{0A} \wedge x_{2c}) \vee (x_{1A} \wedge x_{3c})$$





## Interview calendar: properties (2)

---

The meeting for the graphic design position is sometime after the Sancode interview.

- ▶ Given an interval of 4 days, we must exclude that the 20th of August is associated with the graphic design position, that the 23rd of August is associated to the Sancode interview, and that 21st and 22nd are respectively the graphic design and Sancode interviews:

$$\neg x_{0g} \wedge \neg x_{3s} \wedge \neg(x_{1g} \wedge x_{2s})$$

## Interview calendar: properties (3)

---

Of the interview for the sales rep position and the Laneplex interview, one is on August 23rd and the other is on August 20th.

$$(x_{0s} \wedge x_{3L}) \vee (x_{0L} \wedge x_{3s})$$

The Streeter Inc. interview is 2 days after the Alpha Plus interview.

$$(x_{0A} \wedge x_{2I}) \vee (x_{1A} \wedge x_{3I})$$

On the 23rd there is no interview for social media roles.

$$\neg x_{3m}$$

# Interview calendar: properties (4)

---

Do not forget to consider some hidden conditions to avoid the generation of non-valid assignments. In particular, we must encode the following properties:

- ▶ Each day must be associated with exactly one company
- ▶ Each day must be associated with exactly one position
- ▶ Each company must be associated with exactly one day
- ▶ Each position must be associated with exactly one day



# Encoding *ExactlyOne*

---

Encoding *ExactlyOne*( $x_1, \dots, x_n$ ) is easy if you split it into two simpler conditions:

$$\textit{ExactlyOne}(x_1 \dots x_n) = \textit{AtLeastOne}(x_1 \dots x_n) \wedge \textit{AtMostOne}(x_1 \dots x_n)$$

The latter conditions can be formalized (and consequently we can implement the respective function to automate the definition of the clauses) into the formulas:

$$\textit{AtLeastOne}(x_1 \dots x_n) = x_1 \vee x_2 \dots \vee x_n$$

$$\textit{AtMostOne}(x_1 \dots x_n) = \{ \neg x_i \vee \neg x_j \mid 0 \leq i < j \leq n \}$$

# Interview calendar: results

---

Now we can feed the encoding into MathSAT

⇒ The solver returns **SAT**, but probably we can write some code to quickly read the valid assignment in a human-readable format.



# Solving an hard Sudoku

## Exercise 2.2

			9			1		
							3	5
		8		7				
				5		9		
1		4	3			2		
	7				9			3
		5		2	7			
	4	9				8		
7			1				2	

Can we find the solution to this Sudoku using a SAT solver?

# Solving Sudoku: variables

---

As always, we first define the variables that efficiently describe the problem:

- ▶  $x_{ijk}$  states if number  $k$  is placed in the cell in row  $i$  and column  $j$ .
- ▶ We will instantiate  $9 * 9 * 9 = 729$  different variables.

# Solving Sudoku: properties (1)

---

The three basic rules to solve a Sudoku are the following:

- ▶ Each column contains all of the digits from 1 to 9
- ▶ Each row contains all of the digits from 1 to 9
- ▶ Each of the nine  $3 \times 3$  subgrids contains all of the digits from 1 to 9

Defining each rule is not difficult: for each digit, we encode an *ExactlyOne* constraint considering the right cells on the grid.





# Solving Sudoku: properties (2)

---

From our previous experience, there is a hidden rule that we could encode:

- ▶ Each cell must contain exactly one number

But notice how the three Sudoku basic rules already ensure the uniqueness of the digit in a single cell!



# Solving Sudoku: properties (3)

---

Lastly, we must add some constraints to indicate the digits which are already placed in the grid.

- ▶ For each digit already placed in the grid one of the 729 variables will be surely **TRUE**.
- ▶ The conjunction of all these true variables represents the specific configuration of the Sudoku we want to solve.





# Solving Sudoku: results

---

Now we can feed the encoding into MathSAT

⇒ The solver returns **SAT**, so a solution exists. A brief manipulation of the output could help us in visualizing the result.



# Solving a Nonogram

## Exercise 2.3

	2	3	4	2	2
2					
3					
3					
3 1					
1					

Your aim in these puzzles is to colour the whole grid in to black and white squares or mark with X. Beside each row of the grid are listed the lengths of the runs of black squares on that row. Above each column are listed the lengths of the runs of black squares in that column. Can we find the solution of this Nonogram?



# How people usually solve it

---



# Solving Nonogram: variables

---

As always, we first define the variables that efficiently describe the problem:

- ▶  $x_{ij}$  states if cell in row  $i$  and column  $j$  should be black.
- ▶ We will instantiate  $5 * 5 = 25$  different variables.



# Solving Nonogram: properties(1)

---

For each row and each column we must define a constraint considering the valid position of black cells. Some will be easier than the others to define; we will see all of them and try to automate the most of the process.

- ▶ For instance, row 4 is straightforward: there is a single valid color assignment for each satisfying the constraint, so we can easily encode the conjunction of this trivial and unique assignment.
- ▶ Row 5 is also trivial: exactly one of the cells should be black.



# Solving Nonogram: properties(2)

---

Let's define a constraint for a non-trivial row, the first one.

- ▶ If two subsequent cells must be black, there are 4 valid assignments to consider:

$$(x_{00} \wedge x_{01} \wedge \neg x_{02} \wedge \neg x_{03} \wedge \neg x_{04})$$

$$\vee (\neg x_{00} \wedge x_{01} \wedge x_{02} \wedge \neg x_{03} \wedge \neg x_{04})$$

$$\vee (\neg x_{00} \wedge \neg x_{01} \wedge x_{02} \wedge x_{03} \wedge \neg x_{04})$$

$$\vee (\neg x_{00} \wedge \neg x_{01} \wedge \neg x_{02} \wedge x_{03} \wedge x_{04})$$



# Solving Nonogram: properties(3)

Converting this formula into a CNF equivalent representation or writing it into a single assertion is not trivial and could be a challenging task...

⇒ But do not forget the existence of **Tseitin's transform** if you generate directly SMT-LIB files!

$$a_1 \Leftrightarrow (x_{00} \wedge x_{01} \wedge \neg x_{02} \wedge \neg x_{03} \wedge \neg x_{04})$$

$$a_2 \Leftrightarrow (\neg x_{00} \wedge x_{01} \wedge x_{02} \wedge \neg x_{03} \wedge \neg x_{04})$$

$$a_3 \Leftrightarrow (\neg x_{00} \wedge \neg x_{01} \wedge x_{02} \wedge x_{03} \wedge \neg x_{04})$$

$$a_4 \Leftrightarrow (\neg x_{00} \wedge \neg x_{01} \wedge \neg x_{02} \wedge x_{03} \wedge x_{04})$$

$$a_1 \vee a_2 \vee a_3 \vee a_4$$

# Solving Nonogram: properties(4)

---

- ▶ The idea behind the other rows and columns is similar, so we can provide a sort of generalized algorithm to manage the remaining constraints.
- ▶ In this case there are no "hidden" constraints to configure, the only clues to solve the puzzle are the the numbers near the grid.

# Solving Nonogram: results

---

Now we can feed the encoding into MathSAT

⇒ The solver returns **SAT**, so a solution exists. A brief manipulation of the output could help us in visualizing the result; given the simplicity of the chosen nomenclature we can also quickly understand the solution scanning the result.

# Outline

---

1. Advanced SAT solving
2. SAT incrementality and UNSAT core extraction
3. Homeworks

# Working as a receptionist

## Exercise 2.4: receptionist

You are a receptionist in a prestigious hotel and you are waiting 5 new guests. There are 5 available rooms, but you don't know their preferences about the room they want to book until the last moment:

- ▶ Guest A would like to choose room 1 or 2.
- ▶ Guest B would like to choose a room with an even number.
- ▶ Guest C would like the first room.
- ▶ Guest D has the same behaviour as user B.
- ▶ Guest E would like one of the external rooms.

Supposing the guests come one after the other, is there a moment where it is not possible to help every guest? How many guests can be sorted without problems?

# Working as a receptionist: modeling

---

- ▶ The core of the model is easy to define: we need a variable for each pair guest-room. For each guest and each room we define an *ExactlyOne* constraint.
- ▶ To test how many guests can be sorted without issues, we can take advantage of incremental SAT solving  
⇒ The preferences of the guests can be encoded adding selection variables and we can progressively add the various constraints

# Why incremental SAT?

---

What are the advantages of employing incremental SAT?

- ▶ SAT formula can be modified and solved again, while reusing information from previous solving steps!
- ▶ Really useful when the core model is not trivial
- ▶ Effective when applied in "Planning as SAT" problems.

# Working as a receptionist: results

---

- ▶ Automating the process we notice that, once we add the fourth guest, there is a conflict.
- ▶ Which are the elements that causes the conflict?  
⇒ We can use the *get\_core()* function to see the list of literals causing the conflict



# Outline

---

1. Advanced SAT solving
2. SAT incrementality and UNSAT core extraction
3. Homeworks



# Homeworks

## Homework 2.1: diagonal sudoku

### Diagonal Sudoku

		5				1		
			4	9	2			
9								3
	3						6	
	9						1	
	2						7	
1								8
			6	8	7			
		3				4		

Can we find the solution of this Diagonal Sudoku using a SAT solver?

Rajesh Kumar @ [www.FunWithPuzzles.com](http://www.FunWithPuzzles.com)

# Homeworks

---

## Homework 2.2: puzzle baron

Adapt the code written for exercise 2.1 to solve similar puzzles from the following website: <https://logic.puzzlebaron.com/>.

- ▶ To obtain an exercises almost identical to the one shown in class select the "3\*4 grid" and the "challenging" difficulty.
- ▶ Adapt the code to manage a "3\*5" grid, if you can.



## Homework 2.3: the $n$ -queens problem

The  $n$ -queens problem is to place  $n$  chess queens on an  $n * n$  chessboard such that no two queens are mutually attacking (i.e., in the same row, column, or diagonal).

- ▶ Solve the  $n$ -queens problem with  $n = 8$ .
- ▶ Is the solution obtained unique?