

# Multiplication of Two Bignums on a Nvidia Graphic Card

Johannes Häbe  
jh-191149@hs-weingarten.de

Maximilian Nestle  
mn-192181@hs-weingarten.de

Ravensburg-Weingarten University of Applied Sciences

June 12, 2020

## **Abstract**

This paper is about testing the performance of the NVIDIA CUDA Fast Fourier Transform library (cuFFT) by multiplying large numbers (bignums) on the graphics card. Several tests are presented, evaluated and compared.

## **1 Introduction**

The fast multiplication of two large prime numbers is necessary in some procedures to hack asymmetrical encryption algorithms like the RSA encryption. These computations are normally made on the CPU. Within this paper, General Purpose Computing On GPUs (GPGPU) is used to multiply bignum prime numbers with the help of the NVIDIA CUDA Fast Fourier Transform library (cuFFT). For this purpose, the computing time of bignum multiplication on CPU and GPU is compared and evaluated in this paper.

## **2 Hardware and environment**

For the multiplications an Acer Aspire V3-772G is used. The Acer has got a NVIDIA GTX 850M graphics card and an Intel Core i5 4200M CPU. The

graphics card disposes of 2004 MIB storage. The Acer is running the Linux distribution Ubuntu. The code that is used to multiply two bignums on the GPU is using the cuFFT library from NVIDIA. The multiplications on the CPU are done with the `BN_mul()` function which is based on the Karatsuba recursive multiplication algorithm [You98]. The `BN_mul()` function comes with the openssl library.

### 3 Measurement conditions

The times for the multiplications of the two numbers are measured up to the size of 28000 bits for each factor. The step size for the multiplications is 24 bits. That means that we did computations for numbers of the size 24 bits, 48 bits, 72 bits and so on. The numbers used for computations are created randomly. To prevent fluctuations because of random created numbers that are easy to multiply, one hundred multiplications, each with random numbers, are done for each step of 24 bits.

### 4 Evaluation of the measured times

For the time measurement the C library function `clock(void)` is used. The legend of the graphics is explained in the following:

#### CPU

The time needed for the multiplications of the two bignums on the CPU using the `BN_mul()` function.

#### GPU\_All

The sum of the times needed for GPU\_Alloc, GPU\_Calc, GPU\_Clean, CUDA\_Pre, and CUDA\_Post.

#### GPU\_Alloc

The time needed to allocate the amount of graphics card memory needed for the two bignums using `cudaMalloc()` and copying them to the graphics card memory by using `cudaMemcpy()`.

#### GPU\_Calc

The amount of time needed for the calculation of the two bignums on the GPU. This includes converting the bignums to frequency domain, multiplying them with `ComplexPointwiseMulAndScale()` and converting them back to time domain.

Table 1: Average, minimum and maximum times measured of all bit sizes.

	Times in seconds		
	<i>Minimum</i>	<i>Maximum</i>	<i>Average</i>
CPU	$1 \times 10^{-6}$	$9 \times 10^{-5}$	$4,16 \times 10^{-5}$
GPU_All	$1,72 \times 10^{-3}$	$1,48 \times 10^{-2}$	$7,19 \times 10^{-3}$
GPU_Alloc	$1,42 \times 10^{-3}$	$6,13 \times 10^{-3}$	$3,67 \times 10^{-3}$
GPU_Calc	$8,7 \times 10^{-5}$	$4,48 \times 10^{-4}$	$2,45 \times 10^{-4}$
GPU_Clean	$1,71 \times 10^{-4}$	$8,17 \times 10^{-4}$	$4,23 \times 10^{-4}$
CUDA_Pre	$8 \times 10^{-6}$	$6,88 \times 10^{-3}$	$2,44 \times 10^{-3}$
CUDA_Post	$2 \times 10^{-6}$	$9,21 \times 10^{-4}$	$3,97 \times 10^{-4}$

### GPU\_Clean

The sum of the times needed to copy the data back to the host by using `cudaMemcpy()` and to free the graphics card memory by using `cufftDestroy()` and `cudaFree()`.

### CUDA\_Pre

The time needed to prepare the data for the multiplication. The algorithm needs to convert the two numbers from the datatype bignum to float vectors. Float vectors are required for the `cudaMemcpy()` function. Also the size of the vectors needs to be adjusted, because cuFFT saves the solution in one of the initial bignums.

### CUDA\_Post


The time needed to prepare the result. This includes removing excess zeros, processing carry and turning the result from a float vector to a bignum.

In table 1 the minimum, maximum and average times for the calculations from 24 bits to 28800 bits are seen. The minimum is for all seven categories located between 24 and 120 bits, the maximum was always close to 28000 bits. We can derive from the table, that GPU\_Alloc and CUDA\_Pre cost by far the most time. With Numbers by Apple, the second grade polynomial of GPU\_Calc and CPU were computed and visualized in figure 1 with the original graphs. The slope of the blue polynomial is getting smaller, while the slope of the green polynomial is increasing.

$$GPU\_Calc_{poly}(x) = -1.269 * 10^{-10}x^2 + 3.086 * 10^{-7}x + 0.0001$$

$$CPU_{poly}(x) = 1.77 * 10^{-11}x^2 + 6.295 * 10^{-8}x - 4.799 * 10^{-6}x$$

Figure 1: GPU\_Calc (blue) and CPU (red) with computed polynomial.



It seems like the GPU is getting more effective in comparison to the CPU, the bigger the numbers get.

The measurements were also done on two more computers, to make sure, that the structure of the resulting graphs is nearly the same and not a specific result of the depending hardware of the computers. The assumption was confirmed.

## 5 Issues and Improvements

## 6 Conclusion

## References

- [You98] YOUNG, Eric: `bn_mul.c`. (1995-1998). [https://opensource.apple.com/source/OpenSSL/OpenSSL-22/openssl/crypto/bn/bn\\_mul.c.auto.html](https://opensource.apple.com/source/OpenSSL/OpenSSL-22/openssl/crypto/bn/bn_mul.c.auto.html)