

10 PIN

CAVO ENCODER + CONNETTORE VOLANTE 10 pin (Versione OEMER) ENCODER CABLE + 10 pin FLYING CONNECTOR (OEMER Version)



Cavo flessibile schermato per posa mobile in PUR

Lato motore: Connettore femmina volante size 18, 10 pin
saldato secondo lo schema sotto riportato.

Lato inverter: cavi liberi spelati e terminati, pronti per il
collegamento alla morsettiera/connettore dell'inverter.

PUR Flexible shielded encoder cable for chains.

*Motor side: 10 pin size 18 female flying connector welded in
accordance with the diagram below.*

*Inverter side: free cables ready to be connected to the inverter
terminal board/connector.*

SPECIFICHE CAVO – CABLE SPECIFICATION

Cavo Encoder 3x2x0,34+2x0,5 schermato PUR +
Connettore 10 Pin

*Encoder Cable 3x2x0,34+2x0,5 shielded PUR +
10 Pin Connector*

Lunghezze Standard Disponibili Standard Length Available

5mt


10mt

15mt

20mt

25mt

CONNESSIONI E COLORI CAVO – CONNECTION AND CABLE COLORS



PIN	Incremental TTL – HTL	Incremental Sinus 1Vp/p	Absolute Sincos HiPerface	Colore Cavo - Cable Color
A	A	COS+	SIN+	Bianco – White
B	Z	Z	Data+	Verde – Green
C	B	SIN+	COS+	Rosa – Pink
D	-	-	-	-
E	SHIELD	SHIELD	SHIELD	Bianco/Rosso - White/Red
F	+Vdc	+Vdc	+Vdc	Rosso – Red
G	0V...(GND)	0V...(GND)	0V...(GND)	Blu – Blue
H	A-	REF COS (COS-)	REF SIN	Marrone – Brown
I	Z-	Z-	Data-	Giallo – Yellow
J	B-	REF SIN (SIN-)	REF COS	Grigio – Grey

Technical data and drawings are subject to change without notice.