

1 Explainability in Reinforcement Learning

2 Maxime Alaarabiou

3 Saturday 1st August, 2026

Chapter 1

Clustering Agent Representations

As discussed in the previous chapter, current explainability methods for Reinforcement Learning still lack intrinsic approaches capable of explaining the internal mechanisms of deep neural policies. To the best of our knowledge, only [Zahavy et al., 2017] have proposed exploiting the latent space learned by neural policies in order to identify the concepts used by the agent. Its main idea is to analyze the latent representations produced by the neural network and organize them into clusters that correspond to high-level concepts.

While the core idea of this paper is closely aligned with our vision of explainability in RL, this approach suffers from two important limitations. First, the clusters are manually constructed. Such a procedure heavily depends on the user’s expertise and neither guarantees reproducibility or scales. Second, no evaluation protocol is proposed to assess the quality of the obtained clusters. Their relevance is essentially determined through visual inspection.

The Clustering Agent Representations (CAR) method proposed in this chapter addresses these two limitations. It automates concept discovery by relying on unsupervised clustering algorithms to identify the concept structure of the latent space. It introduces an objective evaluation metric based on the stability of the extracted representations across independently trained policy.

This chapter is organized as follows:

- Section 1.1 lays out the theoretical assumptions underlying the proposed CAR method, which we term the representation convergence hypothesis.
- Section 1.2 then details the CAR method itself, covering both the extraction of latent representations using surrogate policies and the automatic detection of concept structures through clustering.
- Section 1.3 finally introduces the metrics we propose for evaluation.

1.1 Representation Convergence Hypothesis

The Clustering Agent Representations (CAR) method relies on a assumption, referred to as the Representation Convergence Hypothesis. This hypothesis

follows the two assumptions established previously throughout this manuscript.

The first assumption rejects the notion that deep neural networks constitute irreducible black boxes ???. Adopting a mechanistic perspective, we consider that every process results from a sequence of causal computations. Although these computations may be highly complex, they remain explainable through the analysis of the internal mechanisms.

The second assumption states that neural networks achieve generalization by learning concepts ??. During optimization, the network progressively organizes its latent space into representations that capture the information required to solve the task.

Following these hypotheses, it becomes possible to explain the Neural Network (NN)’s process by understanding the organization of its latent space. This family of approaches is commonly referred to as mechanistic interpretability.

In mechanistic interpretability, universality refers to the consistency with which a concept is recovered across different models or independent extraction processes [Templeton et al., 2024].

The Representation Convergence Hypothesis provides a theoretical explanation for this phenomenon. We hypothesize that, for a given task and a given neural network architecture, there exists a privileged conceptual organization. This organization naturally emerges because it constitutes an efficient representation required to solve the task. Under this assumption, the universality of a concept is not merely an empirical observation but the expected consequence of a common underlying conceptual structure shared by independently learned representations.

It is important to clarify that this hypothesis does not imply convergence at the parameter level. Independently trained models are expected to converge toward different sets of weights. The proposed hypothesis concerns a abstract level of representation. We assume that the conceptual organization induced by their Latent Representation (LR) converges toward an equivalent conceptual structure, even though the numerical implementation of the networks differ.

The remainder of this chapter builds upon this hypothesis. This principle forms the theoretical foundation of the *Clustering Universality* metric, introduced in Subsection 1.3.3.

1.2 Method

As developed in Chapter ??, several hypotheses have been proposed regarding the organization of latent representations in deep neural networks. Following the work of [Zahavy et al., 2017], we analyze the latent space through clustering techniques, placing our approach within the broader field of Deep Clustering. This design choice is motivated by our rejection of the superposition hypothesis and, more generally, of any view that assumes a linearly organized concept structure, as discussed in Section ??.

The CAR methodology is composed of two main stages. The first stage trains multiple independent neural networks, called surrogate policies, which implement the same decision policy. The second stage clusters their latent representations in order to identify the underlying conceptual organization.

This section is organized as follows. In the first subsection, we justify the use of multiple surrogate policies in order to study the stability of representations.




Figure 1.1: Illustration of the Clustering Agent Representation method.

82 In the second subsection, we detail how these surrogate policies are trained so
 83 as to best match the original policy.

84 1.2.1 Multiple surrogate policies

85 The CAR method was developed with the aim of verifying the representation
 86 convergence hypothesis presented in Section 1.1. To test this hypothesis, several
 87 neural networks must be trained independently and their latent representations
 88 compared. If similar conceptual structures consistently emerge, this provides
 89 empirical evidence supporting the Representation Convergence Hypothesis.

90 In supervised learning, this protocol is straightforward since several models
 91 can be independently trained on the same target function. Reinforcement
 92 learning, introduces an additional difficulty. Because of stochastic exploration,
 93 independently trained agents are not guaranteed to converge toward the same
 94 policy. Even if they achieve comparable performance, they may solve the task
 95 using different strategies. Making it impossible to determine whether differences
 96 observed in the latent space originate from the learning dynamics or from genuine
 97 differences between the learned policies.

98 To overcome this limitation, we consider an already trained initial policy.
 99 This policy is then imitated using supervised behavioral cloning. To this end,
 100 we independently train several surrogate neural networks. Since all surrogate
 101 models approximate the same target function, they are converge toward equivalent
 102 decision policies. This makes it possible to investigate whether equivalent policies
 103 also exhibit equivalent conceptual organizations.

104 It is important to emphasize that the use of surrogate policies does not
 105 make CAR a surrogate explainability method, as defined in Subsection ???. The
 106 surrogate policies remain deep neural networks. Their role is not to simplify the
 107 decision process but to provide multiple independent realizations of the same pol-
 108 icy function, enabling the study of representation convergence. The explanations




Figure 1.2: Architecture of the surrogate policy π : the encoder maps the observation O to the embedding Z , from which the decoder reconstructs the action distribution parameters.

are therefore still extracted directly from the internal representations of deep neural networks, making CAR a fully intrinsic and mechanistic explainability approach.

1.2.2 Training surrogate policies

Throughout the remainder of this manuscript, the initial policy we aim to explain is denoted as π (represented in green in Figure 1.1). This initial policy is obtained without imposing any constraints on its origin. It may result from classical or deep reinforcement learning [?], alpha-beta algorithm [?], or even from demonstrations provided by humans [Ross and Bagnell, 2010]. The crucial requirement is the availability of a dataset containing a sufficient number of projections from the observation space $\mathcal{O}$ to the action space $\mathcal{A}$ induced by π .

The replicated policies are referred to as surrogate policies, denoted by π' (shown in red in Figure 1.1). For any observation O , the distribution over the action space produced by π' should approximate that of π as closely as possible.

The surrogate policy π' is implemented as a NN parameterized by Θ . This network is composed of two principal components: an encoder and a decoder. The encoder, represented by the function f_{enc} , maps observations from $\mathcal{O}$ into a Latent Space (LS) Z (shown in blue in Figure 1.1). The decoder then reconstructs actions from this latent representation. Figure 1.2 details this architecture, showing how the encoder layers progressively shape the observation into the embedding before the decoder reconstructs the action distribution parameters from it.

To train π' to accurately replicate the action distribution, we define a global

loss function $\mathcal{L}$ optimized via gradient descent as introduced in Section ?? . This loss, defined in Equation (1.1), is computed as the Mean Squared Error (MSE) between the parameters of the action distributions, obtained by applying the function p , which maps a distribution to its parameterization. In practice, this function does not need to be explicitly defined, as neural policies directly output the parameters of the action distribution. Once training is complete, this loss ensures that π' closely approximates the behavior of the original policy π .

$$\min_{\Theta} \sum_{O \in \mathcal{O}} \mathcal{L}(O) = \min_{\Theta} \sum_{O \in \mathcal{O}} \text{MSE}\left(p(\pi(O)), p(\pi'_{\Theta}(O))\right) \quad (1.1)$$

We denote by $\mathcal{E}$ the set of embeddings obtained by applying f_{enc} to a subset of observations $\mathbb{O} \subseteq \mathcal{O}$.

On the set $\mathcal{E}$, we use a clustering function f_{clust} to partition the point cloud of embedded observations into distinct clusters. Each observation is assigned a cluster label based on its proximity in the LS, resulting in the clustering $\mathcal{C}$.

To demonstrate this clustering faithfully reflects the agent's internal decision-making process, we introduce a set of evaluation metrics, which will be detailed in the following section.

1.3 Evaluation Metrics

A key contribution of this work is the development of three evaluation metrics, designed to assess the effectiveness of CAR:

- **Behavior Reconstruction** : it measures how well a surrogate policy faithfully reproduces the behavior of the original policy by comparing their cumulative rewards.
- **Clustering Universality** : it evaluates the stability of clusterings by measuring the similarity of clusters obtained from independently trained surrogate policies.
- **Abstraction Score** : it quantifies the extent to which LS clusters capture abstractions rather than directly reflecting the structure of observations or actions.

The remainder of this section details the motivation for each metric and describes how they are calculated. In the first subsection, we develop the *Behavior Reconstruction*. We then introduce the ARI measure, which serves as the foundation for the two other metrics introduced in the subsequent subsections, namely *Clustering Universality* and *Abstraction Score*.

The following notations will be adopted for the rest of the manuscript: we consider n surrogate policies, denoted as $\pi'_1, \dots, \pi'_n$, trained as described in Section 1.2. Each surrogate policy is associated with a projection function $f_{enc_1}, \dots, f_{enc_n}$, which is applied to the set of observations $\mathbb{O}$, yielding embeddings $\mathcal{E}_1, \dots, \mathcal{E}_n$. A clustering function is then applied to each embedding set, producing partitions $\mathcal{C}_1, \dots, \mathcal{C}_n$.

1.3.1 Behavior Reconstruction

We argue that explaining a function b that closely approximates another function a is essentially the same as explaining a . If b accurately captures the key decision patterns of a , understanding b provides meaningful insights into how a works [Guidotti et al., 2018]. In our setting, this means that generating explanations for π' that faithfully reproduce π amounts to explaining π directly. To verify that π' is indeed a faithful copy, we introduce the *Behavior Reconstruction* metric.

This metric is computed by comparing the cumulative rewards obtained by the original policy π and the surrogate policies π' over m evaluation episodes. The behavior reconstruction metric is then defined as:

$$\text{Behavior Reconstruction} = \frac{1}{n \sum_{i=1}^m g_{\pi}^i} \sum_{j=1}^n \sum_{k=1}^m g_{\pi'_j}^k \quad (1.2)$$

In imitation learning, it is unlikely to expect the surrogate policy π' to outperform the initial policy π it aims to approximate through supervised learning [Ross and Bagnell, 2010]. Consequently this metric ranges in $[0, 1]$. Values approaching 1 indicate minimal loss in reproducing π , while values close to 0 indicate poor reproduction.

We deliberately adopt a reward-based definition rather than alternatives based on actions or action distributions (e.g., training loss, accuracy, KL divergence [Shlens, 2014], or optimal transport [Peyré and Cuturi, 2020]). Since surrogate policies are trained in a supervised manner, they cannot develop strategies beyond those demonstrated by the initial policy. This means that if the rewards achieved are comparable, the surrogate policy is effectively copying the original policy’s behavior.

1.3.2 Adjusted Rand Index

Within CAR, concepts are assumed to correspond to clusters in the latent space. Combined with the Representation Convergence Hypothesis, this leads to a direct experimental prediction: if independently trained surrogate policies converge toward the same conceptual organization, then clustering their latent representations should produce similar partitions.

When a particular observation is processed by the network, it is expected to activate the same concept regardless of the specific neural implementation of the policy. If independently trained policies converge toward the same conceptual organization, then a given observation should activate the same concept across all models. As a consequence, observations grouped together within a cluster for one policy should also be grouped together for another independently trained policy.

In the clustering literature, the most used measures for comparing two partitions is the Adjusted Rand Index (ARI) [Hubert and Arabie, 1985]. This measure quantifies the agreement between cluster assignments independently of the spatial organization of the clusters. Both metrics introduced later in this chapter, namely *Clustering Universality* and *Abstraction Score*, rely on the Adjusted Rand Index. Since the ARI is a complex measure, we review its definition and discuss its main properties before introducing our proposed metrics.

The ARI is derived from the Rand Index (RI) [Rand, 1971], which measures the agreement between two partitions by considering every possible pair of point cloud. For each pair, four situations are possible: the point may belong to the same cluster in both partitions, to different clusters in both partitions, or they may disagree by being grouped together in only one of the two partitions. The Rand Index measures the proportion of pairs for which the two partitions agree:

$$\text{RI} = \frac{\text{number of agreeing pairs}}{\text{total number of pairs}}.$$

Although the Rand Index is intuitive, it suffers from an important limitation. In most clustering problems, the majority of pairs of points belong to different clusters. Consequently, even two completely independent partitions will agree on a large number of pairs, simply because both assign them to different clusters. This effect becomes more pronounced as the number of points or clusters increases.

The Adjusted Rand Index (ARI) addresses this issue by accounting for the agreement that would be expected purely by chance. It compares the observed agreement RI to the expected agreement under random partitions $\mathbb{E}[\text{RI}]$. The score is then normalized by the maximum agreement achievable beyond this random baseline, $\max(\text{RI}) - \mathbb{E}[\text{RI}]$. As a result, an ARI of 0 corresponds to the level of agreement expected from random clusterings, while an ARI of 1 indicates perfect agreement between the two partitions:

$$\text{ARI} = \frac{\text{RI} - \mathbb{E}[\text{RI}]}{\max(\text{RI}) - \mathbb{E}[\text{RI}]}$$

In practice, the ARI is computed directly from the cluster assignments of the two partitions. Let clustering A be composed of partitions $\{A_i\}$ and clustering B of partitions $\{B_j\}$. Let $a_i = |A_i|$ denote the number of samples in partition i of clustering A , and $b_j = |B_j|$ the number of samples in partition j of clustering B . Furthermore, let $n_{ij} = |A_i \cap B_j|$ be the number of samples shared by partition i of clustering A and partition j of clustering B , and let n be the total number of samples. With these definitions, the Adjusted Rand Index (ARI) can be computed as:

$$\text{ARI} = \frac{\sum_{i,j} \binom{n_{ij}}{2} - \left[\sum_i \binom{a_i}{2} \sum_j \binom{b_j}{2} \right] / \binom{n}{2}}{\frac{1}{2} \left[\sum_i \binom{a_i}{2} + \sum_j \binom{b_j}{2} \right] - \left[\sum_i \binom{a_i}{2} \sum_j \binom{b_j}{2} \right] / \binom{n}{2}}$$

1.3.3 Clustering Universality

Having introduced the Adjusted Rand Index, we can now define the *Clustering Universality* metric. While the ARI quantifies the similarity between two conceptual partitions, the objective of CAR is to assess the consistency of conceptual organizations across an entire set of independently trained surrogate policies.

To this end, the same set of observations is projected into the latent space of each surrogate policy and clustered independently. Under the Representation Convergence Hypothesis, these independently obtained partitions are expected to be similar. *Clustering Universality* quantifies this by computing the mean pairwise Adjusted Rand Index:

$$\text{Clustering Universality} = \frac{1}{\binom{n}{2}} \sum_{i=1}^n \sum_{j=0}^{i-1} \text{ARI}(\mathcal{C}_i, \mathcal{C}_j). \quad (1.3)$$

249 This metric takes values in $[-1, 1]$. A value close to 1 indicates that surrogate
 250 policies produce highly similar partitions, suggesting that the clusters reflect
 251 intrinsic properties of the policy. Conversely, a value near 0 implies that the
 252 similarity between partitions is no better than that of two randomly generated
 253 clusterings, meaning that the clustering fails to capture any meaningful structure
 254 in the policy. A negative value, on the other hand, signals that the agreement
 255 between partitions is worse than what would be expected by chance, indicating
 256 a systematic disagreement between the clusterings.

257 1.3.4 Abstraction Score

258 If *Clustering Universality* is high, it becomes important to determine what
 259 underlies this stability. Two possibilities arise:

- 260 (i) the LS merely reproduces the structure of the observation space or action
 261 distribution, offering no abstraction, as defined in Definition ??;
- 262 (ii) the LS captures similarities in decision-making processes, yielding behav-
 263 iorally meaningful clusters.

264 To distinguish among these cases, we introduce the *Abstraction Score*. This
 265 metric contextualizes latent clusterings by examining how their patterns align
 266 with reference structures derived from the raw observation and action data. We
 267 consider : $\mathcal{C}_{obs}$, the clustering in the observation space $\mathbb{O}$, and $\mathcal{C}_{act}$, the clustering
 268 in the action-space distribution parameters. The clusterings $\mathcal{C}_{obs}$ and $\mathcal{C}_{act}$ are
 269 performed using the same algorithm, distance metric, and hyperparameters as
 270 those used for $\mathcal{C}_i$ in the LS, ensuring that any biases introduced by the clustering
 271 procedure itself are minimized.

272 For each latent clustering $\mathcal{C}_i$, we define its similarity to these baselines using
 273 the ARI:

$$\begin{aligned} A_i^{obs} &= \text{ARI}(\mathcal{C}_i, \mathcal{C}_{obs}) \\ A_i^{act} &= \text{ARI}(\mathcal{C}_i, \mathcal{C}_{act}) \end{aligned}$$

274 The *Abstraction Score* is subsequently calculated as one minus the average of
 275 the maximum absolute similarity values across these two reference baselines:

$$\text{Abstraction Score} = 1 - \frac{1}{n} \sum_{i=1}^n \max(|A_i^{obs}|, |A_i^{act}|) \quad (1.4)$$

276 The *Abstraction Score* ranges from $[0, 1]$. A score around 0 means that the
 277 latent clusters are strongly aligned with either the observation or the action
 278 space, reflecting minimal abstraction, cases (i). A score close to 1 indicates that
 279 the latent clusters are independent of both the observation and action spaces,
 280 capturing abstractions that meaningfully reflect the agent’s behavior, case (ii).

281 The following chapter presents the results of applying these metrics to specific
 282 examples.

Bibliography

- [Guidotti et al., 2018] Guidotti, R., Monreale, A., Ruggieri, S., Turini, F., Pedreschi, D., and Giannotti, F. (2018). A survey of methods for explaining black box models. **Article**.
- [Hubert and Arabie, 1985] Hubert, L. and Arabie, P. (1985). Comparing partitions. Journal of classification, 2(1):193–218. **Article**.
- [Peyré and Cuturi, 2020] Peyré, G. and Cuturi, M. (2020). Computational optimal transport. **Article**.
- [Rand, 1971] Rand, W. M. (1971). Objective criteria for the evaluation of clustering methods. Journal of the American Statistical association, 66(336):846–850.
- [Ross and Bagnell, 2010] Ross, S. and Bagnell, D. (2010). Efficient reductions for imitation learning. In Teh, Y. W. and Titterton, M., editors, Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics, volume 9 of Proceedings of Machine Learning Research, pages 661–668, Chia Laguna Resort, Sardinia, Italy. PMLR. **Article**.
- [Shlens, 2014] Shlens, J. (2014). Notes on kullback-leibler divergence and likelihood. **Article**.
- [Templeton et al., 2024] Templeton, A., Conerly, T., Marcus, J., Lindsey, J., Bricken, T., Chen, B., et al. (2024). Scaling monosemanticity: Extracting interpretable features from claude 3 sonnet. Transformer Circuits Thread. **Web**.
- [Zahavy et al., 2017] Zahavy, T., Zrihem, N. B., and Mannor, S. (2017). Graying the black box: Understanding dqns. **Article**.