


DWG NO.	736990	REV.	3
---------	--------	------	---

3	83215	R.N.	98-06-17
2	81455	A.K.	98-04-22
1	80440	A.H.	98-03-30
REV.	RELEASE	BY	DATE

UNLESS OTHERWISE SPECIFIED TORQUE SOCKET HEAD CAP SCREWS TO THE FOLLOWING VALUES		
SIZE	Nm	FT-LB
M6	10	7
M8	25	18
M10	53	40
M12	95	70
M16	220	160
M20	390	290
M24	660	490
M30	1300	960
M36	2300	1700
M42	3700	2700
M48	5500	4000
THE THREAD OF THE SOCKET HEAD CAP SCREW MUST BE LIBERALLY COATED WITH GREASE BEFORE BEING INSTALLED AND TORQUED		

THIS DRAWING IS THE PROPERTY
OF HUSKY INJECTION MOLDING
SYSTEMS LTD. AND THE
INFORMATION HEREIN PRODUCED
IS STRICTLY CONFIDENTIAL.
THIS DRAWING SHALL NOT BE
REPRODUCED OR USED WITHOUT
THE WRITTEN PERMISSION OF
HUSKY INJECTION MOLDING
SYSTEMS LTD.

ISO METHOD A



THIRD ANGLE PROJECTION

HUSKY INJECTION MOLDING SYSTEMS LTD. MEDIUM TONNAGE MACHINE			
TITLE EJECTOR CYLINDER ASSY G/GL160-750 - P2/P3			
DRAWN	A. KIEDYK	98-02-03	
CHECKED	K. BOWNESS	98-02-03	
SHEET 1 OF 1	SIZE 3	DWG NO.	REV.
RELEASE 78234	SCALE NTS	736990	3