



RTM View Shell

Permission Model Workshop

Role matrix, permission-group scenarios and hands-on exercises

Training workshop C-04 — for Administrators (facilitated session)
Edition EN · 2026-07-03 · RTM View Shell

Document revision history

This table lists the revision history of this document.

Version	Date	Summary of changes	Product release ID	Shipped-with (commit/barrier)
1.0	2026-07-03	Initial (regenerated)	RTM-REL-2026.06	(pending push)

Contents

Document revision history.....	2
Contents.....	3
1. About this workshop.....	4
2. The role × feature matrix.....	4
3. The model in three rules.....	4
4. Scenario walk-throughs.....	4
Scenario A — read-only sales supervisors.....	4
Scenario B — regional editors.....	5
Scenario C — the empty-list trap.....	5
5. Lab exercises.....	6
Exercise 1 — build the sales supervisors group.....	6
Exercise 2 — prove the empty-list rule.....	6
Exercise 3 — deletion guardrail.....	6
Exercise 4 — concurrency.....	6
6. Common pitfalls.....	6
Appendix A — Answer key & facilitator notes.....	7

1. About this workshop

This is a facilitated, hands-on workshop for administrators learning to design permission groups in RTM View Shell. It pairs a short model recap with scenarios and lab exercises you complete in a test tenant. Allow about 60–90 minutes. Each exercise has an expected outcome; an answer key is in Appendix A.

You will need: a test tenant, an administrator account, and a few sample dashboards and queues to assign. The reference for every control is the Permission Groups Configuration Guide (A-03).

2. The role × feature matrix

Roles set the outer boundary; permission groups refine access within it:

Feature	Superadmin	Administrator	Editor	Viewer
Tenant management	Yes	—	—	—
Switch tenants	Yes	—	—	—
User management	Yes	Yes	—	—
Permission groups	Yes	Yes	—	—
Tenant settings / SSO	Yes	Yes	—	—
Create / edit / delete dashboard	Yes	Yes	Yes (PG)	—
View dashboard	Yes	Yes	Yes (PG)	Yes (PG)
View widget catalogue	Yes	Yes	Yes	—
View audit log	Yes	Yes	—	—

(PG) = further restricted by the user's permission group.

3. The model in three rules

1. **One group per user.** Every non-Superadmin user belongs to exactly one permission group; change the group to change access.
2. **Most-permissive wins.** Effective access is the union of the group's grants — adding a grant never reduces access.
3. **Empty list denies; backend enforces.** An empty resource list (queues, skills, BU/SG) denies all of that type; every limit is enforced in the application, not just the UI.

4. Scenario walk-throughs

Scenario A — read-only sales supervisors

Goal: supervisors view (not edit) the sales dashboards and see only sales queues. Design: a group with the Dashboards menu visible; View only on the sales dashboards; the sales queues added on the Queues tab (nothing else); the Sales business unit on BU/SG. Result: read-only sales visibility, backend-enforced.

Scenario B — regional editors

Goal: a regional team builds and edits its own dashboards but must not see other regions' data.

Design: Editor-role users in a group with Edit on the region's dashboards (creators get Full automatically), and only that region's queues and business unit assigned.

Scenario C — the empty-list trap

Symptom: a brand-new group's users see no queue data at all. Cause: the Queues tab is empty — which denies all, not allows all. Fix: add the specific queues the group should see.

5. Lab exercises

Exercise 1 — build the sales supervisors group

4. Create a group “Sales Supervisors”, active.
5. Screens tab: tick View only on two sales dashboards.
6. Queues tab: add two sales queues; add nothing else.
7. Assign a test Viewer user and sign in as them.

Expected: the user sees only the two sales dashboards (read-only) and only the two sales queues.

Exercise 2 — prove the empty-list rule

8. Create a group “Empty Test” with the Dashboards menu visible but no queues added.
9. Assign a test user and sign in.
10. Observe the queue data; then add one queue and refresh.

Expected: with an empty Queues tab the user sees no queues; after adding one, only that queue appears.

Exercise 3 — deletion guardrail

11. Try to delete a group that still has a user assigned.
12. Note the result; then move the user to another group and retry.

Expected: deletion is blocked while a user is assigned; it succeeds only after the last user is moved.

Exercise 4 — concurrency

13. Open the same group in two browser sessions.
14. Save a change in the first; then save a different change in the second.

Expected: the second save is rejected with “Record modified by another user”; reload and reapply.

6. Common pitfalls

- Assuming an empty resource list means “all” — it means “none”.
- Designing users before groups — create the groups first, then assign.
- Relying on a hidden menu for security — the backend check is what protects data.
- Forgetting that a dashboard’s creator group gets Full automatically.

Appendix A — Answer key & facilitator notes

Exercise	Expected outcome
1 — Sales Supervisors	Sees only the 2 sales dashboards (read-only) and 2 sales queues
2 — Empty-list rule	No queues with empty tab; only the added queue appears after
3 — Deletion guardrail	Blocked while a user is assigned; succeeds after reassignment
4 — Concurrency	Second save rejected — “Record modified by another user”

Facilitator tip: run Exercise 2 first if time is short — the empty-list rule is the single most common misconfiguration.