



RTM View Shell

Permission Groups Configuration

Menus, screens, queues, skills, business units & supergroups

Administrator guide A-03 — for Administrator and Superadmin

Edition EN · 2026-07-03 · RTM View Shell

Document revision history

This table lists the revision history of this document.

Version	Date	Summary of changes	Product release ID	Shipped-with (commit/barrier)
1.0	2026-07-03	Initial (regenerated)	RTM-REL-2026.06	(pending push)

Contents

Document revision history.....	2
Contents.....	3
1. How access works.....	4
2. Creating, editing and deleting a group.....	4
3. The Menu tab — which sections appear.....	4
4. The Screens tab — dashboard access.....	5
5. The resource tabs — Queues, Skills, BU / SG.....	5
6. Worked example — read-only sales supervisors.....	5
Appendix A — Menu keys and role limits.....	6
Appendix B — Dashboard access levels.....	6
Appendix C — Resource-tab rule.....	6

1. How access works

Every user except the Superadmin belongs to exactly one permission group (PG). The group, not the user, carries the access rules; to change what a user can reach you change their group, or move them to a different one. The Superadmin bypasses all permission-group checks and has full access across every tenant.

Two principles to fix in mind:

- **Most-permissive wins.** Where rules could combine, a user's effective access is the union of what their group grants — access is never reduced by adding a grant.
- **The backend enforces, not the UI.** Hiding a menu item is cosmetic. Every restriction here is also checked in the application on every request, so a user cannot reach restricted data by guessing a URL or calling the API directly.

Permission groups are managed on the Permission Groups screen (/admin/permission-groups): a list of groups on the left, an editor with five tabs on the right.

2. Creating, editing and deleting a group

Create a group with “New group”, give it a name (unique within your organisation) and an optional description, and mark it active. **Edit** by selecting its card and adjusting the tabs, then saving. A group can be made inactive without deleting it.

Delete is only allowed when no users are assigned; if any are, the delete control is disabled and tells you how many users must be moved first. Saving a change refreshes the group's cached permissions immediately; live sessions pick it up on their next action.

Concurrency

If two administrators edit the same group at once, the second save is rejected with “Record modified by another user”. Reload and reapply.

3. The Menu tab — which sections appear

The Menu tab controls which navigation items the group's users see. Some items are inherently limited to certain roles regardless of the group:

Menu item	Permission key	Available to roles
Dashboards / Screens	menu.dashboards	All
User Management	menu.users	Superadmin, Administrator
Permission Groups	menu.permissionGroups	Superadmin, Administrator
Widget Catalogue	menu.widgetCatalog	Superadmin, Administrator, Editor
Audit	menu.audit	Superadmin, Administrator
Tenant Settings	menu.tenantSettings	Superadmin, Administrator
Tenant Management	menu.tenants	Superadmin only

Rows that do not apply to the group's role are greyed out. The menu only governs visibility — the screens are still protected by the tabs below and by the backend.

4. The Screens tab — dashboard access

The Screens tab gives each group three independent permissions — View, Edit, Delete — via checkboxes:

Permission	Meaning
View	Open and read the dashboard
Edit	Change it (implies View)
Delete	Remove it (implies View)
Full	View + Edit + Delete

When a user creates a dashboard, their own group is granted Full on it automatically. A dashboard also appears to a user if it is marked public, unless the group is explicitly denied.

5. The resource tabs — Queues, Skills, BU / SG

The remaining tabs restrict the contact-centre resources whose data the group may see: Queues, Skills, Business Units and Agent Supergroups. Each is a list you add allowed items to.

An empty list means access is denied, not allowed

If a group's Queues tab is empty, the group sees no queues — not all of them. To grant access you add the specific items. This is the safe default: a new or misconfigured group exposes nothing until you deliberately grant it.

Business Units and Agent Supergroups share one tab and scope a group's view of the organisation — e.g. limiting a regional team to its own business unit. As with menus, these limits are enforced in the application layer, not merely the UI.

6. Worked example — read-only sales supervisors

1. Create the group “Sales Floor Supervisors”, active.
2. Menu tab: leave Dashboards visible; admin-only items stay greyed out.
3. Screens tab: tick View (not Edit or Delete) on each sales dashboard.
4. Queues tab: add the specific sales queues — and nothing else.
5. BU / SG tab: add the Sales business unit.
6. Save. Assign supervisors to this group in User Management (A-02).

The supervisors now see exactly the sales dashboards and queues, read-only — and the backend enforces it even against a crafted direct request.

Appendix A — Menu keys and role limits

See §3. Menu visibility is necessary but never sufficient — the Screens and resource tabs plus the backend check are what protect data.

Appendix B — Dashboard access levels

View = read · Edit = change (implies View) · Delete = remove (implies View) · Full = View+Edit+Delete. A dashboard's creator group receives Full automatically. Public dashboards are visible to all tenant users unless a group is explicitly denied.

Appendix C — Resource-tab rule

For Queues, Skills, Business Units and Agent Supergroups: an empty list denies all of that type; grants are explicit additions; enforcement is in the application layer. Editing a group refreshes its cached permissions immediately for live sessions.