



RTM View Shell

SSO Integration Guide

OIDC, SAML 2.0 and AD/LDAP — per-tenant federation

Administrator guide A-05 — for Administrator and Superadmin

Edition EN · 2026-07-03 · RTM View Shell

Document revision history

This table lists the revision history of this document.

Version	Date	Summary of changes	Product release ID	Shipped-with (commit/barrier)
1.0	2026-07-03	Initial (regenerated)	RTM-REL-2026.06	(pending push)

Contents

Document revision history.....	2
Contents.....	3
1. What SSO gives you.....	4
2. Where SSO is configured.....	4
3. Claim mapping.....	4
4. Just-in-time provisioning.....	4
5. SSO and two-factor.....	5
6. Choosing a protocol.....	5
7. Verification and troubleshooting.....	5
Appendix A — Provider field reference.....	6
Appendix B — Claim mapping (minimum).....	6
Appendix C — MFA interplay.....	6

1. What SSO gives you

Single Sign-On lets a tenant's users authenticate with their existing corporate identity instead of a separate RTM View Shell password. It is configured per tenant and supports three protocols:

- **OpenID Connect (OIDC)** — modern token-based federation.
- **SAML 2.0** — the long-established enterprise standard.
- **Active Directory / LDAP** — direct directory authentication.

When SSO is active, the sign-in page offers a prominent Sign in with SSO option; local sign-in can remain as a fallback.

Release status

In the current version SSO is a configurable stub: the screens accept and store a provider configuration, but live federation is delivered in a later sprint. Until then, users sign in with local accounts plus e-mail two-factor. Everything you configure now is preserved and activates when the provider integration ships.

2. Where SSO is configured

A tenant's SSO settings live with its Tenant Settings (A-07). For the chosen protocol you provide:

Field	Used by	Notes
Provider	all	OIDC, SAML2, or AD_LDAP
Metadata / discovery URL	OIDC, SAML2	The provider's discovery or metadata endpoint
Client ID	OIDC	The application's client identifier at the provider
Client secret	OIDC	Stored encrypted; never shown in plaintext
Claim mappings	all	How provider claims map to local user fields (§3)
Active	all	Turns this configuration on

Credentials are encrypted at rest; only an administrator can replace them, and they are never displayed back.

3. Claim mapping

A claim mapping tells RTM View Shell how to read the provider's assertion and fill in the local user. At minimum map the user identifier and e-mail; optionally first/last name and a tenant-selector claim. The tenant is normally determined by the subdomain; a claim-based mapping is available where one address serves several tenants.

4. Just-in-time provisioning

On a successful SSO sign-in, if no local account exists yet, RTM View Shell creates one from the mapped claims; if it exists, its mapped fields are updated. New SSO users still need a permission group to see anything — decide whether to assign a default group at rollout or provision + assign manually before first sign-in.

5. SSO and two-factor

If your provider performs its own multi-factor check and asserts it (amr contains mfa), RTM View Shell skips its system-level code — the user is not asked twice. If the provider does not assert MFA, the system applies its own two-factor. Either way you keep a second factor without double-prompting.

6. Choosing a protocol

- **Choose OIDC** for modern providers (Azure AD / Entra ID, Okta, Google Workspace, Keycloak) — simplest to operate, uses discovery.
- **Choose SAML 2.0** when your IdP or policy standardises on SAML.
- **Choose AD / LDAP** to authenticate against an on-premises directory without a federation layer.

7. Verification and troubleshooting

When SSO goes live, verify end-to-end: a test user reaches the provider from the SSO button, returns authenticated, lands in the correct tenant, and has the expected permission group. Common issues: a mismatched return URL/audience, a claim mapping that doesn't match the provider's actual claim names, or a user with no permission group. The audit log records each SSO.Login — the first place to look.

Appendix A — Provider field reference

See §2. The client secret and credentials are encrypted at rest and never displayed back; replace rather than view them.

Appendix B — Claim mapping (minimum)

Map at least the user identifier and e-mail; optionally first/last name and a tenant-selector claim. Tenant is normally taken from the subdomain. New users are provisioned just-in-time and need a permission group assigned to gain access.

Appendix C — MFA interplay

Provider asserts `amr=mfa` → system 2FA skipped. Provider does not assert MFA → system e-mail 2FA applies. Either path keeps a second factor without double-prompting.