Exemple d’utilisation Web-Dir-Finder-Pro

L'environnement virtuel (VENV)

```
┌──(root㉿urus)-[/home/urus/Bureau]
└─# python3 -m venv venv

┌──(root㉿urus)-[/home/urus/Bureau]
└─# source venv/bin/activate
```

Installer les dépendances

```
┌──(venv)─(root㉿urus)-[/home/urus/Bureau]
└─# pip install requests
Collecting requests
  Using cached requests-2.33.1-py3-none-any.whl.metadata (4.8 kB)
Collecting charset_normalizer<4,⩾2 (from requests)
  Using cached charset_normalizer-3.4.7-cp313-cp313-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl.metadata (40 kB)
Collecting idna<4,⩾2.5 (from requests)
  Using cached idna-3.11-py3-none-any.whl.metadata (8.4 kB)
Collecting urllib3<3,⩾1.26 (from requests)
  Using cached urllib3-2.6.3-py3-none-any.whl.metadata (6.9 kB)
Collecting certifi⩾2023.5.7 (from requests)
  Using cached certifi-2026.2.25-py3-none-any.whl.metadata (2.5 kB)
Using cached requests-2.33.1-py3-none-any.whl (64 kB)
Using cached charset_normalizer-3.4.7-cp313-cp313-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (215 kB)
Using cached idna-3.11-py3-none-any.whl (71 kB)
Using cached urllib3-2.6.3-py3-none-any.whl (131 kB)
Using cached certifi-2026.2.25-py3-none-any.whl (153 kB)
Installing collected packages: urllib3, idna, charset_normalizer, certifi, requests
Successfully installed certifi-2026.2.25 charset_normalizer-3.4.7 idna-3.11 requests-2.33.1 urllib3-2.6.3
```

Cloner le dépôt

```
┌──(venv)─(root㉿urus)-[/home/urus/Bureau]
└─# git clone https://github.com/Maxime288/Web-Dir-Finder-Pro.git
Clonage dans 'Web-Dir-Finder-Pro' ...
remote: Enumerating objects: 12, done.
remote: Counting objects: 100% (12/12), done.
remote: Compressing objects: 100% (8/8), done.
remote: Total 12 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
Réception d'objets: 100% (12/12), 6.17 Kio | 631.00 Kio/s, fait.
Résolution des deltas: 100% (1/1), fait.
```

Je me mets dans le dossier Web-Dir-Finder-Pro et je donne le droit de lancer le script :

```
┌──(venv)─(root㉿urus)-[/home/urus/Bureau]
└─# cd Web-Dir-Finder-Pro
```

```
┌──(venv)─(root㉿urus)-[/home/urus/Bureau/Web-Dir-Finder-Pro]
└─# chmod +x web_dir_finder.py
```

Je lance le script :

Résultat :

```
┌──(venv)─(root㉿urus)-[/home/urus/Bureau/Web-Dir-Finder-Pro]
└─# python3 web_dir_finder.py -u http://192.168.1.134 -w common.txt -t 20

  __          __  _      _____  _
  \ \        / / | |    |  __ \(_)
   \ \  ^  / /__| |__  | |  | |_ _ __
    \ V  V / _ \ '_ \ | |  | | | '__|
     \  ^  /  __/ |_) || |__| | | |
      V  V \___|_.__/ _____/|_|_|
          Multi-Threaded Directory Discovery v1.1

 [*] Cible   : http://192.168.1.134
 [*] Threads : 20
 [*] Début   : 21:54:19

 [i] Chargement de 5 mots ...

[>] 301 Redirect    : /twiki                → http://192.168.1.134/twiki/
[>] 301 Redirect    : /mutillidae           → http://192.168.1.134/mutillidae/
[>] 301 Redirect    : /phpMyAdmin           → http://192.168.1.134/phpMyAdmin/
[>] 301 Redirect    : /dav                  → http://192.168.1.134/dav/
[>] 301 Redirect    : /dvwa                 → http://192.168.1.134/dvwa/


[*] Scan terminé à 21:54:19
```