

C8E

0.1

Generated by Doxygen 1.7.2

Fri Dec 24 2010 18:11:17



# Contents

<b>1</b>	<b>File Index</b>	<b>1</b>
1.1	File List	1
<b>2</b>	<b>File Documentation</b>	<b>3</b>
2.1	src/C8E.c File Reference	3
2.1.1	Function Documentation	3
2.1.1.1	main	3
2.1.1.2	printUsage	3
2.2	src/CartridgeReader.c File Reference	4
2.2.1	Function Documentation	4
2.2.1.1	readCartridge	4
2.3	src/CartridgeReader.h File Reference	4
2.3.1	Detailed Description	4
2.3.2	Function Documentation	5
2.3.2.1	readCartridge	5
2.4	src/CPU.c File Reference	5
2.4.1	Detailed Description	6
2.4.2	Function Documentation	6
2.4.2.1	cleanupCPU	6
2.4.2.2	CPUTick	6
2.4.2.3	handleOpCode	6
2.4.2.4	setupCPU	6
2.5	src/CPU.h File Reference	6
2.5.1	Detailed Description	7
2.5.2	Define Documentation	7
2.5.2.1	MAX_STACK_SIZE	7
2.5.3	Function Documentation	7
2.5.3.1	cleanupCPU	7
2.5.3.2	setupCPU	7
2.6	src/Display.c File Reference	7
2.6.1	Define Documentation	8
2.6.1.1	DISPLAY_IDLE_TIME	8
2.6.1.2	SCREEN_HEIGHT	8
2.6.1.3	SCREEN_RATIO	8
2.6.1.4	SCREEN_WIDTH	8
2.6.2	Function Documentation	8
2.6.2.1	cleanupDisplay	8
2.6.2.2	clearScreen	9
2.6.2.3	render	9

2.6.2.4	reshape	9
2.6.2.5	setupDisplay	9
2.7	src/Display.h File Reference	9
2.7.1	Detailed Description	10
2.7.2	Function Documentation	10
2.7.2.1	cleanupDisplay	10
2.7.2.2	clearScreen	10
2.7.2.3	drawSprite	10
2.7.2.4	setupDisplay	10
2.8	src/Logs.c File Reference	11
2.8.1	Function Documentation	11
2.8.1.1	addEntry	11
2.8.1.2	closeLogs	11
2.8.1.3	setupLogs	11
2.9	src/Logs.h File Reference	12
2.9.1	Define Documentation	12
2.9.1.1	DEFAULT_DEBUG_LEVEL	12
2.9.1.2	DEFAULT_OUTPUT_FILENAME	12
2.9.2	Enumeration Type Documentation	13
2.9.2.1	DEBUG_LEVELS	13
2.9.3	Function Documentation	13
2.9.3.1	addEntry	13
2.9.3.2	closeLogs	13
2.9.3.3	setupLogs	13
2.10	src/Memory.c File Reference	14
2.10.1	Detailed Description	14
2.10.2	Function Documentation	14
2.10.2.1	cleanupMemory	14
2.10.2.2	read	15
2.10.2.3	setupMemory	15
2.10.2.4	write	15
2.11	src/Memory.h File Reference	15
2.11.1	Define Documentation	16
2.11.1.1	DATA_SPACE_START	16
2.11.1.2	DATA_SPACE_STOP	16
2.11.1.3	MAX_REGISTERS	17
2.11.1.4	RESERVED_MEMORY_START	17
2.11.1.5	RESERVED_MEMORY_STOP	17
2.11.2	Function Documentation	17
2.11.2.1	cleanupMemory	17
2.11.2.2	read	17
2.11.2.3	setupMemory	17
2.11.2.4	write	18

# Chapter 1

## File Index

### 1.1 File List

Here is a list of all files with brief descriptions:

src/ <a href="#">C8E.c</a> . . . . .	3
src/ <a href="#">CartridgeReader.c</a> . . . . .	4
src/ <a href="#">CartridgeReader.h</a> (Define all functions, variables and defines for cartridge management ) . . . . .	4
src/ <a href="#">CPU.c</a> . . . . .	5
src/ <a href="#">CPU.h</a> . . . . .	6
src/ <a href="#">Display.c</a> . . . . .	7
src/ <a href="#">Display.h</a> (Define all functions, variables and defines for display management ) . . . . .	9
src/ <a href="#">Logs.c</a> . . . . .	11
src/ <a href="#">Logs.h</a> . . . . .	12
src/ <a href="#">Memory.c</a> (Define all functions, variables and defines for memory management ) . . . . .	14
src/ <a href="#">Memory.h</a> . . . . .	15



## Chapter 2

# File Documentation

### 2.1 src/C8E.c File Reference

```
#include <GLUT/glut.h>
#include <stdlib.h>
#include "Logs.h"
#include "Memory.h"
#include "CartridgeReader.h"
#include "Display.h"
#include "CPU.h"
```

#### Functions

- void [printUsage](#) ()
- int [main](#) (int argc, char \*\*argv)

#### 2.1.1 Function Documentation

##### 2.1.1.1 int main ( int *argc*, char \*\* *argv* )

Definition at line 24 of file C8E.c.

##### 2.1.1.2 void printUsage ( )

Definition at line 15 of file C8E.c.

## 2.2 src/CartridgeReader.c File Reference

```
#include "CartridgeReader.h"
#include <stdio.h>
```

### Functions

- int [readCartridge](#) (const char \*const filename, unsigned char \*data)  
*Provide a pointer to the cartridge data.*

### 2.2.1 Function Documentation

2.2.1.1 int [readCartridge](#) ( const char \*const filename, unsigned char \* data )

Provide a pointer to the cartridge data.

#### Parameters

in	filename	Point the file to load into memory
out	data	Buffer that eventually receive the cartridge data. It must be initialized and big enough.

#### Returns

The number of bytes read if the file exists, -1 otherwise.

Definition at line 30 of file CartridgeReader.c.

## 2.3 src/CartridgeReader.h File Reference

Define all functions, variables and defines for cartridge management.

### Functions

- int [readCartridge](#) (const char \*const filename, unsigned char \*data)  
*Provide a pointer to the cartridge data.*

### 2.3.1 Detailed Description

Define all functions, variables and defines for cartridge management.

#### Version

0.1



**Date**

December 12, 2010

**Author**

Maxime Gaudin

Definition in file [CartridgeReader.h](#).

**2.3.2 Function Documentation****2.3.2.1 int readCartridge ( const char \*const filename, unsigned char \* data )**

Provide a pointer to the cartridge data.

**Parameters**

in	filename	Point the file to load into memory
out	data	Buffer that eventually receive the cartridge data. It must be initialized and big enough.

**Returns**

The number of bytes read if the file exists, -1 otherwise.

Definition at line 30 of file CartridgeReader.c.

**2.4 src/CPU.c File Reference**

```
#include "CPU.h"
#include <GLUT/glut.h>
#include <stdlib.h>
#include <time.h>
#include "Logs.h"
#include "Display.h"
#include "Memory.h"
```

**Functions**

- void [CPUTick](#) (int)
- int [setupCPU](#) ()
- void [cleanupCPU](#) ()
- void [handleOpCode](#) ()

### 2.4.1 Detailed Description

#### Version

0.1

#### Date

December 13, 2010

#### Author

Maxime Gaudin

Definition in file [CPU.c](#).

### 2.4.2 Function Documentation

#### 2.4.2.1 void cleanupCPU ( )

Definition at line 88 of file CPU.c.

#### 2.4.2.2 void CPUTick ( int *na* )

Definition at line 383 of file CPU.c.

#### 2.4.2.3 void handleOpCode ( )

Definition at line 389 of file CPU.c.

#### 2.4.2.4 int setupCPU ( )

Definition at line 65 of file CPU.c.

## 2.5 src/CPU.h File Reference

### Defines

- #define [MAX\\_STACK\\_SIZE](#) 0xF  
*Define the maximum stack size, i.e. the maximum amount of subroutine calls.*

### Functions

- int [setupCPU](#) ()
- void [cleanupCPU](#) ()

### 2.5.1 Detailed Description

#### Version

0.1

#### Date

December 12, 2010

#### Author

Maxime Gaudin

Definition in file [CPU.h](#).

### 2.5.2 Define Documentation

#### 2.5.2.1 #define MAX\_STACK\_SIZE 0xF

Define the maximum stack size, i.e. the maximum amount of subroutine calls.

Definition at line 31 of file CPU.h.

### 2.5.3 Function Documentation

#### 2.5.3.1 void cleanupCPU ( )

Definition at line 88 of file CPU.c.

#### 2.5.3.2 int setupCPU ( )

Definition at line 65 of file CPU.c.

## 2.6 src/Display.c File Reference

```
#include "Display.h"
#include <string.h>
#include <stdlib.h>
#include <GLUT/glut.h>
#include "Logs.h"
```

#### Defines

- #define [SCREEN\\_WIDTH](#) 64

- #define `SCREEN_HEIGHT` 32
- #define `SCREEN_RATIO` 10
- #define `DISPLAY_IDLE_TIME` 16

## Functions

- void `render` ()
- void `reshape` (int width, int height)
- int `setupDisplay` (int argc, char \*\*argv)  
*Setup all display related memory buffer and glut framework.*
- int `cleanupDisplay` ()
- int `clearScreen` ()  
*Clear screen.*

### 2.6.1 Define Documentation

#### 2.6.1.1 #define `DISPLAY_IDLE_TIME` 16

Definition at line 43 of file Display.c.

#### 2.6.1.2 #define `SCREEN_HEIGHT` 32

Definition at line 40 of file Display.c.

#### 2.6.1.3 #define `SCREEN_RATIO` 10

Definition at line 41 of file Display.c.

#### 2.6.1.4 #define `SCREEN_WIDTH` 64

Definition at line 39 of file Display.c.

### 2.6.2 Function Documentation

#### 2.6.2.1 int `cleanupDisplay` ( )

Definition at line 65 of file Display.c.

### 2.6.2.2 int clearScreen ( )

Clear screen.

#### Returns

1 if any pixel has been erase, 0 Otherwise.

Definition at line 110 of file Display.c.

### 2.6.2.3 void render ( )

Definition at line 84 of file Display.c.

### 2.6.2.4 void reshape ( int width, int height )

Definition at line 71 of file Display.c.

### 2.6.2.5 int setupDisplay ( int argc, char \*\* argv )

Setup all display related memory buffer and glut framework.

Definition at line 50 of file Display.c.

## 2.7 src/Display.h File Reference

Define all functions, variables and defines for display management.

### Functions

- int [setupDisplay](#) (int argc, char \*\*argv)  
*Setup all display related memory buffer and glut framework.*
- int [cleanupDisplay](#) ()
- int [drawSprite](#) (unsigned char X, unsigned char Y, const char \*const spriteData, unsigned char len)  
*Display a [len] byte sprite contained into [spriteData] at ([X], [Y]). TECHNICAL DESCRIPTION TODO.*
- int [clearScreen](#) ()  
*Clear screen.*

### 2.7.1 Detailed Description

Define all functions, variables and defines for display management.

**Version**

0.1

**Date**

December 12, 2010

**Author**

Maxime Gaudin

Definition in file [Display.h](#).

### 2.7.2 Function Documentation

#### 2.7.2.1 int cleanupDisplay ( )

Definition at line 65 of file Display.c.

#### 2.7.2.2 int clearScreen ( )

Clear screen.

**Returns**

1 if any pixel has been erase, 0 Otherwise.

Definition at line 110 of file Display.c.

#### 2.7.2.3 int drawSprite ( unsigned char *X*, unsigned char *Y*, const char \*const *spriteData*, unsigned char *len* )

Display a [len] byte sprite contained into [spriteData] at ([X], [Y]). TECHNICAL DESCRIPTION TODO.

**Returns**

1 if any pixel has been erase, 0 Otherwise.

#### 2.7.2.4 int setupDisplay ( int *argc*, char \*\* *argv* )

Setup all display related memory buffer and glut framework.

Definition at line 50 of file Display.c.

## 2.8 src/Logs.c File Reference

```
#include "Logs.h"
```

### Functions

- int [setupLogs](#) (int redirect, unsigned char debugLevel, char \*const outputFile-name)  
*Setup output log file and debug level to values passed in paramaters. Moreover, a file descriptor is created and initialized. if [redirect], log are also written in stdout.*
- int [closeLogs](#) ()  
*Close output log file descriptor and flush file buffer.*
- void [addEntry](#) (unsigned char level, const char \*const message)  
*Add new entry in output log file if [level] is below or equal to debug level.*

### 2.8.1 Function Documentation

#### 2.8.1.1 void addEntry ( unsigned char level, const char \*const message )

Add new entry in output log file if [level] is below or equal to debug level.

Definition at line 56 of file Logs.c.

#### 2.8.1.2 int closeLogs ( )

Close output log file descriptor and flush file buffer.

#### Returns

0 if success, 0 otherwise.

Definition at line 50 of file Logs.c.

#### 2.8.1.3 int setupLogs ( int redirect, unsigned char debugLevel, char \*const outputFilename )

Setup output log file and debug level to values passed in paramaters. Moreover, a file descriptor is created and initialized. if [redirect], log are also written in stdout.

#### Returns

0 if success, 0 otherwise.

Definition at line 36 of file Logs.c.

## 2.9 src/Logs.h File Reference

```
#include <stdio.h>
```

### Defines

- `#define DEFAULT_DEBUG_LEVEL 1`  
*Specifies the default debug level : Warning.*
- `#define DEFAULT_OUTPUT_FILENAME "DEBUG_LOGS"`  
*Specifies the default output filename, i.e. the file where log will be written.*

### Enumerations

- `enum DEBUG_LEVELS {`  
    `ERROR = 0, WARNING = 1, DRAWING = 2, DISASSEMBLY = 3,`  
    `LOW_LEVEL_OPERATION = 4 }`

### Functions

- `int setupLogs (int redirect, unsigned char debugLevel, char *const outputFile-name)`  
*Setup output log file and debug level to values passed in parameters. Moreover, a file descriptor is created and initialized. if [redirect], log are also written in stdout.*
- `int closeLogs ()`  
*Close output log file descriptor and flush file buffer.*
- `void addEntry (unsigned char level, const char *const message)`  
*Add new entry in output log file if [level] is below or equal to debug level.*

#### 2.9.1 Define Documentation

##### 2.9.1.1 `#define DEFAULT_DEBUG_LEVEL 1`

Specifies the default debug level : Warning.

Definition at line 23 of file Logs.h.

##### 2.9.1.2 `#define DEFAULT_OUTPUT_FILENAME "DEBUG_LOGS"`

Specifies the default output filename, i.e. the file where log will be written.

Definition at line 26 of file Logs.h.



## 2.9.2 Enumeration Type Documentation

### 2.9.2.1 enum DEBUG\_LEVELS

Enumerator:

*ERROR*

*WARNING*

*DRAWING*

*DISASSEMBLY*

*LOW\_LEVEL\_OPERATION*

Definition at line 20 of file Logs.h.

## 2.9.3 Function Documentation

### 2.9.3.1 void addEntry ( unsigned char *level*, const char \*const *message* )

Add new entry in output log file if [level] is below or equal to debug level.

Definition at line 56 of file Logs.c.

### 2.9.3.2 int closeLogs ( )

Close output log file descriptor and flush file buffer.

**Returns**

0 if success, 0 otherwise.

Definition at line 50 of file Logs.c.

### 2.9.3.3 int setupLogs ( int *redirect*, unsigned char *debugLevel*, char \*const *outputFilename* )

Setup output log file and debug level to values passed in paramaters. Moreover, a file descriptor is created and initialized. if [redirect], log are also written in stdou.

**Returns**

0 if success, 0 otherwise.

Definition at line 36 of file Logs.c.

## 2.10 src/Memory.c File Reference

Define all functions, variables and defines for memory management.

```
#include "Memory.h"
#include "Logs.h"
#include <stdlib.h>
#include <string.h>
```

### Functions

- int [setupMemory](#) ()  
*Initialize memory to 0.*
- void [cleanupMemory](#) ()  
*Cleanup all memory.*
- int [write](#) (unsigned short addr, unsigned char \*const data, unsigned int len)  
*write [len] bytes from [data] into memory at adress [addr]*
- int [read](#) (short addr, unsigned short len, unsigned char \*const buffer)  
*Read [len] bytes of data from address [addr] to buffer.*

### 2.10.1 Detailed Description

Define all functions, variables and defines for memory management.

#### Version

0.1

#### Date

December 12, 2010

#### Author

Maxime Gaudin

Definition in file [Memory.c](#).

### 2.10.2 Function Documentation

#### 2.10.2.1 void [cleanupMemory](#) ( )

Cleanup all memory.

Definition at line 39 of file Memory.c.

### 2.10.2.2 int read ( short *addr*, unsigned short *len*, unsigned char \*const *buffer* )

Read [*len*] bytes of data from address [*addr*] to buffer.

#### Parameters

in	<i>addr</i>	Address where read begins
in	<i>len</i>	Number of bytes read
out	<i>buffer</i>	Pointer to the data buffer

#### Returns

0 if success, 1 otherwise.

Definition at line 56 of file Memory.c.

### 2.10.2.3 int setupMemory ( )

Initialize memory to 0.

#### Returns

0 if success, 1 otherwise.

Definition at line 28 of file Memory.c.

### 2.10.2.4 int write ( unsigned short *addr*, unsigned char \*const *data*, unsigned int *len* )

write [*len*] bytes from [*data*] into memory at adress [*addr*]

#### Parameters

in	<i>addr</i>	Address where data will be written
in	<i>data</i>	Pointer to data buffer
in	<i>len</i>	Number of byte written

#### Returns

0 if success, 1 otherwise.

Definition at line 44 of file Memory.c.

## 2.11 src/Memory.h File Reference

### Defines

- #define [RESERVED\\_MEMORY\\_START](#) 0x0  
*Specifies where memory starts (0x0, what a surprise isn't it ??).*

- `#define RESERVED_MEMORY_STOP 0x200`  
*Specifies where the memory stops.*
- `#define DATA_SPACE_START 0x200`  
*Specifies the beginning of the data space.*
- `#define DATA_SPACE_STOP 0xFF`  
*Specifies the end of the data space.*
- `#define MAX_REGISTERS 0xF`  
*Specifies the maximum number of registers..*

## Functions

- `int setupMemory ()`  
*Initialize memory to 0.*
- `void cleanupMemory ()`  
*Cleanup all memory.*
- `int write (unsigned short addr, unsigned char *const data, unsigned int len)`  
*write [len] bytes from [data] into memory at adress [addr]*
- `int read (short addr, unsigned short len, unsigned char *const buffer)`  
*Read [len] bytes of data from address [addr] to buffer.*

### 2.11.1 Define Documentation

#### 2.11.1.1 `#define DATA_SPACE_START 0x200`

Specifies the beginning of the data space.

Definition at line 36 of file Memory.h.

#### 2.11.1.2 `#define DATA_SPACE_STOP 0xFF`

Specifies the end of the data space.

Definition at line 38 of file Memory.h.

### 2.11.1.3 #define MAX\_REGISTERS 0xF

Specifies the maximum number of registers..

Definition at line 41 of file Memory.h.

### 2.11.1.4 #define RESERVED\_MEMORY\_START 0x0

Specifies where memory starts (0x0, what a surprise isn't it ??).

Definition at line 31 of file Memory.h.

### 2.11.1.5 #define RESERVED\_MEMORY\_STOP 0x200

Specifies where the memory stops.

Definition at line 33 of file Memory.h.

## 2.11.2 Function Documentation

### 2.11.2.1 void cleanupMemory ( )

Cleanup all memory.

Definition at line 39 of file Memory.c.

### 2.11.2.2 int read ( short *addr*, unsigned short *len*, unsigned char \*const *buffer* )

Read [*len*] bytes of data from address [*addr*] to buffer.

#### Parameters

in	<i>addr</i>	Address where read begins
in	<i>len</i>	Number of bytes read
out	<i>buffer</i>	Pointer to the data buffer

#### Returns

0 if success, 1 otherwise.

Definition at line 56 of file Memory.c.

### 2.11.2.3 int setupMemory ( )

Initialize memory to 0.

#### Returns

0 if success, 1 otherwise.

Definition at line 28 of file Memory.c.

**2.11.2.4** `int write ( unsigned short addr, unsigned char *const data, unsigned int len )`

write [len] bytes from [data] into memory at adress [addr]

**Parameters**

in	<i>addr</i>	Address where data will be written
in	<i>data</i>	Pointer to data buffer
in	<i>len</i>	Number of byte written

**Returns**

0 if success, 1 otherwise.

Definition at line 44 of file Memory.c.

# Index

- addEntry
  - Logs.c, [11](#)
  - Logs.h, [13](#)
- C8E.c
  - main, [3](#)
  - printUsage, [3](#)
- CartridgeReader.c
  - readCartridge, [4](#)
- CartridgeReader.h
  - readCartridge, [5](#)
- cleanupCPU
  - CPU.c, [6](#)
  - CPU.h, [7](#)
- cleanupDisplay
  - Display.c, [8](#)
  - Display.h, [10](#)
- cleanupMemory
  - Memory.c, [14](#)
  - Memory.h, [17](#)
- clearScreen
  - Display.c, [8](#)
  - Display.h, [10](#)
- closeLogs
  - Logs.c, [11](#)
  - Logs.h, [13](#)
- CPU.c
  - cleanupCPU, [6](#)
  - CPUTick, [6](#)
  - handleOpCode, [6](#)
  - setupCPU, [6](#)
- CPU.h
  - cleanupCPU, [7](#)
  - MAX\_STACK\_SIZE, [7](#)
  - setupCPU, [7](#)
- CPUTick
  - CPU.c, [6](#)
- DATA\_SPACE\_START
  - Memory.h, [16](#)
- DATA\_SPACE\_STOP
  - Memory.h, [16](#)
- DEBUG\_LEVELS
  - Logs.h, [13](#)
- DEFAULT\_DEBUG\_LEVEL
  - Logs.h, [12](#)
- DEFAULT\_OUTPUT\_FILENAME
  - Logs.h, [12](#)
- DISASSEMBLY
  - Logs.h, [13](#)
- Display.c
  - cleanupDisplay, [8](#)
  - clearScreen, [8](#)
  - DISPLAY\_IDLE\_TIME, [8](#)
  - render, [9](#)
  - reshape, [9](#)
  - SCREEN\_HEIGHT, [8](#)
  - SCREEN\_RATIO, [8](#)
  - SCREEN\_WIDTH, [8](#)
  - setupDisplay, [9](#)
- Display.h
  - cleanupDisplay, [10](#)
  - clearScreen, [10](#)
  - drawSprite, [10](#)
  - setupDisplay, [10](#)
- DISPLAY\_IDLE\_TIME
  - Display.c, [8](#)
- DRAWING
  - Logs.h, [13](#)
- drawSprite
  - Display.h, [10](#)
- ERROR
  - Logs.h, [13](#)
- handleOpCode
  - CPU.c, [6](#)
- Logs.c
  - addEntry, [11](#)
  - closeLogs, [11](#)
  - setupLogs, [11](#)

Logs.h  
   addEntry, 13  
   closeLogs, 13  
   DEBUG\_LEVELS, 13  
   DEFAULT\_DEBUG\_LEVEL, 12  
   DEFAULT\_OUTPUT\_FILENAME, 12  
   DISASSEMBLY, 13  
   DRAWING, 13  
   ERROR, 13  
   LOW\_LEVEL\_OPERATION, 13  
   setupLogs, 13  
   WARNING, 13  
 LOW\_LEVEL\_OPERATION  
   Logs.h, 13  
  
 main  
   C8E.c, 3  
 MAX\_REGISTERS  
   Memory.h, 16  
 MAX\_STACK\_SIZE  
   CPU.h, 7  
 Memory.c  
   cleanupMemory, 14  
   read, 14  
   setupMemory, 15  
   write, 15  
 Memory.h  
   cleanupMemory, 17  
   DATA\_SPACE\_START, 16  
   DATA\_SPACE\_STOP, 16  
   MAX\_REGISTERS, 16  
   read, 17  
   RESERVED\_MEMORY\_START, 17  
   RESERVED\_MEMORY\_STOP, 17  
   setupMemory, 17  
   write, 18  
  
 printUsage  
   C8E.c, 3  
  
 read  
   Memory.c, 14  
   Memory.h, 17  
 readCartridge  
   CartridgeReader.c, 4  
   CartridgeReader.h, 5  
 render  
   Display.c, 9  
 RESERVED\_MEMORY\_START  
   Memory.h, 17  
  
 RESERVED\_MEMORY\_STOP  
   Memory.h, 17  
 reshape  
   Display.c, 9  
 SCREEN\_HEIGHT  
   Display.c, 8  
 SCREEN\_RATIO  
   Display.c, 8  
 SCREEN\_WIDTH  
   Display.c, 8  
 setupCPU  
   CPU.c, 6  
   CPU.h, 7  
 setupDisplay  
   Display.c, 9  
   Display.h, 10  
 setupLogs  
   Logs.c, 11  
   Logs.h, 13  
 setupMemory  
   Memory.c, 15  
   Memory.h, 17  
 src/C8E.c, 3  
 src/CartridgeReader.c, 4  
 src/CartridgeReader.h, 4  
 src/CPU.c, 5  
 src/CPU.h, 6  
 src/Display.c, 7  
 src/Display.h, 9  
 src/Logs.c, 11  
 src/Logs.h, 12  
 src/Memory.c, 14  
 src/Memory.h, 15  
  
 WARNING  
   Logs.h, 13  
 write  
   Memory.c, 15  
   Memory.h, 18