AFRILANG Stdlib

std/c/simmonte

Français. Bibliothèque AFRILANG ‘std/c/simmonte‘ (niveau complex, catégorie complex). Elle expose 6 fonction(s) : estimatePi, integrate, randomNormal, confidence95, bootstrapMean, varianceReduction.
‘import ”std/c/simmonte”‘ · ‘use simmonte‘
- ‘estimatePi(samples number, seed number) → number‘ - ‘integrate(samples number, seed number, a number, b number) → number‘ - ‘randomNormal(n number, seed number) → list number‘ - ‘confidence95(samples list number) → list number‘ - ‘bootstrapMean(data list number, samples number, seed number) → number‘ - ‘varianceReduction(samples number, seed number) → number‘ **English.** AFRILANG library ‘std/c/simmonte‘ (tier complex, category complex). Exports 6 function(s): estimatePi, integrate, randomNormal, confidence95, bootstrapMean, varianceReduction.
‘import ”std/c/simmonte”‘ · ‘use simmonte‘
- ‘estimatePi(samples number, seed number) → number‘ - ‘integrate(samples number, seed number, a number, b number) → number‘ - ‘randomNormal(n number, seed number) → list number‘ - ‘confidence95(samples list number) → list number‘ - ‘bootstrapMean(data list number, samples number, seed number) → number‘ - ‘varianceReduction(samples number, seed number) → number‘

Catégorie / Category	Modules complex (c/)
Niveau / Tier	complex
Fonctions / Functions	6

June 16, 2026

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/c/simmonte' (niveau complex, catégorie complex). Elle expose 6 fonction(s) : estimatePi, integrate, randomNormal, confidence95, bootstrapMean, varianceReduction.

'import "std/c/simmonte"' · 'use simmonte'

```
- `estimatePi(samples number, seed number) → number`
- `integrate(samples number, seed number, a number, b number) → number`
- `randomNormal(n number, seed number) → list number`
- `confidence95(samples list number) → list number`
- `bootstrapMean(data list number, samples number, seed number) → number`
- `varianceReduction(samples number, seed number) → number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/simmonte"
use simmonte
```

```
Niveau : complex · Catégorie : Modules complex (c/)
Domaines avancés — graphes, NLP, réseaux complexes.
```

3. Référence API

```
•
 estimatePi(samples number, seed number) → number•
 integrate(samples number, seed number, a number, b number) → number•
 randomNormal(n number, seed number) → list•
 confidence95(samples list number) → list•
 bootstrapMean(data list number, samples number, seed number) → number•
 varianceReduction(samples number, seed number) → number
```

4. Exemples d'utilisation

```
import "std/c/simmonte"
use simmonte
```

```
create result = estimatePi(/* args */)
say result
```

```
create result = integrate(/* args */)
say result
```

```
create result = randomNormal(/* args */)
say result
```

```
create result = confidence95(/* args */)
say result
```

```
create result = bootstrapMean(/* args */)
say result
```

```
create result = varianceReduction(/* args */)
say result
```

5. Bonnes pratiques

```
•
 Préférez `import "std/c/simmonte"` en tête de fichier.•
 Lancez `afrilang check` avant de livrer.•
 Combinez avec les modules stdlib de la même catégorie.•
 Voir /stdlib/ pour le source live et les démos playground.•
 Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe — source

module simmonte

```
function estimatePi(samples number, seed number) returns number
end
```

```
function integrate(samples number, seed number, a number, b number) returns number
end
```

```
function randomNormal(n number, seed number) returns list number
end
```

```
function confidence95(samples list number) returns list number
end
```

```
function bootstrapMean(data list number, samples number, seed number) returns number
end
```

```
function varianceReduction(samples number, seed number) returns number
end
end
```

English

1. Overview

AFRILANG library ‘std/c/simmonte‘ (tier complex, category complex). Exports 6 function(s): estimatePi, integrate, randomNormal, confidence95, bootstrapMean, varianceReduction.

‘import ”std/c/simmonte”‘ · ‘use simmonte‘

```
- `estimatePi(samples number, seed number) → number`
- `integrate(samples number, seed number, a number, b number) → number`
- `randomNormal(n number, seed number) → list number`
- `confidence95(samples list number) → list number`
- `bootstrapMean(data list number, samples number, seed number) → number`
- `varianceReduction(samples number, seed number) → number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/simmonte"
use simmonte
```

```
Tier: complex · Category: Complex modules (c/)
Advanced domains — graphs, NLP, complex networks.
```

3. API reference

```
•
 estimatePi(samples number, seed number) → number•
 integrate(samples number, seed number, a number, b number) → number•
 randomNormal(n number, seed number) → list•
 confidence95(samples list number) → list•
 bootstrapMean(data list number, samples number, seed number) → number•
 varianceReduction(samples number, seed number) → number
```

4. Usage examples

```
import "std/c/simmonte"
use simmonte
```

```
create result = estimatePi(/* args */)
say result
```

```
create result = integrate(/* args */)
say result
```

```
create result = randomNormal(/* args */)
say result
```

```
create result = confidence95(/* args */)
say result
```

```
create result = bootstrapMean(/* args */)
say result
```

```
create result = varianceReduction(/* args */)
say result
```

5. Best practices

```
•
 Prefer `import "std/c/simmonte"` at the top of your file.•
 Run `afrilang check` before shipping.•
 Combine with related stdlib modules from the same category.•
 See /stdlib/ for the live source and playground demos.•
 Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix — source

module simmonte

```
function estimatePi(samples number, seed number) returns number
end
```

```
function integrate(samples number, seed number, a number, b number) returns number
end
```

```
function randomNormal(n number, seed number) returns list number
end
```

```
function confidence95(samples list number) returns list number
end
```

```
function bootstrapMean(data list number, samples number, seed number) returns number
end
```

```
function varianceReduction(samples number, seed number) returns number
end
end
```

Référence rapide / Quick reference

- Import : `import "std/c/simmonte"`
- Vérification : `afrilang check`
- Documentation : `https://afrilang.dev/stdlib/std/c/simmonte/`

Source (extrait)

```
module simmonte

function estimatePi(samples number, seed number) returns number
end

function integrate(samples number, seed number, a number, b number) returns number
end

function randomNormal(n number, seed number) returns list number
end

function confidence95(samples list number) returns list number
end

function bootstrapMean(data list number, samples number, seed number) returns number
```

```
end

function varianceReduction(samples number, seed number) returns number
end
end
```