# AFRILANG Stdlib

## std/c/gamedijkstra

**Français.** Bibliothèque AFRILANG ‘std/c/gamedijkstra‘ (niveau complex, catégorie complex). Elle expose 6 fonction(s) : gridDijkstra, shortestCost, reachableCells, multiGoal, relaxStep, maxDist.
‘import ”std/c/gamedijkstra”‘ · ‘use gamedijkstra‘
- ‘gridDijkstra(grid list number, width number, start number) → list number‘ - ‘shortestCost(grid list number, width number, start number, goal number) → number‘ - ‘reachableCells(grid list number, width number, start number) → number‘ - ‘multiGoal(grid list number, width number, start number, goals list number) → list number‘ - ‘relaxStep(dist list number, grid **English.** AFRILANG library ‘std/c/gamedijkstra‘ (tier complex, category complex). Exports 6 function(s): gridDijkstra, shortestCost, reachableCells, multiGoal, relaxStep, maxDist.
‘import ”std/c/gamedijkstra”‘ · ‘use gamedijkstra‘
- ‘gridDijkstra(grid list number, width number, start number) → list number‘ - ‘shortestCost(grid list number, width number, start number, goal number) → number‘ - ‘reachableCells(grid list number, width number, start number) → number‘ - ‘multiGoal(grid list number, width number, start number, goals list number) → list number‘ - ‘relaxStep(dist list number, grid list number,

| | |
|---|---|
| Catégorie / Category | Modules complex (c/) |
| Niveau / Tier | complex |
| Fonctions / Functions | 6 |

June 16, 2026

# Contents

# Français

## 1. Vue d'ensemble

Bibliothèque AFRILANG 'std/c/gamedijkstra' (niveau complex, catégorie complex). Elle expose 6 fonction(s) : gridDijkstra, shortestCost, reachableCells, multiGoal, relaxStep, maxDist.

'import "std/c/gamedijkstra"' · 'use gamedijkstra'

```
- `gridDijkstra(grid list number, width number, start number) → list number`
- `shortestCost(grid list number, width number, start number, goal number) → number`
- `reachableCells(grid list number, width number, start number) → number`
- `multiGoal(grid list number, width number, start number, goals list number) → list
   number`
- `relaxStep(dist list number, grid list number, width number, u number) → list
   number`
- `maxDist(grid list number, width number, start number) → number`
```

## 2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/gamedijkstra"
use gamedijkstra
```

```
Niveau : complex · Catégorie : Modules complex (c/)
Domaines avancés — graphes, NLP, réseaux complexes.
```

## 3. Référence API

```
•
 gridDijkstra(grid list number, width number, start number) → list•
 shortestCost(grid list number, width number, start number, goal number) → number•
 reachableCells(grid list number, width number, start number) → number•
 multiGoal(grid list number, width number, start number, goals list number) → list•
 relaxStep(dist list number, grid list number, width number, u number) → list•
 maxDist(grid list number, width number, start number) → number
```

## 4. Exemples d'utilisation

```
import "std/c/gamedijkstra"
use gamedijkstra
```

```
create result = gridDijkstra(/* args */)
say result
```

```
create result = shortestCost(/* args */)
say result
```

```
create result = reachableCells(/* args */)
say result
```

```
create result = multiGoal(/* args */)
say result
```

```
create result = relaxStep(/* args */)
say result
```

```
create result = maxDist(/* args */)
say result
```

## 5. Bonnes pratiques

```
•
 Préférez `import "std/c/gamedijkstra"` en tête de fichier.•
 Lancez `afrilang check` avant de livrer.•
 Combinez avec les modules stdlib de la même catégorie.•
 Voir /stdlib/ pour le source live et les démos playground.•
 Signalez les problèmes sur GitHub si une export manque.
```

## 6. Annexe — source

module gamedijkstra

```
function gridDijkstra(grid list number, width number, start number) returns list
    number
end
```

```
function shortestCost(grid list number, width number, start number, goal number)
    returns number
end
```

```
function reachableCells(grid list number, width number, start number) returns number
end
```

```
function multiGoal(grid list number, width number, start number, goals list number)
    returns list number
end
```

```
function relaxStep(dist list number, grid list number, width number, u number)
    returns list number
end
```

```
function maxDist(grid list number, width number, start number) returns number
end
end
```

# English

## 1. Overview

AFRILANG library ‘std/c/gamedijkstra‘ (tier complex, category complex). Exports 6 function(s): gridDijkstra, shortestCost, reachableCells, multiGoal, relaxStep, maxDist. ‘import ”std/c/gamedijkstra”‘ · ‘use gamedijkstra‘

```
- `gridDijkstra(grid list number, width number, start number) → list number`
- `shortestCost(grid list number, width number, start number, goal number) → number`
- `reachableCells(grid list number, width number, start number) → number`
- `multiGoal(grid list number, width number, start number, goals list number) → list
   number`
- `relaxStep(dist list number, grid list number, width number, u number) → list
   number`
- `maxDist(grid list number, width number, start number) → number`
```

## 2. Installation & import

Add the module to your program:

```
import "std/c/gamedijkstra"
use gamedijkstra
```

```
Tier: complex · Category: Complex modules (c/)
Advanced domains — graphs, NLP, complex networks.
```

## 3. API reference

```
•
 gridDijkstra(grid list number, width number, start number) → list•
 shortestCost(grid list number, width number, start number, goal number) → number•
 reachableCells(grid list number, width number, start number) → number•
 multiGoal(grid list number, width number, start number, goals list number) → list•
 relaxStep(dist list number, grid list number, width number, u number) → list•
 maxDist(grid list number, width number, start number) → number
```

## 4. Usage examples

```
import "std/c/gamedijkstra"
use gamedijkstra
```

```
create result = gridDijkstra(/* args */)
say result
```

```
create result = shortestCost(/* args */)
say result
```

```
create result = reachableCells(/* args */)
say result
```

```
create result = multiGoal(/* args */)
say result
```

```
create result = relaxStep(/* args */)
say result
```

```
create result = maxDist(/* args */)
say result
```

## 5. Best practices

```
•
 Prefer `import "std/c/gamedijkstra"` at the top of your file.•
 Run `afrilang check` before shipping.•
 Combine with related stdlib modules from the same category.•
 See /stdlib/ for the live source and playground demos.•
 Report issues on GitHub if an export is missing or undocumented.
```

## 6. Appendix — source

module gamedijkstra

```
function gridDijkstra(grid list number, width number, start number) returns list
    number
end
```

```
function shortestCost(grid list number, width number, start number, goal number)
    returns number
end
```

```
function reachableCells(grid list number, width number, start number) returns number
end
```

```
function multiGoal(grid list number, width number, start number, goals list number)
    returns list number
end
```

```
function relaxStep(dist list number, grid list number, width number, u number)
    returns list number
end
```

```
function maxDist(grid list number, width number, start number) returns number
end
end
```

# Référence rapide / Quick reference

- Import : `import "std/c/gamedijkstra"`
- Vérification : `afrilang check`
- Documentation : `https://afrilang.dev/stdlib/std/c/gamedijkstra/`

# Source (extrait)

```
module gamedijkstra

function gridDijkstra(grid list number, width number, start number) returns list
    number
end
```

```
function shortestCost(grid list number, width number, start number, goal number)
    returns number
end

function reachableCells(grid list number, width number, start number) returns number
end

function multiGoal(grid list number, width number, start number, goals list number)
    returns list number
end

function relaxStep(dist list number, grid list number, width number, u number)
    returns list number
end

function maxDist(grid list number, width number, start number) returns number
end
end
```