AFRILANG Stdlib

`std/m/matrotate`

Français. Bibliothèque AFRILANG ‘std/m/matrotate‘ (niveau medium, catégorie medium). Elle expose 4 fonction(s) : rotate2d, apply2d, rotatePoint, degreesToRad.
‘import ”std/m/matrotate”‘ · ‘use matrotate‘
- ‘rotate2d(angle number) → list number‘ - ‘apply2d(m list number, v list number) → list number‘ - ‘rotatePoint(x number, y number, angle number) → list number‘ - ‘degreesToRad(deg number) → number‘ **English.**

AFRILANG library ‘std/m/matrotate‘ (tier medium, category medium). Exports 4 function(s): rotate2d, apply2d, rotatePoint, degreesToRad.
‘import ”std/m/matrotate”‘ · ‘use matrotate‘
- ‘rotate2d(angle number) → list number‘ - ‘apply2d(m list number, v list number) → list number‘ - ‘rotatePoint(x number, y number, angle number) → list number‘ - ‘degreesToRad(deg number) → number‘

Catégorie / Category	Modules medium (m/)
Niveau / Tier	medium
Fonctions / Functions	4

June 16, 2026

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/m/matrotate' (niveau medium, catégorie medium). Elle expose 4 fonction(s) : rotate2d, apply2d, rotatePoint, degreesToRad.

'import "std/m/matrotate"' · 'use matrotate'

```
- `rotate2d(angle number) → list number`
- `apply2d(m list number, v list number) → list number`
- `rotatePoint(x number, y number, angle number) → list number`
- `degreesToRad(deg number) → number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/m/matrotate"
use matrotate
```

```
Niveau : medium · Catégorie : Modules medium (m/)
Bibliothèques intermédiaires — import std/m…/
```

3. Référence API

```
•
 rotate2d(angle number) → list•
 apply2d(m list number, v list number) → list•
 rotatePoint(x number, y number, angle number) → list•
 degreesToRad(deg number) → number
```

4. Exemples d'utilisation

```
import "std/m/matrotate"
use matrotate
```

```
create result = rotate2d(/* args */)
say result
```

```
create result = apply2d(/* args */)
say result
```

```
create result = rotatePoint(/* args */)
say result
```

```
create result = degreesToRad(/* args */)
say result
```

5. Bonnes pratiques

```
•
 Préférez `import "std/m/matrotate"` en tête de fichier.•
 Lancez `afrilang check` avant de livrer.•
 Combinez avec les modules stdlib de la même catégorie.•
 Voir /stdlib/ pour le source live et les démos playground.•
 Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe — source

module matrotate

```
function rotate2d(angle number) returns list number
end
```

```
function apply2d(m list number, v list number) returns list number
end
```

```
function rotatePoint(x number, y number, angle number) returns list number
end
```

```
function degreesToRad(deg number) returns number
end
end
```

English

1. Overview

AFRILANG library ‘std/m/matrotate‘ (tier medium, category medium). Exports 4 function(s): rotate2d, apply2d, rotatePoint, degreesToRad.

‘import ”std/m/matrotate”‘ · ‘use matrotate‘

```
- `rotate2d(angle number) → list number`
- `apply2d(m list number, v list number) → list number`
- `rotatePoint(x number, y number, angle number) → list number`
- `degreesToRad(deg number) → number`
```

2. Installation & import

Add the module to your program:

```
import "std/m/matrotate"
use matrotate
```

```
Tier: medium · Category: Medium modules (m/)
Intermediate libraries — import std/m…/
```

3. API reference

```
•
 rotate2d(angle number) → list•
 apply2d(m list number, v list number) → list•
 rotatePoint(x number, y number, angle number) → list•
 degreesToRad(deg number) → number
```

4. Usage examples

```
import "std/m/matrotate"
use matrotate
```

```
create result = rotate2d(/* args */)
say result
```

```
create result = apply2d(/* args */)
say result
```

```
create result = rotatePoint(/* args */)
say result
```

```
create result = degreesToRad(/* args */)
say result
```

5. Best practices

```
•
 Prefer `import "std/m/matrotate"` at the top of your file.•
 Run `afrilang check` before shipping.•
 Combine with related stdlib modules from the same category.•
 See /stdlib/ for the live source and playground demos.•
 Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix — source

module matrotate

```
function rotate2d(angle number) returns list number
end
```

```
function apply2d(m list number, v list number) returns list number
end
```

```
function rotatePoint(x number, y number, angle number) returns list number
end
```

```
function degreesToRad(deg number) returns number
end
end
```

Référence rapide / Quick reference

- Import : `import "std/m/matrotate"`
- Vérification : `afrilang check`
- Documentation : `https://afrilang.dev/stdlib/std/m/matrotate/`

Source (extrait)

```
module matrotate

function rotate2d(angle number) returns list number
end

function apply2d(m list number, v list number) returns list number
end

function rotatePoint(x number, y number, angle number) returns list number
end

function degreesToRad(deg number) returns number
end
end
```