

AFRILANG Stdlib

std/c/statanova

Bibliothèque AFRILANG `std/c/statanova` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : groupMeans, gra

```
`import "std/c/statanova" · `use statanova`
```

- `groupMeans(groups list number, labels list number) ? list number`
- `grandMean(v list number) ? number`
- `betweenSS(groups list number, labels list number) ? number`
- `withinSS(groups list number, labels list number) ? number`
- `fStatistic(groups list number, labels list number) ? number`
- `etaSquared(groups list number, labels list number) ? number`

Category: complex | Tier: complex | Functions: 6

FRANCAIS

1. Vue d'ensemble

Bibliothèque AFRILANG `std/c/statanova` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : groupMeans, gra

```
`import "std/c/statanova" . `use statanova`  
- `groupMeans(groups list number, labels list number) ? list number`  
- `grandMean(v list number) ? number`  
- `betweenSS(groups list number, labels list number) ? number`  
- `withinSS(groups list number, labels list number) ? number`  
- `fStatistic(groups list number, labels list number) ? number`  
- `etaSquared(groups list number, labels list number) ? number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/statanova"  
use statanova
```

Niveau : complex · Catégorie : Modules complex (c/)

Domaines avancés ? graphes, NLP, réseaux complexes.

3. Référence API

```
? groupMeans(groups list number, labels list number) ? list  
? grandMean(v list number) ? number  
? betweenSS(groups list number, labels list number) ? number  
? withinSS(groups list number, labels list number) ? number  
? fStatistic(groups list number, labels list number) ? number  
? etaSquared(groups list number, labels list number) ? number
```

4. Exemples d'utilisation

```
import "std/c/statanova"  
use statanova  
  
create result = groupMeans(/* args */)   
say result  
  
create result = grandMean(/* args */)   
say result  
  
create result = betweenSS(/* args */)   
say result  
  
create result = withinSS(/* args */)   
say result  
  
create result = fStatistic(/* args */)   
say result  
  
create result = etaSquared(/* args */)   
say result
```

5. Bonnes pratiques

```
? Préférez `import "std/c/statanova"` en tête de fichier.  
? Lancez `afirang check` avant de livrer.  
? Combinez avec les modules stdlib de la même catégorie.  
? Voir /stdlib/ pour le source live et les démos playground.  
? Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe ? source

```
module statanova  
  
function groupMeans(groups list number, labels list number) returns list number  
end
```

```
function grandMean(v list number) returns number
end

function betweenSS(groups list number, labels list number) returns number
end

function withinSS(groups list number, labels list number) returns number
end

function fStatistic(groups list number, labels list number) returns number
end

function etaSquared(groups list number, labels list number) returns number
end
```

ENGLISH

1. Overview

AFRILANG library `std/c/statanova` (tier complex, category complex). Exports 6 function(s): groupMeans, grandMean, betwe

```
`import "std/c/statanova" . `use statanova`  
- `groupMeans(groups list number, labels list number) ? list number`  
- `grandMean(v list number) ? number`  
- `betweenSS(groups list number, labels list number) ? number`  
- `withinSS(groups list number, labels list number) ? number`  
- `fStatistic(groups list number, labels list number) ? number`  
- `etaSquared(groups list number, labels list number) ? number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/statanova"  
use statanova
```

Tier: complex · Category: Complex modules (c/)
Advanced domains ? graphs, NLP, complex networks.

3. API reference

```
? groupMeans(groups list number, labels list number) ? list  
? grandMean(v list number) ? number  
? betweenSS(groups list number, labels list number) ? number  
? withinSS(groups list number, labels list number) ? number  
? fStatistic(groups list number, labels list number) ? number  
? etaSquared(groups list number, labels list number) ? number
```

4. Usage examples

```
import "std/c/statanova"  
use statanova  
  
create result = groupMeans(/* args */)   
say result  
  
create result = grandMean(/* args */)   
say result  
  
create result = betweenSS(/* args */)   
say result  
  
create result = withinSS(/* args */)   
say result  
  
create result = fStatistic(/* args */)   
say result  
  
create result = etaSquared(/* args */)   
say result
```

5. Best practices

```
? Prefer `import "std/c/statanova"` at the top of your file.  
? Run `afirang check` before shipping.  
? Combine with related stdlib modules from the same category.  
? See /stdlib/ for the live source and playground demos.  
? Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix ? source

```
module statanova  
  
function groupMeans(groups list number, labels list number) returns list number  
end
```

```
function grandMean(v list number) returns number
end

function betweenSS(groups list number, labels list number) returns number
end

function withinSS(groups list number, labels list number) returns number
end

function fStatistic(groups list number, labels list number) returns number
end

function etaSquared(groups list number, labels list number) returns number
end
```