

AFRILANG Stdlib

std/c/statbootstrap

Bibliothèque AFRILANG `std/c/statbootstrap` (niveau complex, catégorie complex). Elle expose 6 fonction(s)
: bootstrapMe

```
`import "std/c/statbootstrap" · `use statbootstrap`
```

- `bootstrapMean(v list number, samples number) ? number`
- `bootstrapSE(v list number, samples number) ? number`
- `resample(v list number, size number) ? list number`
- `bootstrapCI(v list number, samples number) ? list number`
- `jackknife(v list number) ? list number`
- `biasCorrected(v list number, stat number) ? number`

Category: complex | Tier: complex | Functions: 6

FRANCAIS

1. Vue d'ensemble

Bibliothèque AFRILANG `std/c/statbootstrap` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : bootstrapMe

```
`import "std/c/statbootstrap" . `use statbootstrap`  
- `bootstrapMean(v list number, samples number) ? number`  
- `bootstrapSE(v list number, samples number) ? number`  
- `resample(v list number, size number) ? list number`  
- `bootstrapCI(v list number, samples number) ? list number`  
- `jackknife(v list number) ? list number`  
- `biasCorrected(v list number, stat number) ? number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/statbootstrap"  
use statbootstrap
```

Niveau : complex · Catégorie : Modules complex (c/)

Domaines avancés ? graphes, NLP, réseaux complexes.

3. Référence API

```
? bootstrapMean(v list number, samples number) ? number  
? bootstrapSE(v list number, samples number) ? number  
? resample(v list number, size number) ? list  
? bootstrapCI(v list number, samples number) ? list  
? jackknife(v list number) ? list  
? biasCorrected(v list number, stat number) ? number
```

4. Exemples d'utilisation

```
import "std/c/statbootstrap"  
use statbootstrap  
  
create result = bootstrapMean(/* args */)   
say result  
  
create result = bootstrapSE(/* args */)   
say result  
  
create result = resample(/* args */)   
say result  
  
create result = bootstrapCI(/* args */)   
say result  
  
create result = jackknife(/* args */)   
say result  
  
create result = biasCorrected(/* args */)   
say result
```

5. Bonnes pratiques

```
? Préférez `import "std/c/statbootstrap"` en tête de fichier.  
? Lancez `afrilang check` avant de livrer.  
? Combinez avec les modules stdlib de la même catégorie.  
? Voir /stdlib/ pour le source live et les démos playground.  
? Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe ? source

```
module statbootstrap  
  
function bootstrapMean(v list number, samples number) returns number  
end
```

```
function bootstrapSE(v list number, samples number) returns number  
end
```

```
function resample(v list number, size number) returns list number  
end
```

```
function bootstrapCI(v list number, samples number) returns list number  
end
```

```
function jackknife(v list number) returns list number  
end
```

```
function biasCorrected(v list number, stat number) returns number  
end  
end
```

ENGLISH

1. Overview

AFRILANG library `std/c/statbootstrap` (tier complex, category complex). Exports 6 function(s): bootstrapMean, bootstrap

```
`import "std/c/statbootstrap" . `use statbootstrap`  
- `bootstrapMean(v list number, samples number) ? number`  
- `bootstrapSE(v list number, samples number) ? number`  
- `resample(v list number, size number) ? list number`  
- `bootstrapCI(v list number, samples number) ? list number`  
- `jackknife(v list number) ? list number`  
- `biasCorrected(v list number, stat number) ? number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/statbootstrap"  
use statbootstrap
```

Tier: complex · Category: Complex modules (c/)
Advanced domains ? graphs, NLP, complex networks.

3. API reference

```
? bootstrapMean(v list number, samples number) ? number  
? bootstrapSE(v list number, samples number) ? number  
? resample(v list number, size number) ? list  
? bootstrapCI(v list number, samples number) ? list  
? jackknife(v list number) ? list  
? biasCorrected(v list number, stat number) ? number
```

4. Usage examples

```
import "std/c/statbootstrap"  
use statbootstrap  
  
create result = bootstrapMean(/* args */)   
say result  
  
create result = bootstrapSE(/* args */)   
say result  
  
create result = resample(/* args */)   
say result  
  
create result = bootstrapCI(/* args */)   
say result  
  
create result = jackknife(/* args */)   
say result  
  
create result = biasCorrected(/* args */)   
say result
```

5. Best practices

```
? Prefer `import "std/c/statbootstrap"` at the top of your file.  
? Run `afirang check` before shipping.  
? Combine with related stdlib modules from the same category.  
? See /stdlib/ for the live source and playground demos.  
? Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix ? source

```
module statbootstrap  
  
function bootstrapMean(v list number, samples number) returns number  
end
```

```
function bootstrapSE(v list number, samples number) returns number  
end
```

```
function resample(v list number, size number) returns list number  
end
```

```
function bootstrapCI(v list number, samples number) returns list number  
end
```

```
function jackknife(v list number) returns list number  
end
```

```
function biasCorrected(v list number, stat number) returns number  
end  
end
```