

AFRILANG Stdlib

std/c/statzscore

Bibliothèque AFRILANG `std/c/statzscore` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : zScores, zScor

```
`import "std/c/statzscore" . `use statzscore`
```

- `zScores(v list number) ? list number`
- `zScore(v list number, val number) ? number`
- `isOutlierZ(v list number, val number, threshold number) ? bool`
- `standardize(v list number) ? list number`
- `destandardize(z list number, mean number, stddev number) ? list number`
- `zMean(v list number) ? number`

Category: complex | Tier: complex | Functions: 6

FRANCAIS

1. Vue d'ensemble

Bibliothèque AFRILANG `std/c/statzscore` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : zScores, zScore

```
`import "std/c/statzscore"` . `use statzscore`  
- `zScores(v list number) ? list number`  
- `zScore(v list number, val number) ? number`  
- `isOutlierZ(v list number, val number, threshold number) ? bool`  
- `standardize(v list number) ? list number`  
- `destandardize(z list number, mean number, stddev number) ? list number`  
- `zMean(v list number) ? number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/statzscore"  
use statzscore
```

Niveau : complex · Catégorie : Modules complex (c/)

Domaines avancés ? graphes, NLP, réseaux complexes.

3. Référence API

```
? zScores(v list number) ? list  
? zScore(v list number, val number) ? number  
? isOutlierZ(v list number, val number, threshold number) ? bool  
? standardize(v list number) ? list  
? destandardize(z list number, mean number, stddev number) ? list  
? zMean(v list number) ? number
```

4. Exemples d'utilisation

```
import "std/c/statzscore"  
use statzscore  
  
create result = zScores(/* args */)   
say result  
  
create result = zScore(/* args */)   
say result  
  
create result = isOutlierZ(/* args */)   
say result  
  
create result = standardize(/* args */)   
say result  
  
create result = destandardize(/* args */)   
say result  
  
create result = zMean(/* args */)   
say result
```

5. Bonnes pratiques

```
? Préférez `import "std/c/statzscore"` en tête de fichier.  
? Lancez `afirilang check` avant de livrer.  
? Combinez avec les modules stdlib de la même catégorie.  
? Voir /stdlib/ pour le source live et les démos playground.  
? Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe ? source

```
module statzscore  
  
function zScores(v list number) returns list number  
end
```

```
function zScore(v list number, val number) returns number
end

function isOutlierZ(v list number, val number, threshold number) returns bool
end

function standardize(v list number) returns list number
end

function destandardize(z list number, mean number, stddev number) returns list number
end

function zMean(v list number) returns number
end
end
```

ENGLISH

1. Overview

AFRILANG library `std/c/statzscore` (tier complex, category complex). Exports 6 function(s): zScores, zScore, isOutlierZ

```
`import "std/c/statzscore"` . `use statzscore`  
- `zScores(v list number) ? list number`  
- `zScore(v list number, val number) ? number`  
- `isOutlierZ(v list number, val number, threshold number) ? bool`  
- `standardize(v list number) ? list number`  
- `destandardize(z list number, mean number, stddev number) ? list number`  
- `zMean(v list number) ? number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/statzscore"  
use statzscore
```

Tier: complex · Category: Complex modules (c/)
Advanced domains ? graphs, NLP, complex networks.

3. API reference

```
? zScores(v list number) ? list  
? zScore(v list number, val number) ? number  
? isOutlierZ(v list number, val number, threshold number) ? bool  
? standardize(v list number) ? list  
? destandardize(z list number, mean number, stddev number) ? list  
? zMean(v list number) ? number
```

4. Usage examples

```
import "std/c/statzscore"  
use statzscore  
  
create result = zScores(/* args */)   
say result  
  
create result = zScore(/* args */)   
say result  
  
create result = isOutlierZ(/* args */)   
say result  
  
create result = standardize(/* args */)   
say result  
  
create result = destandardize(/* args */)   
say result  
  
create result = zMean(/* args */)   
say result
```

5. Best practices

```
? Prefer `import "std/c/statzscore"` at the top of your file.  
? Run `afirang check` before shipping.  
? Combine with related stdlib modules from the same category.  
? See /stdlib/ for the live source and playground demos.  
? Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix ? source

```
module statzscore  
  
function zScores(v list number) returns list number  
end
```

```
function zScore(v list number, val number) returns number
end

function isOutlierZ(v list number, val number, threshold number) returns bool
end

function standardize(v list number) returns list number
end

function destandardize(z list number, mean number, stddev number) returns list number
end

function zMean(v list number) returns number
end
end
```