

AFRILANG Stdlib

std/c/geomcircle

Bibliothèque AFRILANG `std/c/geomcircle` (niveau complex, catégorie complex). Elle expose 6 fonction(s) :
euclidean2d, a

```
`import "std/c/geomcircle" · `use geomcircle`
```

- `euclidean2d(x1 number, y1 number, x2 number, y2 number) ? number`
- `area(r number) ? number`
- `circumference(r number) ? number`
- `contains(cx number, cy number, r number, px number, py number) ? bool`
- `pointAt(cx number, cy number, r number, angle number) ? list number`
- `intersectArea(r1 number, r2 number, d number) ? number`

Category: complex | Tier: complex | Functions: 6

FRANCAIS

1. Vue d'ensemble

Bibliothèque AFRILANG ``std/c/geomcircle`` (niveau complex, catégorie complex). Elle expose 6 fonction(s) : `euclidean2d`, `a`

```
`import "std/c/geomcircle"` . `use geomcircle`  
- `euclidean2d(x1 number, y1 number, x2 number, y2 number) ? number`  
- `area(r number) ? number`  
- `circumference(r number) ? number`  
- `contains(cx number, cy number, r number, px number, py number) ? bool`  
- `pointAt(cx number, cy number, r number, angle number) ? list number`  
- `intersectArea(r1 number, r2 number, d number) ? number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/geomcircle"  
use geomcircle
```

Niveau : complex · Catégorie : Modules complex (c/)

Domaines avancés ? graphes, NLP, réseaux complexes.

3. Référence API

```
? euclidean2d(x1 number, y1 number, x2 number, y2 number) ? number  
? area(r number) ? number  
? circumference(r number) ? number  
? contains(cx number, cy number, r number, px number, py number) ? bool  
? pointAt(cx number, cy number, r number, angle number) ? list  
? intersectArea(r1 number, r2 number, d number) ? number
```

4. Exemples d'utilisation

```
import "std/c/geomcircle"  
use geomcircle  
  
create result = euclidean2d(/* args */)   
say result  
  
create result = area(/* args */)   
say result  
  
create result = circumference(/* args */)   
say result  
  
create result = contains(/* args */)   
say result  
  
create result = pointAt(/* args */)   
say result  
  
create result = intersectArea(/* args */)   
say result
```

5. Bonnes pratiques

```
? Préférez `import "std/c/geomcircle"` en tête de fichier.  
? Lancez `afrilang check` avant de livrer.  
? Combinez avec les modules stdlib de la même catégorie.  
? Voir /stdlib/ pour le source live et les démos playground.  
? Signalez les problèmes sur GitHub si une export manque.
```

6. Annexe ? source

```
module geomcircle  
  
function euclidean2d(x1 number, y1 number, x2 number, y2 number) returns number  
end
```

```
function area(r number) returns number
end

function circumference(r number) returns number
end

function contains(cx number, cy number, r number, px number, py number) returns bool
end

function pointAt(cx number, cy number, r number, angle number) returns list number
end

function intersectArea(r1 number, r2 number, d number) returns number
end
end
```

ENGLISH

1. Overview

AFRILANG library `std/c/geomcircle` (tier complex, category complex). Exports 6 function(s): euclidean2d, area, circumfe

```
`import "std/c/geomcircle"` . `use geomcircle`  
- `euclidean2d(x1 number, y1 number, x2 number, y2 number) ? number`  
- `area(r number) ? number`  
- `circumference(r number) ? number`  
- `contains(cx number, cy number, r number, px number, py number) ? bool`  
- `pointAt(cx number, cy number, r number, angle number) ? list number`  
- `intersectArea(r1 number, r2 number, d number) ? number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/geomcircle"  
use geomcircle
```

Tier: complex · Category: Complex modules (c/)
Advanced domains ? graphs, NLP, complex networks.

3. API reference

```
? euclidean2d(x1 number, y1 number, x2 number, y2 number) ? number  
? area(r number) ? number  
? circumference(r number) ? number  
? contains(cx number, cy number, r number, px number, py number) ? bool  
? pointAt(cx number, cy number, r number, angle number) ? list  
? intersectArea(r1 number, r2 number, d number) ? number
```

4. Usage examples

```
import "std/c/geomcircle"  
use geomcircle  
  
create result = euclidean2d(/* args */)   
say result  
  
create result = area(/* args */)   
say result  
  
create result = circumference(/* args */)   
say result  
  
create result = contains(/* args */)   
say result  
  
create result = pointAt(/* args */)   
say result  
  
create result = intersectArea(/* args */)   
say result
```

5. Best practices

```
? Prefer `import "std/c/geomcircle"` at the top of your file.  
? Run `afrilang check` before shipping.  
? Combine with related stdlib modules from the same category.  
? See /stdlib/ for the live source and playground demos.  
? Report issues on GitHub if an export is missing or undocumented.
```

6. Appendix ? source

```
module geomcircle  
  
function euclidean2d(x1 number, y1 number, x2 number, y2 number) returns number  
end
```

```
function area(r number) returns number
end

function circumference(r number) returns number
end

function contains(cx number, cy number, r number, px number, py number) returns bool
end

function pointAt(cx number, cy number, r number, angle number) returns list number
end

function intersectArea(r1 number, r2 number, d number) returns number
end
end
```