

AFRILANG Stdlib

std/c/statbootstrap

Français. Bibliothèque AFRILANG 'std/c/statbootstrap' (niveau complexe, catégorie complexe). Elle expose 6 fonction(s) : bootstrapMean, bootstrapSE, resample, bootstrapCI, jackknife, biasCorrected.

```
'import "std/c/statbootstrap"' · 'use statbootstrap'
```

- 'bootstrapMean(v list number, samples number) → number'
- 'bootstrapSE(v list number, samples number) → number'
- 'resample(v list number, size number) → list number'
- 'bootstrapCI(v list number, samples number) → list number'
- 'jackknife(v list number) → list number'
- 'biasCorrected(v list number, stat number) → number'

English.

AFRILANG library 'std/c/statbootstrap' (tier complex, category complex). Exports 6 function(s): bootstrapMean, bootstrapSE, resample, bootstrapCI, jackknife, biasCorrected.

```
'import "std/c/statbootstrap"' · 'use statbootstrap'
```

- 'bootstrapMean(v list number, samples number) → number'
- 'bootstrapSE(v list number, samples number) → number'
- 'resample(v list number, size number) → list number'
- 'bootstrapCI(v list number, samples number) → list number'
- 'jackknife(v list number) → list number'
- 'biasCorrected(v list number, stat number) → number'

Catégorie / Category	Modules complex (c/)	
Niveau / Tier	complex	June 16, 2026
Fonctions / Functions	6	

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/c/statbootstrap' (niveau complex, catégorie complex). Elle expose 6 fonction(s) : bootstrapMean, bootstrapSE, resample, bootstrapCI, jackknife, biasCorrected.

```
'import "std/c/statbootstrap"' · 'use statbootstrap'
```

```
- `bootstrapMean(v list number, samples number) → number`
- `bootstrapSE(v list number, samples number) → number`
- `resample(v list number, size number) → list number`
- `bootstrapCI(v list number, samples number) → list number`
- `jackknife(v list number) → list number`
- `biasCorrected(v list number, stat number) → number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/statbootstrap"
use statbootstrap
```

Niveau : complex · Catégorie : Modules complex (c/)
Domaines avancés – graphes, NLP, réseaux complexes.

3. Référence API

- bootstrapMean(v list number, samples number) → number
- bootstrapSE(v list number, samples number) → number
- resample(v list number, size number) → list
- bootstrapCI(v list number, samples number) → list
- jackknife(v list number) → list
- biasCorrected(v list number, stat number) → number

4. Exemples d'utilisation

```
import "std/c/statbootstrap"
use statbootstrap
```

```
create result = bootstrapMean(/* args */)
say result
```

```
create result = bootstrapSE(/* args */)
say result
```

```
create result = resample(/* args */)
say result
```

```
create result = bootstrapCI(/* args */)
say result
```

```
create result = jackknife(/* args */)
say result
```

```
create result = biasCorrected(/* args */)
say result
```

5. Bonnes pratiques

- Préférez ``import "std/c/statbootstrap"`` en tête de fichier.
- Lancez ``afriLang check`` avant de livrer.
- Combinez avec les modules stdlib de la même catégorie.
- Voir `/stdlib/` pour le source live et les démos playground.
- Signalez les problèmes sur GitHub si une export manque.

6. Annexe — source

module statbootstrap

```
function bootstrapMean(v list number, samples number) returns number  
end
```

```
function bootstrapSE(v list number, samples number) returns number  
end
```

```
function resample(v list number, size number) returns list number  
end
```

```
function bootstrapCI(v list number, samples number) returns list number  
end
```

```
function jackknife(v list number) returns list number  
end
```

```
function biasCorrected(v list number, stat number) returns number  
end  
end
```

English

1. Overview

AFRILANG library 'std/c/statbootstrap' (tier complex, category complex). Exports 6 function(s): bootstrapMean, bootstrapSE, resample, bootstrapCI, jackknife, bias-Corrected.

```
'import "std/c/statbootstrap"' · 'use statbootstrap'
```

```
- `bootstrapMean(v list number, samples number) → number`
- `bootstrapSE(v list number, samples number) → number`
- `resample(v list number, size number) → list number`
- `bootstrapCI(v list number, samples number) → list number`
- `jackknife(v list number) → list number`
- `biasCorrected(v list number, stat number) → number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/statbootstrap"
use statbootstrap
```

Tier: complex · Category: Complex modules (c/)
Advanced domains – graphs, NLP, complex networks.

3. API reference

- bootstrapMean(v list number, samples number) → number•
- bootstrapSE(v list number, samples number) → number•
- resample(v list number, size number) → list•
- bootstrapCI(v list number, samples number) → list•
- jackknife(v list number) → list•
- biasCorrected(v list number, stat number) → number

4. Usage examples

```
import "std/c/statbootstrap"
use statbootstrap
```

```
create result = bootstrapMean(/* args */)
say result
```

```
create result = bootstrapSE(/* args */)
say result
```

```
create result = resample(/* args */)
say result
```

```
create result = bootstrapCI(/* args */)
say result
```

```
create result = jackknife(/* args */)
say result
```

```
create result = biasCorrected(/* args */)
say result
```

5. Best practices

- Prefer ``import "std/c/statbootstrap"`` at the top of your file.
- Run ``afrilang check`` before shipping.
- Combine with related stdlib modules from the same category.
- See `/stdlib/` for the live source and playground demos.
- Report issues on GitHub if an export is missing or undocumented.

6. Appendix — source

module statbootstrap

```
function bootstrapMean(v list number, samples number) returns number
end
```

```
function bootstrapSE(v list number, samples number) returns number
end
```

```
function resample(v list number, size number) returns list number
end
```

```
function bootstrapCI(v list number, samples number) returns list number
end
```

```
function jackknife(v list number) returns list number
end
```

```
function biasCorrected(v list number, stat number) returns number
end
end
```

Référence rapide / Quick reference

- Import : `import "std/c/statbootstrap"`
- Vérification : `afrilang check`
- Documentation : <https://afrilang.dev/stdlib/std/c/statbootstrap/>

Source (extrait)

```
module statbootstrap

function bootstrapMean(v list number, samples number) returns number
end

function bootstrapSE(v list number, samples number) returns number
end

function resample(v list number, size number) returns list number
end

function bootstrapCI(v list number, samples number) returns list number
end

function jackknife(v list number) returns list number
```

```
end  
function biasCorrected(v list number, stat number) returns number  
end  
end
```