

AFRILANG Stdlib

std/c/statkurt

Français. Bibliothèque AFRILANG 'std/c/statkurt' (niveau complex, catégorie complex). Elle expose 6 fonction(s) : kurtosis, excessKurtosis, isLeptokurtic, isPlatykurtic, tailRatio, peakedness.

'import "std/c/statkurt"' · 'use statkurt'

- 'kurtosis(v list number) → number' - 'excessKurtosis(v list number) → number' - 'isLeptokurtic(v list number) → bool' - 'isPlatykurtic(v list number) → bool' - 'tailRatio(v list number) → number' - 'peakedness(v list number) → number'

English. AFRILANG library 'std/c/statkurt' (tier complex, category complex). Exports 6 function(s): kurtosis, excessKurtosis, isLeptokurtic, isPlatykurtic, tailRatio, peakedness.

'import "std/c/statkurt"' · 'use statkurt'

- 'kurtosis(v list number) → number' - 'excessKurtosis(v list number) → number' - 'isLeptokurtic(v list number) → bool' - 'isPlatykurtic(v list number) → bool' - 'tailRatio(v list number) → number' - 'peakedness(v list number) → number'

Catégorie / Category	Modules complex (c/)	
Niveau / Tier	complex	June 16, 2026
Fonctions / Functions	6	

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/c/statkurt' (niveau complexe, catégorie complexe). Elle expose 6 fonction(s) : kurtosis, excessKurtosis, isLeptokurtic, isPlatykurtic, tailRatio, peakedness.

```
'import "std/c/statkurt"' · 'use statkurt'
```

```
- `kurtosis(v list number) → number`
- `excessKurtosis(v list number) → number`
- `isLeptokurtic(v list number) → bool`
- `isPlatykurtic(v list number) → bool`
- `tailRatio(v list number) → number`
- `peakedness(v list number) → number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/c/statkurt"
use statkurt
```

Niveau : complexe · Catégorie : Modules complexe (c/)
Domaines avancés – graphes, NLP, réseaux complexes.

3. Référence API

- kurtosis(v list number) → number•
- excessKurtosis(v list number) → number•
- isLeptokurtic(v list number) → bool•
- isPlatykurtic(v list number) → bool•
- tailRatio(v list number) → number•
- peakedness(v list number) → number

4. Exemples d'utilisation

```
import "std/c/statkurt"
use statkurt
```

```
create result = kurtosis(/* args */)
say result
```

```
create result = excessKurtosis(/* args */)
say result
```

```
create result = isLeptokurtic(/* args */)
say result
```

```
create result = isPlatykurtic(/* args */)
say result
```

```
create result = tailRatio(/* args */)
say result
```

```
create result = peakedness(/* args */)
say result
```

5. Bonnes pratiques

- Préférez ``import "std/c/statkurt"`` en tête de fichier.
- Lancez ``afrilang check`` avant de livrer.
- Combinez avec les modules stdlib de la même catégorie.
- Voir `/stdlib/` pour le source live et les démos playground.
- Signalez les problèmes sur GitHub si une export manque.

6. Annexe — source

module statkurt

```
function kurtosis(v list number) returns number  
end
```

```
function excessKurtosis(v list number) returns number  
end
```

```
function isLeptokurtic(v list number) returns bool  
end
```

```
function isPlatykurtic(v list number) returns bool  
end
```

```
function tailRatio(v list number) returns number  
end
```

```
function peakedness(v list number) returns number  
end  
end
```

English

1. Overview

AFRILANG library 'std/c/statkurt' (tier complex, category complex). Exports 6 function(s): kurtosis, excessKurtosis, isLeptokurtic, isPlatykurtic, tailRatio, peakedness.

'import "std/c/statkurt"' · 'use statkurt'

```
- `kurtosis(v list number) → number`  
- `excessKurtosis(v list number) → number`  
- `isLeptokurtic(v list number) → bool`  
- `isPlatykurtic(v list number) → bool`  
- `tailRatio(v list number) → number`  
- `peakedness(v list number) → number`
```

2. Installation & import

Add the module to your program:

```
import "std/c/statkurt"  
use statkurt
```

Tier: complex · Category: Complex modules (c/)
Advanced domains – graphs, NLP, complex networks.

3. API reference

- kurtosis(v list number) → number•
excessKurtosis(v list number) → number•
isLeptokurtic(v list number) → bool•
isPlatykurtic(v list number) → bool•
tailRatio(v list number) → number•
peakedness(v list number) → number

4. Usage examples

```
import "std/c/statkurt"  
use statkurt
```

```
create result = kurtosis(/* args */)   
say result
```

```
create result = excessKurtosis(/* args */)   
say result
```

```
create result = isLeptokurtic(/* args */)   
say result
```

```
create result = isPlatykurtic(/* args */)   
say result
```

```
create result = tailRatio(/* args */)   
say result
```

```
create result = peakedness(/* args */)   
say result
```

5. Best practices

- Prefer ``import "std/c/statkurt"`` at the top of your file.
- Run ``afrilang check`` before shipping.
- Combine with related stdlib modules from the same category.
- See `/stdlib/` for the live source and playground demos.
- Report issues on GitHub if an export is missing or undocumented.

6. Appendix — source

module statkurt

```
function kurtosis(v list number) returns number
end
```

```
function excessKurtosis(v list number) returns number
end
```

```
function isLeptokurtic(v list number) returns bool
end
```

```
function isPlatykurtic(v list number) returns bool
end
```

```
function tailRatio(v list number) returns number
end
```

```
function peakedness(v list number) returns number
end
end
```

Référence rapide / Quick reference

- Import : `import "std/c/statkurt"`
- Vérification : `afrilang check`
- Documentation : <https://afrilang.dev/stdlib/std/c/statkurt/>

Source (extrait)

```
module statkurt

function kurtosis(v list number) returns number
end

function excessKurtosis(v list number) returns number
end

function isLeptokurtic(v list number) returns bool
end

function isPlatykurtic(v list number) returns bool
end

function tailRatio(v list number) returns number
```

```
end  
function peakedness(v list number) returns number  
end  
end
```