

AFRILANG Stdlib

std/m/uriparse

Français. Bibliothèque AFRILANG 'std/m/uriparse' (niveau medium, catégorie medium). Elle expose 5 fonction(s) : getScheme, getHost, getPath, getQuery, hasQuery.

```
'import "std/m/uriparse"' · 'use uriparse'
```

```
- 'getScheme(url text) → text' - 'getHost(url text) → text' - 'getPath(url text) → text' - 'getQuery(url text) → text' - 'hasQuery(url text) → bool'
```

English. AFRILANG library 'std/m/uriparse' (tier medium, category medium). Exports 5 function(s): getScheme, getHost, getPath, getQuery, hasQuery.

```
'import "std/m/uriparse"' · 'use uriparse'
```

```
- 'getScheme(url text) → text' - 'getHost(url text) → text' - 'getPath(url text) → text' - 'getQuery(url text) → text' - 'hasQuery(url text) → bool'
```

Catégorie / Category Modules medium (m/)

Niveau / Tier medium

Fonctions / Functions 5

June 16, 2026

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/m/uriparse' (niveau medium, catégorie medium). Elle expose 5 fonction(s) : getScheme, getHost, getPath, getQuery, hasQuery.

'import "std/m/uriparse"' · 'use uriparse'

```
- `getScheme(url text) → text`
- `getHost(url text) → text`
- `getPath(url text) → text`
- `getQuery(url text) → text`
- `hasQuery(url text) → bool`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/m/uriparse"
use uriparse
```

Niveau : medium · Catégorie : Modules medium (m/)
Bibliothèques intermédiaires – import std/m.../

3. Référence API

- getScheme(url text) → text
- getHost(url text) → text
- getPath(url text) → text
- getQuery(url text) → text
- hasQuery(url text) → bool

4. Exemples d'utilisation

```
import "std/m/uriparse"
use uriparse
```

```
create result = getScheme(/* args */)
say result
```

```
create result = getHost(/* args */)
say result
```

```
create result = getPath(/* args */)
say result
```

```
create result = getQuery(/* args */)
say result
```

```
create result = hasQuery(/* args */)
say result
```

5. Bonnes pratiques

- Préférez ``import "std/m/uriparse"`` en tête de fichier.
- Lancez ``afrilang check`` avant de livrer.
- Combinez avec les modules stdlib de la même catégorie.
- Voir `/stdlib/` pour le source live et les démos playground.
- Signalez les problèmes sur GitHub si une export manque.

6. Annexe — source

module uriparse

```
function getScheme(url text) returns text  
end
```

```
function getHost(url text) returns text  
end
```

```
function getPath(url text) returns text  
end
```

```
function getQuery(url text) returns text  
end
```

```
function hasQuery(url text) returns bool  
end  
end
```

English

1. Overview

AFRILANG library 'std/m/uriparse' (tier medium, category medium). Exports 5 function(s): getScheme, getHost, getPath, getQuery, hasQuery.

'import "std/m/uriparse"' · 'use uriparse'

```
- `getScheme(url text) → text`  
- `getHost(url text) → text`  
- `getPath(url text) → text`  
- `getQuery(url text) → text`  
- `hasQuery(url text) → bool`
```

2. Installation & import

Add the module to your program:

```
import "std/m/uriparse"  
use uriparse
```

Tier: medium · Category: Medium modules (m/)
Intermediate libraries – import std/m.../

3. API reference

- getScheme(url text) → text•
getHost(url text) → text•
getPath(url text) → text•
getQuery(url text) → text•
hasQuery(url text) → bool

4. Usage examples

```
import "std/m/uriparse"  
use uriparse
```

```
create result = getScheme(/* args */)   
say result
```

```
create result = getHost(/* args */)   
say result
```

```
create result = getPath(/* args */)   
say result
```

```
create result = getQuery(/* args */)   
say result
```

```
create result = hasQuery(/* args */)   
say result
```

5. Best practices

- Prefer ``import "std/m/uriparse"`` at the top of your file.
- Run ``afrilang check`` before shipping.
- Combine with related stdlib modules from the same category.
- See `/stdlib/` for the live source and playground demos.
- Report issues on GitHub if an export is missing or undocumented.

6. Appendix — source

module uriparse

```
function getScheme(url text) returns text
end
```

```
function getHost(url text) returns text
end
```

```
function getPath(url text) returns text
end
```

```
function getQuery(url text) returns text
end
```

```
function hasQuery(url text) returns bool
end
end
```

Référence rapide / Quick reference

- Import : `import "std/m/uriparse"`
- Vérification : `afrilang check`
- Documentation : <https://afrilang.dev/stdlib/std/m/uriparse/>

Source (extrait)

```
module uriparse

function getScheme(url text) returns text
end

function getHost(url text) returns text
end

function getPath(url text) returns text
end

function getQuery(url text) returns text
end

function hasQuery(url text) returns bool
end
end
```